

# Package ‘MSstatsQC’

June 25, 2019

**Version** 2.3.0

**Type** Package

**Title** Longitudinal system suitability monitoring and quality control  
for proteomic experiments

**Description** MSstatsQC is an R package which provides longitudinal system suitability monitoring and quality control tools for proteomic experiments.

**License** Artistic License 2.0

**LazyData** TRUE

**URL** <http://msstats.org/msstatsqc>

**BugReports** <https://groups.google.com/forum/#!forum/msstatsqc>

**RoxygenNote** 6.1.0.9000

**Imports** dplyr, plotly, RecordLinkage, ggplot2, ggExtra, stats, grid,  
MSnbase, qcmetrics

**Suggests** knitr, rmarkdown, testthat, RforProteomics

**VignetteBuilder** knitr

**biocViews** ImmunoOncology, Software, QualityControl, Proteomics,  
MassSpectrometry

**git\_url** <https://git.bioconductor.org/packages/MSstatsQC>

**git\_branch** master

**git\_last\_commit** 2b35797

**git\_last\_commit\_date** 2019-05-02

**Date/Publication** 2019-06-24

**Author** Eralp Dogu [aut, cre],  
Sara Taheri [aut],  
Olga Vitek [aut]

**Maintainer** Eralp Dogu <eralp.dogu@gmail.com>

## R topics documented:

ChangePointEstimator	2
CUSUMChart	3
DataProcess	4
DecisionMap	5

MissingDataMap . . . . .	6
MSnbaseToMSstatsQC . . . . .	6
QCloudDDA . . . . .	7
QCloudSRM . . . . .	7
QuiCDIA . . . . .	8
RadarPlot . . . . .	8
RemoveMissing . . . . .	9
RiverPlot . . . . .	10
S9Site54 . . . . .	11
XmRChart . . . . .	11

<b>Index</b>	<b>13</b>
--------------	-----------

---

ChangePointEstimator *A function to identify the time of a change in the mean or variability of a metric*

---

## Description

A function to identify the time of a change in the mean or variability of a metric

## Usage

```
ChangePointEstimator(data = NULL, peptide, L = 1, U = 5, metric,
  normalization = TRUE, ytitle = "Change Point Plot - mean",
  type = "mean", selectMean = NULL, selectSD = NULL)
```

## Arguments

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
peptide	the name of precursor of interest.
L	Lower bound of the guide set.
U	Upper bound of the guide set.
metric	the name of metric of interest.
normalization	TRUE metric is standardized and FALSE if not standardized.
ytitle	the y-axis title of the plot. Defaults to "Change Point Plot - mean". The x-axis title is by default "QCno-name of peptide"
type	the type of the control chart. Two values can be assigned, "mean" or "variability". Default is "mean".
selectMean	the mean of a metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
selectSD	the standard deviation of a metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.

## Value

A plot of likelihood statistics versus time per peptide and metric generated from CP.data.prepare data frame.

**Examples**

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Find the name of the peptides
levels(sampleData$Precursor)
# Calculate change point statistics
ChangePointEstimator(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime")
ChangePointEstimator(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
  ytitle = "Change Point Plot - variability", type = "variability")
ChangePointEstimator(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
  selectMean = 27.78, selectSD = 8.19)
ChangePointEstimator(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea")
ChangePointEstimator(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea",
  selectMean = 35097129, selectSD = 34132861)
ChangePointEstimator(data = sampleData, peptide = "TAAYVNAIEK", metric = "MaxFWHM")
ChangePointEstimator(data = sampleData, peptide = "LVNELTEFAK", metric = "Peak Assymetry")
```

CUSUMChart

*A function to create cumulative sum charts for mean (CUSUMm) and cumulative sum charts for variability (CUSUMv) control charts*

**Description**

A function to create cumulative sum charts for mean (CUSUMm) and cumulative sum charts for variability (CUSUMv) control charts

**Usage**

```
CUSUMChart(data = NULL, peptide, L = 1, U = 5, metric,
  normalization = TRUE, ytitle = "CUSUMm", type = "mean",
  selectMean = NULL, selectSD = NULL, referenceValue = 0.5,
  decisionInterval = 5)
```

**Arguments**

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
peptide	the name of precursor of interest.
L	Lower bound of the guide set.
U	Upper bound of the guide set.
metric	the name of metric of interest.
normalization	TRUE if metric is standardized and FALSE if not standardized.
ytitle	the y-axis title of the plot. Defaults to "CUSUMm". The x-axis title is by default "Time : name of peptide"
type	the type of the control chart. Two values can be assigned, "mean" or "variability". Default is "mean"
selectMean	the mean of a metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.

`selectSD` the standard deviation of a metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.

`referenceValue` the value that is used to tune the control chart for a proper shift size

`decisionInterval` the threshold to detect an out-of-control observation

### Value

A plot of positive and negative CUSUM statistics versus time per peptide and metric generated from `CUSUM.data.prepare` data frame.

### Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Find the name of the peptides
levels(sampleData$Precursor)
# Calculate CUSUM statistics
CUSUMChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime")
CUSUMChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
  ytitle = "CUSUMv", type = "variability")
CUSUMChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
  selectMean = 27.78, selectSD = 8.19)
CUSUMChart(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea")
CUSUMChart(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea",
  selectMean = 35097129, selectSD = 34132861)
CUSUMChart(data = sampleData, peptide = "TAAYVNAIEK", metric = "MaxFWHM")
CUSUMChart(data = sampleData, peptide = "LVNELTEFAK", metric = "Peak Assymetry")
```

---

DataProcess	<i>A data processing function</i>
-------------	-----------------------------------

---

### Description

A data processing function

### Usage

```
DataProcess(data = NULL)
```

### Arguments

`data` Comma-separated (\*.csv), QC file format. It should contain a Precursor column and the metrics columns.

### Value

A data frame that processes using `input.sanity.check` function.

### Examples

```
# The data is "S9Site54" which is defined in the package.
data <- DataProcess(S9Site54)
```

---

DecisionMap	<i>A function to create heatmaps to compare performance with user defined performance criteria</i>
-------------	--

---

### Description

A function to create heatmaps to compare performance with user defined performance criteria

### Usage

```
DecisionMap(data = NULL, method = "XmR", peptideThresholdRed = 0.7,
  peptideThresholdYellow = 0.5, L = 1, U = 5, type = "mean",
  title = "heatmap plot", listMean = NULL, listSD = NULL)
```

### Arguments

data	Comma-separated (*.csv), QC file format. It should contain a Precursor column and the metrics columns.
method	It is either "CUSUM" or "XmR"
peptideThresholdRed	Is a threshold that marks percentage of peptides above it red on the heatmap. Defaults to 0.7
peptideThresholdYellow	Is a threshold that marks percentage of peptides above it and below the peptide-ThresholdRed, yellow on the heatmap. Defaults to 0.5
L	Lower bound of the guide set. Defaults to 1
U	Upper bound of the guide set. Defaults to 5
type	can take two values, "mean" or "dispersion". Defaults to "mean"
title	the title of the plot. Defaults to "heatmap plot"
listMean	List of the means for the metrics. If you don't know the means leave it as NULL and they will be calculated automatically by using L and U. The default is NULL.
listSD	List of the standard deviations for the metrics. If you don't know the standard deviations leave it as NULL and they will be calculated automatically by using L and U. The default is NULL.

### Value

A heatmap to aggregate results per metric generated from heatmap.DataFrame data frame.

### Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Draw Decision maker plot
DecisionMap(data = sampleData, method = "CUSUM")
DecisionMap(data = sampleData, method = "CUSUM", type = "variability")
DecisionMap(data = sampleData, method = "XmR")
DecisionMap(data = sampleData, method = "XmR", type = "variability")
```

```
DecisionMap(data = sampleData, method = "CUSUM", type = "mean",
  listMean = list("BestRetentionTime" = 27.78,
    "TotalArea" = 35097129,
    "MaxFWHM" = 0.28,
    "Peak Assymetry" = 0.98),
  listSD = list("BestRetentionTime" = 8.19,
    "TotalArea" = 34132861,
    "MaxFWHM" = 0.054,
    "Peak Assymetry" = 0.002)
)
```

---

MissingDataMap      *A function to summarize missing values*

---

### Description

A function to summarize missing values

### Usage

```
MissingDataMap(data)
```

### Arguments

data                  Processed data

### Value

A plot of missing values.

### Examples

```
# The data is "S9Site54" which is defined in the package.
#data <- DataProcess(S9Site54)
#MissingDataMap(data)
```

---

MSnbaseToMSstatsQC      *A function to convert MSnbase files to MSstatsQC format*

---

### Description

A function to convert MSnbase files to MSstatsQC format

### Usage

```
MSnbaseToMSstatsQC(msfile)
```

### Arguments

msfile                  data file to be converted

**Value**

A data frame that can be used with MSstatsQC

A csv file that is converted from raw files

---

QCloudDDA

*DDA QC data from QCloud System*

---

**Description**

QC results generated from QCloud system

**Usage**

data(QCloudDDA)

**Format**

csv

**Details**

DDA QC data from QCloud System

**Value**

An example dataset generated from QCloud system

---

QCloudSRM

*SRM QC data from QCloud System*

---

**Description**

QC results generated from QCloud system

**Usage**

data(QCloudSRM)

**Format**

csv

**Details**

SRM QC data from QCloud System

**Value**

An example dataset generated from QCloud system

---

QuiCDIA	<i>DIA iRT data from QuiC System</i>
---------	--------------------------------------

---

**Description**

QC results generated from QuiC system

**Usage**

```
data(QuiCDIA)
```

**Format**

csv

**Details**

DIA iRT data from QuiC System

**Value**

An example dataset generated from QuiC system

---

RadarPlot	<i>A function to create radar plot to aggregate results from X and mR charts or CUSUMm and CUSUMv charts.</i>
-----------	---

---

**Description**

A function to create radar plot to aggregate results from X and mR charts or CUSUMm and CUSUMv charts.

**Usage**

```
RadarPlot(data = NULL, L = 1, U = 5, method = "XmR",
           listMean = NULL, listSD = NULL)
```

**Arguments**

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
L	lower bound of the guide set.
U	upper bound of the guide set.
method	defines the method selected to construct control charts.
listMean	list of the means for each metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
listSD	list of the standard deviations for each metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL. automatically by using L and U. The default is NULL.



**Value**

A radar plot to aggregate results per metric generated from `XmR.Radar.Plot.DataFrame` data frame or `CUSUM.Radar.Plot.DataFrame` data frame.

**Examples**

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Draw XmR radar plot
RadarPlot(data = sampleData)
RadarPlot(data = sampleData, method = "CUSUM")
RadarPlot(data = sampleData,
           listMean = list("BestRetentionTime" = 27.78,
                          "TotalArea" = 35097129,
                          "MaxFWHM" = 0.28,
                          "Peak Assymetry" = 0.98),
           listSD = list("BestRetentionTime" = 8.19,
                        "TotalArea" = 34132861,
                        "MaxFWHM" = 0.054,
                        "Peak Assymetry" = 0.002)
           )
```

---

RemoveMissing

*A data processing function for removing missing values*

---

**Description**

A data processing function for removing missing values

**Usage**

```
RemoveMissing(data = NULL)
```

**Arguments**

`data` Comma-separated (\*.csv), QC file format. It should contain a Precursor column and the metrics columns.

**Value**

A data frame that processes using `input.sanity.check` function.

**Examples**

```
# The data is "S9Site54" which is defined in the package.
# data <- RemoveMissing(S9Site54)
```



---

S9Site54	<i>CPTAC study 9.1 site 54 dataset</i>
----------	--

---

**Description**

system suitability testing results generated during CPTAC Study 9.1 for Site 54

**Usage**

```
data(S9Site54)
```

**Format**

csv

**Details**

CPTAC system suitability testing data for Site 54 from Study 9.1

**Value**

An example dataset generated from CPTAC study 9.1

**References**

<http://www.mcponline.org/content/early/2015/02/18/mcp.M114.047050>

---

XmRChart	<i>A function to construct individual (X) and moving range (mR) control charts</i>
----------	--

---

**Description**

A function to construct individual (X) and moving range (mR) control charts

**Usage**

```
XmRChart(data = NULL, peptide, L = 1, U = 5, metric,
          normalization = FALSE, ytitle = "Individual observations",
          type = "mean", selectMean = NULL, selectSD = NULL)
```

**Arguments**

data	comma-separated (.csv), metric file. It should contain a "Precursor" column and the metrics columns. It should also include "Annotations" for each observation.
peptide	the name of precursor of interest.
L	Lower bound of the guide set.
U	Upper bound of the guide set.
metric	the name of metric of interest.

normalization	TRUE if metric is standardized and FALSE if not standardized.
ytitle	the y-axis title of the plot. Defaults to "Individual observations". The x-axis title is by default "Time : name of peptide"
type	the type of the control chart. Two values can be assigned, "mean" or "variability". Default is "mean".
selectMean	the mean of a metric. It is used when mean is known. It is NULL when mean is not known. The default is NULL.
selectSD	the standard deviation of a metric. It is used when standard deviation is known. It is NULL when mean is not known. The default is NULL.

### Value

A plot of individual values or moving ranges versus time per peptide and metric generated from XmR.data.prepare data frame.

### Examples

```
# First process the data to make sure it's ready to use
sampleData <- DataProcess(S9Site54)
head(sampleData)
# Find the name of the peptides
levels(sampleData$Precursor)
# Calculate X and mR statistics
XmRChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime")
XmRChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
          ytitle = "moving ranges", type = "variability")
XmRChart(data = sampleData, peptide = "VLVLDTDYK", metric = "BestRetentionTime",
          selectMean = 27.78, selectSD = 8.19)
XmRChart(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea")
XmRChart(data = sampleData, peptide = "DDGSWEVIEGYR", metric = "TotalArea",
          selectMean = 35097129, selectSD = 34132861)
XmRChart(data = sampleData, peptide = "TAAYVNAIEK", metric = "MaxFWHM")
XmRChart(data = sampleData, peptide = "LVNELTEFAK", metric = "Peak Assymetry")
```

# Index

- \*Topic **MSnbase**,
    - MSnbaseToMSstatsQC, [6](#)
  - \*Topic **Sum**,
    - CUSUMChart, [3](#)
  - \*Topic **XmR**,
    - XmRChart, [11](#)
  - \*Topic **XmR**
    - RadarPlot, [8](#)
    - RiverPlot, [10](#)
  - \*Topic **change**
    - ChangePointEstimator, [2](#)
  - \*Topic **chart**
    - ChangePointEstimator, [2](#)
    - CUSUMChart, [3](#)
    - XmRChart, [11](#)
  - \*Topic **control**
    - ChangePointEstimator, [2](#)
    - CUSUMChart, [3](#)
    - XmRChart, [11](#)
  - \*Topic **cumulative**
    - CUSUMChart, [3](#)
  - \*Topic **datasets**
    - QCcloudDDA, [7](#)
    - QCcloudSRM, [7](#)
    - QuiCDIA, [8](#)
    - S9Site54, [11](#)
  - \*Topic **heatmap**
    - DecisionMap, [5](#)
  - \*Topic **input**
    - MSnbaseToMSstatsQC, [6](#)
  - \*Topic **point**,
    - ChangePointEstimator, [2](#)
  - \*Topic **qcmetrics**,
    - MSnbaseToMSstatsQC, [6](#)
- ChangePointEstimator, [2](#)  
CUSUMChart, [3](#)
- DataProcess, [4](#)  
DecisionMap, [5](#)
- MissingDataMap, [6](#)  
MSnbaseToMSstatsQC, [6](#)
- QCcloudDDA, [7](#)
- QCcloudSRM, [7](#)  
QuiCDIA, [8](#)
- RadarPlot, [8](#)  
RemoveMissing, [9](#)  
RiverPlot, [10](#)
- S9Site54, [11](#)
- XmRChart, [11](#)