

# Package ‘BayesSpace’

March 6, 2021

**Version** 1.0.0

**Date** 2020-10-23

**Title** Clustering and Resolution Enhancement of Spatial Transcriptomes

**Description** Tools for clustering and enhancing the resolution of spatial gene expression experiments. BayesSpace clusters a low-dimensional representation of the gene expression matrix, incorporating a spatial prior to encourage neighboring spots to cluster together. The method can enhance the resolution of the low-dimensional representation into “sub-spots”, for which features such as gene expression or cell type composition can be imputed.

**Depends** R (>= 4.0.0), SingleCellExperiment

**Imports** Rcpp (>= 1.0.4.6), stats, purrr, scater, scran, SummarizedExperiment, coda, rhdf5, S4Vectors, Matrix, assertthat, mclust, RCurl, DirichletReg, xgboost, utils, ggplot2, scales, BiocFileCache

**License** MIT + file LICENSE

**RoxygenNote** 7.1.1

**LinkingTo** Rcpp, RcppArmadillo, RcppDist, RcppProgress

**NeedsCompilation** yes

**SystemRequirements** C++11

**Encoding** UTF-8

**Suggests** testthat, knitr, rmarkdown, igraph, spatialLIBD, dplyr, viridis, patchwork, RColorBrewer, Seurat

**VignetteBuilder** knitr

**biocViews** Software, Clustering, Transcriptomics, GeneExpression, SingleCell, ImmunoOncology, DataImport

**BugReports** <https://github.com/edward130603/BayesSpace/issues>

**URL** [edward130603.github.io/BayesSpace](https://edward130603.github.io/BayesSpace)

**git\_url** <https://git.bioconductor.org/packages/BayesSpace>

**git\_branch** RELEASE\_3\_12

**git\_last\_commit** 6398aec

**git\_last\_commit\_date** 2020-10-27

**Date/Publication** 2021-03-06

**Author** Edward Zhao [aut],  
 Matt Stone [aut, cre],  
 Xing Ren [ctb],  
 Raphael Gottardo [ctb]

**Maintainer** Matt Stone <mstone@fredhutch.org>

## R topics documented:

clusterPlot . . . . .	2
enhanceFeatures . . . . .	3
exampleSCE . . . . .	5
featurePlot . . . . .	5
getRDS . . . . .	7
mcmcChain . . . . .	7
qTune . . . . .	8
readVisium . . . . .	9
spatialCluster . . . . .	10
spatialEnhance . . . . .	12
spatialPreprocess . . . . .	14
<b>Index</b>	<b>16</b>

---

clusterPlot	<i>Plot spatial cluster assignments.</i>
-------------	--

---

### Description

Plot spatial cluster assignments.

### Usage

```
clusterPlot(
  sce,
  label = "spatial.cluster",
  palette = NULL,
  color = NULL,
  platform = NULL,
  is.enhanced = NULL,
  ...
)
```

### Arguments

sce	SingleCellExperiment. If fill is specified and is a string, it must exist as a column in colData(sce).
label	Labels used to color each spot. May be the name of a column in colData(sce), or a vector of discrete values.
palette	Optional vector of hex codes to use for discrete spot values.
color	Optional hex code to set color of borders around spots. Set to NA to remove borders.

platform	Spatial sequencing platform. If "Visium", the hex spot layout will be used, otherwise square spots will be plotted. NOTE: specifying this argument is only necessary if sce was not created by <code>spatialCluster()</code> or <code>spatialEnhance()</code> .
is.enhanced	True if sce contains subspot-level data instead of spots. Spatial sequencing platform. If true, the respective subspot lattice for each platform will be plotted. NOTE: specifying this argument is only necessary if sce was not created by <code>spatialCluster()</code> or <code>spatialEnhance()</code> .
...	Additional arguments for <code>geom_polygon()</code> . <code>size</code> , to specify the linewidth of these borders, is likely the most useful.

**Value**

Returns a ggplot object.

**See Also**

Other spatial plotting functions: [featurePlot\(\)](#)

**Examples**

```
sce <- exampleSCE()
clusterPlot(sce)
```

---

enhanceFeatures	<i>Predict feature vectors from enhanced PCs.</i>
-----------------	---

---

**Description**

Predict feature vectors from enhanced PCs.

**Usage**

```
enhanceFeatures(
  sce.enhanced,
  sce.ref,
  feature_names = NULL,
  model = c("xgboost", "dirichlet", "lm"),
  use.dimred = "PCA",
  assay.type = "logcounts",
  altExp.type = NULL,
  feature.matrix = NULL,
  rounds = 0,
  train.n = round(ncol(sce.ref) * 2/3)
)
```

**Arguments**

<code>sce.enhanced</code>	SingleCellExperiment object with enhanced PCs.
<code>sce.ref</code>	SingleCellExperiment object with original PCs and expression.
<code>feature_names</code>	List of genes/features to predict expression/values for.
<code>model</code>	Model used to predict enhanced values.
<code>use.dimred</code>	Name of dimension reduction to use.
<code>assay.type</code>	Expression matrix in <code>assays(sce.ref)</code> to predict.
<code>altExp.type</code>	Expression matrix in <code>altExps(sce.ref)</code> to predict. Overrides <code>assay.type</code> if specified.
<code>feature.matrix</code>	Expression/feature matrix to predict, if not directly attached to <code>sce.ref</code> . Must have columns corresponding to the spots in <code>sce.ref</code> . Overrides <code>assay.type</code> and <code>altExp.type</code> if specified.
<code>nrounds</code>	Nonnegative integer to set the <code>nrounds</code> parameter (max number of boosting iterations) for <code>xgboost</code> . <code>nrounds = 100</code> works reasonably well in most cases. If <code>nrounds</code> is set to 0, the parameter will be tuned using a train-test split. We recommend tuning <code>nrounds</code> for improved feature prediction, but note this will increase runtime.
<code>train.n</code>	Number of spots to use in the training dataset for tuning <code>nrounds</code> . By default, 2/3 the total number of spots are used.

**Details**

Enhanced features are computed by fitting a predictive model to a low-dimensional representation of the original expression vectors. By default, a linear model is fit for each gene using the top 15 principal components from each spot, i.e. `lm(gene ~ PCs)`, and the fitted model is used to predict the enhanced expression for each gene from the subspots' principal components.

Diagnostic measures, such as RMSE for `xgboost` or R.squared for linear regression, are added to the 'rowData' of the enhanced experiment if the features are an assay of the original experiment. Otherwise they are stored as an attribute of the returned matrix/altExp.

Note that feature matrices will be returned and are expected to be input as  $p \times n$  matrices of  $p$ -dimensional feature vectors over the  $n$  spots.

**Value**

If `assay.type` or `altExp.type` are specified, the enhanced features are stored in the corresponding slot of `sce.enhanced` and the modified SingleCellExperiment object is returned.

If `feature.matrix` is specified, or if a subset of features are requested, the enhanced features are returned directly as a matrix.

**Examples**

```
set.seed(149)
sce <- exampleSCE()
sce <- spatialCluster(sce, 7, nrep=100, burn.in=10)
enhanced <- spatialEnhance(sce, 7, init=sce$spatial.cluster, nrep=100, burn.in=10)
enhanced <- enhanceFeatures(enhanced, sce, feature_names=c("gene_1", "gene_2"))
```

---

exampleSCE	<i>Create minimal SingleCellExperiment for documentation examples.</i>
------------	--

---

**Description**

Create minimal SingleCellExperiment for documentation examples.

**Usage**

```
exampleSCE(nrow = 8, ncol = 12, n_genes = 100, n_PCs = 10)
```

**Arguments**

nrow	Number of rows of spots
ncol	Number of columns of spots
n_genes	Number of genes to simulate
n_PCs	Number of principal components to include

**Details**

Inspired by scuttle's `mockSCE()`.

**Value**

A SingleCellExperiment object with simulated counts, corresponding logcounts and PCs, and positional data in `colData`. Spots are distributed over an (`nrow` x `ncol`) rectangle.

**Examples**

```
set.seed(149)
sce <- exampleSCE()
```

---

featurePlot	<i>Plot spatial gene expression.</i>
-------------	--------------------------------------

---

**Description**

Plot spatial gene expression.

**Usage**

```
featurePlot(
  sce,
  feature,
  assay.type = "logcounts",
  diverging = FALSE,
  low = NULL,
  high = NULL,
  mid = NULL,
  color = NULL,
  platform = NULL,
  is.enhanced = NULL,
  ...
)
```

**Arguments**

sce	SingleCellExperiment. If feature is specified and is a string, it must exist as a row in the specified assay of sce.
feature	Feature vector used to color each spot. May be the name of a gene/row in an assay of sce, or a vector of continuous values.
assay.type	String indicating which assay in sce the expression vector should be taken from.
diverging	If true, use a diverging color gradient in featurePlot() (e.g. when plotting a fold change) instead of a sequential gradient (e.g. when plotting expression).
low, mid, high	Optional hex codes for low, mid, and high values of the color gradient used for continuous spot values.
color	Optional hex code to set color of borders around spots. Set to NA to remove borders.
platform	Spatial sequencing platform. If "Visium", the hex spot layout will be used, otherwise square spots will be plotted. NOTE: specifying this argument is only necessary if sce was not created by spatialCluster() or spatialEnhance().
is.enhanced	True if sce contains subspot-level data instead of spots. Spatial sequencing platform. If true, the respective subspot lattice for each platform will be plotted. NOTE: specifying this argument is only necessary if sce was not created by spatialCluster() or spatialEnhance().
...	Additional arguments for geom_polygon(). size, to specify the linewidth of these borders, is likely the most useful.

**Value**

Returns a ggplot object.

**See Also**

Other spatial plotting functions: [clusterPlot\(\)](#)

**Examples**

```
sce <- exampleSCE()
featurePlot(sce, "gene_2")
```

---

getRDS

*Download a processed sample from our S3 bucket*


---

**Description**

Datasets are cached locally using BiocFileCache. The first time using this function, you may need to consent to creating a BiocFileCache directory if one does not already exist.

**Usage**

```
getRDS(dataset, sample, cache = TRUE)
```

**Arguments**

dataset	Dataset identifier
sample	Sample identifier
cache	If true, cache the dataset locally with BiocFileCache. Otherwise, download directly from our S3 bucket. Caching saves time on subsequent loads, but consumes disk space.

**Value**

sce A SingleCellExperiment with positional information in colData and PCs based on the top 2000 HVGs

**Examples**

```
sce <- getRDS("2018_thrane_melanoma", "ST_me11_rep2", cache=FALSE)
```

---

mcmcChain

*Read MCMC chain associated with a BayesSpace clustering or enhancement*


---

**Description**

BayesSpace stores the MCMC chain associated with a clustering or enhancement on disk in an HDF5 file. The mcmcChain() function reads any parameters specified by the user into a coda::mcmc object compatible with TidyBayes.

**Usage**

```
mcmcChain(sce, params = NULL)
```

```
removeChain(sce)
```

**Arguments**

sce                    SingleCellExperiment with a file path stored in its metadata.  
 params                List of model parameters to read

**Details**

To interact with the HDF5 file directly, obtain the filename from the SingleCellExperiment's metadata: `metadata(sce)$chain.h5`. Each parameter is stored as a separate dataset in the file, and is represented as a matrix of size  $(n\_iterations \times n\_parameter\_indices)$ .

**Value**

Returns an mcmc object containing the values of the requested parameters over the constructed chain.

**Examples**

```
set.seed(149)
sce <- exampleSCE()
sce <- spatialCluster(sce, 7, nrep=100, burn.in=10, save.chain=TRUE)
chain <- mcmcChain(sce)
removeChain(sce)
```

---

qTune	<i>Tuning the choice of q (number of clusters) before running spatialCluster</i>
-------	--

---

**Description**

Before running `spatialCluster()`, we recommend tuning the choice of  $q$  by choosing the  $q$  that maximizes the model's negative log likelihood over early iterations. `qTune()` computes the average negative log likelihood for a range of  $q$  values over iterations 100:1000, and `qPlot()` displays the results.

**Usage**

```
qPlot(sce, qs = seq(3, 7), force.retune = FALSE, ...)
qTune(sce, qs = seq(3, 7), burn.in = 100, nrep = 1000, ...)
```

**Arguments**

sce                    A SingleCellExperiment object containing the spatial data.  
 qs                    The values of  $q$  to evaluate.  
 force.retune        If specified, existing tuning values in `sce` will be overwritten.  
 ...                    Other parameters are passed to `spatialCluster()`.  
 burn.in, nrep        Integers specifying the range of repetitions to compute.



## Details

qTune() takes the same parameters as spatialCluster() and will run the MCMC clustering algorithm up to nrep iterations for each value of q. The first burn.in iterations are discarded as burn-in and the log likelihood is averaged over the remaining iterations.

qPlot() plots the computed negative log likelihoods as a function of q. If qTune() was run previously, i.e. there exists an attribute of sce named "q.logliks", the pre-computed results are displayed. Otherwise, or if force.retune is specified, qplot() will automatically run qTune() before plotting (and can take the same parameters as spatialCluster()).

## Value

qTune() returns a modified sce with tuning log likelihoods stored as an attribute named "q.logliks".

qPlot() returns a ggplot object.

## Examples

```
set.seed(149)
sce <- exampleSCE()
sce <- qTune(sce, seq(3, 7), burn.in=10, nrep=100)
qPlot(sce)
```

---

readVisium

*Load a Visium spatial dataset as a SingleCellExperiment.*

---

## Description

Load a Visium spatial dataset as a SingleCellExperiment.

## Usage

```
readVisium(dirname)
```

## Arguments

dirname Path to spaceranger output directory (e.g. "sampleID/outs/"). This directory must contain the counts matrix and feature/barcode TSVs in filtered\_feature\_bc\_matrix/, and the spot positions at spatial/tissue\_positions\_list.csv. (These are default locations for spaceranger outputs.)

## Details

We store two variables associated with downstream BayesSpace functions in a list called BayesSpace.data in the SingleCellExperiment's metadata.

- platform is set to "Visium", and is used to determine spot layout and neighborhood structure.
- is.enhanced is set to FALSE to denote the object contains spot-level data.

**Value**

SingleCellExperiment containing the counts matrix in counts and spatial data in colData. Array coordinates for each spot are stored in columns row and col, while image coordinates are stored in columns imagerow and imagecol.

**Examples**

```
## Not run:
sce <- readVisium("path/to/outs/")

## End(Not run)
```

---

<code>spatialCluster</code>	<i>Spatial clustering</i>
-----------------------------	---------------------------

---

**Description**

Cluster a spatial expression dataset.

**Usage**

```
spatialCluster(
  sce,
  q,
  use.dimred = "PCA",
  d = 15,
  platform = c("Visium", "ST"),
  init = NULL,
  init.method = c("mclust", "kmeans"),
  model = c("t", "normal"),
  precision = c("equal", "variable"),
  nrep = 50000,
  burn.in = 1000,
  gamma = NULL,
  mu0 = NULL,
  lambda0 = NULL,
  alpha = 1,
  beta = 0.01,
  save.chain = FALSE,
  chain.fname = NULL
)
```

**Arguments**

<code>sce</code>	A SingleCellExperiment object containing the spatial data.
<code>q</code>	The number of clusters.
<code>use.dimred</code>	Name of a reduced dimensionality result in <code>reducedDims(sce)</code> . If provided, cluster on these features directly.
<code>d</code>	Number of top principal components to use when clustering.

platform	Spatial transcriptomic platform. Specify 'Visium' for hex lattice geometry or 'ST' for square lattice geometry. Specifying this parameter is optional when analyzing SingleCellExperiments processed using <a href="#">readVisium</a> or <a href="#">spatialPreprocess</a> , as this information is included in their metadata.
init	Initial cluster assignments for spots.
init.method	If <code>init</code> is not provided, cluster the top <code>d</code> PCs with this method to obtain initial cluster assignments.
model	Error model. ('normal' or 't')
precision	Covariance structure. ('equal' or 'variable' for EEE and VVV covariance models, respectively.)
nrep	The number of MCMC iterations.
burn.in	The number of MCMC iterations to exclude as burn-in period.
gamma	Smoothing parameter. Defaults to 2 for <code>platform="ST"</code> and 3 for <code>platform="Visium"</code> . (Values in range of 1-3 seem to work well.)
mu0	Prior mean hyperparameter for <code>mu</code> . If not provided, <code>mu0</code> is set to the mean of PCs over all spots.
lambda0	Prior precision hyperparam for <code>mu</code> . If not provided, <code>lambda0</code> is set to a diagonal matrix $0.01I$ .
alpha	Hyperparameter for Wishart distributed precision <code>lambda</code> .
beta	Hyperparameter for Wishart distributed precision <code>lambda</code> .
save.chain	If true, save the MCMC chain to an HDF5 file.
chain.fname	File path for saved chain. Tempfile used if not provided.

### Details

The input SCE must have `row` and `col` columns in its `colData`, corresponding to the array row and column coordinates of each spot. These are automatically parsed by [readVisium](#) or can be added manually when creating the SCE.

Cluster labels are stored in the `spatial.cluster` column of the SCE, and the cluster initialization is stored in `cluster.init`.

### Value

Returns a modified `sce` with cluster assignments stored in `colData` under the name `spatial.cluster`.

### See Also

[spatialPreprocess](#) for preparing the SCE for clustering, [spatialEnhance](#) for enhancing the clustering resolution, [clusterPlot](#) for visualizing the cluster assignments, [featurePlot](#) for visualizing expression levels in spatial context, and [mcmcChain](#) for examining the full MCMC chain associated with the clustering.

### Examples

```
set.seed(149)
sce <- exampleSCE()
sce <- spatialCluster(sce, 7, nrep=100, burn.in=10)
```

---

spatialEnhance                      *Enhance spot resolution*

---

## Description

Backend calls `iterate_deconv()`, written in Rcpp. Inputs are the same as `spatialCluster()` except you have to specify `xdist` and `ydist` instead of `total dist...` (maybe would be better to change `spatialCluster` to match this)

## Usage

```
spatialEnhance(
  sce,
  q,
  platform = c("Visium", "ST"),
  use.dimred = "PCA",
  d = 15,
  init = NULL,
  init.method = c("spatialCluster", "mclust", "kmeans"),
  model = c("t", "normal"),
  nrep = 2e+05,
  gamma = NULL,
  mu0 = NULL,
  lambda0 = NULL,
  alpha = 1,
  beta = 0.01,
  save.chain = FALSE,
  chain.fname = NULL,
  burn.in = 10000,
  jitter_scale = 5,
  jitter_prior = 0.3,
  verbose = FALSE
)
```

## Arguments

<code>sce</code>	A <code>SingleCellExperiment</code> object containing the spatial data.
<code>q</code>	The number of clusters.
<code>platform</code>	Spatial transcriptomic platform. Specify 'Visium' for hex lattice geometry or 'ST' for square lattice geometry. Specifying this parameter is optional when analyzing <code>SingleCellExperiments</code> processed using <a href="#">readVisium</a> , <a href="#">spatialPreprocess</a> , or <a href="#">spatialCluster</a> , as this information is included in their metadata.
<code>use.dimred</code>	Name of a reduced dimensionality result in <code>reducedDims(sce)</code> . If provided, cluster on these features directly.
<code>d</code>	Number of top principal components to use when clustering.
<code>init</code>	Initial cluster assignments for spots.
<code>init.method</code>	If <code>init</code> is not provided, cluster the top <code>d</code> PCs with this method to obtain initial cluster assignments.
<code>model</code>	Error model. ('normal' or 't')

nrep	The number of MCMC iterations.
gamma	Smoothing parameter. (Values in range of 1-3 seem to work well.)
mu0	Prior mean hyperparameter for mu. If not provided, mu0 is set to the mean of PCs over all spots.
lambda0	Prior precision hyperparam for mu. If not provided, lambda0 is set to a diagonal matrix $0.01I$ .
alpha	Hyperparameter for Wishart distributed precision lambda.
beta	Hyperparameter for Wishart distributed precision lambda.
save.chain	If true, save the MCMC chain to an HDF5 file.
chain.fname	File path for saved chain. Tempfile used if not provided.
burn.in	Number of iterations to exclude as burn-in period. The MCMC iterations are currently thinned to every 100; accordingly burn.in is rounded down to the nearest multiple of 100.
jitter_scale	Controls the amount of jittering. Small amounts of jittering are more likely to be accepted but result in exploring the space more slowly. We suggest tuning jitter_scale so that Ychange is on average around 30%.
jitter_prior	Scale factor for the prior variance, parameterized as the proportion (default = 0.3) of the mean variance of the PCs. We suggest making jitter_prior smaller if the jittered values are not expected to vary much from the overall mean of the spot.
verbose	Log progress to stderr.

## Details

The enhanced `SingleCellExperiment` has most of the properties of the input SCE - `rowData`, `colData`, `reducedDims` - but does not include expression data in counts or logcounts. To impute enhanced expression vectors, please use `[enhanceFeatures()]` after running `spatialEnhance`.

The `colData` of the enhanced `SingleCellExperiment` includes the following columns to permit referencing the subspots in spatial context and linking back to the original spots:

- `spot.idx`: Index of the spot this subspot belongs to (with respect to the input SCE).
- `subspot.idx`: Index of the subspot within its parent spot.
- `spot.row`: Array row of the subspot's parent spot.
- `spot.col`: Array col of the subspot's parent spot.
- `row`: Array row of the subspot. This is the parent spot's row plus an offset based on the subspot's position within the spot.
- `col`: Array col of the subspot. This is the parent spot's col plus an offset based on the subspot's position within the spot.
- `imagerow`: Pixel row of the subspot. This is the parent spot's row plus an offset based on the subspot's position within the spot.
- `imagecol`: Pixel col of the subspot. This is the parent spot's col plus an offset based on the subspot's position within the spot.

## Value

Returns a new `SingleCellExperiment` object. By default, the assays of this object are empty, and the enhanced resolution PCs are stored as a reduced dimensionality result accessible with `reducedDim(sce, 'PCA')`.

**See Also**

[spatialCluster](#) for clustering at the spot level before enhancing, [clusterPlot](#) for visualizing the cluster assignments, [enhanceFeatures](#) for imputing enhanced expression, and [mcmcChain](#) for examining the full MCMC chain associated with the enhanced clustering. .

**Examples**

```
set.seed(149)
sce <- exampleSCE()
sce <- spatialCluster(sce, 7, nrep=100, burn.in=10)
enhanced <- spatialEnhance(sce, 7, nrep=100, burn.in=10)
```

---

spatialPreprocess      *Preprocess a spatial dataset for BayesSpace*

---

**Description**

Adds metadata required for downstream analyses, and (optionally) performs PCA on log-normalized expression of top HVGs.

**Usage**

```
spatialPreprocess(
  sce,
  platform = c("Visium", "ST"),
  n.PCs = 15,
  n.HVGs = 2000,
  skip.PCA = FALSE,
  log.normalize = TRUE,
  assay.type = "logcounts"
)
```

**Arguments**

sce	SingleCellExperiment to preprocess
platform	Spatial sequencing platform. Used to determine spot layout and neighborhood structure (Visium = hex, ST = square).
n.PCs	Number of principal components to compute. We suggest using the top 15 PCs in most cases.
n.HVGs	Number of highly variable genes to run PCA upon.
skip.PCA	Skip PCA (if dimensionality reduction was previously computed.)
log.normalize	Whether to log-normalize the input data with scater. May be omitted if log-normalization previously computed.
assay.type	Name of assay in sce containing normalized counts. Leave as "logcounts" unless you explicitly pre-computed a different normalization and added it to sce under another assay. Note that we do not recommend running BayesSpace on PCs computed from raw counts.

**Value**

SingleCellExperiment with PCA and BayesSpace metadata

**Examples**

```
sce <- exampleSCE()  
sce <- spatialPreprocess(sce)
```

# Index

## \* **spatial plotting functions**

clusterPlot, [2](#)

featurePlot, [5](#)

clusterPlot, [2](#), [6](#), [11](#), [14](#)

enhanceFeatures, [3](#), [14](#)

exampleSCE, [5](#)

featurePlot, [3](#), [5](#), [11](#)

getRDS, [7](#)

mcmcChain, [7](#), [11](#), [14](#)

qPlot (qTune), [8](#)

qTune, [8](#)

readVisium, [9](#), [11](#), [12](#)

removeChain (mcmcChain), [7](#)

spatialCluster, [10](#), [12](#), [14](#)

spatialEnhance, [11](#), [12](#)

spatialPreprocess, [11](#), [12](#), [14](#)