

Package ‘ChIPpeakAnno’

January 24, 2021

Type Package

Title Batch annotation of the peaks identified from either ChIP-seq, ChIP-chip experiments or any experiments resulted in large number of chromosome ranges

Version 3.24.1

Encoding UTF-8

Author Lihua Julie Zhu, Jianhong Ou, Jun Yu, Kai Hu, Haibo Liu, Hervé Pagès, Claude Gazin, Nathan Lawson, Ryan Thompson, Simon Lin, David Lapointe and Michael Green

Maintainer Jianhong Ou <ou.jianhong@gmail.com>, Lihua Julie Zhu <julie.zhu@umassmed.edu>

Depends R (>= 3.5), methods, IRanges (>= 2.13.12), GenomicRanges (>= 1.31.8), S4Vectors (>= 0.17.25)

Imports AnnotationDbi, BiocGenerics (>= 0.1.0), Biostrings (>= 2.47.6), DBI, ensemblDb, GenomeInfoDb, GenomicAlignments, GenomicFeatures, RBGL, Rsamtools, SummarizedExperiment, VennDiagram, biomaRt, ggplot2, grDevices, graph, graphics, grid, KEGGREST, matrixStats, multtest, regioneR, rtracklayer, stats, utils

Suggests BSgenome, limma, reactome.db, BiocManager, BiocStyle, BSgenome.Ecoli.NCBI.20080805, BSgenome.Hsapiens.UCSC.hg19, org.Ce.eg.db, org.Hs.eg.db, BSgenome.Celegans.UCSC.ce10, BSgenome.Drerio.UCSC.danRer7, BSgenome.Hsapiens.UCSC.hg38, DelayedArray, idr, seqinr, EnsDb.Hsapiens.v75, EnsDb.Hsapiens.v79, TxDb.Hsapiens.UCSC.hg19.knownGene, TxDb.Hsapiens.UCSC.hg38.knownGene, GO.db, gplots, UpSetR, knitr, rmarkdown, testthat, trackViewer, motifStack, OrganismDbi

Description The package includes functions to retrieve the sequences around the peak, obtain enriched Gene Ontology (GO) terms, find the nearest gene, exon, miRNA or custom features such as most conserved elements and other transcription factor binding sites supplied by users. Starting 2.0.5, new functions have been added for finding the peaks with bi-directional promoters with summary statistics (peaksNearBDP), for summarizing the occurrence of motifs in peaks (summarizePatternInPeaks) and for

adding other IDs to annotated peaks or enrichedGO (addGeneIDs).
 This package leverages the biomaRt, IRanges, Biostrings,
 BSgenome, GO.db, multtest and stat packages.

License GPL (>= 2)

LazyLoad yes

LazyData true

biocViews Annotation, ChIPSeq, ChIPchip

VignetteBuilder knitr

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/ChIPpeakAnno>

git_branch RELEASE_3_12

git_last_commit 1cc103f

git_last_commit_date 2020-10-29

Date/Publication 2021-01-23

R topics documented:

ChIPpeakAnno-package	4
addAncestors	5
addGeneIDs	6
addMetadata	8
annoGR-class	9
annoPeaks	10
annotatedPeak	12
annotatePeakInBatch	13
assignChromosomeRegion	17
bdp	20
bindist-class	21
binOverFeature	21
binOverGene	22
binOverRegions	23
ChIPpeakAnno-deprecated	25
cntOverlaps	26
condenseMatrixByColnames	26
convert2EntrezID	27
countPatternInSeqs	27
cumulativePercentage	28
downstreams	29
egOrgMap	30
enrichedGO	31
enrichmentPlot	32
EnsDb2GR	33
estFragmentLength	33
estLibSize	34
ExonPlusUtr.human.GRCh37	35
featureAlignedDistribution	36
featureAlignedExtendSignal	37
featureAlignedHeatmap	39

featureAlignedSignal	40
findEnhancers	41
findMotifsInPromoterSeqs	43
findOverlappingPeaks	45
findOverlapsOfPeaks	47
genomicElementDistribution	49
genomicElementUpSetR	51
getAllPeakSequence	52
getAnnotation	53
getEnrichedGO	54
getEnrichedPATH	57
getGO	58
getVennCounts	59
HOT.spots	60
IDRfilter	62
makeVennDiagram	63
mergePlusMinusPeaks	65
metagenePlot	67
myPeakList	68
oligoFrequency	68
oligoSummary	69
peakPermTest	70
Peaks.Ste12.Replicate1	72
Peaks.Ste12.Replicate2	73
Peaks.Ste12.Replicate3	73
peaksNearBDP	74
permPool-class	76
pie1	76
plotBinOverRegions	78
preparePool	79
reCenterPeaks	80
summarizeOverlapsByBins	80
summarizePatternInPeaks	82
tileCount	83
tileGRanges	84
toGRanges	85
translatePattern	87
TSS.human.GRCh37	88
TSS.human.GRCh38	88
TSS.human.NCBI36	89
TSS.mouse.GRCm38	90
TSS.mouse.NCBIM37	90
TSS.rat.RGSC3.4	91
TSS.rat.Rnor_5.0	92
TSS.zebrafish.Zv8	92
TSS.zebrafish.Zv9	93
TxDB2GR	94
wgEncodeTfbsV3	94
write2FASTA	95
xget	96

ChIPpeakAnno-package *Batch annotation of the peaks identified from either ChIP-seq or ChIP-chip experiments.*

Description

The package includes functions to retrieve the sequences around the peak, obtain enriched Gene Ontology (GO) terms, find the nearest gene, exon, miRNA or custom features such as most conserved elements and other transcription factor binding sites leveraging biomaRt, IRanges, Biostrings, BSgenome, GO.db, hypergeometric test phyper and multtest package.

Details

Package:	ChIPpeakAnno
Type:	Package
Version:	3.0.0
Date:	2014-10-24
License:	LGPL
LazyLoad:	yes

Author(s)

Lihua Julie Zhu, Jianhong Ou, Hervé Pagès, Claude Gazin, Nathan Lawson, Simon Lin, David Lapointe and Michael Green

Maintainer: Jianhong Ou <jianhong.ou@umassmed.edu>, Lihua Julie Zhu <julie.zhu@umassmed.edu>

References

1. Y. Benjamini and Y. Hochberg (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *J. R. Statist. Soc. B.* Vol. 57: 289-300.
2. Y. Benjamini and D. Yekutieli (2001). The control of the false discovery rate in multiple hypothesis testing under dependency. *Annals of Statistics*. Accepted.
3. S. Durinck et al. (2005) BioMart and Bioconductor: a powerful link between biological biomarts and microarray data analysis. *Bioinformatics*, 21, 3439-3440.
4. S. Dudoit, J. P. Shaffer, and J. C. Boldrick (Submitted). Multiple hypothesis testing in microarray experiments.
5. Y. Ge, S. Dudoit, and T. P. Speed. Resampling-based multiple testing for microarray data hypothesis, Technical Report #633 of UCB Stat. <http://www.stat.berkeley.edu/~gyc>
6. Y. Hochberg (1988). A sharper Bonferroni procedure for multiple tests of significance, *Biometrika*. Vol. 75: 800-802.
7. S. Holm (1979). A simple sequentially rejective multiple test procedure. *Scand. J. Statist.*. Vol. 6: 65-70.
8. N. L. Johnson, S. Kotz and A. W. Kemp (1992) *Univariate Discrete Distributions*, Second Edition. New York: Wiley
9. Zhu L.J. et al. (2010) ChIPpeakAnno: a Bioconductor package to annotate ChIP-seq and ChIP-chip data. *BMC Bioinformatics* 2010, 11:237doi:10.1186/1471-2105-11-237.

Examples

```
if(interactive()){
  data(myPeakList)
  library(ensemldb)
  library(EnsDb.Hsapiens.v75)
  anno <- annoGR(EnsDb.Hsapiens.v75)
  annotatedPeak <-
    annotatePeakInBatch(myPeakList[1:6], AnnotationData=anno)
}
```

addAncestors

Add GO IDs of the ancestors for a given vector of GO ids

Description

Add GO IDs of the ancestors for a given vector of GO IDs leveraging GO.db

Usage

```
addAncestors(go.ids, ontology = c("bp", "cc", "mf"))
```

Arguments

go.ids	A matrix with 4 columns: first column is GO IDs and 4th column is entrez IDs.
ontology	bp for biological process, cc for cellular component and mf for molecular function.

Value

A vector of GO IDs containing the input GO IDs with the GO IDs of their ancestors added.

Author(s)

Lihua Julie Zhu

Examples

```
go.ids = cbind(c("GO:0008150", "GO:0005576", "GO:0003674"),
              c("ND", "IDA", "ND"),
              c("BP", "BP", "BP"),
              c("1", "1", "1"))
library(GO.db)
addAncestors(go.ids, ontology="bp")
```

addGeneIDs	<i>Add common IDs to annotated peaks such as gene symbol, entrez ID, ensemble gene id and refseq id.</i>
------------	--

Description

Add common IDs to annotated peaks such as gene symbol, entrez ID, ensemble gene id and refseq id leveraging organism annotation dataset. For example, org.Hs.eg.db is the dataset from orgs.Hs.eg.db package for human, while org.Mm.eg.db is the dataset from the org.Mm.eg.db package for mouse.

Usage

```
addGeneIDs(
  annotatedPeak,
  orgAnn,
  IDs2Add = c("symbol"),
  feature_id_type = "ensembl_gene_id",
  silence = TRUE,
  mart
)
```

Arguments

annotatedPeak	GRanges or a vector of feature IDs.
orgAnn	organism annotation dataset such as org.Hs.eg.db.
IDs2Add	a vector of annotation identifiers to be added
feature_id_type	type of ID to be annotated, default is ensembl_gene_id
silence	TRUE or FALSE. If TRUE, will not show unmapped entrez id for feature ids.
mart	mart object, see useMart of biomaRt package for details

Details

One of orgAnn and mart should be assigned.

- If orgAnn is given, parameter feature_id_type should be ensembl_gene_id, entrez_id, gene_symbol, gene_alias or refseq_id. And parameter IDs2Add can be set to any combination of identifiers such as "accnum", "ensembl", "ensemblprot", "ensembltrans", "entrez_id", "enzyme", "genename", "pfam", "pmid", "prosite", "refseq", "symbol", "unigene" and "uniprot". Some IDs are unique to an organism, such as "omim" for org.Hs.eg.db and "mgi" for org.Mm.eg.db.

Here is the definition of different IDs :

- accnum: GenBank accession numbers
- ensembl: Ensembl gene accession numbers
- ensemblprot: Ensembl protein accession numbers
- ensembltrans: Ensembl transcript accession numbers
- entrez_id: entrez gene identifiers
- enzyme: EC numbers
- genename: gene name

- pfam: Pfam identifiers
 - pmid: PubMed identifiers
 - prosite: PROSITE identifiers
 - refseq: RefSeq identifiers
 - symbol: gene abbreviations
 - unigene: UniGene cluster identifiers
 - uniprot: Uniprot accession numbers
 - omim: OMIM(Mendelian Inheritance in Man) identifiers
 - mgi: Jackson Laboratory MGI gene accession numbers
- If mart is used instead of orgAnn, for valid parameter feature_id_type and IDs2Add parameters, please refer to [getBM](#) in bioMart package. Parameter feature_id_type should be one valid filter name listed by [listFilters\(mart\)](#) such as ensemble_gene_id. And parameter IDs2Add should be one or more valid attributes name listed by [listAttributes\(mart\)](#) such as external_gene_id, entrezgene, wikigene_name, or mirbase_transcript_name.

Value

GRanges if the input is a GRanges or dataframe if input is a vector.

Author(s)

Jianhong Ou, Lihua Julie Zhu

References

<http://www.bioconductor.org/packages/release/data/annotation/>

See Also

[getBM](#), [AnnotationDb](#)

Examples

```
data(annotatedPeak)
library(org.Hs.eg.db)
addGeneIDs(annotatedPeak[1:6,],orgAnn="org.Hs.eg.db",
           IDs2Add=c("symbol","omim"))
##addGeneIDs(annotatedPeak$feature[1:6],orgAnn="org.Hs.eg.db",
##           IDs2Add=c("symbol","genename"))
if(interactive()){
  mart <- useMart("ENSEMBL_MART_ENSEMBL",host="www.ensembl.org",
                dataset="hsapiens_gene_ensembl")
  ##mart <- useMart(biomart="ensembl",dataset="hsapiens_gene_ensembl")
  addGeneIDs(annotatedPeak[1:6,], mart=mart,
            IDs2Add=c("hgnc_symbol","entrezgene"))
}
```

addMetadata *Add metadata of the GRanges objects used for findOverlapsOfPeaks*

Description

Add metadata to overlapping peaks after calling `findOverlapsOfPeaks`.

Usage

```
addMetadata(ol, colNames = NULL, FUN = c, ...)
```

Arguments

<code>ol</code>	An object of <code>overlappingPeaks</code> , which is output of <code>findOverlapsOfPeaks</code> .
<code>colNames</code>	Names of metadata column to be added. If it is <code>NULL</code> , <code>addMetadata</code> will guess what to add.
<code>FUN</code>	A function to be called
<code>...</code>	Arguments to the function call.

Value

return value is An object of `overlappingPeaks`.

Author(s)

Jianhong Ou

See Also

See Also as [findOverlapsOfPeaks](#)

Examples

```
peaks1 <- GRanges(seqnames=c(6,6,6,6,5),
  IRanges(start=c(1543200,1557200,1563000,1569800,167889600),
    end=c(1555199,1560599,1565199,1573799,167893599),
    names=c("p1","p2","p3","p4","p5")),
  strand="+",
  score=1:5, id=letters[1:5])
peaks2 <- GRanges(seqnames=c(6,6,6,6,5),
  IRanges(start=c(1549800,1554400,1565000,1569400,167888600),
    end=c(1550599,1560799,1565399,1571199,167888999),
    names=c("f1","f2","f3","f4","f5")),
  strand="+",
  score=6:10, id=LETTERS[1:5])
ol <- findOverlapsOfPeaks(peaks1, peaks2)
addMetadata(ol)
```

annoGR-class	<i>Class</i> annoGR
--------------	---------------------

Description

An object of class annoGR represents the annotation data could be used by annotationPeakInBatch.

Usage

```
## S4 method for signature 'annoGR'
info(object)

## S4 method for signature 'GRanges'
annoGR(ranges, feature = "group", date, ...)

## S4 method for signature 'TxDb'
annoGR(
  ranges,
  feature = c("gene", "transcript", "exon", "CDS", "fiveUTR", "threeUTR", "microRNA",
             "tRNAs", "geneModel"),
  date,
  source,
  mdata,
  OrganismDb
)

## S4 method for signature 'EnsDb'
annoGR(
  ranges,
  feature = c("gene", "transcript", "exon", "disjointExons"),
  date,
  source,
  mdata
)
```

Arguments

object	annoGR object.
ranges	an object of GRanges , TxDb or EnsDb
feature	annotation type
date	a Date object
...	could be following parameters
source	character, where the annotation comes from
mdata	data frame, metadata from annotation
OrganismDb	an object of OrganismDb . It is used for extracting gene symbol for geneModel group for TxDb

Slots

seqnames, ranges, strand, elementMetadata, seqinfo slots inherit from [GRanges](#). The ranges must have unique names.

source character, where the annotation comes from

date a [Date](#) object

feature annotation type, could be "gene", "exon", "transcript", "CDS", "fiveUTR", "threeUTR", "microRNA", "tRNAs", "geneModel" for [TxDb](#) object, or "gene", "exon", "transcript" for [EnsDb](#) object

mdata data frame, metadata from annotation

Objects from the Class

Objects can be created by calls of the form `new("annoGR", date, elementMetadata, feature, mdata, ranges, seqinfo`

Author(s)

Jianhong Ou

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library(EnsDb.Hsapiens.v79)
  anno <- annoGR(EnsDb.Hsapiens.v79)
}
```

annoPeaks

Annotate peaks

Description

Annotate peaks by annoGR object in the given range.

Usage

```
annoPeaks(
  peaks,
  annoData,
  bindingType = c("nearestBiDirectionalPromoters", "startSite", "endSite", "fullRange"),
  bindingRegion = c(-5000, 5000),
  ignore.peak.strand = TRUE,
  select = c("all", "bestOne"),
  ...
)
```

Arguments

peaks	peak list, GRanges object
annoData	annotation data, GRanges object
bindingType	<p>Specifying the criteria to associate peaks with annotation. Here is how to use it together with the parameter bindingRegion</p> <ul style="list-style-type: none"> • To obtain peaks within 5kb upstream and up to 3kb downstream of TSS within the gene body, set bindingType = "startSite" and bindingRegion = c(-5000, 3000) • To obtain peaks up to 5kb upstream within the gene body and 3kb downstream of gene/Exon End, set bindingType = "endSite" and bindingRegion = c(-5000, 3000) • To obtain peaks from 5kb upstream to 3kb downstream of genes/Exons , set bindingType = "fullRange" and bindingRegion = c(-5000, 3000) • To obtain peaks with nearest bi-directional promoters within 5kb upstream and 3kb downstream of TSS, set bindingType = "nearestBiDirectionalPromoters" and bindingRegion = c(-5000, 3000) <p>startSite start position of the feature (strand is considered) endSite end position of the feature (strand is considered) fullRange whole range of the feature nearestBiDirectionalPromoters nearest promoters from both direction of the peaks (strand is considered). It will report bidirectional promoters if there are promoters in both directions in the given region (defined by bindingRegion). Otherwise, it will report the closest promoter in one direction.</p>
bindingRegion	Annotation range used together with bindingType, which is a vector with two integer values, default to c (-5000, 5000). The first one must be no bigger than 0, which means upstream. And the second one must be no less than 1, which means downstream (1 is the site position, 2 is the next base of the site position). For details, see bindingType.
ignore.peak.strand	ignore the peaks strand or not.
select	"all" or "bestOne". Return the annotation containing all or the best one. The "bestOne" is selected by the shortest distance to the sites and then similarity between peak and annotations. Ignored if bindingType is nearestBiDirectionalPromoters.
...	Not used.

Value

Output is a [GRanges](#) object of the annotated peaks.

Author(s)

Jianhong Ou

See Also

See Also as [annotatePeakInBatch](#)

Examples

```
library(ensemldb)
library(EnsDb.Hsapiens.v75)
data("myPeakList")
annoGR <- toGRanges(EnsDb.Hsapiens.v75)
seqlevelsStyle(myPeakList) <- seqlevelsStyle(annoGR)
annoPeaks(myPeakList, annoGR)
```

annotatedPeak

Annotated Peaks

Description

TSS annotated putative STAT1-binding regions that are identified in un-stimulated cells using ChIP-seq technology (Robertson et al., 2007)

Usage

```
annotatedPeak
```

Format

GRanges with slot start holding the start position of the peak, slot end holding the end position of the peak, slot names holding the id of the peak, slot strand holding the strands and slot space holding the chromosome location where the peak is located. In addition, the following variables are included.

list("feature") id of the feature such as ensembl gene ID

list("insideFeature") upstream: peak resides upstream of the feature; downstream: peak resides downstream of the feature; inside: peak resides inside the feature; overlapStart: peak overlaps with the start of the feature; overlapEnd: peak overlaps with the end of the feature; includeFeature: peak include the feature entirely

list("distancetoFeature") distance to the nearest feature such as transcription start site

list("start_position") start position of the feature such as gene

list("end_position") end position of the feature such as the gene

Details

obtained by data(TSS.human.GRCh37)

```
data(myPeakList)
```

```
annotatePeakInBatch(myPeakList, AnnotationData = TSS.human.GRCh37, output="b", multiple=F)
```

Examples

```
data(annotatedPeak)
head(annotatedPeak, 4) # show first 4 ranges
if (interactive() || Sys.getenv("USER")=="jianhongou") {
y = annotatedPeak$distancetoFeature[!is.na(annotatedPeak$distancetoFeature)]
hist(as.numeric(as.character(y)),
      xlab="Distance To Nearest TSS", main="", breaks=1000,
      ylim=c(0, 50), xlim=c(min(as.numeric(as.character(y)))-100,
max(as.numeric(as.character(y)))+100))
}
```

annotatePeakInBatch	<i>Obtain the distance to the nearest TSS, miRNA, and/or exon for a list of peaks</i>
---------------------	---

Description

Obtain the distance to the nearest TSS, miRNA, exon et al for a list of peak locations leveraging IRanges and biomaRt package

Usage

```
annotatePeakInBatch(
  myPeakList,
  mart,
  featureType = c("TSS", "miRNA", "Exon"),
  AnnotationData,
  output = c("nearestLocation", "overlapping", "both", "shortestDistance", "inside",
    "upstream&inside", "inside&downstream", "upstream", "downstream",
    "upstreamORdownstream", "nearestBiDirectionalPromoters"),
  multiple = c(TRUE, FALSE),
  maxgap = -1L,
  PeakLocForDistance = c("start", "middle", "end"),
  FeatureLocForDistance = c("TSS", "middle", "start", "end", "geneEnd"),
  select = c("all", "first", "last", "arbitrary"),
  ignore.strand = TRUE,
  bindingRegion = NULL,
  ...
)
```

Arguments

myPeakList	A GRanges object
mart	A mart object, used if AnnotationData is not supplied, see useMart of bioMaRt package for details
featureType	A character vector used with mart argument if AnnotationData is not supplied; it's value is "TSS", "miRNA" or "Exon"

AnnotationData	A GRanges or annoGR object. It can be obtained from function <code>getAnnotation</code> or customized annotation of class <code>GRanges</code> containing additional variable: <code>strand</code> (1 or + for plus strand and -1 or - for minus strand). Pre-compiled annotations, such as <code>TSS.human.NCBI36</code> , <code>TSS.mouse.NCBIM37</code> , <code>TSS.rat.RGSC3.4</code> and <code>TSS.zebrafish.Zv8</code> , are provided by this package (attach them with <code>data()</code> function). Another method to provide annotation data is to obtain through <code>biomaRt</code> real time by using the parameters of <code>mart</code> and <code>featureType</code>
output	<p>nearestLocation (default) will output the nearest features calculated as <code>PeakLoc - FeatureLocForDistance</code></p> <p>overlapping will output overlapping features with maximum gap specified as <code>maxgap</code> between peak range and feature range</p> <p>shortestDistance will output nearest features</p> <p>both will output all the nearest features, in addition, will output any features that overlap the peak that is not the nearest features</p> <p>upstream&inside will output all upstream and overlapping features with maximum gap</p> <p>inside&downstream will output all downstream and overlapping features with maximum gap</p> <p>upstream will output all upstream features with maximum gap.</p> <p>downstream will output all downstream features with maximum gap.</p> <p>upstreamORdownstream will output all upstream features with maximum gap or downstream with maximum gap</p> <p>nearestBiDirectionalPromoters will use annoPeaks to annotate peaks. Nearest promoters from both direction of the peaks (<code>strand</code> is considered). It will report bidirectional promoters if there are promoters in both directions in the given region (defined by <code>bindingRegion</code>). Otherwise, it will report the closest promoter in one direction.</p>
multiple	Not applicable when output is nearest. TRUE: output multiple overlapping features for each peak. FALSE: output at most one overlapping feature for each peak. This parameter is kept for backward compatibility, please use <code>select</code> .
maxgap	The maximum <i>gap</i> that is allowed between 2 ranges for the ranges to be considered as overlapping. The <i>gap</i> between 2 ranges is the number of positions that separate them. The <i>gap</i> between 2 adjacent ranges is 0. By convention when one range has its start or end strictly inside the other (i.e. non-disjoint ranges), the <i>gap</i> is considered to be -1.
PeakLocForDistance	Specify the location of peak for calculating distance, i.e., middle means using middle of the peak to calculate distance to feature, start means using start of the peak to calculate the distance to feature. To be compatible with previous version, by default using start
FeatureLocForDistance	Specify the location of feature for calculating distance, i.e., middle means using middle of the feature to calculate distance of peak to feature, start means using start of the feature to calculate the distance to feature, TSS means using start of feature when feature is on plus strand and using end of feature when feature is on minus strand, geneEnd means using end of feature when feature is on plus strand and using start of feature when feature is on minus strand. To be compatible with previous version, by default using TSS
select	"all" may return multiple overlapping peaks, "first" will return the first overlapping peak, "last" will return the last overlapping peak and "arbitrary" will return one of the overlapping peaks.

- ignore.strand When set to TRUE, the strand information is ignored in the annotation.
- bindingRegion Annotation range used for [annoPeaks](#), which is a vector with two integer values, default to c(-5000, 5000). The first one must be no bigger than 0. And the second one must be no less than 1. Once bindingRegion is defined, annotation will be based on [annoPeaks](#). Here is how to use it together with the parameter output and FeatureLocForDistance.
- To obtain peaks with nearest bi-directional promoters within 5kb upstream and 3kb downstream of TSS, set output = "nearestBiDirectionalPromoters" and bindingRegion = c(-5000, 3000)
 - To obtain peaks within 5kb upstream and up to 3kb downstream of TSS within the gene body, set output="overlapping", FeatureLocForDistance="TSS" and bindingRegion = c(-5000, 3000)
 - To obtain peaks up to 5kb upstream within the gene body and 3kb downstream of gene/Exon End, set output="overlapping", FeatureLocForDistance="geneEnd" and bindingRegion = c(-5000, 3000)
 - To obtain peaks from 5kb upstream to 3kb downstream of genes/Exons, set output="overlapping", bindingType = "fullRange" and bindingRegion = c(-5000, 3000)
- For details, see [annoPeaks](#).
- ... Parameters could be passed to [annoPeaks](#)

Value

An object of [GRanges](#) with slot start holding the start position of the peak, slot end holding the end position of the peak, slot space holding the chromosome location where the peak is located, slot rownames holding the id of the peak. In addition, the following variables are included.

- list("feature")
id of the feature such as ensembl gene ID
- list("insideFeature")
upstream: peak resides upstream of the feature; downstream: peak resides downstream of the feature; inside: peak resides inside the feature; overlapStart: peak overlaps with the start of the feature; overlapEnd: peak overlaps with the end of the feature; includeFeature: peak include the feature entirely
- list("distancetoFeature")
distance to the nearest feature such as transcription start site. By default, the distance is calculated as the distance between the start of the binding site and the TSS that is the gene start for genes located on the forward strand and the gene end for genes located on the reverse strand. The user can specify the location of peak and location of feature for calculating this
- list("start_position")
start position of the feature such as gene
- list("end_position")
end position of the feature such as the gene
- list("strand") 1 or + for positive strand and -1 or - for negative strand where the feature is located
- list("shortestDistance")
The shortest distance from either end of peak to either end the feature.
- list("fromOverlappingOrNearest")
nearest: indicates this feature's start (feature's end for features at minus strand) is closest to the peak start; Overlapping: indicates this feature overlaps with this peak although it is not the nearest feature start

Author(s)

Lihua Julie Zhu, Jianhong Ou

References

1. Zhu L.J. et al. (2010) ChIPpeakAnno: a Bioconductor package to annotate ChIP-seq and ChIP-chip data. BMC Bioinformatics 2010, 11:237doi:10.1186/1471-2105-11-237
2. Zhu L (2013). "Integrative analysis of ChIP-chip and ChIP-seq dataset." In Lee T and Luk ACS (eds.), Tilling Arrays, volume 1067, chapter 4, pp. -19. Humana Press. http://dx.doi.org/10.1007/978-1-62703-607-8_8

See Also

[getAnnotation](#), [findOverlappingPeaks](#), [makeVennDiagram](#), [addGeneIDs](#), [peaksNearBDP](#), [summarizePatternInPeaks](#), [annoGR](#), [annoPeaks](#)

Examples

```
#if (interactive()){
  ## example 1: annotate myPeakList by TxDb or EnsDb.
  data(myPeakList)
  library(ensemldb)
  library(EnsDb.Hsapiens.v75)
  annoData <- annoGR(EnsDb.Hsapiens.v75)
  annotatePeak = annotatePeakInBatch(myPeakList[1:6], AnnotationData=annoData)
  annotatePeak

  ## example 2: annotate myPeakList (GRanges)
  ## with TSS.human.NCBI36 (Granges)
  data(TSS.human.NCBI36)
  annotatedPeak = annotatePeakInBatch(myPeakList[1:6],
                                     AnnotationData=TSS.human.NCBI36)
  annotatedPeak

  ## example 3: you have a list of transcription factor binding sites from
  ## literature and are interested in determining the extent of the overlap
  ## to the list of peaks from your experiment. Prior calling the function
  ## annotatePeakInBatch, need to represent both dataset as GRanges
  ## where start is the start of the binding site, end is the end of the
  ## binding site, names is the name of the binding site, space and strand
  ## are the chromosome name and strand where the binding site is located.

  myexp <- GRanges(seqnames=c(6,6,6,6,5,4,4),
                  IRanges(start=c(1543200,1557200,1563000,1569800,
                                167889600,100,1000),
                          end=c(1555199,1560599,1565199,1573799,
                                167893599,200,1200),
                          names=c("p1","p2","p3","p4","p5","p6", "p7")),
                  strand="+")
  literature <- GRanges(seqnames=c(6,6,6,6,5,4,4),
                       IRanges(start=c(1549800,1554400,1565000,1569400,
                                       167888600,120,800),
                               end=c(1550599,1560799,1565399,1571199,
```



```

                                167888999,140,1400),
                                names=c("f1","f2","f3","f4","f5","f6","f7")),
                                strand=rep(c("+", "-"), c(5, 2)))
annotatedPeak1 <- annotatePeakInBatch(myexp,
                                    AnnotationData=literature)
pie(table(annotatedPeak1$insideFeature))
annotatedPeak1
### use toGRanges or rtracklayer::import to convert BED or GFF format
### to GRanges before calling annotatePeakInBatch
test.bed <- data.frame(space=c("4", "6"),
                       start=c("100", "1000"),
                       end=c("200", "1100"),
                       name=c("peak1", "peak2"))
test.GR = toGRanges(test.bed)
annotatePeakInBatch(test.GR, AnnotationData = literature)
#}

```

```
assignChromosomeRegion
```

Summarize peak distribution over exon, intron, enhancer, proximal promoter, 5 prime UTR and 3 prime UTR

Description

Summarize peak distribution over exon, intron, enhancer, proximal promoter, 5 prime UTR and 3 prime UTR

Usage

```

assignChromosomeRegion(
  peaks.RD,
  exon,
  TSS,
  utr5,
  utr3,
  proximal.promoter.cutoff = 1000L,
  immediate.downstream.cutoff = 1000L,
  nucleotideLevel = FALSE,
  precedence = NULL,
  TxDb = NULL
)

```

Arguments

peaks.RD	peaks in GRanges: See example below
exon	exon data obtained from getAnnotation or customized annotation of class GRanges containing additional variable: strand (1 or + for plus strand and -1 or - for minus strand). This parameter is for backward compatibility only. TxDb should be used instead.

TSS	TSS data obtained from getAnnotation or customized annotation of class GRanges containing additional variable: strand (1 or + for plus strand and -1 or - for minus strand). For example, data(TSS.human.NCBI36), data(TSS.mouse.NCBIM37), data(TSS.rat.RGSC3.4) and data(TSS.zebrafish.Zv8). This parameter is for backward compatibility only. TxDb should be used instead.
utr5	5 prime UTR data obtained from getAnnotation or customized annotation of class GRanges containing additional variable: strand (1 or + for plus strand and -1 or - for minus strand). This parameter is for backward compatibility only. TxDb should be used instead.
utr3	3 prime UTR data obtained from getAnnotation or customized annotation of class GRanges containing additional variable: strand (1 or + for plus strand and -1 or - for minus strand). This parameter is for backward compatibility only. TxDb should be used instead.
proximal.promoter.cutoff	Specify the cutoff in bases to classify proximal promoter or enhancer. Peaks that reside within proximal.promoter.cutoff upstream from or overlap with transcription start site are classified as proximal promoters. Peaks that reside upstream of the proximal.promoter.cutoff from gene start are classified as enhancers. The default is 1000 bases.
immediate.downstream.cutoff	Specify the cutoff in bases to classify immediate downstream region or enhancer region. Peaks that reside within immediate.downstream.cutoff downstream of gene end but not overlap 3 prime UTR are classified as immediate downstream. Peaks that reside downstream over immediate.downstream.cutoff from gene end are classified as enhancers. The default is 1000 bases.
nucleotideLevel	Logical. Choose between peak centric and nucleotide centric view. Default=FALSE
precedence	If no precedence specified, double count will be enabled, which means that if a peak overlap with both promoter and 5'UTR, both promoter and 5'UTR will be incremented. If a precedence order is specified, for example, if promoter is specified before 5'UTR, then only promoter will be incremented for the same example. The values could be any combinations of "Promoters", "immediateDownstream", "fiveUTRs", "threeUTRs", "Exons" and "Introns", Default=NULL
TxDb	an object of TxDb

Value

A list of two named vectors: percentage and jaccard (Jaccard Index). The information in the vectors:

list("Exons")	Percent or the picard index of the peaks resided in exon regions.
list("Introns")	Percent or the picard index of the peaks resided in intron regions.
list("fiveUTRs")	Percent or the picard index of the peaks resided in 5 prime UTR regions.
list("threeUTRs")	Percent or the picard index of the peaks resided in 3 prime UTR regions.
list("Promoter")	Percent or the picard index of the peaks resided in proximal promoter regions.
list("ImmediateDownstream")	Percent or the picard index of the peaks resided in immediate downstream regions.

```
list("Intergenic.Region")
```

Percent or the picard index of the peaks resided in intergenic regions.

The Jaccard index, also known as Intersection over Union. The Jaccard index is between 0 and 1. The higher the index, the more significant the overlap between the peak region and the genomic features in consideration.

Author(s)

Jianhong Ou, Lihua Julie Zhu

References

1. Zhu L.J. et al. (2010) ChIPpeakAnno: a Bioconductor package to annotate ChIP-seq and ChIP-chip data. BMC Bioinformatics 2010, 11:237doi:10.1186/1471-2105-11-237
2. Zhu L.J. (2013) Integrative analysis of ChIP-chip and ChIP-seq dataset. Methods Mol Biol. 2013;1067:105-24. doi: 10.1007/978-1-62703-607-8_8.

See Also

[genomicElementDistribution](#), [genomicElementUpSetR](#), [binOverFeature](#), [binOverGene](#), [binOverRegions](#)

Examples

```
if (interactive() || Sys.getenv("USER")=="jianhongou"){
  ##Display the list of genomes available at UCSC:
  #library(rtracklayer)
  #ucscGenomes()[, "db"]
  ## Display the list of Tracks supported by makeTxDbFromUCSC()
  #supportedUCSCTables()
  ##Retrieving a full transcript dataset for Human from UCSC
  ##TranscriptDb <-
  ##   makeTxDbFromUCSC(genome="hg19", tablename="ensGene")
  if(require(TxDb.Hsapiens.UCSC.hg19.knownGene)){
    TxDb <- TxDb.Hsapiens.UCSC.hg19.knownGene
    exons <- exons(TxDb, columns=NULL)
    fiveUTRs <- unique(unlist(fiveUTRsByTranscript(TxDb)))
    Feature.distribution <-
      assignChromosomeRegion(exons, nucleotideLevel=TRUE, TxDb=TxDb)
    barplot(Feature.distribution$percentage)
    assignChromosomeRegion(fiveUTRs, nucleotideLevel=FALSE, TxDb=TxDb)
    data(myPeakList)
    assignChromosomeRegion(myPeakList, nucleotideLevel=TRUE,
      precedence=c("Promoters", "immediateDownstream",
        "fiveUTRs", "threeUTRs",
        "Exons", "Introns"),
      TxDb=TxDb)
  }
}
```

bdp *obtain the peaks near bi-directional promoters*

Description

Obtain the peaks near bi-directional promoters. Also output percent of peaks near bi-directional promoters.

Usage

```
bdp(peaks, annoData, maxgap = 2000L, ...)
```

Arguments

peaks	peak list, GRanges object
annoData	annotation data, annoGR object
maxgap	maxgap between peak and TSS
...	Not used.

Value

Output is a list of [GRanges](#) object of the peaks near bi-directional promoters.

Author(s)

Jianhong Ou

See Also

See Also as [annoPeaks](#), [annoGR](#)

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  library(ensemldb)
  library(EnsDb.Hsapiens.v75)
  data("myPeakList")
  annoGR <- annoGR(EnsDb.Hsapiens.v75)
  seqlevelsStyle(myPeakList) <- seqlevelsStyle(annoGR)
  ChIPpeakAnno::bdp(myPeakList, annoGR)
}
```

bindist-class	<i>Class "bindist"</i>
---------------	------------------------

Description

An object of class "bindist" represents the relevant fixed-width range of binding site from the feature and number of possible binding site in each range.

Objects from the Class

Objects can be created by calls of the form `new("bindist", counts="integer", mids="integer", halfBinSize="int`

See Also

[preparePool](#), [peakPermTest](#)

binOverFeature	<i>Aggregate peaks over bins from the TSS</i>
----------------	---

Description

Aggregate peaks over bins from the feature sites.

Usage

```
binOverFeature(
  ...,
  annotationData = GRanges(),
  select = c("all", "nearest"),
  radius = 5000L,
  nbins = 50L,
  minGeneLen = 1L,
  aroundGene = FALSE,
  mbins = nbins,
  featureSite = c("FeatureStart", "FeatureEnd", "bothEnd"),
  PeakLocForDistance = c("all", "end", "start", "middle"),
  FUN = sum,
  errFun = sd,
  xlab,
  ylab,
  main
)
```

Arguments

...	Objects of <code>GRanges</code> to be analyzed
annotationData	An object of <code>GRanges</code> or <code>annoGR</code> for annotation
select	Logical: annotate the peaks to all features or the nearest one
radius	The radius of the longest distance to feature site

nbins	The number of bins
minGeneLen	The minimal gene length
aroundGene	Logical: count peaks around features or a given site of the features. Default = FALSE
mbins	if aroundGene set as TRUE, the number of bins intra-feature. The value will be normalized by value * (radius/genelen) * (mbins/nbins)
featureSite	which site of features should be used for distance calculation
PeakLocForDistance	which site of peaks should be used for distance calculation
FUN	the function to be used for score calculation
errFun	the function to be used for errorbar calculation or values for the errorbar.
xlab	titles for each x axis
ylab	titles for each y axis
main	overall titles for each plot

Value

A data.frame with bin values.

Author(s)

Jianhong Ou

Examples

```
bed <- system.file("extdata", "MACS_output.bed", package="ChIPpeakAnno")
gr1 <- toGRanges(bed, format="BED", header=FALSE)
data(TSS.human.GRCh37)
binOverFeature(gr1, annotationData=TSS.human.GRCh37,
               radius=5000, nbins=10, FUN=length, errFun=0)
```

binOverGene	<i>coverage of gene body</i>
-------------	------------------------------

Description

calculate the coverage of gene body per gene per bin.

Usage

```
binOverGene(
  cvglists,
  TxDb,
  upstream.cutoff = 0L,
  downstream.cutoff = upstream.cutoff,
  nbinsGene = 100L,
  nbinsUpstream = 20L,
```

```

    nbinsDownstream = nbinsUpstream,
    includeIntron = FALSE,
    minGeneLen = nbinsGene,
    maxGeneLen = Inf
  )

```

Arguments

`cvglists` A list of [SimpleRleList](#) or [RleList](#). It represents the coverage for samples.

`TxDb` An object of [TxDb](#). It is used for extracting the annotations.

`upstream.cutoff, downstream.cutoff`
cutoff length for upstream or downstream of transcript.

`nbinsGene, nbinsUpstream, nbinsDownstream`
The number of bins for gene, upstream and downstream.

`includeIntron` A logical value which indicates including intron or not.

`minGeneLen, maxGeneLen`
minimal or maximal length of gene.

Author(s)

Jianhong Ou

See Also

[binOverRegions](#), [plotBinOverRegions](#)

Examples

```

if(Sys.getenv("USER")==="jianhongou"){
  path <- system.file("extdata", package="ChIPpeakAnno")
  library(TxDb.Hsapiens.UCSC.hg19.knownGene)
  library(rtracklayer)
  files <- dir(path, "bigWig")
  if(.Platform$OS.type != "windows"){
    cvglists <- lapply(file.path(path, files), import,
                      format="BigWig", as="RleList")
    names(cvglists) <- sub(".bigWig", "", files)
    d <- binOverGene(cvglists, TxDb.Hsapiens.UCSC.hg19.knownGene)
    plotBinOverRegions(d)
  }
}

```

binOverRegions

coverage of chromosome regions

Description

calculate the coverage of 5'UTR, CDS and 3'UTR per transcript per bin.

Usage

```
binOverRegions(
  cvglists,
  TxDb,
  upstream.cutoff = 1000L,
  downstream.cutoff = upstream.cutoff,
  nbinsCDS = 100L,
  nbinsUTR = 20L,
  nbinsUpstream = 20L,
  nbinsDownstream = nbinsUpstream,
  includeIntron = FALSE,
  minCDSLen = nbinsCDS,
  minUTRlen = nbinsUTR,
  maxCDSLen = Inf,
  maxUTRlen = Inf
)
```

Arguments

cvglists A list of [SimpleRleList](#) or [RleList](#). It represents the coverage for samples.

TxDb An object of [TxDb](#). It is used for extracting the annotations.

upstream.cutoff, downstream.cutoff
cutoff length for upstream or downstream of transcript.

nbinsCDS, nbinsUTR, nbinsUpstream, nbinsDownstream
The number of bins for CDS, UTR, upstream and downstream.

includeIntron A logical value which indicates including intron or not.

minCDSLen, minUTRlen
minimal length of CDS or UTR of transcript.

maxCDSLen, maxUTRlen
maximal length of CDS or UTR of transcript.

Author(s)

Jianhong Ou

See Also

[binOverGene](#), [plotBinOverRegions](#)

Examples

```
if(Sys.getenv("USER")=="jianhongou"){
  path <- system.file("extdata", package="ChIPpeakAnno")
  library(TxDb.Hsapiens.UCSC.hg19.knownGene)
  library(rtracklayer)
  files <- dir(path, "bigWig")
  if(.Platform$OS.type != "windows"){
    cvglists <- lapply(file.path(path, files), import,
                      format="BigWig", as="RleList")
    names(cvglists) <- sub(".bigWig", "", files)
  }
  d <- binOverRegions(cvglists, TxDb.Hsapiens.UCSC.hg19.knownGene)
```



```

plotBinOverRegions(d)
}
}

```

ChIPpeakAnno-deprecated

Deprecated Functions in Package ChIPpeakAnno

Description

These functions are provided for compatibility with older versions of R only, and may be defunct as soon as the next release.

Arguments

Peaks1	GRanges: See example below.
Peaks2	GRanges: See example below.
maxgap, minoverlap	Used in the internal call to <code>findOverlaps()</code> to detect overlaps. See ?findOverlaps in the IRanges package for a description of these arguments.
multiple	TRUE or FALSE: TRUE may return multiple overlapping peaks in Peaks2 for one peak in Peaks1; FALSE will return at most one overlapping peaks in Peaks2 for one peak in Peaks1. This parameter is kept for backward compatibility, please use <code>select</code> .
NameOfPeaks1	Name of the Peaks1, used for generating column name.
NameOfPeaks2	Name of the Peaks2, used for generating column name.
select	all may return multiple overlapping peaks, first will return the first overlapping peak, last will return the last overlapping peak and arbitrary will return one of the overlapping peaks.
annotate	Include <code>overlapFeature</code> and <code>shortestDistance</code> in the <code>OverlappingPeaks</code> or not. 1 means yes and 0 means no. Default to 0.
ignore.strand	When set to TRUE, the strand information is ignored in the overlap calculations.
connectedPeaks	If multiple peaks involved in overlapping in several groups, set it to "merge" will count it as only 1, while set it to "min" will count it as the minimal involved peaks in any concentered groups
...	Objects of GRanges : See also findOverlapsOfPeaks .

Details

`findOverlappingPeaks` is now deprecated wrappers for [findOverlapsOfPeaks](#)

See Also

[Deprecated](#), [findOverlapsOfPeaks](#), [toGRanges](#)

cntOverlaps	<i>count overlaps</i>
-------------	-----------------------

Description

Count overlaps with max gap.

Usage

```
cntOverlaps(A, B, maxgap = 0L, ...)
```

Arguments

A, B	A GRanges object.
maxgap	A single integer ≥ 0 .
...	parameters passed to <code>numOverlaps#'</code>

condenseMatrixByColnames	<i>Condense matrix by colnames</i>
--------------------------	------------------------------------

Description

Condense matrix by colnames

Usage

```
condenseMatrixByColnames(mx, iname, sep = ";", cnt = FALSE)
```

Arguments

mx	a matrix to be condensed
iname	the name of the column to be condensed
sep	separator for condensed values,default ;
cnt	TRUE/FALSE specifying whether adding count column or not?

Value

dataframe of condensed matrix

Author(s)

Jianhong Ou, Lihua Julie Zhu

Examples

```
a<-matrix(c(rep(rep(1:5,2),2),rep(1:10,2)),ncol=4)
colnames(a)<-c("con.1","con.2","index.1","index.2")
condenseMatrixByColnames(a,"con.1")
condenseMatrixByColnames(a,2)
```

convert2EntrezID	<i>Convert other common IDs to entrez gene ID.</i>
------------------	--

Description

Convert other common IDs such as ensemble gene id, gene symbol, refseq id to entrez gene ID leveraging organism annotation dataset. For example, org.Hs.eg.db is the dataset from orgs.Hs.eg.db package for human, while org.Mm.eg.db is the dataset from the org.Mm.eg.db package for mouse.

Usage

```
convert2EntrezID(IDs, orgAnn, ID_type = "ensembl_gene_id")
```

Arguments

IDs	a vector of IDs such as ensembl gene ids
orgAnn	organism annotation dataset such as org.Hs.eg.db
ID_type	type of ID: can be ensembl_gene_id, gene_symbol or refseq_id

Value

vector of entrez ids

Author(s)

Lihua Julie Zhu

Examples

```
ensemblIDs = c("ENSG00000115956", "ENSG00000071082", "ENSG00000071054",
  "ENSG00000115594", "ENSG00000115594", "ENSG00000115598", "ENSG00000170417")
library(org.Hs.eg.db)
entrezIDs = convert2EntrezID(IDs=ensemblIDs, orgAnn="org.Hs.eg.db",
  ID_type="ensembl_gene_id")
```

countPatternInSeqs	<i>Output total number of patterns found in the input sequences</i>
--------------------	---

Description

Output total number of patterns found in the input sequences

Usage

```
countPatternInSeqs(pattern, sequences)
```

Arguments

pattern	DNAstringSet object
sequences	a vector of sequences

Value

Total number of occurrence of the pattern in the sequences

Author(s)

Lihua Julie Zhu

See Also

summarizePatternInPeaks, translatePattern

Examples

```
library(Biostrings)
filepath =
  system.file("extdata", "examplePattern.fa", package="ChIPpeakAnno")
dict = readDNAStringSet(filepath = filepath, format="fasta",
                        use.names=TRUE)
sequences = c("ACTGGGGGGGCCTGGGCCCCCAAAT",
              "AAAAAACCCCTTTGGCCATCCCGGGACGGGCCCAT",
              "ATCGAAAATTCC")
countPatternInSeqs(pattern=dict[1], sequences=sequences)
countPatternInSeqs(pattern=dict[2], sequences=sequences)
pattern = DNAStringSet("ATNGMAA")
countPatternInSeqs(pattern=pattern, sequences=sequences)
```

cumulativePercentage *Plot the cumulative percentage tag allocation in sample*

Description

Plot the difference between the cumulative percentage tag allocation in paired samples.

Usage

```
cumulativePercentage(bamfiles, gr, input = 1, binWidth = 1000, ...)
```

Arguments

bamfiles	Bam file names.
gr	An object of GRanges
input	Which file name is input. default 1.
binWidth	The width of each bin.
...	parameter for summarizeOverlaps .

Value

A list of data.frame with the cumulative percentages.

Author(s)

Jianhong Ou

References

Normalization, bias correction, and peak calling for ChIP-seq Aaron Diaz, Kiyoub Park, Daniel A. Lim, Jun S. Song *Stat Appl Genet Mol Biol*. Author manuscript; available in PMC 2012 May 3. Published in final edited form as: *Stat Appl Genet Mol Biol*. 2012 Mar 31; 11(3): 10.1515/1544-6115.1750 /j/sagmb.2012.11.issue-3/1544-6115.1750/1544-6115.1750.xml. Published online 2012 Mar 31. doi: 10.1515/1544-6115.1750 PMID: PMC3342857

Examples

```
## Not run:
path <- system.file("extdata", "reads", package="MMDiffBamSubset")
files <- dir(path, "bam$", full.names = TRUE)
library(BSgenome.Hsapiens.UCSC.hg19)
gr <- as(seqinfo(Hsapiens)["chr1"], "GRanges")
cumulativePercentage(files, gr)

## End(Not run)
```

downstreams

Get downstream coordinates

Description

Returns an object of the same type and length as x containing downstream ranges. The output range is defined as

Usage

```
downstreams(gr, upstream, downstream)
```

Arguments

gr A GenomicRanges object
upstream, downstream non-negative interges.

Details

(end(x) - upstream) to (end(x) + downstream - 1)
 for ranges on the + and * strand, and as
 (start(x) - downstream + 1) to (start(x) + downstream)
 for ranges on the - strand.

Note that the returned object might contain out-of-bound ranges.

Value

A GenomicRanges object

Examples

```
gr <- GRanges("chr1", IRanges(rep(10, 3), width=6), c("+", "-", "*"))
downstreams(gr, 2, 2)
```

egOrgMap	<i>Convert between the name of the organism annotation package ("OrgDb") and the name of the organism.</i>
----------	--

Description

Give a species name and return the organism annotation package name or give an organism annotation package name then return the species name.

Usage

```
egOrgMap(name)
```

Arguments

name The name of the organism annotation package or the species.

Value

A object of character

Author(s)

Jianhong Ou

Examples

```
egOrgMap("org.Hs.eg.db")
egOrgMap("Mus musculus")
```

enrichedGO

Enriched Gene Ontology terms used as example

Description

Enriched Gene Ontology terms used as example

Usage

enrichedGO

Format

A list of 3 dataframes.

list("bp") dataframe described the enriched biological process with 9 columns

go.id:GO biological process id
go.term:GO biological process term
go.Definition:GO biological process description
Ontology: Ontology branch, i.e. BP for biological process
count.InDataset: count of this GO term in this dataset
count.InGenome: count of this GO term in the genome
pvalue: pvalue from the hypergeometric test
totaltermInDataset: count of all GO terms in this dataset
totaltermInGenome: count of all GO terms in the genome

list("mf") dataframe described the enriched molecular function with the following 9 columns

go.id:GO molecular function id
go.term:GO molecular function term
go.Definition:GO molecular function description
Ontology: Ontology branch, i.e. MF for molecular function
count.InDataset: count of this GO term in this dataset
count.InGenome: count of this GO term in the genome
pvalue: pvalue from the hypergeometric test
totaltermInDataset: count of all GO terms in this dataset
totaltermInGenome: count of all GO terms in the genome

list("cc") dataframe described the enriched cellular component the following 9 columns

go.id:GO cellular component id
go.term:GO cellular component term
go.Definition:GO cellular component description
Ontology: Ontology type, i.e. CC for cellular component
count.InDataset: count of this GO term in this dataset
count.InGenome: count of this GO term in the genome
pvalue: pvalue from the hypergeometric test
totaltermInDataset: count of all GO terms in this dataset
totaltermInGenome: count of all GO terms in the genome

Author(s)

Lihua Julie Zhu

Examples

```
data(enrichedGO)
dim(enrichedGO$mf)
dim(enrichedGO$cc)
dim(enrichedGO$bp)
```

enrichmentPlot	<i>plot enrichment results</i>
----------------	--------------------------------

Description

Plot the GO/KEGG/reactome enrichment results

Usage

```
enrichmentPlot(
  res,
  n = 20,
  strlength = 30,
  orderBy = c("pvalue", "termId", "none")
)
```

Arguments

res	output of getEnrichedGO , getEnrichedPATH .
n	number of terms to be plot.
strlength	shorten the description of term by the number of char.
orderBy	order the data by pvalue, termId or none.

Value

an object of ggplot

Examples

```
data(enrichedGO)
enrichmentPlot(enrichedGO)
if (interactive() || Sys.getenv("USER")=="jianhongou") {

  library(org.Hs.eg.db)
  library(GO.db)
  bed <- system.file("extdata", "MACS_output.bed", package="ChIPpeakAnno")
  gr1 <- toGRanges(bed, format="BED", header=FALSE)
  gff <- system.file("extdata", "GFF_peaks.gff", package="ChIPpeakAnno")
  gr2 <- toGRanges(gff, format="GFF", header=FALSE, skip=3)
  library(EnsDb.Hsapiens.v75) ##(hg19)
```



```

annoData <- toGRanges(EnsDb.Hsapiens.v75)
gr1.anno <- annoPeaks(gr1, annoData)
gr2.anno <- annoPeaks(gr2, annoData)
over <- lapply(GRangesList(gr1=gr1.anno, gr2=gr2.anno),
              getEnrichedGO, orgAnn="org.Hs.eg.db",
              maxP=.05, minG0term=10, condense=TRUE)
enrichmentPlot(over)
}

```

EnsDb2GR

EnsDb object to GRanges

Description

convert EnsDb object to GRanges

Usage

```
EnsDb2GR(ranges, feature)
```

Arguments

ranges	an EnsDb object
feature	feature type, could be disjointExons, gene, exon and transcript

estFragmentLength

estimate the fragment length

Description

estimate the fragment length for bam files

Usage

```

estFragmentLength(
  bamfiles,
  index = bamfiles,
  plot = TRUE,
  lag.max = 1000,
  minFragmentSize = 100,
  ...
)

```

Arguments

bamfiles	The file names of the 'BAM' ('SAM' for asBam) files to be processed.
index	The names of the index file of the 'BAM' file being processed; this is given without the '.bai' extension.
plot	logical. If TRUE (the default) the acf is plotted.
lag.max	maximum lag at which to calculate the acf. See acf
minFragmentSize	minimal fragment size to avoid the phantom peak.
...	Not used.

Value

numeric vector

Author(s)

Jianhong Ou

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  path <- system.file("extdata", "reads", package="MMDiffBamSubset")
  if(file.exists(path)){
    WT.AB2 <- file.path(path, "WT_2.bam")
    Null.AB2 <- file.path(path, "Null_2.bam")
    Resc.AB2 <- file.path(path, "Resc_2.bam")
    estFragmentLength(c(WT.AB2, Null.AB2, Resc.AB2))
  }
}
```

estLibSize

estimate the library size

Description

estimate the library size of bam files

Usage

```
estLibSize(bamfiles, index = bamfiles, ...)
```

Arguments

bamfiles	The file names of the 'BAM' ('SAM' for asBam) files to be processed.
index	The names of the index file of the 'BAM' file being processed; this is given without the '.bai' extension.
...	Not used.

Value

numeric vector

Author(s)

Jianhong Ou

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  path <- system.file("extdata", "reads", package="MMDiffBamSubset")
  if(file.exists(path)){
    WT.AB2 <- file.path(path, "WT_2.bam")
    Null.AB2 <- file.path(path, "Null_2.bam")
    Resc.AB2 <- file.path(path, "Resc_2.bam")
    estLibSize(c(WT.AB2, Null.AB2, Resc.AB2))
  }
}
```

ExonPlusUtr.human.GRCh37

Gene model with exon, 5' UTR and 3' UTR information for human sapiens (GRCh37) obtained from biomaRt

Description

Gene model with exon, 5' UTR and 3' UTR information for human sapiens (GRCh37) obtained from biomaRt

Usage

ExonPlusUtr.human.GRCh37

Format

GRanges with slot start holding the start position of the exon, slot end holding the end position of the exon, slot rownames holding ensembl transcript id and slot space holding the chromosome location where the gene is located. In addition, the following variables are included.

list("strand") 1 for positive strand and -1 for negative strand

list("description") description of the transcript

list("ensembl_gene_id") gene id

list("utr5start") 5' UTR start

list("utr5end") 5' UTR end

list("utr3start") 3' UTR start

list("utr3end") 3' UTR end

Details

used in the examples Annotation data obtained by: `mart = useMart(biomart = "ensembl", dataset = "hsapiens_gene_ensembl") ExonPlusUtr.human.GRCh37 = getAnnotation(mart=human, featureType="ExonPlusUtr")`

Examples

```
data(ExonPlusUtr.human.GRCh37)
slotNames(ExonPlusUtr.human.GRCh37)
```

featureAlignedDistribution

plot distribution in given ranges

Description

plot distribution in the given feature ranges

Usage

```
featureAlignedDistribution(
  cvglists,
  feature.gr,
  upstream,
  downstream,
  n.tile = 100,
  zeroAt,
  ...
)
```

Arguments

<code>cvglists</code>	Output of featureAlignedSignal or a list of SimpleRleList or RleList
<code>feature.gr</code>	An object of GRanges with identical width. If the width equal to 1, you can use <code>upstream</code> and <code>downstream</code> to set the range for plot. If the width not equal to 1, you can use <code>zeroAt</code> to set the zero point of the heatmap.
<code>upstream, downstream</code>	upstream or ddownstream from the <code>feature.gr</code> .
<code>n.tile</code>	The number of tiles to generate for each element of <code>feature.gr</code> , default is 100
<code>zeroAt</code>	zero point position of <code>feature.gr</code>
<code>...</code>	any paramters could be used by matplot

Value

invisible matrix of the plot.

Author(s)

Jianhong Ou

See Also

See Also as [featureAlignedSignal](#), [featureAlignedHeatmap](#)

Examples

```
cvglists <- list(A=RleList(chr1=Rle(sample.int(5000, 100),
                                sample.int(300, 100))),
               B=RleList(chr1=Rle(sample.int(5000, 100),
                                sample.int(300, 100))))
feature.gr <- GRanges("chr1", IRanges(seq(1, 4900, 100), width=100))
featureAlignedDistribution(cvglists, feature.gr, zeroAt=50, type="1")
```

featureAlignedExtendSignal

extract signals in given ranges from bam files

Description

extract signals in the given feature ranges from bam files (DNaseq only). The reads will be extended to estimated fragment length.

Usage

```
featureAlignedExtendSignal(
  bamfiles,
  index = bamfiles,
  feature.gr,
  upstream,
  downstream,
  n.tile = 100,
  fragmentLength,
  librarySize,
  pe = c("auto", "PE", "SE"),
  adjustFragmentLength,
  gal,
  ...
)
```

Arguments

bamfiles	The file names of the 'BAM' ('SAM' for asBam) files to be processed.
index	The names of the index file of the 'BAM' file being processed; this is given without the '.bai' extension.
feature.gr	An object of GRanges with identical width.
upstream, downstream	upstream or dwonstream from the feature.gr.
n.tile	The number of tiles to generate for each element of feature.gr, default is 100
fragmentLength	Estimated fragment length.

librarySize	Estimated library size.
pe	Pair-end or not. Default auto.
adjustFragmentLength	A numeric vector with length 1. Adjust the fragments/reads length to.
gal	A GAlignmentsList object or a list of GAlignmentPairs. If bamfiles is missing, gal is required.
...	Not used.

Value

A list of matrix. In each matrix, each row record the signals for corresponding feature.

Author(s)

Jianhong Ou

See Also

See Also as [featureAlignedSignal](#), [estLibSize](#), [estFragmentLength](#)

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  path <- system.file("extdata", package="MMDiffBamSubset")
  if(file.exists(path)){
    WT.AB2 <- file.path(path, "reads", "WT_2.bam")
    Null.AB2 <- file.path(path, "reads", "Null_2.bam")
    Resc.AB2 <- file.path(path, "reads", "Resc_2.bam")
    peaks <- file.path(path, "peaks", "WT_2_Macs_peaks.xls")
    estLibSize(c(WT.AB2, Null.AB2, Resc.AB2))
    feature.gr <- toGRanges(peaks, format="MACS")
    feature.gr <- feature.gr[seqnames(feature.gr)=="chr1" &
      start(feature.gr)>30000000 &
      end(feature.gr)<75000000]
    sig <- featureAlignedExtendSignal(c(WT.AB2, Null.AB2, Resc.AB2),
      feature.gr=reCenterPeaks(feature.gr, width=1),
      upstream = 505,
      downstream = 505,
      n.tile=101,
      fragmentLength=250,
      librarySize=1e9)
    featureAlignedHeatmap(sig, reCenterPeaks(feature.gr, width=1010),
      zeroAt=.5, n.tile=101)
  }
}
```

featureAlignedHeatmap *Heatmap representing signals in given ranges*

Description

plot heatmap in the given feature ranges

Usage

```
featureAlignedHeatmap(
  cvglists,
  feature.gr,
  upstream,
  downstream,
  zeroAt,
  n.tile = 100,
  annoMcols = c(),
  sortBy = names(cvglists)[1],
  color = colorRampPalette(c("yellow", "red"))(50),
  lower.extreme,
  upper.extreme,
  margin = c(0.1, 0.01, 0.15, 0.1),
  gap = 0.01,
  newpage = TRUE,
  gp = gpar(fontsize = 10),
  ...
)
```

Arguments

cvglists	Output of featureAlignedSignal or a list of SimpleRleList or RleList
feature.gr	An object of GRanges with identical width. If the width equal to 1, you can use upstream and downstream to set the range for plot. If the width not equal to 1, you can use zeroAt to set the zero point of the heatmap.
upstream, downstream	upstream or dwonstream from the feature.gr. It must keep same as feature-AlignedSignal . It is used for x-axis label.
zeroAt	zero point position of feature.gr
n.tile	The number of tiles to generate for each element of feature.gr, default is 100
annoMcols	The columns of metadata of feature.gr that specifies the annotations shown of the right side of the heatmap.
sortBy	Sort the feature.gr by columns by annoMcols and then the signals of the given samples. Default is the first sample. Set to NULL to disable sort.
color	vector of colors used in heatmap
lower.extreme, upper.extreme	The lower and upper boundary value of each samples
margin	Margin for of the plot region.
gap	Gap between each heatmap columns.

newpage	Call grid.newpage or not. Default, TRUE
gp	A gpar object can be used for text.
...	Not used.

Value

invisible gList object.

Author(s)

Jianhong Ou

See Also

See Also as [featureAlignedSignal](#), [featureAlignedDistribution](#)

Examples

```
cvglists <- list(A=RleList(chr1=Rle(sample.int(5000, 100),
                                sample.int(300, 100))),
               B=RleList(chr1=Rle(sample.int(5000, 100),
                                sample.int(300, 100))))
feature.gr <- GRanges("chr1", IRanges(seq(1, 4900, 100), width=100))
feature.gr$anno <- rep(c("type1", "type2"), c(25, 24))
featureAlignedHeatmap(cvglists, feature.gr, zeroAt=50, annoMcols="anno")
```

featureAlignedSignal *extract signals in given ranges*

Description

extract signals in the given feature ranges

Usage

```
featureAlignedSignal(
  cvglists,
  feature.gr,
  upstream,
  downstream,
  n.tile = 100,
  ...
)
```


Arguments

cvglists	List of SimpleRleList or RleList
feature.gr	An object of GRanges with identical width.
upstream, downstream	Set the feature.gr to upstream and dwonstream from the center of the feature.gr if they are set.
n.tile	The number of tiles to generate for each element of feature.gr, default is 100
...	Not used.

Value

A list of matrix. In each matrix, each row record the signals for corresponding feature. rownames of the matrix show the seqnames and coordinates.

Author(s)

Jianhong Ou

See Also

See Also as [featureAlignedHeatmap](#), [featureAlignedDistribution](#)

Examples

```
cvglists <- list(A=RleList(chr1=Rle(sample.int(5000, 100),
                                   sample.int(300, 100))),
               B=RleList(chr1=Rle(sample.int(5000, 100),
                                   sample.int(300, 100))))
feature.gr <- GRanges("chr1", IRanges(seq(1, 4900, 100), width=100))
featureAlignedSignal(cvglists, feature.gr)
```

findEnhancers

Find possible enhancers depend on DNA interaction data

Description

Find possible enhancers by data from chromosome conformation capture techniques such as 3C, 5C or HiC.

Usage

```
findEnhancers(
  peaks,
  annoData,
  DNAinteractiveData,
  bindingType = c("nearestBiDirectionalPromoters", "startSite", "endSite"),
  bindingRegion = c(-5000, 5000),
  ignore.peak.strand = TRUE,
  ...
)
```

Arguments

peaks	peak list, GRanges object
annoData	annotation data, GRanges object
DNAinteractiveData	DNA interaction data, GRanges object with interaction blocks informations.
bindingType	<p>Specifying the criteria to associate peaks with annotation. Here is how to use it together with the parameter bindingRegion. The annotation will be shift to a new position depend on the DNA interaction region.</p> <ul style="list-style-type: none"> • To obtain peaks within 5kb upstream and up to 3kb downstream of shift TSS within the gene body, set bindingType = "startSite" and bindingRegion = c(-5000, 3000) • To obtain peaks up to 5kb upstream within the gene body and 3kb downstream of shift gene/Exon End, set bindingType = "endSite" and bindingRegion = c(-5000, 3000) • To obtain peaks with nearest bi-directional enhancer regions within 5kb upstream and 3kb downstream of shift TSS, set bindingType = "nearest-BiDirectionalPromoters" and bindingRegion = c(-5000, 3000) <p>startSite start position of the feature (strand is considered) endSite end position of the feature (strand is considered) nearestBiDirectionalPromoters nearest enhancer regions from both direction of the peaks (strand is considered). It will report bidirectional enhancer regions if there are enhancer regions in both directions in the given region (defined by bindingRegion). Otherwise, it will report the closest enhancer regions in one direction.</p>
bindingRegion	Annotation range used together with bindingType, which is a vector with two integer values, default to c (-5000, 5000). The first one must be no bigger than 0. And the second one must be no less than 1. For details, see bindingType.
ignore.peak.strand	ignore the peaks strand or not.
...	Not used.

Value

Output is a [GRanges](#) object of the annotated peaks.

Author(s)

Jianhong Ou

See Also

See Also as [annotatePeakInBatch](#)

Examples

```
bed <- system.file("extdata",
                  "wgEncodeUmassDekker5CGm12878PkV2.bed.gz",
                  package="ChIPpeakAnno")
DNAinteractiveData <- toGRanges(gzfile(bed))
```

```
library(EnsDb.Hsapiens.v75)
annoData <- toGRanges(EnsDb.Hsapiens.v75, feature="gene")
data("myPeakList")
findEnhancers(myPeakList[500:1000], annoData, DNAinteractiveData)
```

findMotifsInPromoterSeqs

Find occurrence of input motifs in the promoter regions of the input gene list

Description

Find occurrence of input motifs in the promoter regions of the input gene list

Usage

```
findMotifsInPromoterSeqs(
  patternFilePath1,
  patternFilePath2,
  findPairedMotif = FALSE,
  BSgenomeName,
  txdb,
  geneIDs,
  upstream = 5000L,
  downstream = 5000L,
  name.motif1 = "motif1",
  name.motif2 = "motif2",
  max.distance = 100L,
  min.distance = 1L,
  motif.orientation = c("both", "motif1UpstreamOfMotif2", "motif2UpstreamOfMoif1"),
  ignore.strand = FALSE,
  format = "fasta",
  skip = 0L,
  motif1LocForDistance = "end",
  motif2LocForDistance = "start",
  outfile,
  append = FALSE
)
```

Arguments

patternFilePath1

File path containing a list of known motifs. Required

patternFilePath2

File path containing a motif required to be in the flanking regions of the motif(s) in the first file, i.e. patternFilePath1. Required if findPairedMotif is set to TRUE

findPairedMotif

Find motifs in paired configuration only or not. Default FALSE

<code>BsgenomeName</code>	A <code>Bsgenome</code> object. For a list of existing <code>Bsgenomes</code> , please refer use the function available. <code>genomes</code> in <code>Bsgenome</code> package. For example, <code>Bsgenome.Hsapiens.UCSC.hg38</code> is for hg38, <code>Bsgenome.Hsapiens.UCSC.hg19</code> is for hg19, <code>Bsgenome.Mmusculus.UCSC.mm10</code> is for mm10, <code>Bsgenome.Celegans.UCSC.ce6</code> is for ce6 <code>Bsgenome.Rnorvegicus.UCSC.rn5</code> is for rn5, <code>Bsgenome.Drerio.UCSC.danRer7</code> is for Zv9, and <code>Bsgenome.Dmelanogaster.UCSC.dm3</code> is for dm3. Required
<code>txdb</code>	A <code>TxDb</code> object. For creating and using <code>TxDb</code> object, please refer to <code>GenomicFeatures</code> package. For a list of existing <code>TxDb</code> object, please search for annotation package starting with <code>TxDb</code> at http://www.bioconductor.org/packages/release/BiocViews.html#___An such as <code>TxDb.Rnorvegicus.UCSC.rn5.refGene</code> for rat, <code>TxDb.Mmusculus.UCSC.mm10.knownGene</code> for mouse, <code>TxDb.Hsapiens.UCSC.hg19.knownGene</code> and <code>TxDb.Hsapiens.UCSC.hg38.knownGene</code> for human, <code>TxDb.Dmelanogaster.UCSC.dm3.ensGene</code> for <i>Drosophila</i> and <code>TxDb.Celegans.UCSC.ce6</code> for <i>C.elegans</i>
<code>geneIDs</code>	One or more gene entrez IDs. For example the entrez ID for EWSIR is 2130 https://www.genecards.org/cgi-bin/carddisp.pl?gene=EWSR1 You can use the <code>addGeneIDs</code> function in <code>ChIPpeakAnno</code> to convert other types of Gene IDs to entrez ID
<code>upstream</code>	Number of bases upstream of the TSS to search for the motifs. Default 5000L
<code>downstream</code>	Number of bases downstream of the TSS to search for the motifs. Default 5000L
<code>name.motif1</code>	Name of the motif in <code>inputfilePath2</code> for labeling the output file column. Default <code>motif1</code> . used only when searching for motifs in paired configuration
<code>name.motif2</code>	Name of the motif in <code>inputfilePath2</code> for labeling the output file column. Default <code>motif2</code> used only when searching for motifs in paired configuration
<code>max.distance</code>	maximum required gap between a paired motifs to be included in the output file. Default 100L
<code>min.distance</code>	Minimum required gap between a paired motifs to be included in the output file. Default 1L
<code>motif.orientation</code>	Required relative orientation between paired motifs: both means any orientation, <code>motif1UpstreamOfMotif2</code> means <code>motif1</code> needs to be located on the upstream of <code>motif2</code> , and <code>motif2UpstreamOfMoif1</code> means <code>motif2</code> needs to be located on the upstream of <code>motif1</code> . Default both
<code>ignore.strand</code>	Specify whether paired motifs should be located on the same strand. Default FALSE
<code>format</code>	The format of the files specified in <code>inputFilePath1</code> and <code>inputFilePath2</code> . Default <code>fasta</code>
<code>skip</code>	Specify number of lines to skip at the beginning of the input file. Default 0L
<code>motif1LocForDistance</code>	Specify whether to use the start or end of the <code>motif1</code> location to calculate distance between paired motifs. Only applicable when <code>findPairedMotif</code> is set to TRUE. Default end
<code>motif2LocForDistance</code>	Specify whether to use the start or end of the <code>motif2</code> location to calculate distance between paired motifs. Only applicable when <code>findPairedMotif</code> is set to TRUE. Default start
<code>outfile</code>	File path to save the search results
<code>append</code>	Specify whether to append the results to the specified output file, i.e., <code>outfile</code> . Default FALSE

Details

This function outputs the motif occurring locations in the promoter regions of input gene list and input motifs. It also can find paired motifs within specified gap threshold

Value

A vector of numeric. It is the background corrected log2-transformed ratios, CPMRatios or Odd-Ratios.

An object of GRanges with metadata "tx_start", "tx_end tx_strand", "tx_id", "tx_name", "Gene ID", and motif specific information such as motif name, motif found, motif strand etc.

Author(s)

Lihua Julie Zhu

Examples

```
library("BSgenome.Hsapiens.UCSC.hg38")
library("TxDb.Hsapiens.UCSC.hg38.knownGene")

patternFilePath1 =system.file("extdata", "motifIRF4.fa", package="ChIPpeakAnno")
patternFilePath2 =system.file("extdata", "motifAP1.fa", package="ChIPpeakAnno")
pairedMotifs <- findMotifsInPromoterSeqs(patternFilePath1 = patternFilePath1,
  patternFilePath2 = patternFilePath2,
  findPairedMotif = TRUE,
  name.motif1 = "IRF4", name.motif2 = "AP1",
  BSgenomeName = BSgenome.Hsapiens.UCSC.hg38,
  geneIDs = 7486, txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  outfile = "testPaired.xls")

unPairedMotifs <- findMotifsInPromoterSeqs(patternFilePath1 = patternFilePath1,
  BSgenomeName = BSgenome.Hsapiens.UCSC.hg38,
  geneIDs = 7486, txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  outfile = "testUnPaired.xls")
```

findOverlappingPeaks *Find the overlapping peaks for two peak ranges.*

Description

Find the overlapping peaks for two input peak ranges.

Usage

```
findOverlappingPeaks(
  Peaks1,
  Peaks2,
  maxgap = -1L,
  minoverlap = 0L,
```

```

multiple = c(TRUE, FALSE),
NameOfPeaks1 = "TF1",
NameOfPeaks2 = "TF2",
select = c("all", "first", "last", "arbitrary"),
annotate = 0,
ignore.strand = TRUE,
connectedPeaks = c("min", "merge"),
...
)

```

Arguments

Peaks1	GRanges: See example below.
Peaks2	GRanges: See example below.
maxgap, minoverlap	Used in the internal call to <code>findOverlaps()</code> to detect overlaps. See <code>?findOverlaps</code> in the IRanges package for a description of these arguments.
multiple	TRUE or FALSE: TRUE may return multiple overlapping peaks in Peaks2 for one peak in Peaks1; FALSE will return at most one overlapping peaks in Peaks2 for one peak in Peaks1. This parameter is kept for backward compatibility, please use select.
NameOfPeaks1	Name of the Peaks1, used for generating column name.
NameOfPeaks2	Name of the Peaks2, used for generating column name.
select	all may return multiple overlapping peaks, first will return the first overlapping peak, last will return the last overlapping peak and arbitrary will return one of the overlapping peaks.
annotate	Include overlapFeature and shortestDistance in the OverlappingPeaks or not. 1 means yes and 0 means no. Default to 0.
ignore.strand	When set to TRUE, the strand information is ignored in the overlap calculations.
connectedPeaks	If multiple peaks involved in overlapping in several groups, set it to "merge" will count it as only 1, while set it to "min" will count it as the minimal involved peaks in any concentered groups
...	Objects of GRanges : See also <code>findOverlapsOfPeaks</code> .

Details

The new function `findOverlapsOfPeaks` is recommended.

Efficiently perform overlap queries with an interval tree implemented in **IRanges**.

Value

OverlappingPeaks

a data frame consists of input peaks information with added information: `overlapFeature` (upstream: peak1 resides upstream of the peak2; downstream: peak1 resides downstream of the peak2; inside: peak1 resides inside the peak2 entirely; `overlapStart`: peak1 overlaps with the start of the peak2; `overlapEnd`: peak1 overlaps with the end of the peak2; `includeFeature`: peak1 include the peak2 entirely) and `shortestDistance` (shortest distance between the overlapping peaks)

MergedPeaks GRanges contains merged overlapping peaks

Author(s)

Lihua Julie Zhu

References

1. Interval tree algorithm from: Cormen, Thomas H.; Leiserson, Charles E.; Rivest, Ronald L.; Stein, Clifford. Introduction to Algorithms, second edition, MIT Press and McGraw-Hill. ISBN 0-262-53196-8
2. Zhu L.J. et al. (2010) ChIPpeakAnno: a Bioconductor package to annotate ChIP-seq and ChIP-chip data. BMC Bioinformatics 2010, 11:237 doi:10.1186/1471-2105-11-237
3. Zhu L (2013). Integrative analysis of ChIP-chip and ChIP-seq dataset. In Lee T and Luk ACS (eds.), Tiling Arrays, volume 1067, chapter 4, pp. -19. Humana Press. http://dx.doi.org/10.1007/978-1-62703-607-8_8

See Also

findOverlapsOfPeaks, annotatePeakInBatch, makeVennDiagram

Examples

```

if (interactive())
{
peaks1 =
  GRanges(seqnames=c(6,6,6,6,5),
          IRanges(start=c(1543200,1557200,1563000,1569800,167889600),
                  end=c(1555199,1560599,1565199,1573799,167893599),
                  names=c("p1","p2","p3","p4","p5")),
          strand=as.integer(1))
peaks2 =
  GRanges(seqnames=c(6,6,6,6,5),
          IRanges(start=c(1549800,1554400,1565000,1569400,167888600),
                  end=c(1550599,1560799,1565399,1571199,167888999),
                  names=c("f1","f2","f3","f4","f5")),
          strand=as.integer(1))
t1 = findOverlappingPeaks(peaks1, peaks2, maxgap=1000,
                          NameOfPeaks1="TF1", NameOfPeaks2="TF2", select="all", annotate=1)
r = t1$OverlappingPeaks
pie(table(r$overlapFeature))
as.data.frame(t1$MergedPeaks)
}

```

findOverlapsOfPeaks *Find the overlapped peaks among two or more set of peaks.*

Description

Find the overlapping peaks for two or more (less than five) set of peak ranges.

Usage

```

findOverlapsOfPeaks(
  ...,
  maxgap = -1L,
  minoverlap = 0L,
  ignore.strand = TRUE,
  connectedPeaks = c("keepAll", "min", "merge")
)

```

Arguments

... Objects of [GRanges](#): See example below.

maxgap, minoverlap Used in the internal call to `findOverlaps()` to detect overlaps. See `?findOverlaps` in the **IRanges** package for a description of these arguments.

ignore.strand When set to `TRUE`, the strand information is ignored in the overlap calculations.

connectedPeaks If multiple peaks are involved in any group of connected/overlapping peaks in any input peak list, set it to "merge" will add 1 to the overlapping counts, while set it to "min" will add the minimal involved peaks in each group of connected/overlapped peaks to the overlapping counts. Set it to "keepAll" will add the number of involved peaks for each peak list to the corresponding overlapping counts. In addition, it will output counts as if connectedPeaks were set to "min". For examples (<https://support.bioconductor.org/p/133486/#133603>), if 5 peaks in group1 overlap with 2 peaks in group 2, setting connectedPeaks to "merge" will add 1 to the overlapping counts; setting it to "keepAll" will add 5 peaks to count.group1, 2 to count.group2, and 2 to counts; setting it to "min" will add 2 to the overlapping counts.

Details

Efficiently perform overlap queries with an interval tree implemented with `GRanges`.

Value

return value is An object of `overlappingPeaks`.

venn_cnt an object of `VennCounts`

peaklist a list consists of all overlapping peaks or unique peaks

uniquePeaks an object of [GRanges](#) consists of all unique peaks

mergedPeaks an object of [GRanges](#) consists of all merged overlapping peaks

peaksInMergedPeaks an object of [GRanges](#) consists of all peaks in each samples involved in the overlapping peaks

overlappingPeaks a list of data frame consists of the annotation of all the overlapped peaks

all.peaks a list of `GRanges` object which contain the input peaks with formatted rownames.

Author(s)

Jianhong Ou

References

- 1.Interval tree algorithm from: Cormen, Thomas H.; Leiserson, Charles E.; Rivest, Ronald L.; Stein, Clifford. Introduction to Algorithms, second edition, MIT Press and McGraw-Hill. ISBN 0-262-53196-8
- 2.Zhu L.J. et al. (2010) ChIPpeakAnno: a Bioconductor package to annotate ChIP-seq and ChIP-chip data. BMC Bioinformatics 2010, 11:237doi:10.1186/1471-2105-11-237
3. Zhu L (2013). "Integrative analysis of ChIP-chip and ChIP-seq dataset." In Lee T and Luk ACS (eds.), Tilling Arrays, volume 1067, chapter 4, pp. -19. Humana Press. http://dx.doi.org/10.1007/978-1-62703-607-8_8, http://link.springer.com/protocol/10.1007%2F978-1-62703-607-8_8

See Also

[annotatePeakInBatch](#), [makeVennDiagram](#), [getVennCounts](#), [findOverlappingPeaks](#)

Examples

```
peaks1 <- GRanges(seqnames=c(6,6,6,6,5),
                  IRanges(start=c(1543200,1557200,1563000,1569800,167889600),
                          end=c(1555199,1560599,1565199,1573799,167893599),
                          names=c("p1","p2","p3","p4","p5")),
                  strand="+")
peaks2 <- GRanges(seqnames=c(6,6,6,6,5),
                  IRanges(start=c(1549800,1554400,1565000,1569400,167888600),
                          end=c(1550599,1560799,1565399,1571199,167888999),
                          names=c("f1","f2","f3","f4","f5")),
                  strand="+")
t1 <- findOverlapsOfPeaks(peaks1, peaks2, maxgap=1000)
makeVennDiagram(t1)
t1$venn_cnt
t1$peaklist
```

genomicElementDistribution

Genomic Element distribution

Description

Plot pie chart for genomic element distribution

Usage

```
genomicElementDistribution(
  peaks,
  TxDb,
  seqlev,
  nucleotideLevel = FALSE,
  ignore.strand = TRUE,
  promoterRegion = c(upstream = 2000, downstream = 100),
  geneDownstream = c(upstream = 0, downstream = 1000),
  labels = list(geneLevel = c(promoter = "Promoter", geneDownstream = "Downstream"),
```

```

geneBody = "Gene body", distalIntergenic = "Distal Intergenic"), ExonIntron = c(exon
= "Exon", intron = "Intron", intergenic = "Intergenic"), Exons = c(utr5 = "5' UTR",
utr3 = "3' UTR", CDS = "CDS", otherExon = "Other exon"), group = c(geneLevel =
"Gene Level", promoterLevel = "Promoter Level", Exons = "Exon level", ExonIntron =
"Exon/Intron/Intergenic")),
labelColors = c(promoter = "#D55E00", geneDownstream = "#E69F00", geneBody =
"#51C6E6", distalIntergenic = "#AAAAAA", exon = "#009DDA", intron = "#666666",
intergenic = "#DDDDDD", utr5 = "#0072B2", utr3 = "#56B4E9", CDS = "#0033BF",
otherExon = "#009E73"),
plot = TRUE,
promoterLevel
)

```

Arguments

peaks	peak list, GRanges object or a GRangesList .
TxDb	an object of TxDb
seqlev	sequence level should be involved. Default is all the sequence levels in intersect of peaks and TxDb.
nucleotideLevel	Logical. Choose between peak centric and nucleotide centric view. Default=FALSE
ignore.strand	logical. Whether the strand of the input ranges should be ignored or not. Default=TRUE
promoterRegion	numeric. The upstream and downstream of genes to define promoter region.
geneDownstream	numeric. The upstream and downstream of genes to define gene downstream region.
labels	list. A list for labels for the genomic elements.
labelColors	named character vector. The colors for each labels.
plot	logic. Plot the pie chart for the genomic elements or not.
promoterLevel	list. The breaks, labels, and colors for divided range of promoters. The breaks must be from 5' -> 3' and the percentage will use the fixed precedence 3' -> 5'

Details

The distribution will be calculated by geneLevel, ExonIntron, and Exons The geneLevel will be categorized as promoter region, gene body, gene downstream and distal intergenic region. The ExonIntron will be categorized as exon, intron and intergenic. The Exons will be categorized as 5' UTR, 3'UTR and CDS. The precedence will follow the order of labels defination. For example, for ExonIntron, if a peak overlap with both exon and intron, and exon is specified before intron, then only exon will be incremented for the same example.

Value

Invisible list of data for plot.

Examples

```

if (interactive() || Sys.getenv("USER")=="jianhongou"){
  data(myPeakList)
  if(require(TxDb.Hsapiens.UCSC.hg19.knownGene)){
    seqinfo(myPeakList) <-

```

```

seqinfo(TxDb.Hsapiens.UCSC.hg19.knownGene)[seqlevels(myPeakList)]
myPeakList <- GenomicRanges::trim(myPeakList)
myPeakList <- myPeakList[width(myPeakList)>0]
  genomicElementDistribution(myPeakList,
    TxDb.Hsapiens.UCSC.hg19.knownGene)
  genomicElementDistribution(myPeakList,
    TxDb.Hsapiens.UCSC.hg19.knownGene,
    nucleotideLevel = TRUE)
  genomicElementDistribution(myPeakList,
    TxDb.Hsapiens.UCSC.hg19.knownGene,
    promoterLevel=list(
      #from 5' -> 3', fixed precedence 3' -> 5'
      breaks = c(-2000, -1000, -500, 0, 100),
      labels = c("upstream 1-2Kb", "upstream 0.5-1Kb",
        "upstream <500b", "TSS - 100b"),
      colors = c("#FFE5CC", "#FFCA99",
        "#FFAD65", "#FF8E32"))
    )
}

```

genomicElementUpSetR *Genomic Element data for upset plot*

Description

Prepare data for upset plot for genomic element distribution

Usage

```

genomicElementUpSetR(
  peaks,
  TxDb,
  seqlev,
  ignore.strand = TRUE,
  breaks = list(distal_upstream = c(-1e+05, -10000, -1, 1), proximal_upstream =
    c(-10000, -5000, -1, 1), distal_promoter = c(-5000, -2000, -1, 1), proximal_promoter
    = c(-2000, 200, -1, 0), `5'UTR` = fiveUTRsByTranscript, `3'UTR` =
    threeUTRsByTranscript, CDS = cds, exon = exons, intron = intronsByTranscript,
  gene_body = genes, immediate_downstream = c(0, 2000, 1, 1), proximal_downstream =
    c(2000, 5000, 1, 1), distal_downstream = c(5000, 1e+05, 1, 1))
)

```

Arguments

peaks	peak list, GRanges object or a GRangesList .
TxDb	an object of TxDb
seqlev	sequence level should be involved. Default is all the sequence levels in intersect of peaks and TxDb.
ignore.strand	logical. Whether the strand of the input ranges should be ignored or not. Default=TRUE

breaks list. A list for labels and sets for the genomic elements. The element could be an S4 method for signature 'TxDb' or a numeric vector with length of 4. The three numbers are c(upstream point, downstream point, promoter (-1) or downstream (1), remove gene body or not (1: remove, 0: keep)).

Details

The data will be calculated by for each breaks. No precedence will be considered.

Value

list of data for plot.

Examples

```
if (interactive() || Sys.getenv("USER")=="jianhongou"){
  data(myPeakList)
  if(require(TxDb.Hsapiens.UCSC.hg19.knownGene)){
    seqinfo(myPeakList) <-
    seqinfo(TxDb.Hsapiens.UCSC.hg19.knownGene)[seqlevels(myPeakList)]
    myPeakList <- GenomicRanges::trim(myPeakList)
    myPeakList <- myPeakList[width(myPeakList)>0]
    x <- genomicElementUpSetR(myPeakList,
      TxDb.Hsapiens.UCSC.hg19.knownGene)
    library(UpSetR)
    upset(x$plotData, nsets=13, nintersects=NA)
  }
}
```

getAllPeakSequence *Obtain genomic sequences around the peaks*

Description

Obtain genomic sequences around the peaks leveraging the BSgenome and biomaRt package

Usage

```
getAllPeakSequence(
  myPeakList,
  upstream = 200L,
  downstream = upstream,
  genome,
  AnnotationData
)
```

Arguments

myPeakList An object of [GRanges](#): See example below

upstream upstream offset from the peak start, e.g., 200

downstream downstream offset from the peak end, e.g., 200

genome BSgenome object or mart object. Please refer to available.genomes in BSgenome package and useMart in bioMaRt package for details

AnnotationData GRanges object with annotation information.

Value

GRanges with slot start holding the start position of the peak, slot end holding the end position of the peak, slot rownames holding the id of the peak and slot seqnames holding the chromosome where the peak is located. In addition, the following variables are included:

upstream	upstream offset from the peak start
downstream	downstream offset from the peak end
sequence	the sequence obtained

Author(s)

Lihua Julie Zhu, Jianhong Ou

References

Durinck S. et al. (2005) BioMart and Bioconductor: a powerful link between biological biomarts and microarray data analysis. *Bioinformatics*, 21, 3439-3440.

Examples

```
#### use Annotation data from BSgenome
peaks <- GRanges(seqnames=c("NC_008253", "NC_010468"),
                 IRanges(start=c(100, 500), end=c(300, 600),
                         names=c("peak1", "peak2")))
library(BSgenome.Ecoli.NCBI.20080805)
seq <- getAllPeakSequence(peaks, upstream=20, downstream=20, genome=Ecoli)
write2FASTA(seq, file="test.fa")
```

getAnnotation	<i>Obtain the TSS, exon or miRNA annotation for the specified species</i>
---------------	---

Description

Obtain the TSS, exon or miRNA annotation for the specified species using the biomaRt package

Usage

```
getAnnotation(
  mart,
  featureType = c("TSS", "miRNA", "Exon", "5utr", "3utr", "ExonPlusUtr", "transcript")
)
```

Arguments

mart	A mart object, see useMart of biomaRt package for details.
featureType	TSS, miRNA, Exon, 5'UTR, 3'UTR, transcript or Exon plus UTR. The default is TSS.

Value

GRanges with slot start holding the start position of the feature, slot end holding the end position of the feature, slot names holding the id of the feature, slot space holding the chromosome location where the feature is located. In addition, the following variables are included.

```
list("strand") 1 for positive strand and -1 for negative strand where the feature is located
list("description")
                description of the feature such as gene
```

Note

For featureType of TSS, start is the transcription start site if strand is 1 (plus strand), otherwise, end is the transcription start site

Author(s)

Lihua Julie Zhu, Jianhong Ou

References

Durinck S. et al. (2005) BioMart and Bioconductor: a powerful link between biological biomarts and microarray data analysis. *Bioinformatics*, 21, 3439-3440.

Examples

```
if (interactive())
{
  mart <- useMart(biomart="ensembl", dataset="hsapiens_gene_ensembl")
  Annotation <- getAnnotation(mart, featureType="TSS")
}
```

getEnrichedGO

Obtain enriched gene ontology (GO) terms that near the peaks

Description

Obtain enriched gene ontology (GO) terms based on the features near the enriched peaks using GO.db package and GO gene mapping package such as org.Hs.db.eg to obtain the GO annotation and using hypergeometric test (phyper) and multtest package for adjusting p-values

Usage

```
getEnrichedGO(
  annotatedPeak,
  orgAnn,
  feature_id_type = "ensembl_gene_id",
  maxP = 0.01,
  minGOterm = 10,
  multiAdjMethod = NULL,
  condense = FALSE,
```

```

    removeAncestorByPval = NULL,
    keepByLevel = NULL
)

```

Arguments

annotatedPeak A GRanges object or a vector of feature IDs

orgAnn Organism annotation package such as org.Hs.eg.db for human and org.Mm.eg.db for mouse, org.Dm.eg.db for fly, org.Rn.eg.db for rat, org.Sc.eg.db for yeast and org.Dr.eg.db for zebrafish

feature_id_type The feature type in annotatedPeak such as ensembl_gene_id, refseq_id, gene_symbol or entrez_id

maxP The maximum p-value to be considered to be significant

minGOterm The minimum count in a genome for a GO term to be included

multiAdjMethod The multiple testing procedures, for details, see mt.rawp2adjp in multtest package

condense Condense the results or not.

removeAncestorByPval Remove ancestor by p-value. P-value is calculated by fisher exact test. If gene number in all of the children is significant greater than it in parent term, the parent term will be removed from the list.

keepByLevel If the shortest path from the go term to 'all' is greater than the given level, the term will be removed.

Value

A list with 3 elements

```

list("bp")    enriched biological process with the following 9 variables
               go.id:GO biological process id
               go.term:GO biological process term
               go.Definition:GO biological process description
               Ontology: Ontology branch, i.e. BP for biological process
               count.InDataset: count of this GO term in this dataset
               count.InGenome: count of this GO term in the genome
               pvalue: pvalue from the hypergeometric test
               totaltermInDataset: count of all GO terms in this dataset
               totaltermInGenome: count of all GO terms in the genome
list("mf")    enriched molecular function with the following 9 variables
               go.id:GO molecular function id
               go.term:GO molecular function term
               go.Definition:GO molecular function description
               Ontology: Ontology branch, i.e. MF for molecular function
               count.InDataset: count of this GO term in this dataset
               count.InGenome: count of this GO term in the genome
               pvalue: pvalue from the hypergeometric test
               totaltermInDataset: count of all GO terms in this dataset
               totaltermInGenome: count of all GO terms in the genome

```

```
list("cc")      enriched cellular component the following 9 variables
                go.id:GO cellular component id
                go.term:GO cellular component term
                go.Definition:GO cellular component description
                Ontology: Ontology type, i.e. CC for cellular component
                count.InDataset: count of this GO term in this dataset
                count.InGenome: count of this GO term in the genome
                pvalue: pvalue from the hypergeometric test
                totaltermInDataset: count of all GO terms in this dataset
                totaltermInGenome: count of all GO terms in the genome
```

Author(s)

Lihua Julie Zhu

References

Johnson, N. L., Kotz, S., and Kemp, A. W. (1992) *Univariate Discrete Distributions*, Second Edition. New York: Wiley

See Also

phyper, hyperGtest

Examples

```
data(enrichedGO)
enrichedGO$mf[1:10,]
enrichedGO$bp[1:10,]
enrichedGO$cc
if (interactive()) {
  data(annotatedPeak)
  library(org.Hs.eg.db)
  library(GO.db)
  enriched.GO = getEnrichedGO(annotatedPeak[1:6,],
                             orgAnn="org.Hs.eg.db",
                             maxP=0.01,
                             minGOterm=10,
                             multiAdjMethod= NULL)

  dim(enriched.GO$mf)
  colnames(enriched.GO$mf)
  dim(enriched.GO$bp)
  enriched.GO$cc
}
```

getEnrichedPATH *Obtain enriched PATH that near the peaks*

Description

Obtain enriched PATH that are near the peaks using path package such as reactome.db and path mapping package such as org.Hs.db.eg to obtain the path annotation and using hypergeometric test (phyper) and multtest package for adjusting p-values

Usage

```
getEnrichedPATH(
  annotatedPeak,
  orgAnn,
  pathAnn,
  feature_id_type = "ensembl_gene_id",
  maxP = 0.01,
  minPATHterm = 10,
  multiAdjMethod = NULL
)
```

Arguments

annotatedPeak	GRanges such as data(annotatedPeak) or a vector of feature IDs
orgAnn	organism annotation package such as org.Hs.eg.db for human and org.Mm.eg.db for mouse, org.Dm.eg.db for fly, org.Rn.eg.db for rat, org.Sc.eg.db for yeast and org.Dr.eg.db for zebrafish
pathAnn	pathway annotation package such as KEGG.db, reactome.db, KEGGREST
feature_id_type	the feature type in annotatedPeakRanges such as ensembl_gene_id, refseq_id, gene_symbol or entrez_id
maxP	maximum p-value to be considered to be significant
minPATHterm	minimum count in a genome for a path to be included
multiAdjMethod	multiple testing procedures, for details, see mt.rawp2adjp in multtest package

Value

A dataframe of enriched path with the following variables.

path.id	KEGG PATH ID
EntrezID	Entrez ID
count.InDataset	count of this PATH in this dataset
count.InGenome	count of this PATH in the genome
pvalue	pvalue from the hypergeometric test
totaltermInDataset	count of all PATH in this dataset
totaltermInGenome	count of all PATH in the genome
PATH	PATH name

Author(s)

Jianhong Ou, Kai Hu

References

Johnson, N. L., Kotz, S., and Kemp, A. W. (1992) *Univariate Discrete Distributions*, Second Edition. New York: Wiley

See Also

phyper, hyperGtest

Examples

```
if (interactive() || Sys.getenv("USER")=="jianhongou") {
  data(annotatedPeak)
  library(org.Hs.eg.db)
  library(reactome.db)
  enriched.PATH = getEnrichedPATH(annotatedPeak, orgAnn="org.Hs.eg.db",
    feature_id_type="ensembl_gene_id",
    pathAnn="reactome.db", maxP=0.01,
    minPATHterm=10, multiAdjMethod=NULL)
  head(enriched.PATH)
  enrichedKEGG = getEnrichedPATH(annotatedPeak, orgAnn="org.Hs.eg.db",
    feature_id_type="ensembl_gene_id",
    pathAnn="KEGGREST", maxP=0.01,
    minPATHterm=10, multiAdjMethod=NULL)
  enrichmentPlot(enrichedKEGG)
}
```

getGO

Obtain gene ontology (GO) terms for given genes

Description

Obtain gene ontology (GO) terms using GO gene mapping package such as org.Hs.db.eg to obtain the GO annotation.

Usage

```
getGO(all.genes, orgAnn = "org.Hs.eg.db", writeTo, ID_type = "gene_symbol")
```

Arguments

all.genes	A character vector of feature IDs
orgAnn	Organism annotation package such as org.Hs.eg.db for human and org.Mm.eg.db for mouse, org.Dm.eg.db for fly, org.Rn.eg.db for rat, org.Sc.eg.db for yeast and org.Dr.eg.db for zebrafish
writeTo	File path for output table
ID_type	The feature type in annotatedPeak such as ensembl_gene_id, refseq_id, gene_symbol

Value

An invisible table with genes and GO terms.

Author(s)

Lihua Julie Zhu

See Also

getEnrichedGO

Examples

```
if (interactive()) {
  data(annotatedPeak)
  library(org.Hs.eg.db)
  getGO(annotatedPeak[1:6]$feature,
        orgAnn="org.Hs.eg.db",
        ID_type="ensembl_gene_id")
}
```

getVennCounts

Obtain Venn Counts for Venn Diagram, internal function for makeVennDiagram

Description

Obtain Venn Counts for peak ranges using chromosome ranges or feature field, internal function for makeVennDiagram

Usage

```
getVennCounts(
  ...,
  maxgap = -1L,
  minoverlap = 0L,
  by = c("region", "feature", "base"),
  ignore.strand = TRUE,
  connectedPeaks = c("min", "merge", "keepAll")
)
```

Arguments

... Objects of [GRanges](#). See example below.

maxgap, minoverlap

Used in the internal call to `findOverlaps()` to detect overlaps. See `?findOverlaps` in the **IRanges** package for a description of these arguments.

by

region, feature or base, default region. feature means using feature field in the **GRanges** for calculating overlap, region means using chromosome range for calculating overlap, and base means using calculating overlap in nucleotide level.

`ignore.strand` When set to TRUE, the strand information is ignored in the overlap calculations.

`connectedPeaks` If multiple peaks involved in overlapping in several groups, set it to "merge" will count it as only 1, while set it to "min" will count it as the minimal involved peaks in any concered groups

Value

`vennCounts` vennCounts objects containing counts for Venn Diagram generation, see details in limma package vennCounts

Author(s)

Jianhong Ou

See Also

[makeVennDiagram](#), [findOverlappingPeaks](#)

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){
peaks1 = GRanges(seqnames=c("1", "2", "3"),
                 IRanges(start = c(967654, 2010897, 2496704),
                          end = c(967754, 2010997, 2496804),
                          names = c("Site1", "Site2", "Site3")),
                 strand=as.integer(1),
                 feature=c("a","b", "c"))
peaks2 =
  GRanges(seqnames= c("1", "2", "3", "1", "2"),
          IRanges(start=c(967659, 2010898, 2496700, 3075866, 3123260),
                  end=c(967869, 2011108, 2496920, 3076166, 3123470),
                  names = c("t1", "t2", "t3", "t4", "t5")),
          strand = c(1L, 1L, -1L,-1L,1L),
          feature=c("a","c","d","e", "a"))
getVennCounts(peaks1,peaks2)
getVennCounts(peaks1,peaks2, by="feature")
getVennCounts(peaks1, peaks2, by="base")
}
```

HOT.spots

High Occupancy of Transcription Related Factors regions

Description

High Occupancy of Transcription Related Factors regions of human (hg19)

Usage

HOT.spots

Format

An object of GRangesList

Details

How to generated the data:

```
temp <- tempfile()
url <- "http://metatracks.encodegenetics.org"
download.file(file.path(url, "HOT_All_merged.tar.gz"), temp)
temp2 <- tempfile()
download.file(file.path(url, "HOT_intergenic_All_merged.tar.gz"), temp2)
untar(temp, exdir=dirname(temp))
untar(temp2, exdir=dirname(temp))
f <- dir(dirname(temp), "bed$")
HOT.spots <- sapply(file.path(dirname(temp), f), toGRanges, format="BED")
names(HOT.spots) <- gsub("_merged.bed", "", f)
HOT.spots <- sapply(HOT.spots, unname)
HOT.spots <- GRangesList(HOT.spots)
save(list="HOT.spots",
file="data/HOT.spots.rda",
compress="xz", compression_level=9)
```

Source

<http://metatracks.encodegenetics.org/>

References

Yip KY, Cheng C, Bhardwaj N, Brown JB, Leng J, Kundaje A, Rozowsky J, Birney E, Bickel P, Snyder M, Gerstein M. Classification of human genomic regions based on experimentally determined binding sites of more than 100 transcription-related factors. *Genome Biol.* 2012 Sep 26;13(9):R48. doi: 10.1186/gb-2012-13-9-r48. PubMed PMID: 22950945; PubMed Central PMCID: PMC3491392.

Examples

```
data(HOT.spots)
elementNROWS(HOT.spots)
```

 IDRfilter

Filter peaks by IDR (irreproducible discovery rate)

Description

Using IDR to assess the consistency of replicate experiments and obtain a high-confidence single set of peaks

Usage

```
IDRfilter(
  peaksA,
  peaksB,
  bamfileA,
  bamfileB,
  maxgap = -1L,
  minoverlap = 0L,
  singleEnd = TRUE,
  IDRcutoff = 0.01,
  ...
)
```

Arguments

peaksA, peaksB peaklist, [GRanges](#) object.

bamfileA, bamfileB
file path of bam files.

maxgap, minoverlap
Used in the internal call to `findOverlaps()` to detect overlaps. See `?findOverlaps` in the **IRanges** package for a description of these arguments.

singleEnd (Default TRUE) A logical indicating if reads are single or paired-end.

IDRcutoff If the IDR no less than IDRcutoff, the peak will be removed.

... Not used.

Value

An object `GRanges`

Author(s)

Jianhong Ou

References

Li, Qunhua, et al. "Measuring reproducibility of high-throughput experiments." *The annals of applied statistics* (2011): 1752-1779.

Examples

```

if(interactive()){
  path <- system.file("extdata", "reads", package="MMDiffBamSubset")
  if(file.exists(path)){
    bamfileA <- file.path(path, "reads", "WT_2.bam")
    bamfileB <- file.path(path, "reads", "Resc_2.bam")
    WT.AB2.Peaks <- file.path(path, "peaks", "WT_2_Macs_peaks.xls")
    Resc.AB2.Peaks <- file.path(path, "peaks",
                                "Resc_2_Macs_peaks.xls")
    peaksA=toGRanges(WT.AB2.Peaks, format="MACS")
    peaksB=toGRanges(Resc.AB2.Peaks, format="MACS")
    library(idr)
    library(DelayedArray)
    IDRfilter(peaksA, peaksB,
              bamfileA, bamfileB)
  }
}

```

makeVennDiagram

*Make Venn Diagram from a list of peaks***Description**

Make Venn Diagram from two or more peak ranges, Also calculate p-value to determine whether those peaks overlap significantly.

Usage

```

makeVennDiagram(
  Peaks,
  NameOfPeaks,
  maxgap = -1L,
  minoverlap = 0L,
  totalTest,
  by = c("region", "feature", "base"),
  ignore.strand = TRUE,
  connectedPeaks = c("min", "merge", "keepAll", "keepFirstListConsistent"),
  method = c("hyperG", "permutation"),
  TxDb,
  plot = TRUE,
  ...
)

```

Arguments

Peaks A list of peaks in [GRanges](#) format: See example below.

NameOfPeaks Character vector to specify the name of Peaks, e.g., c("TF1", "TF2"). This will be used as label in the Venn Diagram.


```

        end = c(967869, 2011108, 2496920,
              3076166, 3123470),
        names = c("t1", "t2", "t3", "t4", "t5")),
    strand = c("+", "+", "-", "-", "+"),
    feature=c("a","b","c","d","a"))
makeVennDiagram(list(peaks1, peaks2), NameOfPeaks=c("TF1", "TF2"),
totalTest=100,scaled=FALSE, euler.d=FALSE,
fill=c("#009E73", "#F0E442"), # circle fill color
col=c("#D55E00", "#0072B2"), #circle border color
cat.col=c("#D55E00", "#0072B2"))

makeVennDiagram(list(peaks1, peaks2), NameOfPeaks=c("TF1", "TF2"),
totalTest=100,
fill=c("#009E73", "#F0E442"), # circle fill color
col=c("#D55E00", "#0072B2"), #circle border color
cat.col=c("#D55E00", "#0072B2"))

##### 4-way diagram using annotated feature instead of chromosome ranges

makeVennDiagram(list(peaks1, peaks2, peaks1, peaks2),
NameOfPeaks=c("TF1", "TF2","TF3", "TF4"),
totalTest=100, by="feature",
main = "Venn Diagram for 4 peak lists",
fill=c(1,2,3,4))
}

```

mergePlusMinusPeaks *Merge peaks from plus strand and minus strand*

Description

Merge peaks from plus strand and minus strand within certain distance apart, and output merged peaks as bed format.

Usage

```

mergePlusMinusPeaks(
  peaks.file,
  columns = c("name", "chromosome", "start", "end", "strand", "count", "count",
             "count", "count"),
  sep = "\t",
  header = TRUE,
  distance.threshold = 100,
  plus.strand.start.gt.minus.strand.end = TRUE,
  output.bedfile
)

```

Arguments

peaks.file	Specify the peak file. The peak file should contain peaks from both plus and minus strand
columns	Specify the column names in the peak file
sep	Specify column delimiter, default tab-delimited

metagenePlot	<i>peak distance to features</i>
--------------	----------------------------------

Description

Bar plot for distance to features

Usage

```
metagenePlot(
  peaks,
  AnnotationData,
  PeakLocForDistance = c("middle", "start", "end"),
  FeatureLocForDistance = c("TSS", "middle", "geneEnd"),
  upstream = 1e+05,
  downstream = 1e+05
)
```

Arguments

`peaks` peak list, [GRanges](#) object or a [GRangesList](#).

`AnnotationData` A [GRanges](#) object or a [TxDb](#) object.

`PeakLocForDistance`

Specify the location of peak for calculating distance, i.e., middle means using middle of the peak to calculate distance to feature, start means using start of the peak to calculate the distance to feature. To be compatible with previous version, by default using start

`FeatureLocForDistance`

Specify the location of feature for calculating distance, i.e., middle means using middle of the feature to calculate distance of peak to feature, TSS means using start of feature when feature is on plus strand and using end of feature when feature is on minus strand, geneEnd means using end of feature when feature is on plus strand and using start of feature when feature is on minus strand.

`upstream, downstream`

numeric(1). Upstream or downstream region of features to plot.

Details

the bar heatmap indicates the peaks around features.

Examples

```
path <- system.file("extdata", package="ChIPpeakAnno")
files <- dir(path, "broadPeak")
peaks <- sapply(file.path(path, files), toGRanges, format="broadPeak")
peaks <- GRangesList(peaks)
names(peaks) <- sub(".broadPeak", "", basename(names(peaks)))
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
metagenePlot(peaks, TxDb.Hsapiens.UCSC.hg19.knownGene)
```

 myPeakList

An example GRanges object representing a ChIP-seq peak dataset

Description

the putative STAT1-binding regions identified in un-stimulated cells using ChIP-seq technology (Robertson et al., 2007)

Usage

```
myPeakList
```

Format

GRanges with slot rownames containing the ID of peak as character, slot start containing the start position of the peak, slot end containing the end position of the peak and seqnames containing the chromosome where the peak is located.

Source

Robertson G, Hirst M, Bainbridge M, Bilenky M, Zhao Y, et al. (2007) Genome-wide profiles of STAT1 DNA association using chromatin immunoprecipitation and massively parallel sequencing. Nat Methods 4:651-7

Examples

```
data(myPeakList)
slotNames(myPeakList)
```

 oligoFrequency

get the oligonucleotide frequency

Description

Prepare the oligonucleotide frequency for given Markov order.

Usage

```
oligoFrequency(sequence, MarkovOrder = 3L, last = 1e+06)
```

Arguments

sequence	The sequences packaged in DNASTringSet, DNASTring object or output of function getAllPeakSequence .
MarkovOrder	Markov order.
last	The sequence size to be analyzed.

Value

A numeric vector.

Author(s)

Jianhong Ou

See Also

See Also as [oligoSummary](#)

Examples

```
library(seqinr)
library(Biostrings)
oligoFrequency(DNAString("AATTCGACGTACAGATGACTAGACT"))
```

oligoSummary

Output a summary of consensus in the peaks

Description

Calculate the z-scores of all combinations of oligonucleotide in a given length by Markov chain.

Usage

```
oligoSummary(
  sequence,
  oligoLength = 6L,
  freqs = NULL,
  MarkovOrder = 3L,
  quickMotif = FALSE,
  revcomp = FALSE,
  maxsize = 1e+05
)
```

Arguments

sequence	The sequences packaged in DNAStringSet, DNAString object or output of function getAllPeakSequence .
oligoLength	The length of oligonucleotide.
freqs	Output of function frequency .
MarkovOrder	The order of Markov chain.
quickMotif	Generate the motif by z-score of not.
revcomp	Consider both the given strand and the reverse complement strand when searching for motifs in a complementable alphabet (ie DNA). Default, FALSE.
maxsize	Maximum allowed dataset size (in length of sequences).

Value

A list is returned.

zscore A numeric vector. The z-scores of each oligonucleotide.
counts A numeric vector. The counts number of each oligonucleotide.
motifs a list of motif matrix.

Author(s)

Jianhong Ou

References

van Helden, Jacques, Marcel li del Olmo, and Jose E. Perez-Ortin. "Statistical analysis of yeast genomic downstream sequences reveals putative polyadenylation signals." *Nucleic Acids Research* 28.4 (2000): 1000-1010.

See Also

See Also as [frequency](#)

Examples

```
if(interactive() || Sys.getenv("USER")=="jianhongou"){  
  data(annotatedPeak)  
  library(BSgenome.Hsapiens.UCSC.hg19)  
  library(seqinr)  
  seq <- getAllPeakSequence(annotatedPeak[1:100],  
                             upstream=20,  
                             downstream=20,  
                             genome=Hsapiens)  
  oligoSummary(seq)  
}
```

peakPermTest

Permutation Test for two given peak lists

Description

Performs a permutation test to see if there is an association between two given peak lists.

Usage

```
peakPermTest(  
  peaks1,  
  peaks2,  
  ntimes = 100,  
  seed = as.integer(Sys.time()),  
  mc.cores = getOption("mc.cores", 2L),  
  maxgap = -1L,
```

```

    pool,
    TxDb,
    bindingDistribution,
    bindingType = c("TSS", "geneEnd"),
    featureType = c("transcript", "exon"),
    seqn = NA,
    ...
)

```

Arguments

peaks1, peaks2	an object of GRanges
ntimes	number of permutations
seed	random seed
mc.cores	The number of cores to use. see <code>mclapply</code> .
maxgap	See findOverlaps in the <code>IRanges</code> package for a description of these arguments.
pool	an object of permPool
TxDb	an object of TxDb
bindingDistribution	an object of bindist
bindingType	where the peaks should bind, TSS or geneEnd
featureType	what annotation type should be used for detecting the binding distribution.
seqn	default is NA, which means not filter the universe pool for sampling. Otherwise the universe pool will be filtered by the seqnames in seqn.
...	further arguments to be passed to numOverlaps .

Value

A list of class `permTestResults`. See [permTest](#)

Author(s)

Jianhong Ou

References

Davison, A. C. and Hinkley, D. V. (1997) *Bootstrap methods and their application*, Cambridge University Press, United Kingdom, 156-160

See Also

[preparePool](#), [bindist](#)

Examples

```

path <- system.file("extdata", package="ChIPpeakAnno")
#files <- dir(path, pattern="[12]_WS170.bed", full.names=TRUE)
#peaks1 <- toGRanges(files[1], skip=5)
#peaks2 <- toGRanges(files[2], skip=5)
#peakPermTest(peaks1, peaks2, TxDb=TxDb.Celegans.UCSC.ce6.ensGene)

```

```
if(interactive()){
  peaks1 <- toGRanges(file.path(path, "MACS2_peaks.xls"),
                      format="MACS2")
  peaks2 <- toGRanges(file.path(path, "peaks.narrowPeak"),
                      format="narrowPeak")
  library(TxDb.Hsapiens.UCSC.hg19.knownGene)
  peakPermTest(peaks1, peaks2,
               TxDb=TxDb.Hsapiens.UCSC.hg19.knownGene, min.pctA=10)
}
```

Peaks.Ste12.Replicate1

Ste12-binding sites from biological replicate 1 in yeast (see reference)

Description

Ste12-binding sites from biological replicate 1 in yeast (see reference)

Usage

```
Peaks.Ste12.Replicate1
```

Format

GRanges with slot names containing the ID of peak as character, slot start containing the start position of the peak, slot end containing the end position of the peak and space containing the chromosome where the peak is located.

References

Philippe Lefrançois, Ghia M Euskirchen, Raymond K Auerbach, Joel Rozowsky, Theodore Gibson, Christopher M Yellman, Mark Gerstein and Michael Snyder (2009) Efficient yeast ChIP-Seq using multiplex short-read DNA sequencing BMC Genomics 10:37

Examples

```
data(Peaks.Ste12.Replicate1)
Peaks.Ste12.Replicate1
```

```
Peaks.Ste12.Replicate2
```

Ste12-binding sites from biological replicate 2 in yeast (see reference)

Description

Ste12-binding sites from biological replicate 2 in yeast (see reference)

Usage

```
Peaks.Ste12.Replicate2
```

Format

GRanges with slot names containing the ID of peak as character, slot start containing the start position of the peak, slot end containing the end position of the peak and space containing the chromosome where the peak is located.

Source

<http://www.biomedcentral.com/1471-2164/10/37>

References

Philippe Lefrançois, Ghia M Euskirchen, Raymond K Auerbach, Joel Rozowsky, Theodore Gibson, Christopher M Yellman, Mark Gerstein and Michael Snyder (2009) Efficient yeast ChIP-Seq using multiplex short-read DNA sequencing BMC Genomics 10:37doi:10.1186/1471-2164-10-37

Examples

```
data(Peaks.Ste12.Replicate2)
Peaks.Ste12.Replicate2
```

```
Peaks.Ste12.Replicate3
```

Ste12-binding sites from biological replicate 3 in yeast (see reference)

Description

Ste12-binding sites from biological replicate 3 in yeast (see reference)

Usage

```
Peaks.Ste12.Replicate3
```

Format

GRanges with slot names containing the ID of peak as character, slot start containing the start position of the peak, slot end containing the end position of the peak and space containing the chromosome where the peak is located.

Source

<http://www.biomedcentral.com/1471-2164/10/37>

References

Philippe Lefrançois, Ghia M Euskirchen, Raymond K Auerbach, Joel Rozowsky, Theodore Gibson, Christopher M Yellman, Mark Gerstein and Michael Snyder (2009) Efficient yeast ChIP-Seq using multiplex short-read DNA sequencing *BMC Genomics* 10:37doi:10.1186/1471-2164-10-37

Examples

```
data(Peaks.Ste12.Replicate3)
Peaks.Ste12.Replicate3
```

peaksNearBDP	<i>obtain the peaks near bi-directional promoters</i>
--------------	---

Description

Obtain the peaks near bi-directional promoters. Also output percent of peaks near bi-directional promoters.

Usage

```
peaksNearBDP(myPeakList, AnnotationData, MaxDistance = 5000L, ...)
```

Arguments

myPeakList	GRanges : See example below
AnnotationData	annotation data obtained from <code>getAnnotation</code> or customized annotation of class GRanges containing additional variable: strand (1 or + for plus strand and -1 or - for minus strand). For example, <code>data(TSS.human.NCBI36)</code> , <code>data(TSS.mouse.NCBIM37)</code> , <code>data(TSS.rat.RGSC3.4)</code> and <code>data(TSS.zebrafish.Zv8)</code> .
MaxDistance	Specify the maximum gap allowed between the peak and nearest gene
...	Not used

Value

A list of 4

```
list("peaksWithBDP")
```

annotated Peaks containing bi-directional promoters.

GRangesList with slot start holding the start position of the peak, slot end holding the end position of the peak, slot space holding the chromosome location where the peak is located, slot rownames holding the id of the peak. In addition, the following variables are included.

feature: id of the feature such as ensembl gene ID

insideFeature: upstream: peak resides upstream of the feature; downstream: peak resides downstream of the feature; inside: peak resides inside the feature; overlapStart: peak overlaps with the start of the feature; overlapEnd: peak overlaps with the end of the feature; includeFeature: peak include the feature entirely.

distancetoFeature: distance to the nearest feature such as transcription start site. By default, the distance is calculated as the distance between the start of the binding site and the TSS that is the gene start for genes located on the forward strand and the gene end for genes located on the reverse strand. The user can specify the location of peak and location of feature for calculating this

feature_range: start and end position of the feature such as gene

feature_strand: 1 or + for positive strand and -1 or - for negative strand where the feature is located

```
list("percentPeaksWithBDP")
```

The percent of input peaks containing bi-directional promoters

```
list("n.peaks")
```

The total number of input peaks

```
list("n.peaksWithBDP")
```

The # of input peaks containing bi-directional promoters

Author(s)

Lihua Julie Zhu, Jianhong Ou

References

Zhu L.J. et al. (2010) ChIPpeakAnno: a Bioconductor package to annotate ChIP-seq and ChIP-chip data. BMC Bioinformatics 2010, 11:237doi:10.1186/1471-2105-11-237

See Also

annotatePeakInBatch, findOverlappingPeaks, makeVennDiagram

Examples

```
if (interactive() || Sys.getenv("USER")=="jianhongou")
{
  data(myPeakList)
  data(TSS.human.NCBI36)
  seqlevelsStyle(TSS.human.NCBI36) <- seqlevelsStyle(myPeakList)
  annotatedBDP = peaksNearBDP(myPeakList[1:6,],
                             AnnotationData=TSS.human.NCBI36,
                             MaxDistance=5000,
                             PeakLocForDistance = "middle",
                             FeatureLocForDistance = "TSS")
  c(annotatedBDP$percentPeaksWithBDP, annotatedBDP$n.peaks,
    annotatedBDP$n.peaksWithBDP)
}
```

permPool-class *Class "permPool"*

Description

An object of class "permPool" represents the possible locations to do permutation test.

Slots

grs object of "GRangesList" The list of binding ranges
 N vector of "integer", permutation number for each ranges

Objects from the Class

Objects can be created by calls of the form `new("permPool", grs="GRangesList", N="integer")`.

See Also

[preparePool](#), [peakPermTest](#)

pie1 *Pie Charts*

Description

Draw a pie chart with percentage

Usage

```
pie1(
  x,
  labels = names(x),
  edges = 200,
  radius = 0.8,
  clockwise = FALSE,
  init.angle = if (clockwise) 90 else 0,
  density = NULL,
  angle = 45,
  col = NULL,
  border = NULL,
  lty = NULL,
  main = NULL,
  percentage = TRUE,
  rawNumber = FALSE,
  digits = 3,
  cutoff = 0.01,
  legend = FALSE,
  legendpos = "topright",
  legendcol = 2,
  radius.innerlabel = radius,
  ...
)
```

Arguments

x	a vector of non-negative numerical quantities. The values in x are displayed as the areas of pie slices.
labels	one or more expressions or character strings giving names for the slices. Other objects are coerced by <code>as.graphicsAnnot</code> . For empty or NA (after coercion to character) labels, no label nor pointing line is drawn.
edges	the circular outline of the pie is approximated by a polygon with this many edges.
radius	the pie is drawn centered in a square box whose sides range from -1 to 1. If the character strings labeling the slices are long it may be necessary to use a smaller radius.
clockwise	logical indicating if slices are drawn clockwise or counter clockwise (i.e., mathematically positive direction), the latter is default.
init.angle	number specifying the starting angle (in degrees) for the slices. Defaults to 0 (i.e., "3 o'clock") unless clockwise is true where init.angle defaults to 90 (degrees), (i.e., "12 o'clock").
density	the density of shading lines, in lines per inch. The default value of NULL means that no shading lines are drawn. Non-positive values of density also inhibit the drawing of shading lines.
angle	the slope of shading lines, given as an angle in degrees (counter-clockwise).
col	a vector of colors to be used in filling or shading the slices. If missing a set of 6 pastel colours is used, unless density is specified when <code>par("fg")</code> is used.
border, lty	(possibly vectors) arguments passed to polygon which draws each slice.
main	an overall title for the plot.
percentage	logical. Add percentage in the figure or not. default TRUE.
rawNumber	logical. Instead percentage, add raw number in the figure or not. default FALSE.
digits	When set percentage as TRUE, how many significant digits are to be used for percentage. see format . default 3.
cutoff	When percentage is TRUE, if the percentage is lower than cutoff, it will NOT be shown. default 0.01.
legend	logical. Instead of lable, draw legend for the pie. default, FALSE.
legendpos, legendcol	legend position and legend columns. see legend
radius.innerlabel	position of percentage or raw number label relative to the circle.
...	graphical parameters can be given as arguments to pie. They will affect the main title and labels only.

Author(s)

Jianhong Ou

See Also

[pie](#)

Examples

```
pie1(1:5)
```

plotBinOverRegions *plot the coverage of regions*

Description

plot the output of [binOverRegions](#) or [binOverGene](#)

Usage

```
plotBinOverRegions(dat, ...)
```

Arguments

dat A list of matrix which indicate the coverage of regions per bin
... Parameters could be used by [matplot](#)

Author(s)

Jianhong Ou

See Also

[binOverRegions](#), [binOverGene](#)

Examples

```
if(interactive()){  
  path <- system.file("extdata", package="ChIPpeakAnno")  
  library(TxDb.Hsapiens.UCSC.hg19.knownGene)  
  library(rtracklayer)  
  files <- dir(path, "bigWig")  
  if(.Platform$OS.type != "windows"){  
    cvglists <- lapply(file.path(path, files), import,  
                      format="BigWig", as="RleList")  
    names(cvglists) <- sub(".bigWig", "", files)  
    d <- binOverGene(cvglists, TxDb.Hsapiens.UCSC.hg19.knownGene)  
    plotBinOverRegions(d)  
  }  
}
```

preparePool	<i>prepare data for permutation test</i>
-------------	--

Description

prepare data for permutation test [peakPermTest](#)

Usage

```
preparePool(
  TxDb,
  template,
  bindingDistribution,
  bindingType = c("TSS", "geneEnd"),
  featureType = c("transcript", "exon"),
  seqn = NA
)
```

Arguments

TxDb	an object of TxDb
template	an object of GRanges
bindingDistribution	an object of bindist
bindingType	the relevant position to features
featureType	feature type, transcript or exon.
seqn	seqnames. If given, the pool for permutation will be restrict in the given chromosomes.

Value

a list with two elements, grs, a list of [GRanges](#). N, the numbers of elements should be drawn from in each [GRanges](#).

Author(s)

Jianhong Ou

See Also

[peakPermTest](#), [bindist](#)

Examples

```
if(interactive() || Sys.getenv("USER")==="jianhongou"){
  path <- system.file("extdata", package="ChIPpeakAnno")
  peaksA <- toGRanges(file.path(path, "peaks.narrowPeak"),
                      format="narrowPeak")
  peaksB <- toGRanges(file.path(path, "MACS2_peaks.xls"), format="MACS2")
  library(TxDb.Hsapiens.UCSC.hg19.knownGene)
```

```

    ppp <- preparePool(TxDb.Hsapiens.UCSC.hg19.knownGene,
                      peaksA, bindingType="TSS",
                      featureType="transcript")
  }

```

reCenterPeaks *re-center the peaks*

Description

Create a new list of peaks based on the peak centers of given list.

Usage

```
reCenterPeaks(peaks, width = 2000L, ...)
```

Arguments

peaks	An object of GRanges or annoGR .
width	The width of new peaks
...	Not used.

Value

An object of [GRanges](#).

Author(s)

Jianhong Ou

Examples

```
reCenterPeaks(GRanges("chr1", IRanges(1, 10)), width=2)
```

summarizeOverlapsByBins

Perform overlap queries between reads and genomic features by bins

Description

summarizeOverlapsByBins extends [summarizeOverlaps](#) by providing fixed window size and step to split each feature into bins and then do queries. It will return counts by `signalSummaryFUN`, which applied to bins in one feature, for each feature.

Usage

```
summarizeOverlapsByBins(
  targetRegions,
  reads,
  windowSize = 50,
  step = 10,
  signalSummaryFUN = max,
  mode = countByOverlaps,
  ...
)
```

Arguments

targetRegions A [GRanges](#) object of genomic regions of interest.

reads A [GRanges](#), [GRangesList](#), [GAlignments](#), [GAlignmentsList](#), [GAlignmentPairs](#) or [BamFileList](#) object that represents the data to be counted by [summarizeOverlaps](#).

windowSize Size of windows

step Step of windows

signalSummaryFUN function, which will be applied to the bins in each feature.

mode mode can be one of the pre-defined count methods. see [summarizeOverlaps](#). default is countByOverlaps, alia of countOverlaps(features, reads, ignore.strand=ignore.strand)

... Additional arguments passed to [summarizeOverlaps](#).

Value

A [RangedSummarizedExperiment](#) object. The assays slot holds the counts, rowRanges holds the annotation from features.

Author(s)

Jianhong Ou

Examples

```
f1s <- list.files(system.file("extdata", package="GenomicAlignments"),
  recursive=TRUE, pattern="*bam$", full=TRUE)
names(f1s) <- basename(f1s)
genes <- GRanges(
  seqnames = c(rep("chr2L", 4), rep("chr2R", 5), rep("chr3L", 2)),
  ranges = IRanges(c(1000, 3000, 4000, 7000, 2000, 3000, 3600,
    4000, 7500, 5000, 5400),
  width=c(rep(500, 3), 600, 900, 500, 300, 900,
    300, 500, 500),
  names=letters[1:11]))
se <- summarizeOverlapsByBins(genes, f1s, windowSize=50, step=10)
```

```
summarizePatternInPeaks
```

Output a summary of the occurrence of each pattern in the sequences.

Description

Output a summary of the occurrence of each pattern in the sequences.

Usage

```
summarizePatternInPeaks(
  patternFilePath,
  format = "fasta",
  skip = 0L,
  BSgenomeName,
  peaks,
  outfile,
  append = FALSE
)
```

Arguments

patternFilePath	A character vector containing the path to the file to read the patterns from.
format	Either "fasta" (the default) or "fastq"
skip	Single non-negative integer. The number of records of the pattern file to skip before beginning to read in records.
BSgenomeName	BSgenome object. Please refer to available.genomes in BSgenome package for details
peaks	GRanges containing the peaks
outfile	A character vector containing the path to the file to write the summary output.
append	TRUE or FALSE, default FALSE

Value

A data frame with 3 columns as n.peaksWithPattern (number of peaks with the pattern), n.totalPeaks (total number of peaks in the input) and Pattern (the corresponding pattern). The summary will consider both strand (including reverse complement).

Author(s)

Lihua Julie Zhu

Examples

```
peaks = GRanges(seqnames=c("NC_008253", "NC_010468"),
                IRanges(start=c(100, 500), end=c(300, 600),
                        names=c("peak1", "peak2")))
filepath =system.file("extdata", "examplePattern.fa",
```

```

package="ChIPpeakAnno")
library(BSgenome.Ecoli.NCBI.20080805)
summarizePatternInPeaks(patternFilePath=filepath, format="fasta",
                        skip=0L, BSgenomeName=Ecoli, peaks=peaks)

```

tileCount

Perform overlap queries between reads and genome by windows

Description

tileCount extends [summarizeOverlaps](#) by providing fixed window size and step to split whole genome into windows and then do queries. It will return counts in each windows.

Usage

```

tileCount(
  reads,
  genome,
  windowSize = 1e+06,
  step = 1e+06,
  keepPartialWindow = FALSE,
  mode = countByOverlaps,
  ...
)

```

Arguments

reads	A GRanges , GRangesList , GAlignments , GAlignmentsList , GAlignmentPairs or BamFileList object that represents the data to be counted by summarizeOverlaps .
genome	The object from/on which to get/set the sequence information.
windowSize	Size of windows
step	Step of windows
keepPartialWindow	Keep last partial window or not.
mode	mode can be one of the pre-defined count methods. see summarizeOverlaps . default is countByOverlaps, alia of countOverlaps(features, reads, ignore.strand=ignore.strand)
...	Additional arguments passed to summarizeOverlaps .

Value

A [RangedSummarizedExperiment](#) object. The assays slot holds the counts, rowRanges holds the annotation from genome.

Author(s)

Jianhong Ou

Examples

```
fls <- list.files(system.file("extdata", package="GenomicAlignments"),
                  recursive=TRUE, pattern="*bam$", full=TRUE)
names(fl) <- basename(fl)
genes <- GRanges(seqlengths = c(chr2L=7000, chr2R=10000))
se <- tileCount(fl, genes, windowSize=1000, step=500)
```

tileGRanges

Slide windows on a given [GRanges](#) object

Description

tileGRanges returns a set of genomic regions by sliding the windows in a given step. Each window is called a "tile".

Usage

```
tileGRanges(targetRegions, windowSize, step, keepPartialWindow = FALSE, ...)
```

Arguments

targetRegions	A GRanges object of genomic regions of interest.
windowSize	Size of windows
step	Step of windows
keepPartialWindow	Keep last partial window or not.
...	Not used.

Value

A [GRanges](#) object.

Author(s)

Jianhong Ou

Examples

```
genes <- GRanges(
  seqnames = c(rep("chr2L", 4), rep("chr2R", 5), rep("chr3L", 2)),
  ranges = IRanges(c(1000, 3000, 4000, 7000, 2000, 3000, 3600,
                    4000, 7500, 5000, 5400),
                  width=c(rep(500, 3), 600, 900, 500, 300, 900,
                           300, 500, 500),
                  names=letters[1:11]))
se <- tileGRanges(genes, windowSize=50, step=10)
```

`toGRanges`*Convert dataset to GRanges*

Description

Convert UCSC BED format and its variants, such as GFF, or any user defined dataset such as MACS output file to GRanges

Usage

```
toGRanges(data, ...)

## S4 method for signature 'connection'
toGRanges(
  data,
  format = c("BED", "GFF", "GTF", "MACS", "MACS2", "MACS2.broad", "narrowPeak",
    "broadPeak", "others"),
  header = FALSE,
  comment.char = "#",
  colNames = NULL,
  ...
)

## S4 method for signature 'TxDb'
toGRanges(
  data,
  feature = c("gene", "transcript", "exon", "CDS", "fiveUTR", "threeUTR", "microRNA",
    "tRNAs", "geneModel"),
  OrganismDb,
  ...
)

## S4 method for signature 'EnsDb'
toGRanges(
  data,
  feature = c("gene", "transcript", "exon", "disjointExons"),
  ...
)

## S4 method for signature 'character'
toGRanges(
  data,
  format = c("BED", "GFF", "GTF", "MACS", "MACS2", "MACS2.broad", "narrowPeak",
    "broadPeak", "others"),
  header = FALSE,
  comment.char = "#",
  colNames = NULL,
  ...
)
```

Arguments

data	an object of data.frame, TxDb or EnsDb , or the file name of data to be imported. Alternatively, data can be a readable txt-mode connection (See <code>?read.table</code>).
...	parameters passed to read.table
format	data format. If the data format is set to BED, GFF, narrowPeak or broadPeak, please refer to http://genome.ucsc.edu/FAQ/FAQformat#format1 for column order. "MACS" is for converting the excel output file from MACS1. "MACS2" is for converting the output file from MACS2.
header	A logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: header is set to TRUE if and only if the first row contains one fewer field than the number of columns.
comment.char	character: a character vector of length one containing a single character or an empty string. Use "" to turn off the interpretation of comments altogether.
colNames	If the data format is set to "others", colname must be defined. And the colname must contain space, start and end. The column name for the chromosome # should be named as space.
feature	annotation type
OrganismDb	an object of OrganismDb . It is used for extracting gene symbol for geneModel group for TxDb

Value

An object of [GRanges](#)

Author(s)

Jianhong Ou

Examples

```

macs <- system.file("extdata", "MACS_peaks.xls", package="ChIPpeakAnno")
macsOutput <- toGRanges(macs, format="MACS")
if(interactive() || Sys.getenv("USER")=="jianhongou"){
  ## MACS connection
  macs <- readLines(macs)
  macs <- textConnection(macs)
  macsOutput <- toGRanges(macs, format="MACS")
  close(macs)
  ## bed
  toGRanges(system.file("extdata", "MACS_output.bed", package="ChIPpeakAnno"),
             format="BED")
  ## narrowPeak
  toGRanges(system.file("extdata", "peaks.narrowPeak", package="ChIPpeakAnno"),
             format="narrowPeak")
  ## broadPeak
  toGRanges(system.file("extdata", "TAF.broadPeak", package="ChIPpeakAnno"),
             format="broadPeak")
  ## MACS2
  toGRanges(system.file("extdata", "MACS2_peaks.xls", package="ChIPpeakAnno"),
             format="MACS2")
}

```

```

## GFF
toGRanges(system.file("extdata", "GFF_peaks.gff", package="ChIPpeakAnno"),
           format="GFF")
## EnsDb
library(EnsDb.Hsapiens.v75)
toGRanges(EnsDb.Hsapiens.v75, feature="gene")
## TxDb
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
toGRanges(TxDb.Hsapiens.UCSC.hg19.knownGene, feature="gene")
## data.frame
macs <- system.file("extdata", "MACS_peaks.xls", package="ChIPpeakAnno")
macs <- read.delim(macs, comment.char="#")
toGRanges(macs)
}

```

translatePattern	<i>translate pattern from IUPAC Extended Genetic Alphabet to regular expression</i>
------------------	---

Description

translate pattern containing the IUPAC nucleotide ambiguity codes to regular expression. For example, Y->[C|T], R-> [A|G], S-> [G|C], W-> [A|T], K-> [T|U|G], M-> [A|C], B-> [C|G|T], D-> [A|G|T], H-> [A|C|T], V-> [A|C|G] and N-> [A|C|T|G].

Usage

```
translatePattern(pattern)
```

Arguments

pattern a character vector with the IUPAC nucleotide ambiguity codes

Value

a character vector with the pattern represented as regular expression

Author(s)

Lihua Julie Zhu

See Also

countPatternInSeqs, summarizePatternInPeaks

Examples

```

pattern1 = "AACCNWMK"
translatePattern(pattern1)

```

TSS.human.GRCh37

TSS annotation for human sapiens (GRCh37) obtained from biomaRt

Description

TSS annotation for human sapiens (GRCh37) obtained from biomaRt

Usage

TSS.human.GRCh37

Format

A GRanges object with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

The dataset TSS.human.GRCh37 was obtained by:

```
mart = useMart(biomart = "ENSEMBL_MART_ENSEMBL", host="grch37.ensembl.org", path="/biomart/martservice",
dataset = "hsapiens_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.human.GRCh37)
slotNames(TSS.human.GRCh37)
```

TSS.human.GRCh38

TSS annotation for human sapiens (GRCh38) obtained from biomaRt

Description

TSS annotation for human sapiens (GRCh38) obtained from biomaRt

Usage

TSS.human.GRCh38

Format

A 'GRanges' [package "GenomicRanges"] object with ensembl id as names.

Details

used in the examples Annotation data obtained by:

```
mart = useMart(biomart = "ensembl", dataset = "hsapiens_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.human.GRCh38)
slotNames(TSS.human.GRCh38)
```

TSS.human.NCBI36

TSS annotation for human sapiens (NCBI36) obtained from biomaRt

Description

TSS annotation for human sapiens (NCBI36) obtained from biomaRt

Usage

```
TSS.human.NCBI36
```

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

used in the examples Annotation data obtained by:

```
mart = useMart(biomart = "ensembl_mart_47", dataset = "hsapiens_gene_ensembl", archive=TRUE)
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.human.NCBI36)
slotNames(TSS.human.NCBI36)
```

TSS.mouse.GRCm38 *TSS annotation data for Mus musculus (GRCm38.p1) obtained from biomaRt*

Description

TSS annotation data for Mus musculus (GRCm38.p1) obtained from biomaRt

Usage

TSS.mouse.GRCm38

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

Annotation data obtained by:

```
mart = useMart(biomart = "ensembl", dataset = "mmusculus_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.mouse.GRCm38)
slotNames(TSS.mouse.GRCm38)
```

TSS.mouse.NCBIM37 *TSS annotation data for mouse (NCBIM37) obtained from biomaRt*

Description

TSS annotation data for mouse (NCBIM37) obtained from biomaRt

Usage

TSS.mouse.NCBIM37

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

Annotation data obtained by:

```
mart = useMart(biomart = "ensembl", dataset = "mmusculus_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.mouse.NCBIM37)
slotNames(TSS.mouse.NCBIM37)
```

TSS.rat.RGSC3.4

TSS annotation data for rat (RGSC3.4) obtained from biomaRt

Description

TSS annotation data for rat (RGSC3.4) obtained from biomaRt

Usage

```
TSS.rat.RGSC3.4
```

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

Annotation data obtained by:

```
mart = useMart(biomart = "ensembl", dataset = "rnorvegicus_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.rat.RGSC3.4)
slotNames(TSS.rat.RGSC3.4)
```

TSS.rat.Rnor_5.0 *TSS annotation data for Rattus norvegicus (Rnor_5.0) obtained from biomaRt*

Description

TSS annotation data for Rattus norvegicus (Rnor_5.0) obtained from biomaRt

Usage

```
TSS.rat.Rnor_5.0
```

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

Annotation data obtained by:

```
mart = useMart(biomart = "ensembl", dataset = "rnorvegicus_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.rat.Rnor_5.0)
slotNames(TSS.rat.Rnor_5.0)
```

TSS.zebrafish.Zv8 *TSS annotation data for zebrafish (Zv8) obtained from biomaRt*

Description

A GRanges object to annotate TSS for zebrafish (Zv8) obtained from biomaRt

Usage

```
TSS.zebrafish.Zv8
```

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

Annotation data obtained by: `mart <- useMart(biomart="ENSEMBL_MART_ENSEMBL", host="may2009.archive.ensembl.org", path="/biomart/martservice", dataset="drerio_gene_ensembl")`
`getAnnotation(mart, featureType = "TSS")`

Examples

```
data(TSS.zebrafish.Zv8)
slotNames(TSS.zebrafish.Zv8)
```

TSS.zebrafish.Zv9 *TSS annotation for Danio rerio (Zv9) obtained from biomaRt*

Description

TSS annotation for Danio rerio (Zv9) obtained from biomaRt

Usage

```
TSS.zebrafish.Zv9
```

Format

GRanges with slot start holding the start position of the gene, slot end holding the end position of the gene, slot names holding ensembl gene id, slot seqnames holding the chromosome location where the gene is located and slot strand holding the strand information. In addition, the following variables are included.

list("description") description of the gene

Details

Annotation data obtained by:

```
mart <- useMart(biomart="ENSEMBL_MART_ENSEMBL", host="mar2015.archive.ensembl.org",
path="/biomart/martservice", dataset="drerio_gene_ensembl")
getAnnotation(mart, featureType = "TSS")
```

Examples

```
data(TSS.zebrafish.Zv9)
slotNames(TSS.zebrafish.Zv9)
```

Txdb2GR *Txdb object to GRanges*

Description

convert TxDb object to GRanges

Usage

```
Txdb2GR(ranges, feature, OrganismDb)
```

Arguments

ranges	an Txdb object
feature	feature type, could be geneModel, gene, exon, transcript, CDS, fiveUTR, three-UTR, microRNA, and tRNA
OrganismDb	org db object

wgEncodeTfbsV3 *transcription factor binding site clusters (V3) from ENCODE*

Description

possible binding pool for human (hg19) from transcription factor binding site clusters (V3) from ENCODE data and removed the HOT spots

Usage

```
wgEncodeTfbsV3
```

Format

An object of GRanges.

Details

How to generate the data:

```
temp <- tempfile()
download.file(file.path("http://hgdownload.cse.ucsc.edu", "goldenPath",
"hg19", "encodeDCC",
"wgEncodeRegTfbsClustered",
"wgEncodeRegTfbsClusteredV3.bed.gz"), temp)
data <- read.delim(gzfile(temp, "r"), header=FALSE)
unlink(temp)
colnames(data)[1:4] <- c("seqnames", "start", "end", "TF")
wgEncodeRegTfbsClusteredV3 <- GRanges(as.character(data$seqnames),
```

```
IRanges(data$start, data$end),
TF=data$TF)
data(HOT.spots)
hot <- reduce(unlist(HOT.spots))
ol <- findOverlaps(wgEncodeRegTfbsClusteredV3, hot)
wgEncodeTfbsV3 <- wgEncodeRegTfbsClusteredV3[-unique(queryHits(ol))]
wgEncodeTfbsV3 <- reduce(wgEncodeTfbsV3)
save(list="wgEncodeTfbsV3",
file="data/wgEncodeTfbsV3.rda",
compress="xz", compression_level=9)
```

Source

<http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/wgEncodeRegTfbsClustered/wgEncodeRegTfbsClustered>

Examples

```
data(wgEncodeTfbsV3)
head(wgEncodeTfbsV3)
```

write2FASTA

Write sequences to a file in fasta format

Description

Write the sequences obtained from `getAllPeakSequence` to a file in fasta format leveraging `writeFASTA` in `Biostrings` package. FASTA is a simple file format for biological sequence data. A FASTA format file contains one or more sequences and there is a header line which begins with a `>` preceding each sequence.

Usage

```
write2FASTA(mySeq, file = "", width = 80)
```

Arguments

<code>mySeq</code>	GRanges with variables name and sequence ,e.g., results obtained from <code>getAllPeakSequence</code>
<code>file</code>	Either a character string naming a file or a connection open for reading or writing. If "" (the default for <code>write2FASTA</code>), then the function writes to the standard output connection (the console) unless redirected by <code>sink</code>
<code>width</code>	The maximum number of letters per line of sequence

Value

Output as FASTA file format to the naming file or the console.

Author(s)

Lihua Julie Zhu

Examples

```
peaksWithSequences = GRanges(seqnames=c("1", "2"),
  IRanges(start=c(1000, 2000),
  end=c(1010, 2010),
  names=c("id1", "id2")),
  sequence= c("CCCCCCCCGGGG", "TTTTTTTAAAAA"))

write2FASTA(peaksWithSequences, file="testseq.fasta", width=50)
```

xget

Return the value from a Bimap objects

Description

Search by name for an Bimap object.

Usage

```
xget(
  x,
  envir,
  mode,
  ifnotfound = NA,
  inherits,
  output = c("all", "first", "last")
)
```

Arguments

x, envir, mode, ifnotfound, inherits

see [mget](#)

output return the all or first item for each query

Value

a character vector

Author(s)

Jianhong Ou

See Also

See Also as [mget](#), [mget](#)

Examples

```
library(org.Hs.eg.db)  
xget(as.character(1:10), org.Hs.egSYMBOL)
```

Index

* classes

- annoGR-class, [9](#)
- bindist-class, [21](#)
- permPool-class, [76](#)

* datasets

- annotatedPeak, [12](#)
- enrichedGO, [31](#)
- ExonPlusUtr.human.GRCh37, [35](#)
- HOT.spots, [60](#)
- myPeakList, [68](#)
- Peaks.Ste12.Replicate1, [72](#)
- Peaks.Ste12.Replicate2, [73](#)
- Peaks.Ste12.Replicate3, [73](#)
- TSS.human.GRCh37, [88](#)
- TSS.human.GRCh38, [88](#)
- TSS.human.NCBI36, [89](#)
- TSS.mouse.GRCm38, [90](#)
- TSS.mouse.NCBIM37, [90](#)
- TSS.rat.RGSC3.4, [91](#)
- TSS.rat.Rnor_5.0, [92](#)
- TSS.zebrafish.Zv8, [92](#)
- TSS.zebrafish.Zv9, [93](#)
- wgEncodeTfbsV3, [94](#)

* graph

- makeVennDiagram, [63](#)

* misc

- addAncestors, [5](#)
- addGeneIDs, [6](#)
- addMetadata, [8](#)
- annoPeaks, [10](#)
- annotatePeakInBatch, [13](#)
- assignChromosomeRegion, [17](#)
- bdp, [20](#)
- binOverFeature, [21](#)
- condenseMatrixByColnames, [26](#)
- convert2EntrezID, [27](#)
- countPatternInSeqs, [27](#)
- egOrgMap, [30](#)
- estFragmentLength, [33](#)
- estLibSize, [34](#)
- featureAlignedDistribution, [36](#)
- featureAlignedExtendSignal, [37](#)
- featureAlignedHeatmap, [39](#)

- featureAlignedSignal, [40](#)
- findEnhancers, [41](#)
- findOverlappingPeaks, [45](#)
- findOverlapsOfPeaks, [47](#)
- getAllPeakSequence, [52](#)
- getAnnotation, [53](#)
- getEnrichedGO, [54](#)
- getEnrichedPATH, [57](#)
- getGO, [58](#)
- getVennCounts, [59](#)
- IDRfilter, [62](#)
- mergePlusMinusPeaks, [65](#)
- oligoFrequency, [68](#)
- oligoSummary, [69](#)
- peakPermTest, [70](#)
- peaksNearBDP, [74](#)
- pie1, [76](#)
- preparePool, [79](#)
- reCenterPeaks, [80](#)
- summarizeOverlapsByBins, [80](#)
- summarizePatternInPeaks, [82](#)
- tileCount, [83](#)
- tileGRanges, [84](#)
- toGRanges, [85](#)
- translatePattern, [87](#)
- write2FASTA, [95](#)
- xget, [96](#)

* package

- ChIPpeakAnno-package, [4](#)
- \$,bindist-method (bindist-class), [21](#)
- \$,permPool-method (permPool-class), [76](#)
- \$<-,bindist-method (bindist-class), [21](#)
- \$<-,permPool-method (permPool-class), [76](#)
- _PACKAGE (ChIPpeakAnno-package), [4](#)

- acf, [34](#)
- addAncestors, [5](#)
- addGeneIDs, [6](#), [16](#)
- addMetadata, [8](#)
- annoGR, [14](#), [16](#), [20](#), [21](#), [80](#)
- annoGR (annoGR-class), [9](#)
- annoGR, EnsDb-method (annoGR-class), [9](#)
- annoGR, GRanges-method (annoGR-class), [9](#)
- annoGR, TxDb-method (annoGR-class), [9](#)

- annoGR-class, 9
- annoPeaks, 10, 14–16, 20
- annotatedPeak, 12
- annotatePeakInBatch, 11, 13, 42, 49
- assignChromosomeRegion, 17

- BamFileList, 81, 83
- bdp, 20
- bindist, 71, 79
- bindist (bindist-class), 21
- bindist-class, 21
- bindist-method (bindist-class), 21
- binOverFeature, 19, 21
- binOverGene, 19, 22, 24, 78
- binOverRegions, 19, 23, 23, 78

- ChIPpeakAnno (ChIPpeakAnno-package), 4
- ChIPpeakAnno-deprecated, 25
- ChIPpeakAnno-package, 4
- cntOverlaps, 26
- coerce (annoGR-class), 9
- coerce, annoGR, GRanges-method (annoGR-class), 9
- coerce, GRanges, annoGR-method (annoGR-class), 9
- condenseMatrixByColNames, 26
- convert2EntrezID, 27
- countPatternInSeqs, 27
- cumulativePercentage, 28

- Date, 9, 10
- Deprecated, 25
- downstreams, 29

- egOrgMap, 30
- enrichedGO, 31
- enrichmentPlot, 32
- EnsDb, 9, 10, 86
- EnsDb2GR, 33
- estFragmentLength, 33, 38
- estLibSize, 34, 38
- ExonPlusUtr.human.GRCh37, 35

- featureAlignedDistribution, 36, 40, 41
- featureAlignedExtendSignal, 37
- featureAlignedHeatmap, 37, 39, 41
- featureAlignedSignal, 36–40, 40
- findEnhancers, 41
- findMotifsInPromoterSeqs, 43
- findOverlappingPeaks, 16, 45, 49, 60
- findOverlappingPeaks-deprecated (findOverlappingPeaks), 45
- findOverlaps, 25, 46, 48, 59, 62, 64, 71

- findOverlapsOfPeaks, 8, 25, 46, 47, 64
- format, 77
- frequency, 69, 70

- GAlignmentPairs, 81, 83
- GAlignments, 81, 83
- GAlignmentsList, 81, 83
- genomicElementDistribution, 19, 49
- genomicElementUpSetR, 19, 51
- getAllPeakSequence, 52, 68, 69
- getAnnotation, 16, 53
- getBM, 7
- getEnrichedGO, 32, 54
- getEnrichedPATH, 32, 57
- getGO, 58
- getVennCounts, 49, 59
- GRanges, 9–11, 13–15, 20, 21, 25, 28, 36, 37, 39, 41, 42, 46, 48, 50–54, 59, 62, 63, 67, 71, 74, 79–84, 86
- GRangesList, 50, 51, 67, 81, 83

- HOT.spots, 60

- I DRfilter, 62
- info (annoGR-class), 9
- info, annoGR-method (annoGR-class), 9

- legend, 77
- listAttributes(mart), 7
- listFilters(mart), 7

- makeVennDiagram, 16, 49, 60, 63
- matplot, 36, 78
- mergePlusMinusPeaks, 65
- metagenePlot, 67
- mget, 96
- myPeakList, 68

- numOverlaps, 26, 71

- oligoFrequency, 68
- oligoSummary, 69, 69
- OrganismDb, 86
- overlappingPeaks, 8
- overlappingPeaks (findOverlapsOfPeaks), 47
- overlappingPeaks-class (findOverlapsOfPeaks), 47

- peakPermTest, 21, 64, 70, 76, 79
- Peaks.Ste12.Replicate1, 72
- Peaks.Ste12.Replicate2, 73
- Peaks.Ste12.Replicate3, 73
- peaksNearBDP, 16, 74

permPool, [71](#)
permPool (permPool-class), [76](#)
permPool-class, [76](#)
permPool-method (permPool-class), [76](#)
permTest, [71](#)
pie, [77](#)
pie1, [76](#)
plotBinOverRegions, [23](#), [24](#), [78](#)
preparePool, [21](#), [71](#), [76](#), [79](#)

RangedSummarizedExperiment, [81](#), [83](#)
read.table, [86](#)
reCenterPeaks, [80](#)
RleList, [23](#), [24](#), [36](#), [39](#), [41](#)

SimpleRleList, [23](#), [24](#), [36](#), [39](#), [41](#)
summarizeOverlaps, [28](#), [80](#), [81](#), [83](#)
summarizeOverlapsByBins, [80](#)
summarizePatternInPeaks, [16](#), [82](#)

tileCount, [83](#)
tileGRanges, [84](#)
toGRanges, [25](#), [85](#)
toGRanges, character-method (toGRanges),
[85](#)
toGRanges, connection-method
(toGRanges), [85](#)
toGRanges, data.frame-method
(toGRanges), [85](#)
toGRanges, EnsDb-method (toGRanges), [85](#)
toGRanges, TxDb-method (toGRanges), [85](#)
translatePattern, [87](#)
TSS.human.GRCh37, [88](#)
TSS.human.GRCh38, [88](#)
TSS.human.NCBI36, [89](#)
TSS.mouse.GRCm38, [90](#)
TSS.mouse.NCBIM37, [90](#)
TSS.rat.RGSC3.4, [91](#)
TSS.rat.Rnor_5.0, [92](#)
TSS.zebrafish.Zv8, [92](#)
TSS.zebrafish.Zv9, [93](#)
TxDb, [9](#), [10](#), [17](#), [18](#), [23](#), [24](#), [50](#), [51](#), [64](#), [67](#), [71](#),
[79](#), [86](#)
TxDb2GR, [94](#)

useMart, [6](#)

venn.diagram, [64](#)

wgEncodeTfbsV3, [94](#)
write2FASTA, [95](#)

xget, [96](#)