

Package ‘MSstatsConvert’

March 22, 2023

Title Import Data from Various Mass Spectrometry Signal Processing
Tools to MSstats Format

Version 1.8.2

Description

MSstatsConvert provides tools for importing reports of Mass Spectrometry data processing tools into R format suitable for statistical analysis using the MSstats and MSstatsTMT packages.

License Artistic-2.0

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

biocViews MassSpectrometry, Proteomics, Software, DataImport,
QualityControl

Depends R (>= 4.0)

Imports data.table, log4r, methods, checkmate, utils, stringi

Suggests tinytest, covr, knitr, rmarkdown

Collate 'clean_DIANN.R' 'clean_Philosopher.R' 'clean_Spectronaut.R'
'clean_SpectroMine.R' 'clean_Skyline.R'
'clean_ProteomeDiscoverer.R' 'clean_Progenesis.R'
'clean_OpenSWATH.R' 'clean_OpenMS.R' 'clean_MaxQuant.R'
'clean_DIAUmpire.R' 'MSstatsConvert_core_functions.R'
'utils_MSstatsConvert.R' 'utils_annotation.R'
'utils_balanced_design.R' 'utils_checks.R' 'utils_classes.R'
'utils_clean_features.R' 'utils_dt_operations.R'
'utils_filtering.R' 'utils_fractions.R' 'utils_logging.R'
'utils_shared_peptides.R'

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/MSstatsConvert>

git_branch RELEASE_3_16

git_last_commit c8bd81d

git_last_commit_date 2022-12-12

Date/Publication 2023-03-22

Author Mateusz Staniak [aut, cre],
Meena Choi [aut],
Ting Huang [aut],
Olga Vitek [aut]

Maintainer Mateusz Staniak <mtst@mstaniak.pl>

R topics documented:

.cleanRawPD	2
as.data.frame.MSstatsValidated	3
as.data.table.MSstatsValidated	4
getInputFile	4
MSstatsBalancedDesign	5
MSstatsClean	6
MSstatsConvert	9
MSstatsImport	9
MSstatsLogsSettings	10
MSstatsMakeAnnotation	11
MSstatsPreprocess	12
MSstatsSaveSessionInfo	14
Index	16

.cleanRawPD	<i>Clean raw Proteome Discoverer data</i>
-------------	-------------------------------------------

Description

Clean raw Proteome Discoverer data

Usage

```
.cleanRawPD(
  msstats_object,
  quantification_column,
  protein_id_column,
  sequence_column,
  remove_shared,
  remove_protein_groups = TRUE,
  intensity_columns_regexp = "Abundance"
)
```

Arguments

`msstats_object` an object of class `MSstatsSpectroMineFiles`.
`quantification_column`
chr, name of a column used for quantification.
`protein_id_column`
chr, name of a column with protein IDs.
`sequence_column`
chr, name of a column with peptide sequences.
`remove_shared` lgl, if TRUE, shared peptides will be removed.
`remove_protein_groups`
if TRUE, proteins with `numProteins > 1` will be removed.
`intensity_columns_regexp`
regular expressions that defines intensity columns. Defaults to "Abundance", which means that columns that contain the word "Abundance" will be treated as corresponding to intensities for different channels.

Value

data.table

as.data.frame.MSstatsValidated
Convert output of converters to data.frame

Description

Convert output of converters to data.frame

Usage

```
## S3 method for class 'MSstatsValidated'  
as.data.frame(x)
```

Arguments

x object of class `MSstatsValidated`

Value

data.frame

```
as.data.table.MSstatsValidated
      Convert output of converters to data.table
```

Description

Convert output of converters to data.table

Usage

```
## S3 method for class 'MSstatsValidated'
as.data.table(x)
```

Arguments

x object of class MSstatsValidated

Value

data.tables

```
getInputFile            Get one of files contained in an instance of MSstatsInputFiles class.
```

Description

Get one of files contained in an instance of MSstatsInputFiles class.

Usage

```
getInputFile(msstats_object, file_type)

## S4 method for signature 'MSstatsInputFiles'
getInputFile(msstats_object, file_type = "input")
```

Arguments

msstats_object object that inherits from MSstatsInputFiles class.
file_type character name of a type file. Usually equal to "input".

Value

data.table
data.table

Examples

```
evidence_path = system.file("tinytest/raw_data/MaxQuant/mq_ev.csv",
                             package = "MSstatsConvert")
pg_path = system.file("tinytest/raw_data/MaxQuant/mq_pg.csv",
                       package = "MSstatsConvert")
evidence = read.csv(evidence_path)
pg = read.csv(pg_path)
imported = MSstatsImport(list(evidence = evidence, protein_groups = pg),
                          "MSstats", "MaxQuant")
class(imported)
head(getInputFile(imported, "evidence"))
```

MSstatsBalancedDesign *Creates balanced design by removing overlapping fractions and filling incomplete rows*

Description

Creates balanced design by removing overlapping fractions and filling incomplete rows

Usage

```
MSstatsBalancedDesign(
  input,
  feature_columns,
  fill_incomplete = TRUE,
  handle_fractions = TRUE,
  fix_missing = NULL
)
```

Arguments

input	data.table processed by the MSstatsPreprocess function
feature_columns	str, names of columns that define spectral features
fill_incomplete	if TRUE (default), Intensity values for missing runs will be added as NA
handle_fractions	if TRUE (default), overlapping fractions will be resolved
fix_missing	str, optional. Defaults to NULL, which means no action. If not NULL, must be one of the options: "zero_to_na" or "na_to_zero". If "zero_to_na", Intensity values equal exactly to 0 will be converted to NA. If "na_to_zero", missing values will be replaced by zeros.

Value

data.frame of class MSstatsValidated

Examples

```

unbalanced_data = system.file("tinytest/raw_data/unbalanced_data.csv",
                              package = "MSstatsConvert")
unbalanced_data = data.table::as.data.table(read.csv(unbalanced_data))
balanced = MSstatsBalancedDesign(unbalanced_data,
                                 c("PeptideSequence", "PrecursorCharge",
                                   "FragmentIon", "ProductCharge"))
dim(balanced) # Now balanced has additional rows (with Intensity = NA)
# for runs that were not included in the unbalanced_data table

```

MSstatsClean

Clean files generated by a signal processing tools.

Description

Clean files generated by a signal processing tools.

Clean DIAUmpire files

Clean MaxQuant files

Clean OpenMS files

Clean OpenSWATH files

Clean Progenesis files

Clean ProteomeDiscoverer files

Clean Skyline files

Clean SpectroMine files

Clean Spectronaut files

Clean Philosopher files

Clean DIA-NN files

Usage

```
MSstatsClean(msstats_object, ...)
```

```
## S4 method for signature 'MSstatsDIAUmpireFiles'
```

```
MSstatsClean(msstats_object, use_frag, use_pept)
```

```
## S4 method for signature 'MSstatsMaxQuantFiles'
```

```
MSstatsClean(
  msstats_object,
  protein_id_col,
  remove_by_site = FALSE,
  channel_columns = "Reporterintensitycorrected"
)
```

```
## S4 method for signature 'MSstatsOpenMSFiles'
MSstatsClean(msstats_object)

## S4 method for signature 'MSstatsOpenSWATHFiles'
MSstatsClean(msstats_object)

## S4 method for signature 'MSstatsProgenesisFiles'
MSstatsClean(msstats_object, runs, fix_colnames = TRUE)

## S4 method for signature 'MSstatsProteomeDiscovererFiles'
MSstatsClean(
  msstats_object,
  quantification_column,
  protein_id_column,
  sequence_column,
  remove_shared,
  remove_protein_groups = TRUE,
  intensity_columns_regexp = "Abundance"
)

## S4 method for signature 'MSstatsSkylineFiles'
MSstatsClean(msstats_object)

## S4 method for signature 'MSstatsSpectroMineFiles'
MSstatsClean(msstats_object)

## S4 method for signature 'MSstatsSpectronautFiles'
MSstatsClean(msstats_object, intensity)

## S4 method for signature 'MSstatsPhilosopherFiles'
MSstatsClean(
  msstats_object,
  protein_id_col,
  peptide_id_col,
  channels,
  remove_shared_peptides
)

## S4 method for signature 'MSstatsDIANNFiles'
MSstatsClean(msstats_object, MBR = TRUE)
```

Arguments

`msstats_object` object that inherits from `MSstatsInputFiles` class.

... additional parameter to specific cleaning functions.

`use_frag` TRUE will use the selected fragment for each peptide. 'Selected_fragments' column is required.

Examples

```
evidence_path = system.file("tinytest/raw_data/MaxQuant/mq_ev.csv",
                             package = "MSstatsConvert")
pg_path = system.file("tinytest/raw_data/MaxQuant/mq_pg.csv",
                      package = "MSstatsConvert")
evidence = read.csv(evidence_path)
pg = read.csv(pg_path)
imported = MSstatsImport(list(evidence = evidence, protein_groups = pg),
                          "MSstats", "MaxQuant")
cleaned_data = MSstatsClean(imported, protein_id_col = "Proteins")
head(cleaned_data)
```

MSstatsConvert

MSstatsConvert: An R Package to Convert Data from Mass Spectrometry Signal Processing Tools to MSstats Format

Description

MSstatsConvert helps convert data from different types of mass spectrometry experiments and signal processing tools to a format suitable for statistical analysis with the MSstats and MSstatsTMT packages.

Main functions

[MSstatsLogsSettings](#) for logs management, [MSstatsImport](#) for importing files created by signal processing tools, [MSstatsClean](#) for re-formatting imported files into a consistent format, [MSstatsImport](#) for preprocessing cleaned files, [MSstatsBalancedDesign](#) for handling fractions and creating balanced data.

MSstatsImport

Import files from signal processing tools.

Description

Import files from signal processing tools.

Usage

```
MSstatsImport(input_files, type, tool, tool_version = NULL, ...)
```

Arguments

<code>input_files</code>	list of paths to input files or data. <code>frame</code> objects. Interpretation of this parameter depends on values of parameters <code>type</code> and <code>tool</code> .
<code>type</code>	<code>chr</code> , "MSstats" or "MSstatsTMT".
<code>tool</code>	<code>chr</code> , name of a signal processing tool that generated input files.
<code>tool_version</code>	not implemented yet. In the future, this parameter will allow handling different versions of each signal processing tools.
<code>...</code>	optional additional parameters to <code>data.table::fread</code> .

Value

an object of class `MSstatsInputFiles`.

Examples

```
evidence_path = system.file("tinytest/raw_data/MaxQuant/mq_ev.csv",
                             package = "MSstatsConvert")
pg_path = system.file("tinytest/raw_data/MaxQuant/mq_pg.csv",
                      package = "MSstatsConvert")
evidence = read.csv(evidence_path)
pg = read.csv(pg_path)
imported = MSstatsImport(list(evidence = evidence, protein_groups = pg),
                          "MSstats", "MaxQuant")
class(imported)
head(getInputFile(imported, "evidence"))
```

`MSstatsLogsSettings` *Set how MSstats will log information from data processing*

Description

Set how MSstats will log information from data processing

Usage

```
MSstatsLogsSettings(
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  base = "MSstats_log_",
  pkg_name = "MSstats"
)
```

Arguments

use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file.
base	start of the file name.
pkg_name	currently "MSstats", "MSstatsPTM" or "MSstatsTMT". Each package can use its own separate log settings.

Value

TRUE invisibly in case of successful logging setup.

Examples

```
# No logging and no messages
MSstatsLogsSettings(FALSE, FALSE, FALSE)
# Log, but do not display messages
MSstatsLogsSettings(TRUE, FALSE, FALSE)
# Log to an existing file
file.create("new_log.log")
MSstatsLogsSettings(TRUE, TRUE, log_file_path = "new_log.log")
# Do not log, but display messages
MSstatsLogsSettings(FALSE)
```

MSstatsMakeAnnotation *Create annotation*

Description

Create annotation

Usage

```
MSstatsMakeAnnotation(input, annotation, ...)
```

Arguments

input	data.table preprocessed by the MSstatsClean function
annotation	data.table
...	key-value pairs, where keys are names of columns of annotation

Value

data.table

Examples

```
evidence_path = system.file("tinytest/raw_data/MaxQuant/mq_ev.csv",
                             package = "MSstatsConvert")
pg_path = system.file("tinytest/raw_data/MaxQuant/mq_pg.csv",
                      package = "MSstatsConvert")
evidence = read.csv(evidence_path)
pg = read.csv(pg_path)
imported = MSstatsImport(list(evidence = evidence, protein_groups = pg),
                          "MSstats", "MaxQuant")
cleaned_data = MSstatsClean(imported, protein_id_col = "Proteins")
annot_path = system.file("tinytest/raw_data/MaxQuant/annotation.csv",
                         package = "MSstatsConvert")
mq_annot = MSstatsMakeAnnotation(cleaned_data, read.csv(annot_path),
                                 Run = "Rawfile")

head(mq_annot)
```

MSstatsPreprocess	<i>Preprocess outputs from MS signal processing tools for analysis with MSstats</i>
-------------------	-------------------------------------------------------------------------------------

Description

Preprocess outputs from MS signal processing tools for analysis with MSstats

Usage

```
MSstatsPreprocess(
  input,
  annotation,
  feature_columns,
  remove_shared_peptides = TRUE,
  remove_single_feature_proteins = TRUE,
  feature_cleaning = list(remove_features_with_few_measurements = TRUE,
                          summarize_multiple_psms = max),
  score_filtering = list(),
  exact_filtering = list(),
  pattern_filtering = list(),
  columns_to_fill = list(),
  aggregate_isotopic = FALSE,
  ...
)
```

Arguments

<code>input</code>	data.table processed by the MSstatsClean function.
<code>annotation</code>	annotation file generated by a signal processing tool.
<code>feature_columns</code>	character vector of names of columns that define spectral features.
<code>remove_shared_peptides</code>	logical, if TRUE shared peptides will be removed.
<code>remove_single_feature_proteins</code>	logical, if TRUE, proteins that only have one feature will be removed.
<code>feature_cleaning</code>	named list with maximum two (for MSstats converters) or three (for MSstatsTMT converter) elements. If <code>handle_few_measurements</code> is set to "remove", feature with less than three measurements will be removed (otherwise it should be equal to "keep"). <code>summarize_multiple_psms</code> is a function that will be used to aggregate multiple feature measurements in a run. It should return a scalar and accept an <code>na.rm</code> parameter. For MSstatsTMT converters, setting <code>remove_psms_with_any_missing</code> will remove features which have missing values in a run from that run.
<code>score_filtering</code>	a list of named lists that specify filtering options. Details are provided in the vignette.
<code>exact_filtering</code>	a list of named lists that specify filtering options. Details are provided in the vignette.
<code>pattern_filtering</code>	a list of named lists that specify filtering options. Details are provided in the vignette.
<code>columns_to_fill</code>	a named list of scalars. If provided, columns with names defined by the names of this list and values corresponding to its elements will be added to the output data.frame.
<code>aggregate_isotopic</code>	logical. If TRUE, isotopic peaks will be summed.
<code>...</code>	additional parameters to <code>data.table::fread</code> .

Value

data.table

Examples

```
evidence_path = system.file("tinytest/raw_data/MaxQuant/mq_ev.csv",
                             package = "MSstatsConvert")
pg_path = system.file("tinytest/raw_data/MaxQuant/mq_pg.csv",
                      package = "MSstatsConvert")
evidence = read.csv(evidence_path)
pg = read.csv(pg_path)
```

```

imported = MSstatsImport(list(evidence = evidence, protein_groups = pg),
                          "MSstats", "MaxQuant")
cleaned_data = MSstatsClean(imported, protein_id_col = "Proteins")
annot_path = system.file("tinytest/raw_data/MaxQuant/annotation.csv",
                         package = "MSstatsConvert")
mq_annot = MSstatsMakeAnnotation(cleaned_data, read.csv(annot_path),
                                Run = "Rawfile")

# To filter M-peptides and oxidatin peptides
m_filter = list(col_name = "PeptideSequence", pattern = "M",
               filter = TRUE, drop_column = FALSE)
oxidation_filter = list(col_name = "Modifications", pattern = "Oxidation",
                       filter = TRUE, drop_column = TRUE)
msstats_format = MSstatsPreprocess(
  cleaned_data, mq_annot,
  feature_columns = c("PeptideSequence", "PrecursorCharge"),
  columns_to_fill = list(FragmentIon = NA, ProductCharge = NA),
  pattern_filtering = list(oxidation = oxidation_filter, m = m_filter)
)
# Output in the standard MSstats format
head(msstats_format)

```

MSstatsSaveSessionInfo

Save session information

Description

Save session information

Usage

```

MSstatsSaveSessionInfo(
  path = NULL,
  append = TRUE,
  base = "MSstats_session_info_"
)

```

Arguments

path	optional path to output file. If not provided, "MSstats_session_info" and current timestamp will be used as a file name
append	if TRUE and file given by the path parameter already exists, session info will be appended to the file
base	beginning of a file name

Value

TRUE invisibly after session info was saved

Examples

```
MSstatsSaveSessionInfo("session_info.txt")  
MSstatsSaveSessionInfo("session_info.txt", base = "MSstatsTMT_session_info_")
```

Index

`.cleanRawPD`, 2

`as.data.frame.MSstatsValidated`, 3

`as.data.table.MSstatsValidated`, 4

`getInputFile`, 4

`getInputFile,MSstatsInputFiles-method`
(`getInputFile`), 4

`MSstatsBalancedDesign`, 5, 9

`MSstatsClean`, 6, 9

`MSstatsClean,MSstatsDIANNFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsDIAUmpireFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsMaxQuantFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsOpenMSFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsOpenSWATHFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsPhilosopherFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsProgenesisFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsProteomeDiscovererFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsSkylineFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsSpectroMineFiles-method`
(`MSstatsClean`), 6

`MSstatsClean,MSstatsSpectronautFiles-method`
(`MSstatsClean`), 6

`MSstatsConvert`, 9

`MSstatsImport`, 9, 9

`MSstatsLogsSettings`, 9, 10

`MSstatsMakeAnnotation`, 11

`MSstatsPreprocess`, 12

`MSstatsSaveSessionInfo`, 14