

# Package ‘SpatialCPie’

December 2, 2021

**Title** Cluster analysis of Spatial Transcriptomics data

**Version** 1.10.0

**Description** SpatialCPie is an R package designed to facilitate cluster evaluation for spatial transcriptomics data by providing intuitive visualizations that display the relationships between clusters in order to guide the user during cluster identification and other downstream applications.

The package is built around a shiny “gadget” to allow the exploration of the data with multiple plots in parallel and an interactive UI. The user can easily toggle between different cluster resolutions in order to choose the most appropriate visual cues.

**biocViews** Transcriptomics, Clustering, RNASeq, Software

**Depends** R (>= 3.6)

**Imports** colorspace (>= 1.3-2), data.table (>= 1.12.2), digest (>= 0.6.21), dplyr (>= 0.7.6), ggforce (>= 0.3.0), ggiraph (>= 0.5.0), ggplot2 (>= 3.0.0), ggrepel (>= 0.8.0), grid (>= 3.5.1), igraph (>= 1.2.2), lpSolve (>= 5.6.13), methods (>= 3.5.0), purrr (>= 0.2.5), readr (>= 1.1.1), rlang (>= 0.2.2), shiny (>= 1.1.0), shinycssloaders (>= 0.2.0), shinyjs (>= 1.0), shinyWidgets (>= 0.4.8), stats (>= 3.6.0), SummarizedExperiment (>= 1.10.1), tibble (>= 1.4.2), tidyr (>= 0.8.1), tidyselect (>= 0.2.4), tools (>= 3.6.0), utils (>= 3.5.0), zeallot (>= 0.1.0)

**Suggests** BiocStyle (>= 2.8.2), jpeg (>= 0.1-8), knitr (>= 1.20), rmarkdown (>= 1.10), testthat (>= 2.0.0)

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 6.1.1

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/SpatialCPie>

**git\_branch** RELEASE\_3\_14

**git\_last\_commit** 6b6ce6f

**git\_last\_commit\_date** 2021-10-26

**Date/Publication** 2021-12-02

**Author** Joseph Bergenstraahle [aut, cre]

**Maintainer** Joseph Bergenstraahle <joseph.bergenstrahle@gmail.com>

## R topics documented:

SpatialCPie-package . . . . .	2
parseSpotFile . . . . .	2
runCPie . . . . .	3

<b>Index</b>	<b>5</b>
--------------	----------

---

SpatialCPie-package	<i>SpatialCPie: Cluster analysis of Spatial Transcriptomics data</i>
---------------------	--

---

### Description

SpatialCPie is an R package designed to facilitate cluster evaluation for spatial transcriptomics data by providing intuitive visualizations that display the relationships between clusters in order to guide the user during cluster identification and other downstream applications. The package is built around a shiny "gadget" to allow the exploration of the data with multiple plots in parallel and an interactive UI. The user can easily toggle between different cluster resolutions in order to choose the most appropriate visual cues.

### Author(s)

**Maintainer:** Joseph Bergenstraahle <joseph.bergenstrahle@gmail.com>

---

parseSpotFile	<i>Parse spot detector output</i>
---------------	-----------------------------------

---

### Description

Parses the output from the ST spot detector tool for use with SpatialCPie.

### Usage

```
parseSpotFile(file)
```

### Arguments

file                    spot file

**Value**

`data.frame` with columns "x" and "y" specifying the pixel coordinates of each spot

**Examples**

```
## Create spot file
data <- rbind(
  c(7, 18, 7.00, 18.07, 563.2, 947.0),
  c(8, 11, 8.00, 11.04, 612.5, 627.7)
)
filename <- tempfile()
write.table(
  data,
  file = filename,
  sep = "\t",
  quote = FALSE,
  col.names = c("x", "y", "new_x", "new_y", "pixel_x", "pixel_y")
)

## Parse spot file
parseSpotFile(filename)

## Delete spot file
unlink(filename)
```

---

runCPie

*Run SpatialCPie*


---

**Description**

Runs the SpatialCPie gadget.

**Usage**

```
runCPie(counts, image = NULL, spotCoordinates = NULL,
  margin = "spot", resolutions = 2:4,
  assignmentFunction = function(k, x) kmeans(x, centers = k)$cluster,
  view = NULL)
```

**Arguments**

counts	gene count matrix or a <a href="#">SummarizedExperiment-class</a> object containing count values.
image	image to be used as background to the plot.
spotCoordinates	<code>data.frame</code> with pixel coordinates. The rows should correspond to the columns (spatial areas) in the count file.
margin	which margin to cluster.

**resolutions**     **numeric** vector specifying the clustering resolutions.  
**assignmentFunction**     function to compute cluster assignments.  
**view**     **viewer** object.

### Value

a list with the following items:

- "clusters": Cluster assignments (may differ from assignments)
- "clusterGraph": The cluster tree ggplot object
- "arrayPlot": The pie plot ggplot objects

### Examples

```

if (interactive()) {
  options(device.ask.default = FALSE)

  ## Set up coordinate system
  coordinates <- as.matrix(expand.grid(1:10, 1:10))

  ## Generate data set with three distinct genes generated by three
  ## distinct cell types
  profiles <- diag(rep(1, 3)) + runif(9)
  centers <- cbind(c(5, 2), c(2, 8), c(8, 2))
  mixes <- apply(coordinates, 1, function(x) {
    x <- exp(-colSums((centers - x) ^ 2) / 50)
    x / sum(x)
  })
  means <- 100 * profiles %*% mixes
  counts <- matrix(rpois(prod(dim(means)), means), nrow = nrow(profiles))
  colnames(counts) <- apply(
    coordinates,
    1,
    function(x) do.call(paste, c(as.list(x), list(sep = "x"))))
  )
  rownames(counts) <- paste("gene", 1:nrow(counts))

  ## Run SpatialCPie
  runCPie(counts)
}

```

# Index

`data.frame`, [3](#)

`numeric`, [4](#)

`parseSpotFile`, [2](#)

`runCPie`, [3](#)

`SpatialCPie` (`SpatialCPie-package`), [2](#)

`SpatialCPie-package`, [2](#)

`viewer`, [4](#)