

Package ‘TVTB’

February 20, 2019

Type Package

Title TVTB: The VCF Tool Box

Version 1.8.0

Date 2018-02-24

Description The package provides S4 classes and methods to filter, summarise and visualise genetic variation data stored in VCF files. In particular, the package extends the FilterRules class (S4Vectors package) to define news classes of filter rules applicable to the various slots of VCF objects. Functionalities are integrated and demonstrated in a Shiny web-application, the Shiny Variant Explorer (tSVE).

License Artistic-2.0

Depends R (>= 3.4), methods, utils, stats

Imports AnnotationFilter, BiocGenerics (>= 0.25.1), BiocParallel, Biostrings, ensemblDb, ensemblVEP, GenomeInfoDb, GenomicRanges, GGally, ggplot2, Gviz, limma, IRanges (>= 2.7.1), reshape2, Rsamtools, S4Vectors (>= 0.11.11), SummarizedExperiment, VariantAnnotation (>= 1.19.9)

Suggests EnsDb.Hsapiens.v75 (>= 0.99.7), shiny (>= 0.13.2.9005), DT (>= 0.1.67), rtracklayer, BiocStyle (>= 2.5.19), knitr (>= 1.12), rmarkdown, testthat, covr, pander

biocViews Software, Genetics, GeneticVariability, GenomicVariation, DataRepresentation, GUI, Genetics, DNASEq, WholeGenome, Visualization, MultipleComparison, DataImport, VariantAnnotation, Sequencing, Coverage, Alignment, SequenceMatching

Collate utils.R tSVE.R AllClasses.R AllGenerics.R Genotypes-class.R TVTBparam-class.R VcfFilterRules-class.R countGenos-methods.R autodetectGenotypes.R addCountGenos-methods.R addFrequencies-methods.R addOverallFrequencies-methods.R addPhenoLevelFrequencies-methods.R dropInfo.R readVcf-methods.R variantsInSamples-methods.R vepInPhenoLevel-methods.R plotInfo.R pairsInfo.R show-methods.R

VignetteBuilder knitr

URL <https://github.com/kevinrue/TVTB>

BugReports <https://github.com/kevinrue/TVTB/issues>

git_url <https://git.bioconductor.org/packages/TVTB>
git_branch RELEASE_3_8
git_last_commit 67e1b0c
git_last_commit_date 2018-10-30
Date/Publication 2019-02-19
Author Kevin Rue-Albrecht [aut, cre]
Maintainer Kevin Rue-Albrecht <kevinrue67@gmail.com>

R topics documented:

TVTB-package	2
addCountGenos-methods	3
addFrequencies-methods	4
addOverallFrequencies-methods	6
addPhenoLevelFrequencies-methods	7
autodetectGenotypes-methods	9
countGenos-methods	10
dropInfo-methods	11
Genotypes-class	12
pairsInfo-methods	14
plotInfo-methods	15
readVcf-methods	16
tSVE	18
TVTBparam-class	19
variantsInSamples-methods	22
VcfBasicRules-class	23
VcfFilterRules-class	26
vepInPhenoLevel-methods	29
Index	31

TVTB-package

TVTB: The VCF Tool Box

Description

The package provides S4 classes and methods to filter, summarise and visualise genetic variation data stored in VCF files. In particular, the package extends the FilterRules class (S4Vectors package) to define news classes of filter rules applicable to the various slots of VCF objects. Functionalities are integrated and demonstrated in a Shiny web-application, the Shiny Variant Explorer (tSVE).

Details

This package was not yet installed at build time.

Index: This package was not yet installed at build time.

Author(s)

NA

Maintainer: NA

 addCountGenos-methods *Add count of genotypes to INFO field*

Description

Adds the total occurrences of a set of genotypes as an INFO field for each variant. All given genotypes are counted toward a single total (*e.g.* grand total of `c("0/0", "0|0")`), while other genotypes are silently ignored.

Usage

```
## S4 method for signature 'ExpandedVCF'
addCountGenos(
  vcf, genos, key, description,
  samples = 1:ncol(vcf), force = FALSE)
```

Arguments

vcf	ExpandedVCF object.
genos	character vector of genotypes to count (toward a common unique total).
key	Name of the INFO field to create or update (character vector of length 1). See <i>Details</i> below.
description	character description of the INFO field to create or overwrite (character vector of length 1).
samples	integer, numeric or character vector indicating samples to consider in <code>VariantAnnotation::gen</code> . If not specified, all samples are considered.
force	If TRUE, the field header and data will be overwritten if present; If FALSE, an error is thrown if the field already exists.

Details

In all cases, the new INFO field is inserted after the last existing field. In other words, overwriting an existing INFO field is achieved by dropping it from the data and header of the info slot, and subsequently inserting the new data after the last remaining INFO field.

Value

ExpandedVCF object including an additional INFO field stating the count of genotypes.

Author(s)

Kevin Rue-Albrecht

See Also

[countGenos, ExpandedVCF-method](#) and [geno, VCF-method](#)

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# TVTB parameters
tparam <- TVTBparam(Genotypes(ref = "0|0", het = c("0|1", "1|0"), alt = "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(vcfFile, param = tparam)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vcf <- addCountGenos(
  vcf, het(tparam),
  suffix(tparam)["het"],
  "Number of heterozygous genotypes")
```

addFrequencies-methods

Group-level genotypes counts and allele frequencies

Description

Adds genotypes counts (reference homozygote, heterozygote, and alternate homozygote) and allele frequencies (alternate and minor) as INFO fields in an ExpandedVCF object. Counts and frequencies may be calculated overall (*i.e.* across all samples), or within groups of samples (*i.e.* within phenotype levels). Multiple genotypes can be counted toward a single frequency (*e.g.* combined c("0/0", "0|0") for homozygote reference genotypes).

Usage

```
## S4 method for signature 'ExpandedVCF,list'
addFrequencies(vcf, phenos, force = FALSE)

## S4 method for signature 'ExpandedVCF,character'
addFrequencies(vcf, phenos, force = FALSE)

## S4 method for signature 'ExpandedVCF,missing'
addFrequencies(vcf, force = FALSE)
```

Arguments

vcf	ExpandedVCF object. metadata(vcf)[["TVTBparam"]] must contain a TVTBparam object.
phenos	If NULL, counts and frequencies are calculated across all samples. Otherwise, either a character vector of phenotypes in colnames(colData(vcf)), or a named list in which names are phenotypes in colnames(colData(vcf)) and values are character vectors of phenotype levels in colData(vcf)[, phenotype]. See <i>Details</i> below.

force If TRUE, INFO fields header and data are overwritten with a message, if present.
 If FALSE, an error is thrown if any field already exists.

Details

The phenos argument is central to control the behaviour of this method.

If phenos=NULL, genotypes and frequencies are calculated across all the samples in the ExpandedVCF object, and stored in INFO fields named according to settings stored in the TVTBparam object (see below).

If phenos is a character vector of phenotypes present in colnames(colData(vcf)), counts and frequencies are calculated for each level of those phenotypes, and stored in INFO fields prefixed with "<phenotype>_<level>_" and suffixed with the settings stored in the param object (see below).

Finally, if phenos is a named list, names must be phenotypes present in colnames(colData(vcf)), and values must be levels of those phenotypes. In this case, counts and frequencies are calculated for the given levels of the given phenotypes, and stored in INFO fields as described above.

The param object controls the key (suffix) of INFO fields as follows:

names(ref(param)) Count of reference homozygote genotypes.

names(het(param)) Count of heterozygote genotypes.

names(alt(param)) Count of alternate homozygote genotypes.

aaf(param) Alternate allele frequency.

maf(param) Minor allele frequency

Value

ExpandedVCF object including additional INFO fields for genotype counts and allele frequencies.
 See *Details*.

Author(s)

Kevin Rue-Albrecht

See Also

[addOverallFrequencies, ExpandedVCF-method](#), [addPhenoLevelFrequencies, ExpandedVCF-method, VCF](#), and [TVTBparam](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(read.table(phenoFile, TRUE, row.names = 1))

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
```

```
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vcf <- addFrequencies(vcf, list(super_pop = "AFR"))
```

addOverallFrequencies-methods

Overall genotypes counts and allele frequencies

Description

Adds dataset-wide genotypes counts (reference homozygote, heterozygote, and alternate homozygote) and allele frequencies (alternate and minor) as INFO fields in an ExpandedVCF object. Counts and frequencies may be calculated across all samples. Multiple genotypes can be counted toward a single frequency (*e.g.* combined c("0/0", "0|0") for homozygote reference genotypes).

Usage

```
## S4 method for signature 'ExpandedVCF'
addOverallFrequencies(vcf, force = FALSE)
```

Arguments

vcf	ExpandedVCF object. metadata(vcf)[["TVTBparam"]] must contain a TVTBparam object.
force	If TRUE, INFO fields header and data are overwritten. If FALSE, an error is thrown if any field already exists.

Details

Genotypes and frequencies are calculated across all the samples in the ExpandedVCF object, and stored in INFO fields named according to settings stored in the TVTBparam object (see below).

The param object controls the key of INFO fields as follows:

```
names(ref(param)) Count of reference homozygote genotypes.
names(het(param)) Count of heterozygote genotypes.
names(alt(param)) Count of alternate homozygote genotypes.
aaf(param) Alternate allele frequency.
maf(param) Minor allele frequency
```

Value

ExpandedVCF object including additional INFO fields for genotype counts and allele frequencies.
See *Details*.

Warning

A warning message is issued if genotypes are not fully defined in the TVTBparam.

Author(s)

Kevin Rue-Albrecht

See Also

[addFrequencies, ExpandedVCF, list-method](#), [addPhenoLevelFrequencies, ExpandedVCF-method](#), and [VCF](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(vcfFile, param = tparam)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vcf <- addOverallFrequencies(vcf, tparam)
```

addPhenoLevelFrequencies-methods

Genotypes and allele frequencies for a given phenotype level

Description

Adds genotypes counts (reference homozygote, heterozygote, and alternate homozygote) and allele frequencies (alternate and minor) calculated in a group of samples associated with a given level of a given phenotype as INFO fields in an ExpandedVCF object. Multiple genotypes can be counted toward a single frequency (*e.g.* combined `c("0/0", "0|0")` for homozygote reference genotypes).

Usage

```
## S4 method for signature 'ExpandedVCF'
addPhenoLevelFrequencies(
  vcf, pheno, level, force = FALSE)
```

Arguments

vcf	ExpandedVCF object. metadata(vcf)[["TVTBparam"]] must contain a TVTBparam object.
pheno	Phenotype in colnames(colData(vcf)).
level	Phenotype level in colData(vcf)[,pheno].
force	If TRUE, INFO fields header and data are overwritten. If FALSE, an error is thrown if any field already exists.

Details

Genotypes and frequencies are calculated within the groups of samples associated with the given level of the given phenotype, and stored in INFO fields named according to settings stored in metadata(vcf)[["TVTBparam"]] (see below).

The [TVTBparam](#) object controls the key suffix of INFO fields as follows:

names(ref(param)) Count of reference homozygote genotypes.
 names(het(param)) Count of heterozygote genotypes.
 names(alt(param)) Count of alternate homozygote genotypes.
 aaf(param) Alternate allele frequency.
 maf(param) Minor allele frequency

Value

ExpandedVCF object including additional INFO fields for genotype counts and allele frequencies.
 See *Details*.

Warning

A warning message is issued if genotypes are not fully defined in the [TVTBparam](#).

Author(s)

Kevin Rue-Albrecht

See Also

[addFrequencies](#), [ExpandedVCF](#), [list-method](#), [addOverallFrequencies](#), [ExpandedVCF-method](#), [VCF](#), and [TVTBparam](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(read.table(phenoFile, TRUE, row.names = 1))

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))
```



```
# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vcf <- addPhenoLevelFrequencies(vcf, "super_pop", "AFR")
```

autodetectGenotypes-methods

Define genotypes in the TVTBparam metadata slot

Description

This method attempts to auto-detect genotypes (*i.e.* homozygote reference, heterozygote, and homozygote alternate) in a VCF object, and sets or creates a TVTBparam object accordingly, in the metadata slot.

Usage

```
## S4 method for signature 'VCF'
autodetectGenotypes(vcf)
```

Arguments

vcf VCF object.

Value

VCF object including a new or updated TVTBparam object in `metadata(vcf)[["TVTBparam"]]`.

Warning

A warning message is issued if genotypes cannot be fully defined.

Author(s)

Kevin Rue-Albrecht

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# TVTB parameters
tparam <- TVTBparam()

# Pre-process variants
vcf <- VariantAnnotation::readVcf(vcfFile, param = tparam) # warning expected
```

```
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vcf <- autodetectGenotypes(vcf)
```

countGenos-methods *Count occurrences of genotypes*

Description

Counts the total occurrences of a set of genotypes by row in a matrix of genotype. All given genotypes are counted toward a single total (*e.g.* grand total of `c("0/0", "0|0")`), while other genotypes are silently ignored.

Usage

```
## S4 method for signature 'ExpandedVCF'
countGenos(
  x, genos, pheno = NULL, level = NULL)
```

Arguments

<code>x</code>	ExpandedVCF object.
<code>genos</code>	character vector of genotypes to count (toward a common unique total).
<code>pheno</code>	If <code>x</code> is an ExpandedVCF object, phenotype in <code>colnames(colData(x))</code> .
<code>level</code>	If <code>x</code> is an ExpandedVCF object, phenotype level in <code>colData(x)[,pheno]</code> .

Value

An integer vector representing the aggregated count of the given genotypes in each row.

Author(s)

Kevin Rue-Albrecht

See Also

[VCF](#)

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(read.table(phenoFile, TRUE, row.names = 1))
```

```

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vcf <- countGenos(vcf, het(tparam), "super_pop", "AFR")

```

dropInfo-methods

Remove INFO keys from VCF objects

Description

Given a character vector of INFO keys, removes either the associated header, data, or both from a VCF object. If no INFO key is given (the default), all INFO keys are checked and removed from the given slot if they do not have a matching entry in the other slot.

Usage

```

## S4 method for signature 'VCF'
dropInfo(
  vcf, key = NULL, slot = "both")

```

Arguments

vcf	VCF object.
key	character vector of INFO keys to remove. If NULL (the default), all keys are checked, and removed from the given slot if they do not have a matching entry in the other slot.
slot	Should the INFO keys be removed from the "header", the "data", or "both" (the default)?

Value

An integer vector representing the aggregated count of the given genotypes in each row.

Note

In the future, x should also support genotype quality (GQ) to consider only genotypes above a given quality cut-off.

Author(s)

Kevin Rue-Albrecht

See Also

[VCF](#)

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

dropInfo(vcf)
dropInfo(vcf, "CSQ")
```

Genotypes-class	<i>Genotypes class objects</i>
-----------------	--------------------------------

Description

The Genotypes class stores genotype definitions in a convenient format.

Usage

```
Genotypes(
  ref = NA_character_, het = NA_character_, alt = NA_character_,
  suffix = c(ref="REF", het="HET", alt="ALT"))
```

Arguments

ref	A character vector declaring the encoding of homozygote reference genotypes.
het	A character vector declaring the encoding of heterozygote genotypes.
alt	A character vector declaring the encoding of homozygote alternate genotypes.
suffix	Set the individual INFO key suffixes used to store the statistics of homozygote reference, heterozygote, and homozygote alternate genotypes, in this order. See <i>Details</i> section.

Details

Genotypes may be initialised as `NA_character_` and updated from an imported VCF object using the [autodetectGenotypes](#) method. This may be useful if genotype encodings are not known beforehand.

For each *suffix* stored in the Genotypes object, TVTB may store data in the VCF object under the INFO keys defined as follows:

suffix Statistics across all samples in the ExpandedVCF (e.g. "MAF").

phenotype_level_suffix Statistics across samples associated with a given level of a given phenotype (e.g. "gender_male_MAF").

Users are recommended to avoid using those INFO keys for other purposes.

Value

A Genotypes object that contains genotype definitions.

Accessor methods

In the following code snippets `x` is a Genotypes object.

`ref(x), ref(x) <- value` Gets or sets the vector that declares homozygote reference genotypes.

`het(x), het(x) <- value` Gets or sets the vector that declares heterozygote genotypes.

`alt(x), alt(x) <- value` Gets or sets the vector that declares homozygote alternate genotypes.

`genos(x)` Gets a vector of concatenated homozygote reference, heterozygote, and homozygote alternate genotypes. See also `ref`, `het`, `alt`, and `carrier` accessors.

`carrier(x)` Gets a vector of concatenated heterozygote and homozygote alternate genotypes. See also `het` and `alt` accessors.

`suffix(x)` Gets a named character vector that declares individual suffixes used to store the data for each set of genotypes in the INFO field of the VCF object. Names of this vector are `ref`, `het`, and `alt`.

Author(s)

Kevin Rue-Albrecht

See Also

[VCF](#), [TVTbparam](#), and [addCountGenos-methods](#).

Examples

```
# Constructors ----

genotypes <- Genotypes("0|0", c("0|1", "1|0"), "1|1")

# Accessors ----

## Concatenated homozygote reference, heterozygote, and alternate heterozygote
## genotypes stored in the Genotypes object returned by the genos() accessor.
genos(genotypes)

## Individual genotypes can be extracted with ref(), het(), alt() accessors.
ref(genotypes)
het(genotypes)
alt(genotypes)

## Their individual INFO key suffixes can be extracted with suffix() accessors
## and the relevant name
suffix(genotypes)
suffix(genotypes)["ref"]
```

```

suffix(genotypes)["het"]
suffix(genotypes)["alt"]

## Concatenated heterozygote, and alternate heterozygote genotypes are
## returned by the carrier() accessor.
carrier(genotypes)
names(carrier(genotypes))

```

pairsInfo-methods *Plot an INFO metric on a genomic axis.*

Description

Make a matrix of plots that display a metric calculated in levels of a given phenotype, and stored in columns of the info slot of a VCF object.

Usage

```

## S4 method for signature 'VCF'
pairsInfo(vcf, metric, phenotype, ..., title = metric)

```

Arguments

vcf	VCF object.
metric	Metric to plot on the Y axis. All columns in the info slot of the vcf object that match the pattern "phenotype_(.*)_metric" are plotted in the DataTrack. An error is thrown if no such column is found.
phenotype	Column in the phenoData slot of the vcf object. Levels of this phenotype are plotted and contrasted in the DataTrack. See argument <code>metric</code> for details.
...	Additional arguments, passed to the ggpairs method.
title	Title for the graph, passed to the ggpairs method.

Value

gg object returned by the [ggpairs](#) method.

Author(s)

Kevin Rue-Albrecht

See Also

[ggpairs](#), [addPhenoLevelFrequencies](#), [ExpandedVCF-method](#), and [VCF](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(read.table(phenoFile, TRUE, row.names = 1))

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)
vcf <- addFrequencies(vcf, "super_pop")

# Example usage ----

pairsInfo(vcf, "MAF", "super_pop")
```

plotInfo-methods *Plot an INFO metric on a genomic axis.*

Description

Plot, on a genomic axis, a metric calculated in levels of a given phenotype, and stored in columns of the info slot of a VCF object.

Usage

```
## S4 method for signature 'VCF'
plotInfo(
  vcf, metric, range, annotation, phenotype, type = c("p", "heatmap"),
  zero.rm = FALSE)
```

Arguments

vcf	VCF object.
metric	Metric to plot on the Y axis. All columns in the info slot of the vcf object that match the pattern "phenotype_(.*)_metric" are plotted in the DataTrack. An error is thrown if no such column is found.
range	A GRanges of length one that defines the region to visualise. All variants in the vcf object overlapping this region are plotted.
annotation	An EnsDb annotation package from which to fetch gene annotations. <i>TxDb packages may be supported in the future.</i>
phenotype	Column in the phenoData slot of the vcf object. Levels of this phenotype are plotted and contrasted in the DataTrack. See argument <code>metric</code> for details.
type	Plotting type(s), as listed in DataTrack .
zero.rm	If TRUE, values equal to 0 are not displayed in the DataTrack.

Value

list returned by the plotTracks method.

Author(s)

Kevin Rue-Albrecht

See Also

[plotTracks](#), [addPhenoLevelFrequencies](#), [ExpandedVCF-method](#), and [VCF](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(read.table(phenoFile, TRUE, row.names = 1))

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)
vcf <- addFrequencies(vcf, "super_pop")

# Example usage ----

if (requireNamespace("EnsDb.Hsapiens.v75")){
  plotInfo(
    vcf, "MAF",
    range(GenomicRanges::granges(vcf)),
    EnsDb.Hsapiens.v75::EnsDb.Hsapiens.v75,
    "super_pop"
  )
}
```

readVcf-methods

Read VCF files

Description

Read Variant Call Format (VCF) files, attaches the given TVTBparam in the metadata slot of the resulting VCF object, and attaches optional phenotype information in the phenoData slot.

Usage

```
## S4 method for signature 'character,TVTBparam'
readVcf(
  file, genome, param, ..., colData = DataFrame(), autodetectGT = FALSE)
## S4 method for signature 'TabixFile,TVTBparam'
readVcf(
  file, genome, param, ..., colData = DataFrame(), autodetectGT = FALSE)
```

Arguments

file, genome	See readVcf .
param	TVTBparam object that contains recurrent parameters. The vep slot of param is checked for presence among the INFO keys of the VCF file. The TVTBparam object is coerced to ScanVcfParam using the ranges slot only. All fixed, info, and geno fields are imported (see argument colData to declare samples to import).
...	Additional arguments, passed to methods.
colData	Phenotype information in a DataFrame . If supplied, only samples identifiers present in rownames(colData) are imported from the VCF file. An error is thrown if any of the samples is absent from the VCF file.
autodetectGT	If TRUE, the method updates the genotypes definitions in the TVTBparam object attached to the resulting VCF object after guessing the codes that represent homozygote reference, heterozygote, and homozygote alternate genotypes.

Value

VCF object. See `?VCF` for complete details of the class structure.

Warning

A warning message is issued if genotypes cannot be fully defined, when autodetectGT=TRUE.

Author(s)

Kevin Rue-Albrecht

See Also

[readVcf](#), [TabixFile](#), [ScanVcfParam-method](#), and [VCF](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf.gz", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(read.table(phenoFile, TRUE, row.names = 1))
```

```
# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Example usage ----

vcf <- readVcf(vcfFile, "b37", tparam, colData = phenotypes)
```

tSVE

The Shiny Variant Explorer (tSVE) web-application

Description

Currently unsupported — Package undergoing major updates.

This function starts the interactive tSVE shiny web-application that allows to interactively load and visualise genetic variants and their Ensembl Variant Effect Predictor (VEP) predictions using the package methods. All arguments after the ... set default values for the application (*e.g.* widgets).

Usage

```
tSVE(
  ...,
  refGT = "0|0",
  hetGT = c("0|1", "1|2", "0|2", "1|0", "2|1", "2|0"),
  altGT = c("1|1", "2|2"),
  vepKey = "CSQ",
  refSuffix = "REF", hetSuffix = "HET", altSuffix = "ALT",
  aafSuffix = "AAF", mafSuffix = "MAF",
  genoHeatmap.height = "500px",
  options.width = 120,
  autodetectGTimport = FALSE
)
```

Arguments

...	Additional arguments passed to the runApp function from the shiny package.
refGT	Default homozygote reference genotypes.
hetGT	Default heterozygote genotypes.
altGT	Default homozygote alternate genotypes.
vepKey	Default INFO key for the VEP prediction field.
refSuffix	Default INFO key suffix used to store the data for homozygote reference genotypes.
hetSuffix	Default INFO key suffix used to store the data for heterozygote genotypes.
altSuffix	Default INFO key suffix used to store the data for homozygote alternate genotypes.
aafSuffix	Default INFO key suffix used to store the data for alternate allele frequency.
mafSuffix	Default INFO key suffix used to store the data for minor allele frequency.

`genoHeatmap.height` Default height (in pixels) of the heatmap that represents the genotype of each variant in each sample.
`options.width` Sets `options("width")`.
`autodetectGTimport` Default checkbox value. If FALSE, genotypes (ref, het, alt) are taken *as is* from the *Advanced settings* panel. If TRUE, genotypes selected in the *Advanced settings* panel are updated using the `autodetectGenotypes` method, immediately after variants are imported.

Value

Not applicable (yet).

Author(s)

Kevin Rue-Albrecht

References

Interface to EnsDb adapted from the `ensemldb` package.

See Also

[runEnsDbApp](#).

Examples

```
if (interactive()){
  runEnsDbApp()
}
```

TVTBparam-class

TVTBparam class objects

Description

The TVTBparam class stores recurrent parameters of the TVTB package in a convenient format.

Usage

```
TVTBparam(
  genos, ranges = GRangesList(),
  aaf = "AAF", maf = "MAF", vep = "CSQ", bp = SerialParam(),
  svp = ScanVcfParam(which = reduce(unlist(ranges))))
```

Arguments

genos	A Genotypes object that declares the three sets of homozygote reference, heterozygote, and homozygote alternate genotypes, as well as the individual key suffix used to store data for each set of genotypes in the info slot of a VCF object. See also <i>Details</i> section.
ranges	A GRangesList of genomic regions. See svp argument. <i>In the future, may be used to facet statistics and figures.</i>
aaf	INFO key suffix used to store the alternate allele frequency (AAF).
maf	INFO key suffix used to store the minor allele frequency (MAF).
vep	INFO key suffix used to extract the VEP predictions. See svp argument.
bp	A BiocParallelParam object.
svp	A ScanVcfParam object. If none is supplied, the ScanVcfParam slot which is automatically set to <code>reduce(unlist(ranges))</code> .

Details

For each *suffix* stored in the TVTBparam object, TVTB may store data in the VCF object under the INFO keys defined as follows:

suffix Statistics across all samples in the ExpandedVCF (*e.g.* "MAF").

phenotype_level_suffix Statistics across samples associated with a given level of a given phenotype (*e.g.* "gender_male_MAF").

Users are recommended to avoid using those INFO keys for other purposes.

Value

A TVTBparam object that contains recurrent parameters.

Accessor methods

In the following code snippets `x` is a TVTBparam object.

`genos(x)`, `genos(x) <- value` Gets or sets the Genotypes object stored in the `genos` slot.

`ranges(x)`, `ranges(x) <- value` List of genomic ranges to group variants during analyses and plots.

`ref(x)`, `ref(x) <- value` Gets or sets the character vector that declares homozygote reference genotypes.

`het(x)`, `het(x) <- value` Gets or sets the character vector that declares heterozygote genotypes.

`alt(x)`, `alt(x) <- value` Gets or sets the character vector that declares homozygote alternate genotypes.

`carrier(x)` Gets a character vectors of concatenated heterozygote and homozygote alternate genotypes. See also `het` and `alt` accessors.

`aaf(x)`, `aaf(x) <- value` Gets or sets the INFO key suffix used to store the alternate allele frequency (AAF).

`maf(x)`, `maf(x) <- value` Gets or sets the INFO key suffix used to store the minor allele frequency (MAF).

`vep(x)`, `maf(x) <- value` Gets or sets the INFO key suffix used to extract the VEP predictions.

`bp(x)`, `bp(x) <- value` Gets or sets the `BiocParallel` parameters.

`suffix(x)` Gets a named character vector that declares individual suffixes used to store the data for each set of genotypes in the INFO field of the VCF object. Names of this vector are `ref`, `het`, `alt`, `aaf`, and `maf`.

`svp(x)`, `svp(x) <- value` Gets or sets the `ScanVcfParam` parameters.

Author(s)

Kevin Rue-Albrecht

See Also

[Genotypes](#), [VCF](#), [ExpandedVCF](#), [addCountGenos-methods](#) [vepInPhenoLevel-methods](#), [variantsInSamples-methods](#) and [BiocParallelParam](#).

Examples

```
# Constructors ----

gr1 <- GenomicRanges::GRangesList(GenomicRanges::GRanges(
  "15", IRanges::IRanges(48413170, 48434757, names = "SLC24A5")
))

tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"), ranges = gr1)

# Accessors ----

## The Genotypes object stored in the genos slot of the TVTBparam object
## return by the genos() accessor.
genos(tparam)

## Genomic ranges stored in the TVTBparam object returned by the ranges()
## accessor.
ranges(tparam)

## Individual genotypes can be extracted with ref(), het(), alt() accessors.
ref(tparam)
het(tparam)
alt(tparam)

## Their individual INFO key suffixes can be extracted with suffix() applied to
## the above accessors.
suffix(tparam)
suffix(tparam)["ref"]
suffix(tparam)["het"]
suffix(tparam)["alt"]
suffix(tparam)["aaf"]
suffix(tparam)["maf"]

## Heterozygote, and alternate heterozygote genotypes are
## returned by the carrier() accessor.
carrier(tparam)

## INFO key suffix of alternate/minor allele frequency returned by the aaf()
## and maf() accessors.
```

```

aaf(tparam)
maf(tparam)

## INFO key suffix of the VEP predictions returned by the vep() accessor.
vep(tparam)

## BiocParallel parameters
bp(tparam)

## ScanVcfParam parameters
svp(tparam)

```

variantsInSamples-methods

Identify variants observed in samples

Description

Identifies variants observed (uniquely) in at least one sample of a given group.

Usage

```

## S4 method for signature 'ExpandedVCF'
variantsInSamples(
  vcf, samples = 1:ncol(vcf), unique = FALSE)

```

Arguments

vcf	ExpandedVCF object. metadata(vcf)[["TVTBparam"]] must contain a TVTBparam object.
samples	integer, numeric or character vector indicating samples to consider in VariantAnnotation::genotypes. If not specified, all samples are considered.
unique	If TRUE, consider only variants <i>unique</i> to the phenotype level (<i>i.e.</i> not seen in any other phenotype level).

Value

An named integer vector of indices indicating the name and index of variants that are (uniquely) observed in at least one non-reference genotype in the given group of samples.

Warning

A warning message is issued if genotypes are not fully defined in the TVTBparam.

Author(s)

Kevin Rue-Albrecht

See Also

[VCF](#) and [TVTBparam](#).

Examples

```

# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(
  read.table(file = phenoFile, header = TRUE, row.names = 1))

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

variantsInSamples(
  vcf,
  which(SummarizedExperiment::colData(vcf)[,"super_pop"] == "EUR"))

```

VcfBasicRules-class *VCF filters class objects sub-types*

Description

The VcfFixedRules and VcfInfoRules classes store filters applicable to the fixed and info slots of VCF objects, respectively.

The VcfVepRules stores filters applicable to Ensembl VEP predictions stores in a given INFO key.

Details

All arguments are first passed to S4Vectors::FilterRules before re-typing the resulting as a VcfFixedRules, VcfInfoRules, or VcfVepRules class.

Accessor methods

In the following code snippets x is an object from any of the classes described in this help page, except when specified otherwise.

active(x), active(x)<- Gets or sets the active state of each filter rule in x. Inherited from [FilterRules](#)

vep(x), vep(x)<- Gets or sets the INFO key where the Ensembl VEP predictions to use for filtering are stored. Returns NA_character_ for filters not applicable to VEP predictions.

type(x) Returns "filter" (linkS4class{FilterRules}), "fixed" (linkS4class{VcfFixedRules}), "info" (linkS4class{VcfInfoRules}), or "vep" (linkS4class{VcfVepRules}) as a character vector of length(x).

Constructors

```
VcfFixedRules(exprs = list(), ..., active = TRUE)
VcfInfoRules(exprs = list(), ..., active = TRUE)
VcfVepRules(exprs = list(), ..., active = TRUE, vep = "CSQ")
```

All methods construct an object of the corresponding class with the rules given in the list `exprs` or in `...`. The initial active state of the rules is given by `active`, which is recycled as necessary.

See the constructor of `FilterRules` for more details.

Subsetting and Replacement

In the following code snippets `x` and `value` are objects from any of the classes described in this help page.

```
x[i]: Subsets the filter rules using the same interface as for List.
x[[i]]: Extracts an expression or function via the same interface as for List.
x[i] <- value: Replaces a filter rule by one of the same class. The active state(s) and name(s) are transferred from value to x.
x[[i]] <- value: The same interface as for List. The default active state for new rules is TRUE.
```

Combining

In the following code snippets `x`, `values`, and `...` are objects from any of the classes described in this help page, or `VcfFilterRules`.

```
append(x, values, after = length(x)): Appends the values onto x at the index given by after.
c(x, ...): Concatenates the filters objects in ... onto the end of x.
```

Note that combining rules of different types (*e.g.* `VcfFixedRules` and `VcfVepRules`) produces a `VcfFilterRules` object.

Evaluating

As described in the `S4Vectors` documentation:

```
eval(expr, envir, enclos): Evaluates a rule instance (passed as the expr argument) in their respective context of a VCF object (passed as the envir argument). i.e.:
  • VcfFixedRules: fixed(envir)
  • VcfInfoRules: info(envir)
  • VcfVepRules: mcols(parseCSQToGRanges(envir, ...))
  • FilterRules: envir
```

```
evalSeparately(expr, envir, enclos):
  subsetByFilter(x, filter)
  summary(object)
```

See [eval](#), [FilterRules](#), [ANY-method](#) for details.

Author(s)

Kevin Rue-Albrecht

See Also

[FilterRules](#), [VcfFilterRules](#), and [VCF](#).

Examples

```
# Constructors ----

fixedRules <- VcfFixedRules(list(
  pass = expression(FILTER == "PASS"),
  qual = expression(QUAL > 20)
))
fixedRules

infoRules <- VcfInfoRules(list(
  common = expression(MAF > 0.01), # minor allele frequency
  alt = expression(ALT > 0) # count of alternative homozygotes
))
infoRules

vepRules <- VcfVepRules(list(
  missense = expression(Consequence %in% c("missense_variant")),
  CADD = expression(CADD_PHRED > 15)
))
vepRules

filterRules <- S4Vectors::FilterRules(list(
  PASS = function(x) fixed(x)$FILTER == "PASS",
  COMMON = function(x) info(x)$MAF > 0.05
))
filterRules

# Accessors ----

## get/set the active state directly
S4Vectors::active(infoRules)
S4Vectors::active(infoRules)["common"] <- FALSE

## See S4Vectors::FilterRules for more examples

# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(vcfFile, param = tparam)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)
vcf <- addOverallFrequencies(vcf)

# Applying filters to VCF objects ----
```

```

## Evaluate filters
S4Vectors::eval(fixedRules, vcf)
S4Vectors::eval(infoRules, vcf)
S4Vectors::eval(vepRules, vcf)
S4Vectors::eval(filterRules, vcf)

summary(S4Vectors::eval(vepRules, vcf))

## Evaluate filters separately
S4Vectors::evalSeparately(vepRules, vcf)

summary(S4Vectors::evalSeparately(vepRules, vcf))

## Subset VCF by filters
S4Vectors::subsetByFilter(vcf, vepRules)

# Subsetting and Replacement ----

vep1 <- vepRules[1] # VcfVepRules
vepRules[[1]] # expression

# Replace the expression (active reset to TRUE, original name retained)
vepRules[[2]] <- expression(CADD_PHRED > 30)

# Replace the rule (active state and name transferred from v5obj)
vepRules[2] <- VcfVepRules(
  list(newRule = expression(CADD_PHRED > 30)),
  active = FALSE)

```

VcfFilterRules-class *VcfFilterRules class objects*

Description

The VcfFilterRules class can stores multiple types of filters applicable to various slots of VCF objects.

Details

All arguments must be VcfFixedRules, VcfInfoRules, VcfVepRules, VcfFilterRules of FilterRules objects.

Accessor methods

In the following code snippets x is a VcfFilterRules object.

`active(x)`, `active(x)<-` Get or set the active state of each filter rule in x. Inherited from [FilterRules](#)

`vep(x)`, `vep(x)<-` Gets or sets the INFO key where the Ensembl VEP predictions to use for filtering are stored.

`type(x)` Gets the type of each filter stored in a VcfFilterRules object. *Read-only.*

Constructors

`VcfFilterRules(...)` constructs an `VcfFilterRules` object from `VcfFixedRules`, `VcfInfoRules`, `VcfVepRules`, and `VcfFilterRules` objects in ...

Subsetting and Replacement

In the code snippets below, `x` is a `VcfFilterRules` object.

`x[i, drop = TRUE]`: Subsets the filter rules using the same interface as for [Vector](#). If all filter rules are of the same type and `drop=TRUE` (default), the resulting object is re-typed to the most specialised class, if possible. In other words, if all remaining filter rules are of type "vep", the object will be type as `VcfVepRules`.

`x[[i]]`: Extracts an expression or function via the same interface as for [List](#).

`x[i] <- value`: Replaces a filter rule by one of any valid class (`VcfFixedRules`, `VcfInfoRules`, `VcfVepRules`, or `VcfFilterRules`). The active state(s), name(s), and type(s) (if applicable) are transferred from `value`.

`x[[i]] <- value`: The same interface as for [List](#). The default active state for new rules is `TRUE`.

Combining

In the following code snippets `x` is an object of class `VcfFilterRules`, while `values` and ... are objects from any of the classes `VcfFixedRules`, `VcfInfoRules`, `VcfVepRules`, or `VcfFilterRules`:

`append(x, values, after = length(x))`: Appends the values onto `x` at the index given by `after`.

`c(x, ...)`: Concatenates the filters objects in ... onto the end of `x`.

Evaluating

As described in the [S4Vectors](#) documentation:

`eval(expr, envir, enclos)` Evaluates each active rule in a `VcfFilterRules` instance (passed as the `expr` argument) in their respective context of a VCF object (passed as the `envir` argument).

`evalSeparately(expr, envir, enclos)`:

`subsetByFilter(x, filter)`

`summary(object)`

See [eval, FilterRules, ANY-method](#) for details.

Author(s)

Kevin Rue-Albrecht

See Also

[FilterRules](#), [VcfFixedRules](#), [VcfInfoRules](#), [VcfVepRules](#), and [VCF](#).

Examples

```

# Constructors ----

fixedR <- VcfFixedRules(list(
  pass = expression(FILTER == "PASS"),
  qual = expression(QUAL > 20)
))
fixedR

infoR <- VcfInfoRules(list(
  common = expression(MAF > 0.1), # minor allele frequency
  present = expression(ALT + HET > 0) # count of non-REF homozygotes
))
# ...is synonym to...
infoR <- VcfInfoRules(list(
  common = expression(MAF > 0.1), # minor allele frequency
  present = expression(ALT > 0 || HET > 0)
))
infoR

vepR <- VcfVepRules(list(
  missense = expression(Consequence %in% c("missense_variant")),
  CADD = expression(CADD_PHRED > 15)
))
vepR

vcfRules <- VcfFilterRules(fixedR, infoR, vepR)
vcfRules

# Accessors ----

## Type of each filter stored in the VcfFilterRules object
type(vcfRules)

# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(vcfFile, param = tparam)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)
vcf <- addOverallFrequencies(vcf, tparam)

# Applying filters to VCF objects ----

## Evaluate filters
eval(vcfRules, vcf)

## Evaluate filters separately

```

```

as.data.frame(evalSeparately(vcfRules, vcf))

# Interestingly, the only common missense variant has a lower CADD score
## Deactivate the CADD score filter
active(vcfRules)["CADD"] <- FALSE

## Subset VCF by filters (except CADD, deactivated above)
subsetByFilter(vcf, vcfRules)

# Subsetting and Replacement ----

v123 <- vcfRules[1:3]

# Extract the expression
v5expr <- vcfRules[[5]]
# Subset the object
v5obj <- vcfRules[5]

# Replace the expression (active reset to TRUE, original name retained)
v123[[2]] <- v5expr

# Replace the rule (active state and name transferred from v5obj)
v123[2] <- v5obj

```

vepInPhenoLevel-methods

VEP predictions of variants observed in samples

Description

Returns VEP predictions for variants observed (uniquely) in samples associated with a given phenotype level.

Usage

```

## S4 method for signature 'ExpandedVCF'
vepInPhenoLevel(
  vcf, phenoCol, level, vepCol, unique = FALSE)

```

Arguments

vcf	ExpandedVCF object. metadata(vcf)[["TVTBparam"]] must contain a TVTBparam object.
phenoCol	Name of a column in pheno.
level	Phenotype level; only variants observed in at least one sample will be considered.
vepCol	VEP prediction fields; character vector of metadata columns in <code>ensemblVEP::parseCSQToGRanges</code>
unique	If TRUE, consider only variants unique to the phenotype level (<i>i.e.</i> absent from all other phenotype levels).

Value

A GRanges including all VEP predictions associated with a variant seen in at least one sample (heterozygote or alternate homozygote) associated with the phenotype level. The GRanges contains at least one column for the VEP prediction value. Additional columns containing another VEP prediction field may be added using the facet argument.

Note

If available, "Feature" is a recommended value for this argument, as VEP typically produce one prediction per variant per feature.

Warning

A warning message is issued if genotypes are not fully defined in the TVTBparam.

Author(s)

Kevin Rue-Albrecht

See Also

[VCF](#), [ensemblVEP](#), [GRanges](#), and [DataFrame](#).

Examples

```
# Example data ----

# VCF file
vcfFile <- system.file("extdata", "moderate.vcf", package = "TVTB")

# Phenotype file
phenoFile <- system.file("extdata", "moderate_pheno.txt", package = "TVTB")
phenotypes <- S4Vectors::DataFrame(
  read.table(file = phenoFile, header = TRUE, row.names = 1))

# TVTB parameters
tparam <- TVTBparam(Genotypes("0|0", c("0|1", "1|0"), "1|1"))

# Pre-process variants
vcf <- VariantAnnotation::readVcf(
  vcfFile, param = tparam, colData = phenotypes)
vcf <- VariantAnnotation::expand(vcf, row.names = TRUE)

# Example usage ----

vepInPhenoLevel(vcf, "super_pop", "AFR", c("CADD_PHRED", "Feature", "IMPACT"))
```

Index

*Topic **methods**

- addCountGenos-methods, 3
- autodetectGenotypes-methods, 9
- countGenos-methods, 10
- dropInfo-methods, 11
- variantsInSamples-methods, 22
- vepInPhenoLevel-methods, 29

*Topic **package**

- TVTB-package, 2
- [,VcfFilterRules,ANY,ANY,ANY-method (VcfFilterRules-class), 26
- [,VcfFilterRules,ANY,ANY,logical-method (VcfFilterRules-class), 26
- [,VcfFilterRules,ANY,ANY,missing-method (VcfFilterRules-class), 26
- [,VcfFixedRules,ANY,ANY-method (VcfBasicRules-class), 23
- [,VcfInfoRules,ANY,ANY-method (VcfBasicRules-class), 23
- [,VcfVepRules,ANY,ANY-method (VcfBasicRules-class), 23
- [<-,VcfFilterRules,numeric,missing,VcfFilterRules-method (VcfFilterRules-class), 26
- [<-,VcfFilterRules,numeric,missing,VcfFixedRules-method (VcfFilterRules-class), 26
- [<-,VcfFilterRules,numeric,missing,VcfInfoRules-method (VcfFilterRules-class), 26
- [<-,VcfFilterRules,numeric,missing,VcfVepRules-method (VcfFilterRules-class), 26
- [<-,VcfFixedRules,numeric,missing,VcfFixedRules-method (VcfBasicRules-class), 23
- [<-,VcfInfoRules,numeric,missing,VcfInfoRules-method (VcfBasicRules-class), 23
- [<-,VcfVepRules,numeric,missing,VcfVepRules-method (VcfBasicRules-class), 23
- [[,VcfFilterRules,ANY,ANY-method (VcfFilterRules-class), 26
- [[,VcfFixedRules,ANY,ANY-method (VcfBasicRules-class), 23
- [[,VcfInfoRules,ANY,ANY-method (VcfBasicRules-class), 23
- [[,VcfVepRules,ANY,ANY-method (VcfBasicRules-class), 23
- [[<-,VcfFilterRules,ANY,ANY-method (VcfFilterRules-class), 26
- [[<-,VcfFixedRules,ANY,ANY-method (VcfBasicRules-class), 23
- [[<-,VcfInfoRules,ANY,ANY-method (VcfBasicRules-class), 23
- [[<-,VcfVepRules,ANY,ANY-method (VcfBasicRules-class), 23
- aaf (TVTBparam-class), 19
- aaf, TVTBparam-method (TVTBparam-class), 19
- aaf<- (TVTBparam-class), 19
- aaf<-, TVTBparam, character-method (TVTBparam-class), 19
- addCountGenos (addCountGenos-methods), 3
- addCountGenos, ExpandedVCF-method (addCountGenos-methods), 3
- addCountGenos-methods, 3
- addFrequencies (addFrequencies-methods), 4
- addFrequencies, ExpandedVCF, character-method (addFrequencies-methods), 4
- addFrequencies, ExpandedVCF, list-method (addFrequencies-methods), 4
- addFrequencies, ExpandedVCF, missing-method (addFrequencies-methods), 4
- addFrequencies-methods, 4
- addOverallFrequencies (addOverallFrequencies-methods), 6
- addOverallFrequencies, ExpandedVCF-method (addOverallFrequencies-methods), 6
- addOverallFrequencies-methods, 6
- addPhenoLevelFrequencies (addPhenoLevelFrequencies-methods), 7
- addPhenoLevelFrequencies, ExpandedVCF-method (addPhenoLevelFrequencies-methods), 7
- addPhenoLevelFrequencies-methods, 7
- alt, Genotypes-method (Genotypes-class), 12

- alt, TVTBparam-method (TVTBparam-class), 19
- alt<- , Genotypes, character-method (Genotypes-class), 12
- alt<- , TVTBparam, character-method (TVTBparam-class), 19
- alt<- , TVTBparam, list-method (TVTBparam-class), 19
- append, VcfFilterRules, FilterRules-method (VcfFilterRules-class), 26
- append, VcfFixedRules, FilterRules-method (VcfBasicRules-class), 23
- append, VcfInfoRules, FilterRules-method (VcfBasicRules-class), 23
- append, VcfVepRules, FilterRules-method (VcfBasicRules-class), 23
- autodetectGenotypes, 12
- autodetectGenotypes (autodetectGenotypes-methods), 9
- autodetectGenotypes, VCF-method (autodetectGenotypes-methods), 9
- autodetectGenotypes-methods, 9

- BiocParallelParam, 21
- bp (TVTBparam-class), 19
- bp, TVTBparam-method (TVTBparam-class), 19
- bp<- (TVTBparam-class), 19
- bp<- , TVTBparam, BiocParallelParam-method (TVTBparam-class), 19

- c, VcfFilterRules-method (VcfFilterRules-class), 26
- c, VcfFixedRules-method (VcfBasicRules-class), 23
- c, VcfInfoRules-method (VcfBasicRules-class), 23
- c, VcfVepRules-method (VcfBasicRules-class), 23
- carrier (Genotypes-class), 12
- carrier, Genotypes-method (Genotypes-class), 12
- carrier, TVTBparam-method (TVTBparam-class), 19
- class:Genotypes (Genotypes-class), 12
- class:TVTBparam (TVTBparam-class), 19
- class:VcfFilterRules (VcfFilterRules-class), 26
- class:VcfFixedRules (VcfBasicRules-class), 23
- class:VcfInfoRules (VcfBasicRules-class), 23
- class:VcfVepRules (VcfBasicRules-class), 23
- ExpandedVCF, 21
- FilterRules, 23, 25–27
- genos (Genotypes-class), 12
- genos, Genotypes-method (Genotypes-class), 12
- genos, TVTBparam-method (TVTBparam-class), 19
- genos<- (TVTBparam-class), 19
- genos<- , TVTBparam, Genotypes-method (TVTBparam-class), 19
- Genotypes, 21
- Genotypes (Genotypes-class), 12
- Genotypes-class, 12
- Genotypes-methods (Genotypes-class), 12
- ggpairs, 14
- GRanges, 30
- het (Genotypes-class), 12
- het, Genotypes-method (Genotypes-class), 12
- het, TVTBparam-method (TVTBparam-class), 19
- het<- (Genotypes-class), 12
- het<- , Genotypes, character-method (Genotypes-class), 12

- het<- ,TVTBparam,character-method (TVTBparam-class), 19
- het<- ,TVTBparam,list-method (TVTBparam-class), 19
- initialize,Genotypes-method (Genotypes-class), 12
- initialize,TVTBparam-method (TVTBparam-class), 19
- initialize,VcfFilterRules-method (VcfFilterRules-class), 26
- initialize,VcfFixedRules-method (VcfBasicRules-class), 23
- initialize,VcfInfoRules-method (VcfBasicRules-class), 23
- initialize,VcfVepRules-method (VcfBasicRules-class), 23
- List, 24, 27
- maf (TVTBparam-class), 19
- maf ,TVTBparam-method (TVTBparam-class), 19
- maf<- (TVTBparam-class), 19
- maf<- ,TVTBparam,character-method (TVTBparam-class), 19
- pairsInfo (pairsInfo-methods), 14
- pairsInfo,VCF-method (pairsInfo-methods), 14
- pairsInfo-methods, 14
- phenoData, 14, 15
- plotInfo (plotInfo-methods), 15
- plotInfo,VCF-method (plotInfo-methods), 15
- plotInfo-methods, 15
- plotTracks, 16
- ranges (TVTBparam-class), 19
- ranges,TVTBparam-method (TVTBparam-class), 19
- ranges<- (TVTBparam-class), 19
- ranges<- ,TVTBparam,GRangesList-method (TVTBparam-class), 19
- readVcf, 17
- readVcf,character,TVTBparam-method (readVcf-methods), 16
- readVcf,TabixFile,TVTBparam-method (readVcf-methods), 16
- readVcf-methods, 16
- ref,Genotypes-method (Genotypes-class), 12
- ref,TVTBparam-method (TVTBparam-class), 19
- ref<- ,Genotypes,character-method (Genotypes-class), 12
- ref<- ,TVTBparam,character-method (TVTBparam-class), 19
- ref<- ,TVTBparam,list-method (TVTBparam-class), 19
- runApp, 18
- runEnsDbApp, 19
- ScanVcfParam, 17, 20
- suffix (Genotypes-class), 12
- suffix,Genotypes-method (Genotypes-class), 12
- suffix,TVTBparam-method (TVTBparam-class), 19
- svp (TVTBparam-class), 19
- svp,TVTBparam-method (TVTBparam-class), 19
- svp<- (TVTBparam-class), 19
- svp<- ,TVTBparam,ScanVcfParam-method (TVTBparam-class), 19
- tSVE, 18
- TVTB-package, 2
- TVTBparam, 4-6, 8, 13, 17, 22, 29
- TVTBparam (TVTBparam-class), 19
- TVTBparam-class, 19
- TVTBparam-methods (TVTBparam-class), 19
- TxDb, 15
- type,FilterRules-method (VcfBasicRules-class), 23
- type,VcfFilterRules-method (VcfFilterRules-class), 26
- type,VcfFixedRules-method (VcfBasicRules-class), 23
- type,VcfInfoRules-method (VcfBasicRules-class), 23
- type,VcfVepRules-method (VcfBasicRules-class), 23
- variantsInSamples (variantsInSamples-methods), 22
- variantsInSamples,ExpandedVCF-method (variantsInSamples-methods), 22
- variantsInSamples-methods, 22
- VCF, 5, 7, 8, 10, 11, 13, 14, 16, 17, 21, 22, 25, 27, 30
- VcfBasicRules-class, 23
- VcfFilterRules, 25
- VcfFilterRules (VcfFilterRules-class), 26
- VcfFilterRules-class, 26
- VcfFixedRules, 27

VcfFixedRules (VcfBasicRules-class), 23
VcfFixedRules-class
 (VcfBasicRules-class), 23
VcfInfoRules, 27
VcfInfoRules (VcfBasicRules-class), 23
VcfInfoRules-class
 (VcfBasicRules-class), 23
VcfVepRules, 27
VcfVepRules (VcfBasicRules-class), 23
VcfVepRules-class
 (VcfBasicRules-class), 23
Vector, 27
vep (TVTBparam-class), 19
vep, FilterRules-method
 (VcfBasicRules-class), 23
vep, TVTBparam-method (TVTBparam-class),
 19
vep, VcfFilterRules-method
 (VcfFilterRules-class), 26
vep, VcfFixedRules-method
 (VcfBasicRules-class), 23
vep, VcfInfoRules-method
 (VcfBasicRules-class), 23
vep, VcfVepRules-method
 (VcfBasicRules-class), 23
vep<- (TVTBparam-class), 19
vep<-, TVTBparam, character-method
 (TVTBparam-class), 19
vep<-, VcfFilterRules, character-method
 (VcfFilterRules-class), 26
vep<-, VcfVepRules, character-method
 (VcfBasicRules-class), 23
vepInPhenoLevel
 (vepInPhenoLevel-methods), 29
vepInPhenoLevel, ExpandedVCF-method
 (vepInPhenoLevel-methods), 29
vepInPhenoLevel-methods, 29