

Package ‘bugsigdbr’

September 27, 2022

Version 1.2.2

Title R-side access to published microbial signatures from BugSigDB

Description The bugsigdbr package implements convenient access to bugsigdb.org from within R/Bioconductor. The goal of the package is to facilitate import of BugSigDB data into R/Bioconductor, provide utilities for extracting microbe signatures, and enable export of the extracted signatures to plain text files in standard file formats such as GMT.

URL <https://github.com/waldronlab/bugsigdbr>

BugReports <https://github.com/waldronlab/bugsigdbr/issues>

Depends R (>= 4.1)

Imports BiocFileCache, methods, vroom, utils

Suggests BiocStyle, knitr, ontologyIndex, rmarkdown, testthat (>= 3.0.0)

License GPL-3

VignetteBuilder knitr

biocViews DataImport, GeneSetEnrichment, Metagenomics, Microbiome

Encoding UTF-8

RoxygenNote 7.1.2

git_url <https://git.bioconductor.org/packages/bugsigdbr>

git_branch RELEASE_3_15

git_last_commit 0bedd3e

git_last_commit_date 2022-09-06

Date/Publication 2022-09-27

Author Ludwig Geistlinger [aut, cre],
Jennifer Wokaty [aut],
Levi Waldron [aut]

Maintainer Ludwig Geistlinger <ludwig_geistlinger@hms.harvard.edu>

R topics documented:

browseSignature	2
browseTaxon	3
extractTaxLevel	3
getMetaSignatures	4
getOntology	6
getSignatures	7
importBugSigDB	8
restrictTaxLevel	9
subsetByOntology	10
writeGMT	11
Index	12

browseSignature	<i>Displaying BugSigDB signatures pages in a web browser</i>
-----------------	--

Description

Functionality for programmatically displaying microbe signatures on BugSigDB signature pages.

Usage

```
browseSignature(sname)
```

Arguments

sname character. Signature name. Expected to start with a prefix of the form "bsdb:<X>/<Y>/<Z>_" encoding the corresponding BugSigDB signature ID.

Value

The URL of the selected BugSigDB signature page. If interactive, opens the URL in the default web browser.

References

BugSigDB: <https://bugsigdb.org>

Examples

```
sname <- "bsdb:215/1/1_eczema:infant-with-eczema_vs_healthy-control_UP"
browseSignature(sname)
```

`browseTaxon`*Displaying BugSigDB taxon pages in a web browser*

Description

Functionality for programmatically displaying BugSigDB taxon pages.

Usage

```
browseTaxon(tax.id)
```

Arguments

`tax.id` character. NCBI taxonomy ID.

Value

The URL of the selected BugSigDB taxon page. If interactive, opens the URL in the default web browser.

References

BugSigDB: <https://bugsigdb.org>

Examples

```
# BugSigDB taxon page for Escherichia coli
browseTaxon("562")
```

`extractTaxLevel`*Extract specific taxonomic levels from a microbe signature*

Description

Functionality for extracting specific taxonomic levels (such as genus and species) from a microbe signature containing taxonomic clades in MetaPhlAn format.

Usage

```
extractTaxLevel(
  sig,
  tax.id.type = c("metaphlan", "taxname"),
  tax.level = "mixed",
  exact.tax.level = TRUE
)
```

Arguments

sig	character. Microbe signature containing taxonomic clades in MetaPhlAn format.
tax.id.type	Character. Taxonomic ID type of the returned microbe sets. Either "metaphlan" (default) or "taxname".
tax.level	character. Either "mixed" or any subset of c("kingdom", "phylum", "class", "order", "family", "genus", "species", "strain"). This full vector is equivalent to "mixed".
exact.tax.level	logical. Should only the exact taxonomic level specified by tax.level be returned? Defaults to TRUE. If FALSE, a more general tax.level is extracted for microbes given at a more specific taxonomic level.

Value

a character vector storing taxonomic clades restricted to chosen taxonomic level(s).

References

BugSigDB: <https://bugsigdb.org>

Examples

```
ord <- "k__Bacteria|p__Firmicutes|c__Bacilli|o__Lactobacillales"
sig <- c("f__Lactobacillaceae|g__Lactobacillus",
        "f__Aerococcaceae|g__Abiotrophia|s__Abiotrophia defectiva",
        "f__Lactobacillaceae|g__Limosilactobacillus|s__Limosilactobacillus mucosae")
sig <- paste(ord, sig, sep = "|")
sig <- extractTaxLevel(sig, tax.level = "genus")
sig <- extractTaxLevel(sig, tax.level = "genus", exact.tax.level = FALSE)
sig <- extractTaxLevel(sig,
                      tax.id.type = "taxname",
                      tax.level = "genus",
                      exact.tax.level = FALSE)
```

getMetaSignatures

Obtain meta-signatures for a column of interest

Description

Functionality for obtaining meta-signatures for a column of interest

Usage

```
getMetaSignatures(  
  df,  
  column,  
  direction = c("BOTH", "UP", "DOWN"),  
  min.studies = 2,  
  min.taxa = 5,  
  comb.fun = sum,  
  ...  
)
```

Arguments

df	data.frame storing BugSigDB data. Typically obtained via importBugSigDB .
column	character. Column of interest. Need to be a valid column name of df.
direction	character. Indicates direction of abundance change for signatures to be included in the computation of meta-signatures. Use "UP" to restrict computation to signatures with increased abundance in the exposed group. Use "DOWN" to restrict to signatures with decreased abundance in the exposed group. Defaults to "BOTH" which will not filter signatures by direction of abundance change.
min.studies	integer. Minimum number of studies for a category in column to be included. Defaults to 2, which will then only compute meta-signatures for categories investigated by at least two studies.
min.taxa	integer. Minimum size for meta-signatures. Defaults to 5, which will then only include meta-signatures containing at least 5 taxa.
comb.fun	function. Function for combining sample size of the exposed group and sample size of the unexposed group into an overall study sample size. Defaults to sum which will simply add sample sizes of exposed and unexposed group.
...	additional argument passed on to getSignatures .

Value

A list of meta-signatures, each meta-signature being a named numeric vector. Names are the taxa of the meta-signature, numeric values correspond to sample size weights associated with each taxon.

See Also

[getSignatures](#)

Examples

```
df <- importBugSigDB()  
# Body-site specific meta-signatures composed from signatures reported as both  
# increased or decreased across all conditions of study:  
bs.meta.sigs <- getMetaSignatures(df, column = "Body site")  
# Condition-specific meta-signatures from feces samples, increased
```

```
# in conditions of study. Use taxonomic names instead of the default NCBI IDs:
df.feces <- df[df$`Body site` == "feces", ]
cond.meta.sigs <- getMetaSignatures(df.feces, column = "Condition",
                                   direction = "UP", tax.id.type = "taxname")
names(cond.meta.sigs)
cond.meta.sigs["bipolar disorder"]
```

getOntology

Obtain the EFO and UBERON ontology

Description

Lightweight wrapper around `ontologyIndex::get_ontology` to parse the Experimental Factor Ontology (EFO) or the Uber-anatomy ontology (UBERON) from OBO format into an R object.

Usage

```
getOntology(onto = c("efo", "uberon"), cache = TRUE)
```

Arguments

onto	character. Ontology to obtain. Should be either "efo" (default) to obtain the Experimental Factor Ontology (EFO) or "uberon" to obtain the Uber-anatomy ontology (UBERON).
cache	logical. Should a locally cached version used if available? Defaults to TRUE.

Value

An object of class `ontology_index` as defined in the `ontologyIndex` package.

References

EFO: <https://www.ebi.ac.uk/ols/ontologies/efo>

UBERON: <https://www.ebi.ac.uk/ols/ontologies/uberon>

See Also

`get_ontology` from the `ontologyIndex` package.

Examples

```
uberon <- getOntology("uberon")
```

getSignatures	<i>Obtain microbe signatures from BugSigDB</i>
---------------	--

Description

Functionality for obtaining microbe signatures from BugSigDB

Usage

```
getSignatures(  
  df,  
  tax.id.type = c("ncbi", "metaphlan", "taxname"),  
  tax.level = "mixed",  
  exact.tax.level = TRUE,  
  min.size = 1  
)
```

Arguments

df	data.frame storing BugSigDB data. Typically obtained via <code>importBugSigDB</code> .
tax.id.type	Character. Taxonomic ID type of the returned microbe sets. Either "ncbi" (default), "metaphlan", or "taxname".
tax.level	character. Either "mixed" or any subset of c("kingdom", "phylum", "class", "order", "family", "genus", "species", "strain"). This full vector is equivalent to "mixed".
exact.tax.level	logical. Should only the exact taxonomic level specified by tax.level be returned? Defaults to TRUE. If FALSE, a more general tax.level is extracted for microbes given at a more specific taxonomic level.
min.size	integer. Minimum signature size. Defaults to 1, which will filter out empty signature. Use min.size = 0 to keep empty signatures.

Value

a list of microbe signatures. Each signature is a character vector of taxonomic IDs depending on the chosen tax.id.type.

References

BugSigDB: <https://bugsigdb.org>

See Also

`importBugSigDB`

Examples

```
df <- importBugSigDB()
sigs <- getSignatures(df)
```

importBugSigDB	<i>Obtain published microbial signatures from bugsigdb.org</i>
----------------	--

Description

Obtain published microbial signatures from bugsigdb.org

Usage

```
importBugSigDB(version = "10.5281/zenodo.6468009", cache = TRUE)
```

Arguments

version	character. A Zenodo DOI, git commit hash, or "devel". Defaults to the most recent stable release on Zenodo, which includes complete and reviewed content from BugSigDB.
cache	logical. Should a locally cached version used if available? Defaults to TRUE.

Value

a `data.frame`.

References

BugSigDB: <https://bugsigdb.org>

Stable release: <https://doi.org/10.5281/zenodo.5606165>

Latest version (incl. not reviewed content): <https://github.com/waldronlab/BugSigDBExports>

Examples

```
df <- importBugSigDB()
```

restrictTaxLevel	<i>Restrict microbe signatures to specific taxonomic levels</i>
------------------	---

Description

Functionality for restricting microbe signatures to specific taxonomic levels such as genus and species.

Usage

```
restrictTaxLevel(df, tax.level = "mixed", exact.tax.level = TRUE, min.size = 1)
```

Arguments

df	data.frame storing BugSigDB data. Typically obtained via <code>importBugSigDB</code> .
tax.level	character. Either "mixed" or any subset of <code>c("kingdom", "phylum", "class", "order", "family", "genus", "species", "strain")</code> . This full vector is equivalent to "mixed".
exact.tax.level	logical. Should only the exact taxonomic level specified by <code>tax.level</code> be returned? Defaults to TRUE. If FALSE, a more general <code>tax.level</code> is extracted for microbes given at a more specific taxonomic level.
min.size	integer. Minimum signature size. Defaults to 1, which will filter out empty signatures. Use <code>min.size = 0</code> to keep empty signatures.

Value

a data.frame with microbe signature columns restricted to chosen taxonomic level(s).

References

BugSigDB: <https://bugsigdb.org>

See Also

`importBugSigDB`

Examples

```
df <- importBugSigDB()
df <- restrictTaxLevel(df, tax.level = "genus")
```

subsetByOntology	<i>Ontology-based subsetting of BugSigDB signatures</i>
------------------	---

Description

This function facilitates ontology-based queries for experimental factors and body sites.

Usage

```
subsetByOntology(df, column = c("Body site", "Condition"), term, ontology)
```

Arguments

df	data.frame storing BugSigDB data. Typically obtained via <code>importBugSigDB</code> .
column	character. Column of df on which subsetting should be performed. Should be either "Body site" (default) or "Condition".
term	character. A valid term of ontology. Subsetting by this term then involves subsetting column to all descendants of that term in the the chosen ontology and that are present in the chosen column of df.
ontology	an object of class <code>ontology_index</code> as defined in the <code>ontologyIndex</code> package. Typically obtained via <code>getOntology</code> .

Value

a data.frame with the chosen column restricted to descendants of the chosen term in the chosen ontology.

References

EFO: <https://www.ebi.ac.uk/ols/ontologies/efo>

UBERON: <https://www.ebi.ac.uk/ols/ontologies/uberon>

See Also

`importBugSigDB`, `getOntology`

Examples

```
# (1) Obtain BugSigDB data
df <- importBugSigDB()

# (2) Obtain ontology of interest as an R object
uberon <- getOntology("uberon")

# (3) High-level query on body site
sdf <- subsetByOntology(df,
                        column = "Body site",
```

```
term = "digestive system element",
ontology = uberon)
table(sdf[, "Body site"])
```

writeGMT	<i>Write microbe signatures to file in GMT format</i>
----------	---

Description

Functionality for writing microbe signatures to file in GMT format.

Usage

```
writeGMT(sigs, gmt.file)
```

Arguments

sigs	A list of microbe signatures (character vectors of taxonomic IDs).
gmt.file	character. Path to output file in GMT format.

Value

none, writes to file.

References

GMT file format: http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/Data_formats

Examples

```
bsdb <- importBugSigDB()
sigs <- getSignatures(bsdb)
writeGMT(sigs, gmt.file = "signatures.gmt")
file.remove("signatures.gmt")
```

Index

browseSignature, [2](#)
browseTaxon, [3](#)

data.frame, [8](#)

extractTaxLevel, [3](#)

getMetaSignatures, [4](#)
getOntology, [6](#), [10](#)
getSignatures, [5](#), [7](#)

importBugSigDB, [5](#), [7](#), [8](#), [9](#), [10](#)

restrictTaxLevel, [9](#)

subsetByOntology, [10](#)

writeGMT, [11](#)