

# Package ‘cleaver’

November 10, 2019

**Version** 1.24.0

**Title** Cleavage of Polypeptide Sequences

**Maintainer** Sebastian Gibb <mail@sebastiangibb.de>

**Depends** R (>= 3.0.0), methods, Biostrings (>= 1.29.8)

**Imports** S4Vectors, IRanges

**Suggests** testthat (>= 0.8), knitr, BiocStyle (>= 0.0.14), rmarkdown, BRAIN, UniProt.ws (>= 2.1.4)

**Description** In-silico cleavage of polypeptide sequences. The cleavage rules are taken from:  
[http://web.expasy.org/peptide\\_cutter/peptidecutter\\_enzymes.html](http://web.expasy.org/peptide_cutter/peptidecutter_enzymes.html)

**License** GPL (>= 3)

**URL** <https://github.com/sgibb/cleaver/>

**BugReports** <https://github.com/sgibb/cleaver/issues/>

**LazyLoad** yes

**VignetteBuilder** knitr

**biocViews** Proteomics

**git\_url** <https://git.bioconductor.org/packages/cleaver>

**git\_branch** RELEASE\_3\_10

**git\_last\_commit** 57cef7d

**git\_last\_commit\_date** 2019-10-29

**Date/Publication** 2019-11-09

**Author** Sebastian Gibb [aut, cre] (<<https://orcid.org/0000-0001-7406-4443>>)

## R topics documented:

cleaver-package . . . . .	2
cleave-methods . . . . .	2

<b>Index</b>	<b>9</b>
--------------	----------

---

cleaver-package      *Cleavage of polypeptide sequences*

---

### Description

This package cleaves polypeptide sequences. It provides three functions: [cleave](#), [cleavageRanges](#) and [cleavageSites](#).

### Details

The cleavage rules are taken from: [https://web.expasy.org/peptide\\_cutter/peptidecutter\\_enzymes.html](https://web.expasy.org/peptide_cutter/peptidecutter_enzymes.html)

Package: cleaver  
License: GPL (>= 3)  
URL: <https://github.com/sgibb/cleaver/>

### Author(s)

Sebastian Gibb <[mail@sebastiangibb.de](mailto:mail@sebastiangibb.de)>

### References

<https://github.com/sgibb/cleaver/>

Gasteiger E., Hoogland C., Gattiker A., Duvaud S., Wilkins M.R., Appel R.D., Bairoch A.; "Protein Identification and Analysis Tools on the ExPASy Server". (In) John M. Walker (ed): The Proteomics Protocols Handbook, Humana Press (2005).

[https://web.expasy.org/peptide\\_cutter/peptidecutter\\_enzymes.html](https://web.expasy.org/peptide_cutter/peptidecutter_enzymes.html)

### See Also

[cleave](#), [cleavageRanges](#) and [cleavageSites](#).

---

cleave-methods      *Cleavage of polypeptide sequences*

---

### Description

This functions cleave polypeptide sequences. Use `cleavageSites` to find the cleavage sites, `cleavageRanges` to find the cleavage ranges and `cleave` to get the cleavage products.

### Usage

```
## S4 method for signature 'character'  
cleave(x, enzym = "trypsin", missedCleavages = 0,  
       custom = NULL, unique = TRUE)
```

```
## S4 method for signature 'AAString'
```

```

cleave(x, enzym = "trypsin", missedCleavages = 0,
       custom = NULL, unique = TRUE)

## S4 method for signature 'AAStringSet'
cleave(x, enzym = "trypsin", missedCleavages = 0,
       custom = NULL, unique = TRUE)

## S4 method for signature 'character'
cleavageRanges(x, enzym = "trypsin", missedCleavages = 0,
               custom = NULL)

## S4 method for signature 'AAString'
cleavageRanges(x, enzym = "trypsin", missedCleavages = 0,
               custom = NULL)

## S4 method for signature 'AAStringSet'
cleavageRanges(x, enzym = "trypsin", missedCleavages = 0,
               custom = NULL)

## S4 method for signature 'character'
cleavageSites(x, enzym = "trypsin", custom = NULL)

## S4 method for signature 'AAString'
cleavageSites(x, enzym = "trypsin", custom = NULL)

## S4 method for signature 'AAStringSet'
cleavageSites(x, enzym = "trypsin", custom = NULL)

```

### Arguments

x	polypeptide sequences.
enzym	character, cleavage rule.
missedCleavages	numeric, number of missed cleavages.
custom	character, of length 1 or 2. Could be used to define own cleavage rules. The first element would be the pattern and the optional second element would be an exception (non-cleavage) pattern. Perl-like regular expressions are supported, see <a href="#">gregexpr</a> for details. If custom is set the enzym is ignored.
unique	logical, if TRUE all duplicated cleavage products per peptide are removed.

### Details

The cleavage rules are taken from: [https://web.expasy.org/peptide\\_cutter/peptidecutter\\_enzymes.html](https://web.expasy.org/peptide_cutter/peptidecutter_enzymes.html)

Cleavage rules (cleavage between P1 and P1'):

Rule name	P4	P3	P2	P1	P1'
arg-c proteinase	-	-	-	R	-
asp-n endopeptidase	-	-	-	-	D
bnps-skatole-c	-	-	-	W	-
caspase1	F,W,Y,L	-	H,A,T	D	not P,E,D,Q,K
caspase2	D	V	A	D	not P,E,D,Q,K

caspase3	D	M	Q	D	not P,E,D,Q,K
caspase4	L	E	V	D	not P,E,D,Q,K
caspase5	L,W	E	H	D	-
caspase6	V	E	H,I	D	not P,E,D,Q,K
caspase7	D	E	V	D	not P,E,D,Q,K
caspase8	I,L	E	T	D	not P,E,D,Q,K
caspase9	L	E	H	D	-
caspase10	I	E	A	D	-
chymotrypsin-high	-	-	-	F,Y	not P
	-	-	-	W	not M,P
chymotrypsin-low	-	-	-	F,L,Y	not P
	-	-	-	W	not M,P
	-	-	-	M	not P,Y
	-	-	-	H	not D,M,P,W
clostripain	-	-	-	R	-
cnbr	-	-	-	M	-
enterokinase	D,E	D,E	D,E	K	-
factor xa	A,F,G,I,L,T,V,M	D,E	G	R	-
formic acid	-	-	-	D	-
glutamyl endopeptidase	-	-	-	D	-
granzyme-b	I	E	P	D	-
hydroxylamine	-	-	-	N	G
iodosobenzoic acid	-	-	-	W	-
lysc	-	-	-	K	-
lysn	-	-	-	-	K
neutrophil elastase	-	-	-	A,V	-
ntcb	-	-	-	-	C
pepsin1.3	-	not H,K,R	not P	not R	F,L
pepsin	-	not H,K,R	not P	not R	F,L,W,Y
	-	not H,K,R	not P	F,L,W,Y	-
	-	not H,K,R	not P	F,L	-
proline endopeptidase	-	-	not H,K,R	P	not P
proteinase k	-	-	-	A,E,F,I,L,T,V,W,Y	-
staphylococcal peptidase i	-	-	not E	E	-
thermolysin	-	-	-	not D,E	A,F,I,L,M,V
thrombin	-	-	G	R	G
	A,F,G,I,L,T,V,M	A,F,G,I,L,T,V,W	P	R	not D,E
trypsin	-	-	-	K,R	not P
	-	-	W	K	P
	-	-	M	R	P

## Exceptions:

Rule name	Enzyme name	P4	P3	P2	P1	P1'	P2'
trypsin	-	-	C,D	K	D	-	-
		-	-	C	K	H,Y	-
		-	-	C	R	K	-
		-	-	R	R	H,R	-

Rule name

Enzyme name

arg-c proteinase	Arg-C proteinase
asp-n endopeptidase	Asp-N endopeptidase
bnps-skatole-c	BNPS-Skatole
caspase1	Caspase 1
caspase2	Caspase 2
caspase3	Caspase 3
caspase4	Caspase 4
caspase5	Caspase 5
caspase6	Caspase 6
caspase7	Caspase 7
caspase8	Caspase 8
caspase9	Caspase 9
caspase10	Caspase 10
chymotrypsin-high	Chymotrypsin-high specificity (C-term to [FYW], not before P)
chymotrypsin-low	Chymotrypsin-low specificity (C-term to [FYWML], not before P)
clostripain	Clostripain (Clostridiopeptidase B)
cnbr	CNBr
enterokinase	Enterokinase
factor xa	Factor Xa
formic acid	Formic acid
glutamyl endopeptidase	Glutamyl endopeptidase
granzyme-b	Granzyme B
hydroxylamine	Hydroxylamine
iodosobenzoic acid	Iodosobenzoic acid
lysc	LysC
lysn	LysN
neutrophil elastase	Neutrophil elastase
ntcb	NTCB (2-nitro-5-thiocyanobenzoic acid)
pepsin1.3	Pepsin (pH == 1.3)
pepsin	Pepsin (pH > 2)
proline endopeptidase	Proline-endopeptidase
proteinase k	Proteinase K
staphylococcal peptidase i	Staphylococcal Peptidase I
thermolysin	Thermolysin
thrombin	Thrombin
trypsin	Trypsin

## Value

**cleave** If *x* is a character it returns a list of the same length as *x*. Each element contains a character vector with the corresponding cleavage products of the polypeptides. If *x* is an [AAString](#) or an [AAStringSet](#) an [AAStringSet](#) or an [AAStringSetList](#) instance of the same length as *x* is returned. Each element contains an [AAString](#) or an [AAStringSet](#) instance with the corresponding cleavage products of the polypeptides.

**cleavageRanges** If *x* is a character it returns a list of the same length as *x*. Each element contains a two-column matrix with the start and end positions of the peptides. If *x* is an [AAString](#) or an [AAStringSet](#) instance an [IRanges](#) or an [IRangesList](#) of the same length as *x* is returned.

**cleavageSites** Returns a list of the same length as *x*. Each element contains an integer vector with the cleavage positions.

Overview:

Input	cleave	cleavageRanges	cleavageSites
character	list of character	list of matrix	list of integer
<a href="#">AAString</a>	<a href="#">AAStringSet</a>	<a href="#">IRanges</a>	list of integer
<a href="#">AAStringSet</a>	<a href="#">AAStringSetList</a>	<a href="#">IRangesList</a>	list of integer

**Author(s)**

Sebastian Gibb <[mail@sebastiangibb.de](mailto:mail@sebastiangibb.de)>

**References**

Gasteiger E., Hoogland C., Gattiker A., Duvaud S., Wilkins M.R., Appel R.D., Bairoch A.; "Protein Identification and Analysis Tools on the ExPASy Server". (In) John M. Walker (ed): The Proteomics Protocols Handbook, Humana Press (2005).

[https://web.expasy.org/peptide\\_cutter/peptidecutter\\_enzymes.html](https://web.expasy.org/peptide_cutter/peptidecutter_enzymes.html)

**See Also**

[AAString](#), [AAStringSet](#), [AAStringSetList](#), [IRanges](#), [IRangesList](#)

**Examples**

```
library("cleaver")

## Gastric juice peptide 1 (UniProtKB/Swiss-Prot: GAJU_HUMAN/P01358)
gaju <- "LAAGKVEDSD"

cleave(gaju, "trypsin")
# $LAAGKVEDSD
# [1] "LAAGK" "VEDSD"

cleavageRanges(gaju, "trypsin")
# $LAAGKVEDSD
#   start end
# [1,]    1  5
# [2,]    6 10

cleavageSites(gaju, "trypsin")
# $LAAGKVEDSD
# [1] 5

cleave(gaju, "trypsin", missedCleavages=1)
# $LAAGKVEDSD
# [1] "LAAGKVEDSD"

cleavageRanges(gaju, "trypsin", missedCleavages=1)
# $LAAGKVEDSD
#   start end
# [1,]    1 10

cleave(gaju, "trypsin", missedCleavages=0:1)
# $LAAGKVEDSD
# [1] "LAAGK" "VEDSD" "LAAGKVEDSD"

cleavageRanges(gaju, "trypsin", missedCleavages=0:1)
```

```

# $LAAGKVEDSD
#      start end
# [1,]    1  5
# [2,]    6 10
# [3,]    1 10

cleave(gaju, "pepsin")
# $LAAGKVEDSD
# [1] "LAAGKVEDSD"
# (no cleavage)

## use AAStringSet
gaju <- AAStringSet("LAAGKVEDSD")

cleave(gaju)
# AAStringSetList of length 1
# [["LAAGKVEDSD"]] LAAGK VEDSD

## Beta-enolase (UniProtKB/Swiss-Prot: ENOB_THUAL/P86978)
enob <- "SITKIKAREILD"

cleave(enob, "trypsin")
# $SITKIKAREILD
# [1] "SITK" "IK" "AR" "EILD"

cleave(enob, "trypsin", missedCleavages=2)
# $SITKIKAREILD
# [1] "SITKIKAR" "IKAREILD"

cleave(enob, "trypsin", missedCleavages=0:2)
# $SITKIKAREILD
# [1] "SITK" "IK" "AR" "EILD" "SITKIK" "IKAR"
# [7] "AREILD" "SITKIKAR" "IKAREILD"

## define own cleavage rule: cleave at K
cleave(enob, custom="K")
# $SITKIKAREILD
# [1] "SITK" "IK" "AREILD"

cleavageRanges(enob, custom="K")
# $SITKIKAREILD
#      start end
# [1,]    1  4
# [2,]    5  6
# [3,]    7 12

## define own cleavage rule: cleave at K but not if followed by A
cleave(enob, custom=c("K", "K(?=A)"))
# $SITKIKAREILD
# [1] "SITK" "IKAREILD"

cleavageRanges(enob, custom=c("K", "K(?=A)"))
# $SITKIKAREILD
#      start end

```

```
# [1,]    1  4
# [2,]    5 12

cleavageSites(enob, custom=c("K", "K(?=A)"))
# $SITKIKAREILD
# [1] 4
```



# Index

## \*Topic **methods**

cleave-methods, [2](#)

## \*Topic **package**

cleaver-package, [2](#)

AAString, [5](#), [6](#)

AAStringSet, [5](#), [6](#)

AAStringSetList, [5](#), [6](#)

cleavageRanges, [2](#)

cleavageRanges (cleave-methods), [2](#)

cleavageRanges, AAString-method  
(cleave-methods), [2](#)

cleavageRanges, AAStringSet-method  
(cleave-methods), [2](#)

cleavageRanges, character-method  
(cleave-methods), [2](#)

cleavageSites, [2](#)

cleavageSites (cleave-methods), [2](#)

cleavageSites, AAString-method  
(cleave-methods), [2](#)

cleavageSites, AAStringSet-method  
(cleave-methods), [2](#)

cleavageSites, character-method  
(cleave-methods), [2](#)

cleave, [2](#)

cleave (cleave-methods), [2](#)

cleave, AAString-method  
(cleave-methods), [2](#)

cleave, AAStringSet-method  
(cleave-methods), [2](#)

cleave, character-method  
(cleave-methods), [2](#)

cleave-methods, [2](#)

cleaver-package, [2](#)

gregexpr, [3](#)

IRanges, [5](#), [6](#)

IRangesList, [5](#), [6](#)