

Package ‘dittoSeq’

September 29, 2022

Type Package

Title User Friendly Single-Cell and Bulk RNA Sequencing Visualization

Version 1.8.1

Description A universal, user friendly, single-cell and bulk RNA sequencing visualization toolkit that allows highly customizable creation of color blindness friendly, publication-quality figures. dittoSeq accepts both SingleCellExperiment (SCE) and Seurat objects, as well as the import and usage, via conversion to an SCE, of SummarizedExperiment or DGEList bulk data. Visualizations include dimensionality reduction plots, heatmaps, scatterplots, percent composition or expression across groups, and more. Customizations range from size and title adjustments to automatic generation of annotations for heatmaps, overlay of trajectory analysis onto any dimensionality reduction plot, hidden data overlay upon cursor hovering via ggplotly conversion, and many more. All with simple, discrete inputs. Color blindness friendliness is powered by legend adjustments (enlarged keys), and by allowing the use of shapes or letter-overlay in addition to the carefully selected dittoColors().

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.2.0

Depends ggplot2

Imports methods, colorspace (>= 1.4), gridExtra, cowplot, reshape2, pheatmap, grDevices, ggrepel, ggridges, stats, utils, SummarizedExperiment, SingleCellExperiment, S4Vectors

Suggests plotly, testthat, Seurat (>= 2.2), DESeq2, edgeR, ggplot.multistats, knitr, rmarkdown, BiocStyle, scRNAseq, ggrastr (>= 0.2.0), ComplexHeatmap, bluster, scater, scan

biocViews Software, Visualization, RNASeq, SingleCell, GeneExpression, Transcriptomics, DataImport

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/dittoSeq>

git_branch RELEASE_3_15
git_last_commit fc99201
git_last_commit_date 2022-05-31
Date/Publication 2022-09-29
Author Daniel Bunis [aut, cre],
 Jared Andrews [aut, ctb]
Maintainer Daniel Bunis <daniel.bunis@ucsf.edu>

R topics documented:

addDimReduction	3
addPrcomp	4
Darken	5
demux.calls.summary	6
demux.SNP.summary	7
demuxlet.example	9
dittoBarPlot	10
dittoColors	14
dittoDimPlot	15
dittoDotPlot	24
dittoFreqPlot	29
dittoHeatmap	37
dittoHex	43
dittoPlot	52
dittoPlotVarsAcrossGroups	60
dittoScatterPlot	67
dittoSeq	74
gene	75
getGenes	76
getMetas	77
getReductions	78
importDemux	79
importDittoBulk	83
isBulk	86
isGene	87
isMeta	89
Lighten	90
meta	91
metaLevels	92
multi_dittoDimPlot	93
multi_dittoDimPlotVaryCells	95
multi_dittoPlot	98
setBulk	100
Simulate	101

addDimReduction	<i>Add any dimensionality reduction space to a SingleCellExperiment object containing bulk or single-cell data</i>
-----------------	--

Description

Add any dimensionality reduction space to a SingleCellExperiment object containing bulk or single-cell data

Usage

```
addDimReduction(object, embeddings, name, key = .gen_key(name))
```

Arguments

object	the bulk or single-cell SingleCellExperiment object to add the dimensionality reduction to. (dittoSeq utilizes the SingleCellExperiment object even for bulk data because it provides a convenient slots for all data that dittoSeq requires)
embeddings	a numeric matrix or matrix-like object, with number of rows equal to ncol(object), containing the coordinates of all cells / samples within the dimensionality reduction space.
name	String name for the reduction slot. Example: "pca". This will become the name of the slot, and what should be provided to the reduction.use input when making a dittoDimPlot . When the name given is the same as that of a slot that already exists inside the object, the previous slot is replaced with the newly provided data.
key	String, like "PC", which sets the default axes-label prefix when this reduction is used for making a dittoDimPlot . If nothing is provided, a key will be automatically generated.

Value

Outputs a [SingleCellExperiment](#) object with an added or replaced dimensionality reduction slot.

Author(s)

Daniel Bunis

See Also

[addPrcomp](#) for a prcomp specific PCA import wrapper

[importDittoBulk](#) for initial import of bulk RNAseq data into dittoSeq as a [SingleCellExperiment](#).

[dittoDimPlot](#) for visualizing how samples group within added dimensionality reduction spaces

Examples

```

example("importDittoBulk", echo = FALSE)

# Calculate PCA
# NOTE: This is typically not done with all genes in the dataset.
# The inclusion of this example code is not an endorsement of a particular
# method of PCA. Consult yourself, a bioinformatician, or literature for
# tips on proper techniques.
embeds <- prcomp(t(logcounts(myRNA)), center = TRUE, scale = TRUE)$x

myRNA <- addDimReduction(
  object = myRNA,
  embeddings = embeds,
  name = "pca",
  key = "PC")

# Visualize conditions metadata on a PCA plot
dittoDimPlot(myRNA, "conditions", reduction.use = "pca", size = 3)

```

addPrcomp	<i>Add a prcomp pca calculation to a SingleCellExperiment object containing bulk or single-cell data</i>
-----------	--

Description

Add a prcomp pca calculation to a SingleCellExperiment object containing bulk or single-cell data

Usage

```
addPrcomp(object, prcomp, name = "pca", key = "PC")
```

Arguments

object	the SingleCellExperiment object.
prcomp	a prcomp output which will be added to the object
name	String name for the reduction slot. Normally, this will be "pca", but you can hold any number of PCA calculations so long as a unique name is given to each. This will become the name of the slot and what should be provided to the reduction.use input when making a dittoDimPlot . When the name given is the same as that of a slot that already exists inside the object, the previous slot is replaced with the newly provided data.
key	String, like "PC", which sets the default axes-label prefix when this reduction is used for making a dittoDimPlot

Value

Outputs an [SingleCellExperiment](#) object with an added or replaced pca reduction slot.

Author(s)

Daniel Bunis

See Also

[addDimReduction](#) for adding other types of dimensionality reductions
[importDittoBulk](#) for initial import of bulk RNAseq data into dittoSeq as a [SingleCellExperiment](#).
[dittoDimPlot](#) for visualizing how samples group within added dimensionality reduction spaces

Examples

```
example("importDittoBulk", echo = FALSE)

# Calculate PCA with prcomp
# NOTE: This is typically not done with all genes in a dataset.
# The inclusion of this example code is not an endorsement of a particular
# method of PCA. Consult yourself, a bioinformatician, or literature for
# tips on proper techniques.
calc <- prcomp(t(logcounts(myRNA)), center = TRUE, scale = TRUE)

myRNA <- addPrcomp(
  object = myRNA,
  prcomp = calc)

# Now we can visualize conditions metadata on a PCA plot
dittoDimPlot(myRNA, "conditions", reduction.use = "pca", size = 3)
```

 Darken

Darkens input colors by a set amount

Description

A wrapper for the `darken` function of the `colorspace` package.

Usage

```
Darken(colors, percent.change = 0.25, relative = TRUE)
```

Arguments

`colors` the color(s) input. Can be a list of colors, for example, `/codedittoColors()`.
`percent.change` # between 0 and 1. the percentage to darken by. Defaults to 0.25 if not given.
`relative` TRUE/FALSE. Whether the percentage should be a relative change versus an absolute one. Default = TRUE.

Value

Return a darkened version of the color in hexadecimal color form (`"#RRGGBB"` in base 16)

Author(s)

Daniel Bunis

Examples

```
Darken("blue") #"blue" = "#0000FF"
#Output: "#0000BF"
Darken(dittoColors()[1:8]) #Works for multiple color inputs as well.
```

demux.calls.summary *Plots the number of annotations per sample, per lane*

Description

Plots the number of annotations per sample, per lane

Usage

```
demux.calls.summary(
  object,
  singlets.only = FALSE,
  main = "Sample Annotations by Lane",
  sub = NULL,
  ylab = "Annotations",
  xlab = "Sample",
  color = dittoColors()[2],
  theme = NULL,
  rotate.labels = TRUE,
  data.out = FALSE
)
```

Arguments

object	A Seurat or SingleCellExperiment object
singlets.only	Whether to only show data for cells called as singlets by demuxlet. Default is TRUE. Note: if doublets are included, only one of their sample calls will be used.
main	plot title. Default = "Sample Annotations by Lane"
sub	plot subtitle
ylab	y axis label, default is "Annotations"
xlab	x axis label, default is "Sample"
color	bars color. Default is the dittoColors skyBlue.
theme	A complete ggplot theme. Default is a slightly modified theme_bw().
rotate.labels	whether sample names / x-axis labels should be rotated or not. Default is TRUE.
data.out	Logical, whether underlying data for the plot should be output instead of the plot itself.

Value

A faceted ggplot summarizing how many cells in each lane were anotated to each sample. Assumes that the Sample calls of each cell, and which lane each cell belonged to, are stored in 'Sample' and 'Lane' metadata slots, respectively, as would be the case if demuxlet information was imported with [importDemux](#).

Alternatively, value will be a data.frame containing the underlying data if data.out = TRUE is provided.

Author(s)

Daniel Bunis

See Also

[demux.SNP.summary](#) for plotting the number of SNPs measured per cell. This is the other Demuxlet-associated QC visualization included with dittoSeq.

[importDemux](#), for how to import relevant demuxlet information as metadata.

Kang et al. Nature Biotechnology, 2018 <https://www.nature.com/articles/nbt.4042> for more information about the demuxlet cell-sample deconvolution method.

Examples

```
example(importDemux, echo = FALSE)

demux.calls.summary(myRNA)

# Exclude doublets by setting 'singlets only = TRUE'
demux.calls.summary(myRNA,
  singlets.only = TRUE)

# To return the underlying data.frame
demux.calls.summary(myRNA, data.out = TRUE)
```

demux.SNP.summary *Plots the number of SNPs sequenced per droplet*

Description

Plots the number of SNPs sequenced per droplet

Usage

```
demux.SNP.summary(
  object,
  group.by = "Lane",
  color.by = group.by,
  plots = c("jitter", "boxplot"),
  boxplot.color = "grey30",
  add.line = 50,
  min = 0,
  ...
)
```

Arguments

<code>object</code>	A Seurat or SingleCellExperiment object
<code>group.by</code>	String "name" of a metadata to use for grouping values. Default is "Lane".
<code>color.by</code>	String "name" of a metadata to use for coloring. Default is whatever was provided to <code>group.by</code> .
<code>plots</code>	String vector which sets the types of plots to include: possibilities = "jitter", "boxplot", "vlnplot", "ridgeplot". NOTE: The order matters, so use <code>c("back", "middle", "front")</code> when inputting multiple to put them in the order you want.
<code>boxplot.color</code>	The color of the lines of the boxplot.
<code>add.line</code>	numeric value(s) where a dashed horizontal line should go. Default = 50, a high confidence minimum number of SNPs per cell for highly accurate demuxlet sample deconvolution.
<code>min</code>	numeric value which sets the minimum value shown on the y-axis.
<code>...</code>	extra arguments passed to <code>dittoPlot</code>

Details

This function is a wrapper that essentially runs `dittoPlot("demux.N.SNP")` with a few modified defaults. The altered defaults:

- Data is grouped and colored by the "Lane" metadata (unless `group.by` or `color.by` are adjusted otherwise).
- Data is displayed as boxplots with gray lines on top of dots for individual cells (unless `plots` or `boxplot.color` are adjusted otherwise).
- The plot is set to have minimum y axis value of zero (unless `min` is adjusted otherwise).
- A dashed line is added at the value 50, a very conservative minimum number of SNPs for high confidence sample calls (unless `add.line` is adjusted otherwise).

Value

A ggplot, made with `dittoPlot` showing a summary of how many SNPs were available to Demuxlet for each cell of a dataset.

Alternatively, a plotly object if `data.hover = TRUE` is provided.

Alternatively, list containing a ggplot and the underlying data as a dataframe if `data.out = TRUE` is provided.

Author(s)

Daniel Bunis

See Also

[demux.calls.summary](#) for plotting the number of sample annotations assigned within each lane. This is the other Demuxlet-associated QC visualization included with dittoSeq.

[dittoPlot](#), as `demux.SNP.summary` is essentially just a dittoPlot wrapper.

[importDemux](#), for how to import relevant demuxlet information as metadata.

Kang et al. Nature Biotechnology, 2018 <https://www.nature.com/articles/nbt.4042> for more information about the demuxlet cell-sample deconvolution method.

Examples

```
example(importDemux, echo = FALSE)
demux.SNP.summary(myRNA)

#Function wraps dittoPlot. See dittoPlot docs for more examples
```

demuxlet.example *demuxlet.example*

Description

A dataframe containing mock demuxlet information for the 80-cell Seurat::pbmc_small dataset

Usage

```
demuxlet.example
```

Format

An object of class `data.frame` with 80 rows and 7 columns.

Details

This data was created based on the structure of real demuxlet.best output files. Barcodes from Seurat's pbmc_small example data were used as the BARCODES column. Cells were then assigned randomly as either SNG (singlets), DBL (doublets), or AMB (ambiguous). Cells were then randomly assign to sample1-10 (or multiple samples for doublets), and this information was combined using the paste function into the typical structure of a demuxlet CALL column. Random sampling of remaining data from a separate, actual, demuxlet dataset was used for remaining columns.

Value

A dataframe

Note

This is a slightly simplified example. Real demuxlet.best data has additional columns.

Author(s)

Daniel Bunis

dittoBarPlot	<i>Outputs a stacked bar plot to show the percent composition of samples, groups, clusters, or other groupings</i>
--------------	--

Description

Outputs a stacked bar plot to show the percent composition of samples, groups, clusters, or other groupings

Usage

```
dittoBarPlot(  
  object,  
  var,  
  group.by,  
  scale = c("percent", "count"),  
  split.by = NULL,  
  cells.use = NULL,  
  retain.factor.levels = FALSE,  
  data.out = FALSE,  
  do.hover = FALSE,  
  color.panel = dittoColors(),  
  colors = seq_along(color.panel),  
  split.nrow = NULL,  
  split.ncol = NULL,  
  split.adjust = list(),  
  y.breaks = NA,  
  min = 0,  
  max = NULL,  
  var.labels.rename = NULL,  
  var.labels.reorder = NULL,  
  x.labels = NULL,  
  x.labels.rotate = TRUE,  
  x.reorder = NULL,  
  theme = theme_classic(),  
  xlab = group.by,
```

```

  ylab = "make",
  main = "make",
  sub = NULL,
  legend.show = TRUE,
  legend.title = NULL
)

```

Arguments

<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>var</code>	String name of a metadata that contains discrete data, or a factor or vector containing such data for all cells/samples in the target object.
<code>group.by</code>	String name of a metadata to use for separating the cells/samples into discrete groups.
<code>scale</code>	"count" or "percent". Sets whether data should be shown as counts versus percentage.
<code>split.by</code>	1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with ggplot faceting. When 2 metadatas are named, <code>c(row,col)</code> , the first is used as rows and the second is used for columns of the resulting grid. When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code>
<code>cells.use</code>	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include. Note: When <code>cells.use</code> is combined with <code>scale = "percent"</code> , left out cells are not considered in calculating percentages. Percents will always total to 1.
<code>retain.factor.levels</code>	Logical which controls whether factor identities of <code>var</code> and <code>group.by</code> data should be respected. Set to TRUE to faithfully reflect ordering of groupings encoded in factor levels, but Note that this will also force retention of groupings that could otherwise be removed via <code>cells.use</code> .
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot ("p") and a data.frame ("data") containing the underlying data.
<code>do.hover</code>	Logical which sets whether the ggplot output should be converted to a ggplotly object with data about individual bars displayed when you hover your cursor over them.
<code>color.panel</code>	String vector which sets the colors to draw from. <code>dittoColors()</code> by default.
<code>colors</code>	Integer vector, which sets the indexes / order, of colors from <code>color.panel</code> to actually use. (Provides an alternative to directly modifying <code>color.panel</code> .)
<code>split.nrow</code> , <code>split.ncol</code>	Integers which set the dimensions of faceting/splitting when a single metadata is given to <code>split.by</code> .

<code>split.adjust</code>	<p>A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code>.</p> <p>For options, when giving 1 metadata to <code>split.by</code>, see facet_wrap, OR when giving 2 metadatas to <code>split.by</code>, see facet_grid.</p>
<code>y.breaks</code>	Numeric vector which sets the plot's tick marks / major gridlines. <code>c(break1,break2,break3,etc.)</code>
<code>min, max</code>	Scalars which control the zoom of the plot. These inputs set the minimum / maximum values of the y-axis. Default = set based on the limits of the data, 0 to 1 for <code>scale = "percent"</code> , or 0 to maximum count for <code>scale = "count"</code> .
<code>var.labels.rename</code>	<p>String vector for renaming the distinct identities of <code>var</code> values.</p> <p>Hint: use metaLevels or <code>unique(<var-data>)</code> to assess current values.</p>
<code>var.labels.reorder</code>	<p>Integer vector. A sequence of numbers, from 1 to the number of distinct <code>var</code> value identities, for rearranging the order of labels' groupings within the plot.</p> <p>Method: Make a first plot without this input. Then, treating the top-most grouping as index 1, and the bottom-most as index n. Values of <code>var.labels.reorder</code> should be these indices, but in the order that you would like them rearranged to be.</p>
<code>x.labels</code>	String vector which will replace the x-axis groupings' labels. Regardless of <code>x.reorder</code> , the first component of <code>x.labels</code> sets the name for the left-most x-axis grouping.
<code>x.labels.rotate</code>	Logical which sets whether the x-axis grouping labels should be rotated.
<code>x.reorder</code>	<p>Integer vector. A sequence of numbers, from 1 to the number of groupings, for rearranging the order of x-axis groupings.</p> <p>Method: Make a first plot without this input. Then, treating the leftmost grouping as index 1, and the rightmost as index n. Values of <code>x.reorder</code> should be these indices, but in the order that you would like them rearranged to be.</p> <p>Recommendation for advanced users: If you find yourself coming back to this input too many times, an alternative solution that can be easier long-term is to make the target data into a factor, and to put its levels in the desired order: <code>factor(data, levels = c("level1", "level2", ...))</code>. metaLevels can be used to quickly get the identities that need to be part of this 'levels' input.</p>
<code>theme</code>	A ggplot theme which will be applied before <code>dittoSeq</code> adjustments. Default = <code>theme_classic()</code> . See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
<code>xlab</code>	String which sets the x-axis title. Default is <code>group.by</code> so it defaults to the name of the grouping information. Set to <code>NULL</code> to remove.
<code>ylab</code>	String which sets the y-axis title. Default = "make" and if left as make, a title will be automatically generated.
<code>main</code>	String, sets the plot title
<code>sub</code>	String, sets the plot subtitle
<code>legend.show</code>	Logical which sets whether the legend should be displayed.
<code>legend.title</code>	String which adds a title to the legend.

Details

The function creates a dataframe containing counts and percent makeup of var identities for each x-axis grouping (determined by the `group.by` input). If a set of cells/samples to use is indicated with the `cells.use` input, only those cells/samples are used for counts and percent makeup calculations. Then, a vertical bar plot is generated (`ggplot2::geom_col()`) showing either percent makeup if `scale = "percent"`, which is the default, or raw counts if `scale = "count"`.

Value

A `ggplot` plot where discrete data, grouped by sample, condition, cluster, etc. on the x-axis, is shown on the y-axis as either counts or percent-of-total-per-grouping in a stacked barplot.

Alternatively, if `data.out = TRUE`, a list containing the plot ("p") and a dataframe of the underlying data ("data").

Alternatively, if `do.hover = TRUE`, a `plotly` conversion of the `ggplot` output in which underlying data can be retrieved upon hovering the cursor over the plot.

Many characteristics of the plot can be adjusted using discrete inputs

- Colors can be adjusted with `color.panel` and/or `colors`.
- y-axis zoom and tick marks can be adjusted using `min`, `max`, and `y.breaks`.
- Titles can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.title` arguments.
- The legend can be removed by setting `legend.show = FALSE`.
- x-axis labels and groupings can be changed / reordered using `x.labels` and `x.reorder`, and rotation of these labels can be turned off with `x.labels.rotate = FALSE`.
- y-axis var-group labels and their order can be changed / reordered using `var.labels` and `var.labels.reorder`.

Author(s)

Daniel Bunis

See Also

[dittoFreqPlot](#) for a data representation that focuses on pre-sample frequencies of each the var-data values individually, rather than emphasizing total makeup of samples/groups.

Examples

```
example(importDittoBulk, echo = FALSE)
myRNA

dittoBarPlot(myRNA, "clustering", group.by = "groups")
dittoBarPlot(myRNA, "clustering", group.by = "groups",
  scale = "count")

# Reordering the x-axis groupings to have "C" (#3) come first
dittoBarPlot(myRNA, "clustering", group.by = "groups",
  x.reorder = c(3,1,2,4))
```

```

### Accessing underlying data:
# as dataframe
dittoBarPlot(myRNA, "clustering", group.by = "groups",
  data.out = TRUE)
# through hovering the cursor over the relevant parts of the plot
if (requireNamespace("plotly", quietly = TRUE)) {
  dittoBarPlot(myRNA, "clustering", group.by = "groups",
    do.hover = TRUE)
}

### Previous Version Compatibility
# Mistakenly, dittoBarPlot used to remove factor identities entirely from the
# data it used. This manifests as ignorance of a user's set orderings for
# their data. That is no longer done by default, but to recreate old plots,
# restoring this behavior can be achieved with 'retain.factor.levels = FALSE'
# Set factor level ordering for a metadata we'll give to 'group.by'
myRNA$groups_reverse_levels <- factor(
  myRNA$groups,
  levels = c("D", "C", "B", "A"))
# dittoBarPlot will now respect this level order by default.
dittoBarPlot(myRNA, "clustering", group.by = "groups_reverse_levels")
# But that respect can be turned off...
dittoBarPlot(myRNA, "clustering", group.by = "groups_reverse_levels",
  retain.factor.levels = FALSE)

```

dittoColors

Extracts the dittoSeq default colors

Description

Creates a string vector of 40 unique colors, in hexadecimal form, repeated 100 times. Or, if `get.names` is set to `TRUE`, outputs the names of the colors which can be helpful as reference when adjusting how colors get used.

These colors are a modification of the protanope and deuteranope friendly colors from Wong, B. Nature Methods, 2011.

Truly, only the first 1-7 are maximally (red-green) color-blindness friendly, but the lightened and darkened versions (plus grey) in slots 8-40 still work relatively well at extending their utility further. Note that past 40, the colors simply repeat in order to most easily allow dittoSeq visualizations to handle situations requiring even more colors.

The colors are:

1-7 = Suggested color panel from Wong, B. Nature Methods, 2011, minus black

- 1- orange = "#E69F00"
- 2- skyBlue = "#56B4E9"
- 3- bluishGreen = "#009E73"

- 4- yellow = "#F0E442"
- 5- blue = "#0072B2"
- 6- vermilion = "#D55E00"
- 7- reddishPurple = "#CC79A7"

8 = gray40

9-16 = 25% darker versions of colors 1-8

17-24 = 25% lighter versions of colors 1-8

25-32 = 40% lighter versions of colors 1-8

33-40 = 40% darker versions of colors 1-8

Usage

```
dittoColors(reps = 100, get.names = FALSE)
```

Arguments

reps	Integer which sets how many times the original set of colors should be repeated
get.names	Logical, whether only the names of the default dittoSeq color panel should be returned instead

Value

A string vector with length = 24.

Author(s)

Daniel Bunis

Examples

```
dittoColors()  
  
#To retrieve names:  
dittoColors(get.names = TRUE)
```

dittoDimPlot

Shows data overlaid on a tsne, pca, or similar type of plot

Description

Shows data overlaid on a tsne, pca, or similar type of plot

Usage

```
dittoDimPlot(
  object,
  var,
  reduction.use = .default_reduction(object),
  size = 1,
  opacity = 1,
  dim.1 = 1,
  dim.2 = 2,
  cells.use = NULL,
  shape.by = NULL,
  split.by = NULL,
  split.adjust = list(),
  extra.vars = NULL,
  show.others = TRUE,
  split.show.all.others = TRUE,
  split.nrow = NULL,
  split.ncol = NULL,
  assay = .default_assay(object),
  slot = .default_slot(object),
  adjustment = NULL,
  swap.rownames = NULL,
  color.panel = dittoColors(),
  colors = seq_along(color.panel),
  shape.panel = c(16, 15, 17, 23, 25, 8),
  min.color = "#F0E442",
  max.color = "#0072B2",
  min = NULL,
  max = NULL,
  order = c("unordered", "increasing", "decreasing", "randomize"),
  main = "make",
  sub = NULL,
  xlab = "make",
  ylab = "make",
  rename.var.groups = NULL,
  rename.shape.groups = NULL,
  theme = theme_bw(),
  show.axes.numbers = TRUE,
  show.grid.lines = if (is.character(reduction.use)) {
    !grepl("umap|tsne",
           tolower(reduction.use))
  } else {
    TRUE
  },
),
do.letter = FALSE,
do.ellipse = FALSE,
do.label = FALSE,
labels.size = 5,
```



```

labels.highlight = TRUE,
labels.repel = TRUE,
labels.split.by = split.by,
do.hover = FALSE,
hover.data = var,
hover.assay = .default_assay(object),
hover.slot = .default_slot(object),
hover.adjustment = NULL,
add.trajectory.lineages = NULL,
add.trajectory.curves = NULL,
trajectory.cluster.meta,
trajectory.arrow.size = 0.15,
do.contour = FALSE,
contour.color = "black",
contour.linetype = 1,
legend.show = TRUE,
legend.size = 5,
legend.title = "make",
legend.breaks = waiver(),
legend.breaks.labels = waiver(),
shape.legend.size = 5,
shape.legend.title = shape.by,
do.raster = FALSE,
raster.dpi = 300,
data.out = FALSE
)

```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
var	String name of a "gene" or "metadata" (or "ident" for a Seurat object) to use for coloring the plots. This is the data that will be displayed for each cell/sample. Discrete or continuous data both work. Alternatively, can be a vector of same length as there are cells/samples in the object.
reduction.use	String, such as "pca", "tsne", "umap", or "PCA", etc, which is the name of a dimensionality reduction slot within the object, and which sets what dimensionality reduction space within the object to use. Default = the first dimensionality reduction slot inside the object with "umap", "tsne", or "pca" within its name, (priority: UMAP > t-SNE > PCA) or the first dimensionality reduction slot if none of those exist. Alternatively, a matrix (or data.frame) containing the dimensionality reduction embeddings themselves. The matrix should have as many rows as there are cells/samples in the object. Note that dim.1 and dim.2 will still be used to select which columns to pull from, and column names will serve as the default xlab & ylab.
size	Number which sets the size of data points. Default = 1.

<code>opacity</code>	Number between 0 and 1. Great for when you have MANY overlapping points, this sets how solid the points should be: 1 = not see-through at all. 0 = invisible. Default = 1. (In terms of typical ggplot variables, = alpha)
<code>dim.1</code>	The component number to use on the x-axis. Default = 1
<code>dim.2</code>	The component number to use on the y-axis. Default = 2
<code>cells.use</code>	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
<code>shape.by</code>	Variable for setting the shape of cells/samples in the plot. Note: must be discrete. Can be the name of a gene or meta-data. Alternatively, can be "ident" for clusters of a Seurat object. Alternatively, can be a numeric of length equal to the total number of cells/samples in object. Note: shapes can be harder to see, and to process mentally, than colors. Even as a color blind person myself writing this code, I recommend use of colors for variables with many discrete values.
<code>split.by</code>	1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with ggplot faceting. When 2 metadatas are named, <code>c(row,col)</code> , the first is used as rows and the second is used for columns of the resulting grid. When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code>
<code>split.adjust</code>	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code> . For options, when giving 1 metadata to <code>split.by</code> , see facet_wrap , OR when giving 2 metadatas to <code>split.by</code> , see facet_grid .
<code>extra.vars</code>	String vector providing names of any extra metadata to be stashed in the dataframe supplied to <code>ggplot(data)</code> . Useful for making custom splitting/faceting or other additional alterations <i>after</i> dittoSeq plot generation.
<code>show.others</code>	Logical. Whether other cells should be shown in the background in light gray. Default = TRUE.
<code>split.show.all.others</code>	Logical which sets whether gray "others" cells of facets should include all cells of other facets (TRUE) versus just cells left out by <code>cell.use</code> (FALSE).
<code>split.nrow, split.ncol</code>	Integers which set the dimensions of faceting/splitting when a single metadata is given to <code>split.by</code> .
<code>assay, slot</code>	single strings or integer that set which data to use when plotting gene expression. See gene for more information.
<code>adjustment</code>	When plotting gene expression (or antibody, or other forms of counts data), should that data be used directly (default) or should it be adjusted to be <ul style="list-style-type: none"> "z-score": scaled with the <code>scale()</code> function to produce a relative-to-mean z-score representation

- "relative.to.max": divided by the maximum expression value to give percent of max values between [0,1]

swap.rownames	String. For SummarizedExperiment or SingleCellExperiment objects, the column name of rowData(object) to be used to identify features instead of rownames(object).
color.panel	String vector which sets the colors to draw from. dittoColors() by default, see dittoColors for contents.
colors	Integer vector, the indexes / order, of colors from color.panel to actually use. Useful for quickly swapping the colors of nearby clusters.
shape.panel	Vector of integers corresponding to ggplot shapes which sets what shapes to use. When discrete groupings are supplied by shape.by, this sets the panel of shapes. When nothing is supplied to shape.by, only the first value is used. Default is a set of 6, c(16, 15, 17, 23, 25, 8), the first being a simple, solid, circle. Note: Unfortunately, shapes can be hard to see when points are on top of each other & they are more slowly processed by the brain. For these reasons, even as a color blind person myself writing this code, I recommend use of colors for variables with many discrete values.
min.color	color for lowest values of var/min. Default = yellow
max.color	color for highest values of var/max. Default = blue
min	Number which sets the value associated with the minimum color.
max	Number which sets the value associated with the maximum color.
order	String. If the data should be plotted based on the order of the color data, sets whether to plot (from back to front) in "increasing", "decreasing", "randomize" order. If left as "unordered", plot order is simply based on the order of cells within the object.
main	String, sets the plot title. Default title is automatically generated if not given a specific value. To remove, set to NULL.
sub	String, sets the plot subtitle
xlab, ylab	Strings which set the labels for the axes. Default labels are generated if you do not give this a specific value. To remove, set to NULL.
rename.var.groups	String vector which sets new names for the identities of var groups.
rename.shape.groups	String vector which sets new names for the identities of shape.by groups.
theme	A ggplot theme which will be applied before dittoSeq adjustments. Default = theme_bw(). See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
show.axes.numbers	Logical which controls whether the axes values should be displayed.
show.grid.lines	Logical which sets whether gridlines of the plot should be shown. They are removed when set to FALSE. Default = FALSE for umap and tsne reduction.use, TRUE otherwise.

<code>do.letter</code>	Logical which sets whether letters should be added on top of the colored dots. For extended colorblindness compatibility. NOTE: <code>do.letter</code> is ignored if <code>do.hover = TRUE</code> or <code>shape.by</code> is provided a metadata because lettering is incompatible with plotly and with changing the dots' to be different shapes.
<code>do.ellipse</code>	Logical. Whether the groups should be surrounded by median-centered ellipses.
<code>do.label</code>	Logical. Whether to add text labels near the center (median) of clusters for grouping vars.
<code>labels.size</code>	Size of the the labels text
<code>labels.highlight</code>	Logical. Whether the labels should have a box behind them
<code>labels.repel</code>	Logical, that sets whether the labels' placements will be adjusted with ggrepel to avoid intersections between labels and plot bounds. TRUE by default.
<code>labels.split.by</code>	String of one or two metadata names which controls the facet-split calculations for label placements. Defaults to <code>split.by</code> , so generally there is no need to adjust this except when you are utilizing the <code>extra.vars</code> input to achieve manual faceting control.
<code>do.hover</code>	Logical which controls whether the output will be converted to a plotly object so that data about individual points will be displayed when you hover your cursor over them. <code>hover.data</code> argument is used to determine what data to use.
<code>hover.data</code>	String vector of gene and metadata names, example: <code>c("meta1", "gene1", "meta2")</code> which determines what data to show on hover when <code>do.hover</code> is set to TRUE.
<code>hover.assay</code> , <code>hover.slot</code> , <code>hover.adjustment</code>	Similar to the non-hover versions of these inputs, when showing expression data upon hover, these set what data will be shown.
<code>add.trajectory.lineages</code>	List of vectors representing trajectory paths, each from start-cluster to end-cluster, where vector contents are the names of clusters provided in the <code>trajectory.cluster.meta</code> input. If the slingshot package was used for trajectory analysis, you can provide <code>add.trajectory.lineages = slingLineages('object')</code> .
<code>add.trajectory.curves</code>	List of matrices, each representing coordinates for a trajectory path, from start to end, where matrix columns represent x (<code>dim.1</code>) and y (<code>dim.2</code>) coordinates of the paths. Alternatively, a list of lists(/princurve objects) can be provided. Thus, if the slingshot package was used for trajectory analysis, you can provide <code>add.trajectory.curves = slingCurves('object')</code>
<code>trajectory.cluster.meta</code>	String name of metadata containing the clusters that were used for generating trajectories. Required when plotting trajectories using the <code>add.trajectory.lineages</code> method. Names of clusters inside the metadata should be the same as the contents of <code>add.trajectory.lineages</code> vectors.
<code>trajectory.arrow.size</code>	Number representing the size of trajectory arrows, in inches. Default = 0.15.

<code>do.contour</code>	Logical. Whether density-based contours should be displayed.
<code>contour.color</code>	String that sets the color(s) of the <code>do.contour</code> contours.
<code>contour.linetype</code>	String or numeric which sets the type of line used for <code>do.contour</code> contours. Defaults to "solid", but see linetype for other options.
<code>legend.show</code>	Logical. Whether the legend should be displayed. Default = TRUE.
<code>legend.size</code>	Number representing the size at which color legend shapes should be plotted (for discrete variable plotting) in the color legend. Default = 5. *Enlarging the colors legend is incredibly helpful for making colors more distinguishable by color blind individuals.
<code>legend.title</code>	String which sets the title for the color legend. Default = NULL normally, but var when a shape legend will also be shown.
<code>legend.breaks</code>	Numeric vector which sets the discrete values to show in the color-scale legend for continuous data.
<code>legend.breaks.labels</code>	String vector, with same length as <code>legend.breaks</code> , which renames what's displayed next to the tick marks of the color-scale.
<code>shape.legend.size</code>	Number representing the size at which shapes should be plotted in the shape legend.
<code>shape.legend.title</code>	String which sets the title of the shapes legend. Default is <code>shape.by</code>
<code>do.raster</code>	Logical. When set to TRUE, rasterizes the internal plot area. Useful for editing in external programs (e.g. Illustrator).
<code>raster.dpi</code>	Number indicating dpi to use for rasterization. Default = 300.
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot ("p"), a data.frame containing the underlying data for target cells ("Target_data"), and a data.frame containing the underlying data for non-target cells ("Others_data").

Details

The function creates a dataframe containing the metadata or expression data associated with the given `var` (or if a vector of data is provided directly, it just uses that), plus X and Y coordinates data determined by the `reduction.use` and `dim.1` (x-axis) and `dim.2` (y-axis) inputs. Any extra data requested with `shape.by`, `split.by` or `extra.var` is added as well. For expression/counts data, `assay`, `slot`, and `adjustment` inputs can be used to change which data is used, and if it should be adjusted in some way.

Next, if a set of cells or samples to use is indicated with the `cells.use` input, then the dataframe is split into `Target_data` and `Others_data` based on subsetting by the target cells/samples.

Finally, a scatter plot is then created using these dataframes where non-target cells will be displayed in gray if `show.others=TRUE`, and target cell data is displayed on top, colored based on the `var`-associated data, and with shapes determined by the `shape.by`-associated data. If `split.by` was used, the plot will be split into a matrix of panels based on the associated groupings.

Value

A ggplot or plotly object where colored dots (or other shapes) are overlaid onto a tSNE, PCA, UMAP, ..., plot of choice.

Alternatively, if `data.out=TRUE`, a list containing three slots is output: the plot (named 'p'), a `data.table` containing the underlying data for target cells (named 'Target_data'), and a `data.table` containing the underlying data for non-target cells (named 'Others_data').

Alternatively, if `do.hover` is set to `TRUE`, the plot is converted from ggplot to plotly & cell/sample information, determined by the `hover.data` input, is retrieved, added to the dataframe, and displayed upon hovering the cursor over the plot.

Many characteristics of the plot can be adjusted using discrete inputs

- size and opacity can be used to adjust the size and transparency of the data points.
- Color can be adjusted with `color.panel` and/or `colors` for discrete data, or `min.color`, `max.color`, and `min.color` for continuous data.
- Shapes can be adjusted with `shape.panel`.
- Color and shape labels can be changed using `rename.var.groups` and `rename.shape.groups`.
- Titles and axes labels can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.title` arguments.
- Legends can also be adjusted in other ways, using variables that all start with "legend." for easy tab-completion lookup.

Additional Features

Many other tweaks and features can be added as well. Each is accessible through 'tab' autocompletion starting with "do.---" or "add.---", and if additional inputs are involved in implementing or tweaking these, the associated inputs will start with the "---.":

- If `do.label` is set to `TRUE`, labels will be added based on median centers of the discrete var-data groupings. The size of the text in the labels can be adjusted using the `labels.size` input. By default labels will repel each other and the bounds of the plot, and labels will be highlighted with a white background. Either of these can be turned off by setting `labels.repel = FALSE` or `labels.highlight = FALSE`,
- If `do.ellipse` is set to `TRUE`, ellipses will be added to highlight distinct var-data groups' positions based on median positions of their cell/sample components.
- If `do.contour` is provided, density gradient contour lines will be overlaid with color and `linetype` adjustable via `contour.color` and `contour.linetype`.
- If `add.trajectory.lineages` is provided a list of vectors (each vector being cluster names from start-cluster-name to end-cluster-name), and a metadata name pointing to the relevant clustering information is provided to `trajectory.cluster.meta`, then median centers of the clusters will be calculated and arrows will be overlaid to show trajectory inference paths in the current dimensionality reduction space.
- If `add.trajectory.curves` is provided a list of matrices (each matrix containing x, y coordinates from start to end), paths and arrows will be overlaid to show trajectory inference curves in the current dimensionality reduction space. Arrow size is controlled with the `trajectory.arrow.size` input.

Author(s)

Daniel Bunis and Jared Andrews

See Also

[getGenes](#) and [getMetas](#) to see what the `var`, `split.by`, etc. options are of an object.

[getReductions](#) to see what the `reduction.use` options are of an object.

[importDittoBulk](#) for how to create a [SingleCellExperiment](#) object from bulk seq data that dittoSeq functions can use & [addDimReduction](#) for how to specifically add calculated dimensionality reductions that dittoDimPlot can utilize.

[dittoScatterPlot](#) for showing very similar data representations, but where genes or metadata are wanted as the axes.

[dittoDimHex](#) and [dittoScatterHex](#) for showing very similar data representations, but where nearby cells are summarized together in hexagonal bins.

[dittoPlot](#) for an alternative continuous data display method where data broken into discrete groupings is shown on a y- (or x-) axis.

[dittoBarPlot](#) for an alternative discrete data display and quantification method.

Examples

```
example(importDittoBulk, echo = FALSE)
myRNA

# Display discrete data:
dittoDimPlot(myRNA, "clustering")
# Display continuous data:
dittoDimPlot(myRNA, "gene1")

# To show currently set clustering for seurat objects, you can use "ident".
# To change the dimensional reduction type, use 'reduction.use'.
dittoDimPlot(myRNA, "clustering",
             reduction.use = "pca",
             dim.1 = 3,
             dim.2 = 4)

# Subset to certain cells with cells.use
dittoDimPlot(myRNA, "clustering",
             cells.us = !myRNA$SNP)

# Data can also be split in other ways with 'shape.by' or 'split.by'
dittoDimPlot(myRNA, "gene1",
             shape.by = "clustering",
             split.by = "SNP") # single split.by element
dittoDimPlot(myRNA, "gene1",
             split.by = c("groups", "SNP")) # row and col split.by elements

# Modify the look with intuitive inputs
dittoDimPlot(myRNA, "clustering",
             size = 2, opacity = 0.7, show.axes.numbers = FALSE,
```

```

ylab = NULL, xlab = "tSNE",
main = "Plot Title",
sub = "subtitle",
legend.title = "clustering")

# MANY additional tweaks are possible.
# Also, many extra features are easy to add as well:
dittoDimPlot(myRNA, "clustering",
  do.label = TRUE, do.ellipse = TRUE)
dittoDimPlot(myRNA, "clustering",
  do.label = TRUE, labels.highlight = FALSE, labels.size = 8)
if (requireNamespace("plotly", quietly = TRUE)) {
  dittoDimPlot(myRNA, "gene1", do.hover = TRUE,
    hover.data = c("gene2", "clustering", "timepoint"))
}
dittoDimPlot(myRNA, "gene1", add.trajectory.lineages = list(c(1,2,4), c(1,3)),
  trajectory.cluster.meta = "clustering",
  sub = "Pseudotime Trajectories")

dittoDimPlot(myRNA, "gene1",
  do.contour = TRUE,
  contour.color = "lightblue", # Optional, black by default
  contour.linetype = "dashed") # Optional, solid by default

# Plotting ordering can also be adjusted with 'order':
dittoDimPlot(myRNA, "timepoint", size = 20,
  order = "increasing")
dittoDimPlot(myRNA, "timepoint", size = 20,
  order = "decreasing")
dittoDimPlot(myRNA, "timepoint", size = 20,
  order = "randomize")

```

dittoDotPlot

Compact plotting of per group summaries for expression of multiple features

Description

Compact plotting of per group summaries for expression of multiple features

Usage

```

dittoDotPlot(
  object,
  vars,
  group.by,
  scale = TRUE,
  split.by = NULL,
  cells.use = NULL,

```



```

    size = 6,
    min.percent = 0.01,
    max.percent = NA,
    min.color = "grey90",
    max.color = "#C51B7D",
    min = "make",
    max = NULL,
    summary.fxn.color = function(x) {
      mean(x[x != 0])
    },
    summary.fxn.size = function(x) {
      mean(x != 0)
    },
    assay = .default_assay(object),
    slot = .default_slot(object),
    adjustment = NULL,
    swap.rownames = NULL,
    do.hover = FALSE,
    main = NULL,
    sub = NULL,
    ylab = group.by,
    y.labels = NULL,
    y.reorder = NULL,
    xlab = NULL,
    x.labels.rotate = TRUE,
    split.nrow = NULL,
    split.ncol = NULL,
    split.adjust = list(),
    theme = theme_classic(),
    legend.show = TRUE,
    legend.color.breaks = waiver(),
    legend.color.breaks.labels = waiver(),
    legend.color.title = "make",
    legend.size.title = "percent\nexpression",
    data.out = FALSE
  )

```

Arguments

<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>vars</code>	String vector (example: <code>c("gene1", "gene2", "gene3")</code>) which selects which variables, typically genes, to show.
<code>group.by</code>	String representing the name of a metadata to use for separating the cells/samples into discrete groups.
<code>scale</code>	String which sets whether the values shown with color (default: mean non-zero expression) should be centered and scaled.
<code>split.by</code>	1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with ggplot faceting.

	When 2 metadatas are named, <code>c(row,col)</code> , the first is used as rows and the second is used for columns of the resulting grid.
	When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code>
<code>cells.use</code>	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
<code>size</code>	Number which sets the dot size associated with the highest value shown by dot size (default: percent non-zero expression).
<code>min.percent</code> , <code>max.percent</code>	Numbers between 0 and 1 which sets the minimum and maximum percent expression to show. When set to NA, the minimum/maximum of the data are used.
<code>min.color</code> , <code>max.color</code>	colors to use for minimum and maximum color values. Default = light grey and purple.
<code>min</code> , <code>max</code>	Numbers which set the values associated with the minimum and maximum colors.
<code>summary.fxn.color</code> , <code>summary.fxn.size</code>	A function which sets how color or size will be used to summarize variables' data for each group. Any function can be used as long as it takes in a numeric vector and returns a single numeric value.
<code>assay</code> , <code>slot</code>	single strings or integer that set which data to use when plotting expression data. See gene for more information about how defaults for these are filled in when not provided.
<code>adjustment</code>	When plotting gene expression (or antibody, or other forms of counts data), should that data be adjusted altogether before <code>cells.use</code> subsetting and splitting into groups? <ul style="list-style-type: none"> • "relative.to.max": divided by the maximum expression value to give percent of max values between [0,1] • "z-score": centered and scaled to produce a relative-to-mean z-score representation • NULL: Default, no adjustment
<code>swap.rownames</code>	String. For SummarizedExperiment or SingleCellExperiment objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .
<code>do.hover</code>	Logical. Default = FALSE. If set to TRUE the object will be converted to an interactive plotly object in which underlying data for individual dots will be displayed when you hover your cursor over them.
<code>main</code>	String which sets the plot title.
<code>sub</code>	String which sets the plot subtitle.
<code>ylab</code>	String which sets the y/grouping-axis label. Default is <code>group.by</code> so it defaults to the name of the grouping information. Set to NULL to remove.

<code>y.labels</code>	String vector, <code>c("label1","label2","label3",...)</code> which overrides the names of the samples/groups.
<code>y.reorder</code>	Integer vector. A sequence of numbers, from 1 to the number of groupings, for rearranging the order of groupings. Method: Make a first plot without this input. Then, treating the bottom-most grouping as index 1, and the top-most as index n, values of <code>y.reorder</code> should be these indices, but in the order that you would like them rearranged to be. Recommendation for advanced users: If you find yourself coming back to this input too many times, an alternative solution that can be easier long-term is to make the target data into a factor, and to put its levels in the desired order: <code>factor(data, levels = c("level1", "level2", ...))</code> . <code>metaLevels</code> can be used to quickly get the identities that need to be part of this 'levels' input.
<code>xlab</code>	String which sets the x/var-axis label. Set to NULL to remove.
<code>x.labels.rotate</code>	Logical which sets whether the var-labels should be rotated.
<code>split.nrow, split.ncol</code>	Integers which set the dimensions of faceting/splitting when a single metadata is given to <code>split.by</code> .
<code>split.adjust</code>	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code> . For options, when giving 1 metadata to <code>split.by</code> , see facet_wrap , OR when giving 2 metadatas to <code>split.by</code> , see facet_grid .
<code>theme</code>	A ggplot theme which will be applied before dittoSeq adjustments. Default = <code>theme_classic()</code> . See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
<code>legend.show</code>	Logical. Whether the legend should be displayed. Default = TRUE.
<code>legend.color.breaks</code>	Numeric vector which sets the discrete values to label in the color-scale legend for continuous data.
<code>legend.color.breaks.labels</code>	String vector, with same length as <code>legend.breaks</code> , which sets the labels for the tick marks of the color-scale.
<code>legend.color.title, legend.size.title</code>	String or NULL, sets the title displayed above legend keys.
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot (p) and data (data).

Details

This function will output a compact summary of expression of multiple genes, or of values of multiple numeric metadata, across cell/sample groups (clusters, sample identity, conditions, etc.), where dot-size and dot-color are used to reflect distinct features of the data. Typically, and by default, size will reflect the percent of non-zero values, and color will reflect the mean of non-zero values for each var and group pairing.

Internally, the data for each element of `vars` is obtained. When elements are genes/features, `assay` and `sSlot` are utilized to determine which expression data to use, and `adjustment` determines if and how the expression data might be adjusted. (Note that 'adjustment' would be applied *before* cells/samples subsetting, and across all groups of cells/samples.)

Groupings are determined using `group.by`, and then data for each variable is summarized based on `summary.fxn.color` & `summary.fxn.size`.

If `scale = TRUE` (default setting), the color summary values are centered and scaled. Doing so 1) puts values for all `vars` in a similar range, and 2) emphasizes relative differences between groups.

Finally, data is plotted as dots of differing colors and sizes.

Value

a `ggplot` object where dots of different colors and sizes summarize continuous data for multiple features (columns) per multiple groups (rows)

Alternatively when `data.out = TRUE`, a list containing the plot ("p") and the underlying data as a dataframe ("data").

Alternatively when `do.hover = TRUE`, a plotly converted version of the plot where additional data will be displayed when the cursor is hovered over the dots.

Many characteristics of the plot can be adjusted using discrete inputs

- Size of the dots can be changed with `size`.
- Subsetting to utilize only certain cells/samples can be achieved with `cells.use`.
- Colors can be adjusted with `min.color` and `max.color`.
- Displayed value ranges can be adjusted with `min` and `max` for color, or `min.percent` and `max.percent` for size.
- Titles and axes labels can be adjusted with `main`, `sub`, `xlab`, `ylab`, `legend.color.title`, and `legend.size.title` arguments.
- The legend can be hidden by setting `legend.show = FALSE`.
- The color legend tick marks and associated labels can be adjusted with `legend.color.breaks` and `legend.color.breaks.labels`, respectively.
- The groupings labels and order can be changed using `y.labels` and `y.reorder`
- Rotation of x-axis labels can be turned off with `x.labels.rotate = FALSE`.

Author(s)

Daniel Bunis

See Also

[dittoPlotVarsAcrossGroups](#) for a method of summarizing expression of multiple features across distinct groups that can be better (and more compact) when the identities of the individual genes are unimportant.

[dittoPlot](#) and [multi_dittoPlot](#) for plotting of expression and metadata vars, each as separate plots, on a per cell/sample basis.

Examples

```

example(importDittoBulk, echo = FALSE)
myRNA

# These random data aren't very exciting, but we can at least add some zeros
# for making slightly more interesting dot plots.
counts(myRNA)[1:4,1:40] <- 0
logcounts(myRNA)[1:4,1:40] <- 0

dittoDotPlot(
  myRNA, c("gene1", "gene2", "gene3", "gene4"),
  group.by = "clustering")

# 'size' adjusts the dot-size associated with the highest percent expression
dittoDotPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  size = 12)

# 'scale' input can be used to control / turn off scaling of avg exp values.
dittoDotPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  scale = FALSE)

# x-axis label rotation can be controlled with 'x.labels.rotate'
dittoDotPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  x.labels.rotate = FALSE)

# Title are adjustable via various discrete inputs:
dittoDotPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  main = "Title",
  sub = "Subtitle",
  ylab = "y-axis label",
  xlab = "x-axis label",
  legend.color.title = "Colors title",
  legend.size.title = "Dot size title")

# For certain specialized applications, it may be helpful to adjust the
# functions used for summarizing the data as well. Inputs are:
# summary.fxn.color & summary.fxn.size
# Requirement for each: Any function that takes in a numeric vector &
# returns, as output, a single numeric value.
dittoDotPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  summary.fxn.color = mean,
  legend.color.title = "mean\nexpression\nincluding 0s",
  main = "scatter::plotDots() defaulting recreation",
  x.labels.rotate = FALSE,
  scale = FALSE)

```

Description

Plot cell type/cluster/identity frequencies per sample and per grouping

Usage

```
dittoFreqPlot(  
  object,  
  var,  
  sample.by = NULL,  
  group.by,  
  color.by = group.by,  
  vars.use = NULL,  
  scale = c("percent", "count"),  
  max.normalize = FALSE,  
  plots = c("boxplot", "jitter"),  
  split.nrow = NULL,  
  split.ncol = NULL,  
  split.adjust = list(),  
  cells.use = NULL,  
  data.out = FALSE,  
  do.hover = FALSE,  
  color.panel = dittoColors(),  
  colors = seq_along(color.panel),  
  y.breaks = NULL,  
  min = 0,  
  max = NULL,  
  var.labels.rename = NULL,  
  var.labels.reorder = NULL,  
  x.labels = NULL,  
  x.labels.rotate = TRUE,  
  x.reorder = NULL,  
  theme = theme_classic(),  
  xlab = group.by,  
  ylab = "make",  
  main = "make",  
  sub = NULL,  
  jitter.size = 1,  
  jitter.width = 0.2,  
  jitter.color = "black",  
  jitter.position.dodge = boxplot.position.dodge,  
  do.raster = FALSE,  
  raster.dpi = 300,  
  boxplot.width = 0.4,  
  boxplot.color = "black",  
  boxplot.show.outliers = NA,  
  boxplot.fill = TRUE,  
  boxplot.position.dodge = vlnplot.width,  
  boxplot.linewidth = 1,
```

```

vlnplot.linewidth = 1,
vlnplot.width = 1,
vlnplot.scaling = "area",
ridgeplot.linewidth = 1,
ridgeplot.scale = 1.25,
ridgeplot.ymax.expansion = NA,
ridgeplot.shape = c("smooth", "hist"),
ridgeplot.bins = 30,
ridgeplot.binwidth = NULL,
add.line = NULL,
line.linetype = "dashed",
line.color = "black",
legend.show = TRUE,
legend.title = color.by
)

```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
var	String name of a metadata that contains discrete data, or a factor or vector containing such data for all cells/samples in the target object.
sample.by	String name of a metadata containing which samples each cell belongs to. Note that when this is not provided, there will only be one data point per grouping. A warning can be expected then for all plots options except "jitter", but this can be a useful exercise when simply trying to quantify cell type frequency fluctuations among 2 particular metadata (given to group.by & color.by) combinations.
group.by	String representing the name of a metadata to use for separating the cells/samples into discrete groups.
color.by	String representing the name of a metadata to use for setting fills. Great for highlighting supersets or subgroups when wanted, but it defaults to group.by so this input can be skipped otherwise.
vars.use	String or string vector naming a subset of the values of var-data which should be shown. If left as NULL, all values are shown. Hint: use <code>metaLevels</code> or <code>unique(<var-data>)</code> to assess options. Note: When <code>var.labels.rename</code> is jointly utilized to update how the var-values are shown, the updated values must be used.
scale	"count" or "percent". Sets whether data should be shown as counts versus percentage.
max.normalize	Logical which sets whether the data for each var-data value (each facet) should be normalized to have the same maximum value. When set to TRUE, lower frequency var-values will make use of just as much plot space as higher frequency vars.
plots	String vector which sets the types of plots to include: possibilities = "jitter", "boxplot", "vlnplot", "ridgeplot".

	Order matters: <code>c("vlnplot", "boxplot", "jitter")</code> will put a violin plot in the back, boxplot in the middle, and then individual dots in the front. See details section for more info.
<code>split.nrow, split.ncol</code>	Integers which set the dimensions of the facet grid. (the <code>split.nrow</code> and <code>split.ncol</code> equivalent of other functions)
<code>split.adjust</code>	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code> . Faceting for this <code>dittoFreqPlot</code> is always by the <code>var-data</code> , so see facet_wrap for options.
<code>cells.use</code>	String vector of cells'(/samples' for bulk data) names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot (p) and data (data).
<code>do.hover</code>	Logical. Default = FALSE. If set to TRUE: object will be converted to a ggplotly object so that data about individual cells will be displayed when you hover your cursor over the jitter points (assuming that there is a "jitter" in plots),
<code>color.panel</code>	String vector which sets the colors to draw from for plot fills. Default = <code>dittoColors()</code> .
<code>colors</code>	Integer vector, the indexes / order, of colors from <code>color.panel</code> to actually use. (Provides an alternative to directly modifying <code>color.panel</code> .)
<code>y.breaks</code>	Numeric vector, a set of breaks that should be used as major gridlines. <code>c(break1,break2,break3,etc.)</code> .
<code>min, max</code>	Scalars which control the zoom of the plot. These inputs set the minimum / maximum values of the data to show. Default = set based on the limits of the data in <code>var</code> .
<code>var.labels.rename</code>	String vector for renaming the distinct identities of <code>var</code> -values. Hint: use metaLevels or <code>unique(<var-data>)</code> to assess current values.
<code>var.labels.reorder</code>	Integer vector. A sequence of numbers, from 1 to the number of distinct <code>var</code> -value identities, for rearranging the order of facets within the plot space. Method: Make a first plot without this input. Then, treating the top-left-most grouping as index 1, and the bottom-right-most as index n. Values of <code>var.labels.reorder</code> should be these indices, but in the order that you would like them rearranged to be.
<code>x.labels</code>	String vector, <code>c("label1","label2","label3",...)</code> which overrides the names of groupings.
<code>x.labels.rotate</code>	Logical which sets whether the labels should be rotated. Default: TRUE for violin and box plots, but FALSE for ridgeplots.
<code>x.reorder</code>	Integer vector. A sequence of numbers, from 1 to the number of groupings, for rearranging the order of x-axis groupings.

Method: Make a first plot without this input. Then, treating the leftmost grouping as index 1, and the rightmost as index n. Values of `x.reorder` should be these indices, but in the order that you would like them rearranged to be.

Recommendation for advanced users: If you find yourself coming back to this input too many times, an alternative solution that can be easier long-term is to make the target data into a factor, and to put its levels in the desired order: `factor(data, levels = c("level1", "level2", ...))`. `metaLevels` can be used to quickly get the identities that need to be part of this 'levels' input.

<code>theme</code>	A ggplot theme which will be applied before dittoSeq adjustments. Default = <code>theme_classic()</code> . See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
<code>xlab</code>	String which sets the grouping-axis label (=x-axis for box and violin plots, y-axis for ridgeplots). Set to NULL to remove.
<code>ylab</code>	String, sets the continuous-axis label (=y-axis for box and violin plots, x-axis for ridgeplots). Default = "make" and if left as make, a title will be automatically generated.
<code>main</code>	String, sets the plot title. Default = "make" and if left as make, a title will be automatically generated. To remove, set to NULL.
<code>sub</code>	String, sets the plot subtitle
<code>jitter.size</code>	Scalar which sets the size of the jitter shapes.
<code>jitter.width</code>	Scalar that sets the width/spread of the jitter in the x direction. Ignored in ridgeplots. Note for when <code>color.by</code> is used to split x-axis groupings into additional bins: ggplot does not shrink jitter widths accordingly, so be sure to do so yourself! Ideally, needs to be $0.5/\text{num_subgroups}$.
<code>jitter.color</code>	String which sets the color of the jitter shapes
<code>jitter.position.dodge</code>	Scalar which adjusts the relative distance between jitter widths when multiple subgroups exist per group.by grouping (a.k.a. when <code>group.by</code> and <code>color.by</code> are not equal). Similar to <code>boxplot.position.dodge</code> input & defaults to the value of that input so that BOTH will actually be adjusted when only, say, <code>boxplot.position.dodge = 0.3</code> is given.
<code>do.raster</code>	Logical. When set to TRUE, rasterizes the jitter plot layer, changing it from individually encoded points to a flattened set of pixels. This can be useful for editing in external programs (e.g. Illustrator) when there are many thousands of data points.
<code>raster.dpi</code>	Number indicating dots/pixels per inch (dpi) to use for rasterization. Default = 300.
<code>boxplot.width</code>	Scalar which sets the width/spread of the boxplot in the x direction
<code>boxplot.color</code>	String which sets the color of the lines of the boxplot
<code>boxplot.show.outliers</code>	Logical, whether outliers should be including in the boxplot. Default is FALSE when there is a jitter plotted, TRUE if there is no jitter.

<code>boxplot.fill</code>	Logical, whether the boxplot should be filled in or not. Known bug: when boxplot fill is turned off, outliers do not render.
<code>boxplot.position.dodge</code>	Scalar which adjusts the relative distance between boxplots when multiple are drawn per grouping (a.k.a. when <code>group.by</code> and <code>color.by</code> are not equal). By default, this input actually controls the value of <code>jitter.position.dodge</code> unless the <code>jitter</code> version is provided separately.
<code>boxplot.linewidth</code>	Scalar which adjusts the thickness of boxplot lines.
<code>vlplot.linewidth</code>	Scalar which sets the thickness of the line that outlines the violin plots.
<code>vlplot.width</code>	Scalar which sets the width/spread of violin plots in the x direction
<code>vlplot.scaling</code>	String which sets how the widths of the of violin plots are set in relation to each other. Options are "area", "count", and "width". If the default is not right for your data, I recommend trying "width". For an explanation of each, see geom_violin .
<code>ridgeplot.linewidth</code>	Scalar which sets the thickness of the ridgeplot outline.
<code>ridgeplot.scale</code>	Scalar which sets the distance/overlap between ridgeplots. A value of 1 means the tallest density curve just touches the baseline of the next higher one. Higher numbers lead to greater overlap. Default = 1.25
<code>ridgeplot.ymax.expansion</code>	Scalar which adjusts the minimal space between the topmost grouping and the top of the plot in order to ensure the curve is not cut off by the plotting grid. The larger the value, the greater the space requested. When left as NA, dittoSeq will attempt to determine an ideal value itself based on the number of groups & linear interpolation between these goal posts: #groups of 3 or fewer: 0.6; #groups=12: 0.1; #groups or 34 or greater: 0.05.
<code>ridgeplot.shape</code>	Either "smooth" or "hist", sets whether ridges will be smoothed (the typical, and default) versus rectangular like a histogram. (Note: as of the time shape "hist" was added, combination of jittered points is not supported by the stat_binline that dittoSeq relies on.)
<code>ridgeplot.bins</code>	Integer which sets how many chunks to break the x-axis into when <code>ridgeplot.shape = "hist"</code> . Overridden by <code>ridgeplot.binwidth</code> when that input is provided.
<code>ridgeplot.binwidth</code>	Integer which sets the width of chunks to break the x-axis into when <code>ridgeplot.shape = "hist"</code> . Takes precedence over <code>ridgeplot.bins</code> when provided.
<code>add.line</code>	numeric value(s) where one or multiple line(s) should be added
<code>line.linetype</code>	String which sets the type of line for <code>add.line</code> . Defaults to "dashed", but any ggplot linetype will work.
<code>line.color</code>	String that sets the color(s) of the <code>add.line</code> line(s)
<code>legend.show</code>	Logical. Whether the legend should be displayed. Default = TRUE.
<code>legend.title</code>	String or NULL, sets the title for the main legend which includes colors and data representations.

Details

The function creates a dataframe containing counts and percent makeup of var identities per sample if `sample.by` is given, or per group if only `group.by` is given. `color.by` can optionally be used to add subgroupings to calculations and ultimate plots, or to convey super-groups of `group.by` groupings.

Typically, `var` will be pointed to clustering or cell type annotations, but in truth it can be given any discrete data.

If a set of cells to use is indicated with the `cells.use` input, only those cells/samples are used for counts and percent makeup calculations.

If a set of var-values to show is indicated with the `vars.use` input, the data.frame is trimmed at the end to include only corresponding rows.

If `max.normalized` is set to TRUE, counts and percent data are transformed to a 0-1 scale, which makes better use of white space for lower frequency var-values.

Either percent of total (`scale = "percent"`), which is the default, or counts (if `scale = "count"`) data is then (gg)plotted with the data representation types in `plots` by utilizing the same machinery as `dittoPlot`. Faceting by var-data values is utilized to achieve per var-value (e.g. cluster or cell type) granularity.

See below for additional customization options!

Value

A ggplot plot where frequencies of discrete data, grouped by sample, condition, etc., is shown on the y-axis by a violin plot, boxplot, and/or jittered points, or on the x-axis by a ridgeplot with or without jittered points.

Alternatively, if `data.out = TRUE`, a list containing the plot ("p") and a dataframe of the underlying data ("data").

Alternatively, if `do.hover = TRUE`, a plotly conversion of the ggplot output in which underlying data can be retrieved upon hovering the cursor over the plot.

Calculation Details

The function is restricted in that each samples' cells, indicated by the unique values of `sample.by`-data, must exist within single `group.by` and `color.by` groupings. Thus, in order to ensure all valid var-data composition data points are generated, prior to calculations...

- var-data are ensured to be a factor, which ensures a calculation will be run for every var-value (a.k.a. cell type or cluster)
- `group.by`-data and `color-by`-data are treated as non-factor data, which ensures that calculations are run only for the groupings that each sample is associated with.

Plot Customization

The `plots` argument determines the types of **data representation** that will be generated, as well as their order from back to front. Options are "jitter", "boxplot", "vlnplot", and "ridgeplot".

Each plot type has specific associated options which are controlled by variables that start with their associated string. For example, all jitter adjustments start with "jitter.", such as `jitter.size` and `jitter.width`.

Inclusion of "ridgeplot" overrides "boxplot" and "vlnplot" presence and changes the plot to be horizontal.

Additionally:

- **Colors can be adjusted** with `color.panel`.
- **Subgroupings:** `color.by` can be utilized to split major `group.by` groupings into subgroups. When this is done in y-axis plotting, `dittoSeq` automatically ensures the centers of all geoms will align, but users will need to manually adjust `jitter.width` to less than $0.5/\text{num_subgroups}$ to avoid overlaps. There are also three inputs through which one can use to control geom-center placement, but the easiest way to do all at once so is to just adjust `vlnplot.width!` The other two: `boxplot.position.dodge`, and `jitter.position.dodge`.
- **Line(s) can be added** at single or multiple value(s) by providing these values to `add.line`. Linetype and color are set with `line.linetype`, which is "dashed" by default, and `line.color`, which is "black" by default.
- **Titles and axes labels** can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.title` arguments.
- The **legend can be hidden** by setting `legend.show = FALSE`.
- **y-axis zoom and tick marks** can be adjusted using `min`, `max`, and `y.breaks`.
- **x-axis labels and groupings** can be changed / reordered using `x.labels` and `x.reorder`, and rotation of these labels can be turned on/off with `x.labels.rotate = TRUE/FALSE`.

Author(s)

Daniel Bunis

See Also

[dittoBarPlot](#) for a data representation that emphasizes total makeup of samples/groups rather than focusing on the var-data values individually.

Examples

```
# Establish some workable example data
example(importDittoBulk, echo = FALSE)
myRNA1 <- myRNA
colnames(myRNA) <- paste0(colnames(myRNA), "_1")
example(importDittoBulk, echo = FALSE)
myRNA <- cbind(myRNA, myRNA1)
myRNA <- setBulk(myRNA, FALSE)
myRNA$sample <- rep(1:12, each = 10)
myRNA$groups <- rep(c("A", "B"), each = 60)
myRNA$subgroups <- rep(as.character(c(1:3,1:3,1:3)), each = 10)
myRNA

# There are three main inputs for this function, in addition to 'object'.
```

```

# var = typically this will be cell types annotations or clustering
# sample.by = the name of a metadata containing sample assignment of cells.
# group.by = how to group the data on the x-axis (y-axis for ridgeplots)
dittoFreqPlot(myRNA,
  var = "clustering",
  sample.by = "sample",
  group.by = "groups")

# 'color.by' can also be set differently from 'group.by' to have the effect
# of highlighting supersets or subgroupings:
dittoFreqPlot(myRNA, "clustering",
  group.by = "groups",
  sample.by = "sample",
  color.by = "subgroups")

# The var-values shown can be subset with 'vars.use'
dittoFreqPlot(myRNA, "clustering",
  group.by = "groups", sample.by = "sample", color.by = "subgroups",
  vars.use = 1:2)

# Lower frequency groups can be expanded to use the entire y-axis by:
# turning on 'max.normalize'-ation:
dittoFreqPlot(myRNA, "clustering",
  group.by = "groups", sample.by = "sample", color.by = "subgroups",
  max.normalize = TRUE)
# or by setting y-scale limits to be set by the contents of facets:
dittoFreqPlot(myRNA, "clustering",
  group.by = "groups", sample.by = "sample", color.by = "subgroups",
  split.adjust = list(scales = "free_y"))

# Data representations can also be selected and reordered with the 'plots'
# input, and further adjusted with inputs applying to each representation.
dittoFreqPlot(myRNA,
  var = "clustering", sample.by = "sample", group.by = "groups",
  plots = c("vlnplot", "boxplot", "jitter"),
  vlnplot.linewidth = 0.2,
  boxplot.fill = FALSE,
  boxplot.linewidth = 0.2)

# Finally, 'sample.by' is not technically required. When not given, a
# single-datapoint of overall composition stats will be shown for each
# grouping.
# Just note, all data representation other than "jitter" will complain
# due to there only being the one datapoint per group.
dittoFreqPlot(myRNA,
  var = "clustering", group.by = "groups", color.by = "subgroups",
  plots = "jitter")

```

Description

Given a set of genes, cells/samples, and metadata names for column annotations, this function will retrieve the expression data for those genes and cells, and the annotation data for those cells. It will then utilize these data to make a heatmap using the [pheatmap](#) function of either the [pheatmap](#) (default) or [ComplexHeatmap](#) package.

Usage

```
dittoHeatmap(
  object,
  genes = getGenes(object, assay),
  metas = NULL,
  cells.use = NULL,
  annot.by = NULL,
  order.by = .default_order(object, annot.by),
  main = NA,
  cell.names.meta = NULL,
  assay = .default_assay(object),
  slot = .default_slot(object),
  swap.rownames = NULL,
  heatmap.colors = colorRampPalette(c("blue", "white", "red"))(50),
  scaled.to.max = FALSE,
  heatmap.colors.max.scaled = colorRampPalette(c("white", "red"))(25),
  annot.colors = c(dittoColors(), dittoColors(1)[seq_len(7)]),
  annotation_col = NULL,
  annotation_colors = NULL,
  data.out = FALSE,
  highlight.features = NULL,
  highlight.genes = NULL,
  show_colnames = isBulk(object),
  show_rownames = TRUE,
  scale = "row",
  cluster_cols = isBulk(object),
  border_color = NA,
  legend_breaks = NA,
  drop_levels = FALSE,
  breaks = NA,
  complex = FALSE,
  ...
)
```

Arguments

<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>genes</code>	String vector, <code>c("gene1", "gene2", "gene3", ...)</code> = the list of genes to put in the heatmap. If not provided, defaults to all genes of the object / assay.
<code>metas</code>	String vector, <code>c("meta1", "meta2", "meta3", ...)</code> = the list of metadata variables to put in the heatmap.

<code>cells.use</code>	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
<code>annot.by</code>	String name of any metadata slots containing how the cells/samples should be annotated.
<code>order.by</code>	Single string, string vector, or numeric vector which sets how cells/samples (columns) will be ordered when <code>cluster_cols = FALSE</code> . Strings should be the name of a gene, or metadata slot, but can also be multiple such values in order of priority. Alternatively, can be a numeric vector which gives the column index order directly.
<code>main</code>	String that sets the title for the heatmap.
<code>cell.names.meta</code>	quoted "name" of a meta.data slot to use for naming the columns instead of using the raw cell/sample names.
<code>assay, slot</code>	single strings or integer that set which expression data to use. See gene for more information about how defaults for these are filled in when not provided.
<code>swap.rownames</code>	String. For SummarizedExperiment or SingleCellExperiment objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .
<code>heatmap.colors</code>	the colors to use within the heatmap when (default setting) <code>scaled.to.max</code> is set to <code>FALSE</code> . Default is a ramp from navy to white to red with 50 slices.
<code>scaled.to.max</code>	Logical, <code>FALSE</code> by default, which sets whether expression should be scaled between [0, 1]. This is recommended for single-cell datasets as they are generally enriched in 0s.
<code>heatmap.colors.max.scaled</code>	the colors to use within the heatmap when <code>scaled.to.max</code> is set to <code>TRUE</code> . Default is a ramp from white to red with 25 slices.
<code>annot.colors</code>	String (color) vector where each color will be assigned to an individual annotation in the generated annotation bars.
<code>data.out</code>	Logical. When set to <code>TRUE</code> , changes the output from the heatmap itself, to a list containing all arguments that would have been passed to pheatmap for heatmap generation. (Can be useful for troubleshooting or customization.)
<code>highlight.features</code>	String vector of genes/metadata whose names you would like to show. Only these genes/metadata will be named in the resulting heatmap.
<code>highlight.genes</code>	Deprecated, use <code>highlight.features</code> instead.
<code>show_colnames, show_rownames, scale, annotation_col, annotation_colors</code>	arguments passed to <code>pheatmap</code> that are over-ruled by certain <code>dittoHeatmap</code> functionality: <ul style="list-style-type: none"> <code>show_colnames (& labels_col)</code>: if <code>cell.names.meta</code> is provided, <code>pheatmap</code>'s <code>labels_col</code> is utilized to show these names and <code>show_colnames</code> parameter is set to <code>TRUE</code>.

- `show_rownames (& labels_row)`: if feature names are provided to `highlight.features`, `pheatmap`'s `labels_row` is utilized to show just these features' names and `show_rownames` parameter is set to `TRUE`.
- `scale`: when parameter `scaled.to.max` is set to `true`, `pheatmap`'s `scale` is set to "none" and the max scaling is performed prior to the `pheatmap` call.
- `annotation_col`: Can be provided as normal by the user and any metadata given to `annot.by` will then be appended.
- `annotation_colors`: `dittoHeatmap` fills this complicated-to-produce input in automatically by pulling from the colors given to `annot.colors`, but it is possible to set all or some manually. `dittoSeq` will just fill any left out annotations. Format is a named (`annotation_col` & `annotation_row` colnames) character vector list where individual color values can also be named.

`cluster_cols`, `border_color`, `legend_breaks`, `breaks`, `drop_levels`, ...

other arguments passed to `pheatmap` directly (or to `pheatmap` if `complex = TRUE`).

`complex` Logical which sets whether the heatmap should be generated with `ComplexHeatmap` (`TRUE`) versus `pheatmap` (`FALSE`, default).

Details

This function serves as a wrapper for creating heatmaps from bulk or single-cell RNAseq data with `pheatmap::pheatmap`, by essentially automating the data extraction and annotation building steps. (Or alternatively with `ComplexHeatmap::pheatmap` if `complex` is set to `true`).

The function will extract the expression matrix for a set of genes and/or an optional subset of cells / samples to use via `cells.use`. This matrix is either left as is, default (for scaling within the ultimate call to `pheatmap`), or if `scaled.to.max = TRUE`, is scaled by dividing each row by its maximum value.

When provided with a set of metadata slot names to use for building annotations (with the `annot.by` input), the relevant metadata is retrieved from the object and compiled into a `pheatmap`-ready `annotation_col` input. The input `annot.colors` is used to establish the set of colors that should be used for building a `pheatmap`-ready `annotation_colors` input as well, unless such an input has been provided by the user. See below for further details.

Value

A `pheatmap` object.

Alternatively, if `complex` is set to `TRUE`, a `Heatmap`

Alternatively, if `data.out` is set to `TRUE`, a list containing all arguments that would have be passed to `pheatmap` to generate such a heatmap.

Many additional characteristics of the plot can be adjusted using discrete inputs

- The cells can be ordered in a set way using the `order.by` input. Such ordering happens by default for single-cell RNAseq data when any metadata are provided to `annot.by` as it is often unfeasible to cluster thousands of cells.
- A plot title can be added with `main`.

- Gene or cell/sample names can be hidden with `show_rownames` and `show_colnames`, respectively, or...
 - Particular features can also be selected for labeling using the `highlight_features` input.
 - Names of all cells/samples can be replaced with the contents of a metadata slot using the `cell_names_meta` input.
- Additional tweaks are possible through use of `pheatmap` inputs which will be directly passed through. Some examples of useful `pheatmap` parameters are:
 - `cluster_cols` and `cluster_rows` for controlling clustering. Note: `cluster_cols` will always be over-written to be `FALSE` when the input order `.by` is used above.
 - `treeheight_row` and `treeheight_col` for setting how large the trees on the side/top should be drawn.
 - `cutree_col` and `cutree_row` for splitting the heatmap based on kmeans clustering
- When `complex` is set to `TRUE`, additional inputs for the `Heatmap` function can be given as well. Some examples:
 - `use_raster` to have the heatmap rasterized/flattened to pixels which can make working with large heatmaps in a figure editor, like Illustrator, simpler.
 - `name` to give the heatmap color scale a custom title.

Customized annotations

In typical operation, `dittoHeatmap` pulls metadata annotations given to `annot.by` to build a `pheatmap-annotation_col` input, then it uses the colors provided to `annot.colors` to create the `pheatmap-annotation_colors` input which sets the annotation coloring. Specifically...

- colors for the values of **discrete** metadata are pulled from the *start* of the `annot.colors` vector, in the order that they are given to `annot.by`
- colors for the values of **continuous** metadata are pulled from the *end* of the `annot.colors` vector, in the order that they are given to `annot.by`

To customize colors or add additional column or row annotations, users can also provide `annotation_colors`, `annotation_col`, or `annotation_row` `pheatmap`-inputs directly. General structure is described below, but see `pheatmap` for additional details and examples.

- `annotation_col` = a `data.frame` with rownames of the barcodes/names of all cells/samples in the dataset & columns representing annotations. Names of columns are used as the annotation titles. `*dittoSeq` will append any `annot.by` annotations to this dataframe.
- `annotation_row` = a `data.frame` with rownames of the genes/feature of the dataset & columns representing annotations. Names of columns are used as the annotation titles.
- `annotation_colors` = a named list of string (color) vectors. Vectors must be named by the row or column annotation title that they are associated with. Optionally, individual colors can be named with the values that they should be associated with.

Partial `annotation_colors` lists (containing vectors for only certain annotations) will have colors for left out annotations filled in automatically. For such filling, `annot.colors` are pulled for column annotations first, then for row annotations.

Author(s)

Daniel Bunis and Jared Andrews

See Also

`pheatmap::pheatmap`, for how to add additional heatmap tweaks, OR or `ComplexHeatmap::pheatmap` and `Heatmap` for when you want to turn on rasterization or any additional customizations offered by this fantastic package.

`metaLevels` for helping to create manual `annotation_colors` inputs. This function universally checks the options/levels of a string, factor (filled only by default), or numerical metadata.

Examples

```
example(importDittoBulk, echo = FALSE)
scrNA <- setBulk(myRNA, FALSE)

# We now have two SCEs for our example purposes:
# 'myRNA' will be treated as a bulk RNAseq dataset
# 'scrNA' will be treated as a single-cell RNAseq dataset

# Pick a set of genes
genes <- getGenes(myRNA)[1:30]

# Make a heatmap with cells/samples annotated by their clusters
dittoHeatmap(myRNA, genes,
  annot.by = "clustering")

# For single-cell data, you will typically have more cells than can be
# clustered quickly. Thus, cell clustering is turned off by default for
# single-cell data.
dittoHeatmap(scrNA, genes,
  annot.by = "clustering")

# Using the 'order.by' input:
# Ordering by a useful metadata or gene is often helpful.
# For single-cell data, order.by defaults to the first element given to
#   annot.by.
# For bulk data, order.by must be set separately.
dittoHeatmap(myRNA, genes,
  annot.by = "clustering",
  order.by = "clustering",
  cluster_cols = FALSE)
# 'order.by' can be multiple metadata/genes, or a vector of indexes directly
dittoHeatmap(scrNA, genes,
  annot.by = "clustering",
  order.by = c("clustering", "timepoint"))
dittoHeatmap(scrNA, genes,
  annot.by = "clustering",
  order.by = ncol(scrNA):1)

# When there are many cells, showing names becomes less useful.
# Names can be turned off with the 'show_colnames' parameter.
dittoHeatmap(scrNA, genes,
  annot.by = "groups",
  show_colnames = FALSE)
```

```

# When there are many many cells & genes, rasterization can be super useful
# as well.
# Rasterization, or flattening of the distinct color objects to a matrix of
# pixels, is the default for large heatmaps in the ComplexHeatmap package,
# and you can have the heatmap rendered with this package (rather than the
# pheatmap package) by setting 'complex = TRUE'.
# Our data here is too small to hit that defaulting switch, so lets give
# the direct input, 'use_raster' as well:
if (requireNamespace("ComplexHeatmap")) { # Checks if you have the package.
  dittoHeatmap(scrNA, genes, annot.by = "groups", show_colnames = FALSE,
    complex = TRUE,
    use_raster = TRUE)
}

# Additionally, it is recommended for single-cell data that the parameter
# scaled.to.max be set to TRUE, or scale be "none" and turned off altogether,
# because these data are generally enriched for zeros that otherwise get
# scaled to a negative value.
dittoHeatmap(myRNA, genes, annot.by = "groups",
  order.by = "groups", show_colnames = FALSE,
  scaled.to.max = TRUE)

```

dittoHex

Show RNAseq data, grouped into hexagonal bins, on a scatter or dimensionality reduction plot

Description

Show RNAseq data, grouped into hexagonal bins, on a scatter or dimensionality reduction plot

Usage

```

dittoDimHex(
  object,
  color.var = NULL,
  bins = 30,
  color.method = NULL,
  reduction.use = .default_reduction(object),
  dim.1 = 1,
  dim.2 = 2,
  cells.use = NULL,
  color.panel = dittoColors(),
  colors = seq_along(color.panel),
  split.by = NULL,
  extra.vars = NULL,
  split.nrow = NULL,

```

```
split.ncol = NULL,
split.adjust = list(),
assay = .default_assay(object),
slot = .default_slot(object),
adjustment = NULL,
swap.rownames = NULL,
assay.extra = assay,
slot.extra = slot,
adjustment.extra = adjustment,
show.axes.numbers = TRUE,
show.grid.lines = !grepl("umap|tsne", tolower(reduction.use)),
main = "make",
sub = NULL,
xlab = "make",
ylab = "make",
theme = theme_bw(),
do.contour = FALSE,
contour.color = "black",
contour.linetype = 1,
min.density = NA,
max.density = NA,
min.color = "#F0E442",
max.color = "#0072B2",
min.opacity = 0.2,
max.opacity = 1,
min = NA,
max = NA,
rename.color.groups = NULL,
do.ellipse = FALSE,
do.label = FALSE,
labels.size = 5,
labels.highlight = TRUE,
labels.repel = TRUE,
labels.split.by = split.by,
add.trajectory.lineages = NULL,
add.trajectory.curves = NULL,
trajectory.cluster.meta,
trajectory.arrow.size = 0.15,
data.out = FALSE,
legend.show = TRUE,
legend.color.title = "make",
legend.color.breaks = waiver(),
legend.color.breaks.labels = waiver(),
legend.density.title = if (isBulk(object)) "Samples" else "Cells",
legend.density.breaks = waiver(),
legend.density.breaks.labels = waiver()
)
```

```
dittoScatterHex(  
  object,  
  x.var,  
  y.var,  
  color.var = NULL,  
  bins = 30,  
  color.method = NULL,  
  split.by = NULL,  
  extra.vars = NULL,  
  cells.use = NULL,  
  color.panel = dittoColors(),  
  colors = seq_along(color.panel),  
  split.nrow = NULL,  
  split.ncol = NULL,  
  split.adjust = list(),  
  assay.x = .default_assay(object),  
  slot.x = .default_slot(object),  
  adjustment.x = NULL,  
  assay.y = .default_assay(object),  
  slot.y = .default_slot(object),  
  adjustment.y = NULL,  
  assay.color = .default_assay(object),  
  slot.color = .default_slot(object),  
  adjustment.color = NULL,  
  assay.extra = .default_assay(object),  
  slot.extra = .default_slot(object),  
  adjustment.extra = NULL,  
  swap.rownames = NULL,  
  min.density = NA,  
  max.density = NA,  
  min.color = "#F0E442",  
  max.color = "#0072B2",  
  min.opacity = 0.2,  
  max.opacity = 1,  
  min = NA,  
  max = NA,  
  rename.color.groups = NULL,  
  xlab = x.var,  
  ylab = y.var,  
  main = "make",  
  sub = NULL,  
  theme = theme_bw(),  
  do.contour = FALSE,  
  contour.color = "black",  
  contour.linetype = 1,  
  do.ellipse = FALSE,  
  do.label = FALSE,  
  labels.size = 5,  
)
```

```

labels.highlight = TRUE,
labels.repel = TRUE,
labels.split.by = split.by,
add.trajectory.lineages = NULL,
add.trajectory.curves = NULL,
trajectory.cluster.meta,
trajectory.arrow.size = 0.15,
legend.show = TRUE,
legend.color.title = "make",
legend.color.breaks = waiver(),
legend.color.breaks.labels = waiver(),
legend.density.title = if (isBulk(object)) "Samples" else "Cells",
legend.density.breaks = waiver(),
legend.density.breaks.labels = waiver(),
data.out = FALSE
)

```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
color.var	Single string giving a gene or metadata that will set the color of cells/samples in the plot. Alternatively, can be a directly supplied numeric or string vector or a factor of length equal to the total number of cells/samples in object.
bins	Numeric or numeric vector giving the number of hexagonal bins in the x and y directions. Set to 30 by default.
color.method	Works differently depending on whether the color.var is continuous versus discrete: Continuous: String signifying a function for how target data should be summarized for each bin. Can be any function that summarizes a numeric vector input with a single numeric output value. Default is median. Other useful options are sum, mean, sd, or mad. Discrete: A string signifying whether the color should (default) be simply based on the "max" grouping of the bin, or based on the "max.prop" portion of cells/samples belonging to any grouping.
reduction.use	String, such as "pca", "tsne", "umap", or "PCA", etc, which is the name of a dimensionality reduction slot within the object, and which sets what dimensionality reduction space within the object to use. Default = the first dimensionality reduction slot inside the object with "umap", "tsne", or "pca" within its name, (priority: UMAP > t-SNE > PCA) or the first dimensionality reduction slot if none of those exist. Alternatively, a matrix (or data.frame) containing the dimensionality reduction embeddings themselves. The matrix should have as many rows as there are cells/samples in the object. Note that dim.1 and dim.2 will still be used to select which columns to pull from, and column names will serve as the default xlab & ylab.
dim.1	The component number to use on the x-axis. Default = 1

<code>dim.2</code>	The component number to use on the y-axis. Default = 2
<code>cells.use</code>	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
<code>color.panel</code>	String vector which sets the colors to draw from. <code>dittoColors()</code> by default, see dittoColors for contents.
<code>colors</code>	Integer vector, the indexes / order, of colors from <code>color.panel</code> to actually use
<code>split.by</code>	1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with <code>ggplot</code> faceting. When 2 metadatas are named, <code>c(row,col)</code> , the first is used as rows and the second is used for columns of the resulting grid. When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code>
<code>extra.vars</code>	String vector providing names of any extra metadata to be stashed in the dataframe supplied to <code>ggplot(data)</code> . Useful for making custom alterations <i>after</i> dittoSeq plot generation.
<code>split.nrow, split.ncol</code>	Integers which set the dimensions of faceting/splitting when a single metadata is given to <code>split.by</code> .
<code>split.adjust</code>	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code> . For options, when giving 1 metadata to <code>split.by</code> , see facet_wrap , OR when giving 2 metadatas to <code>split.by</code> , see facet_grid .
<code>assay, slot, adjustment, assay.x, assay.y, assay.color, assay.extra, slot.x, slot.y, slot.color, slot.extra</code>	<code>assay, slot, and adjustment</code> set which data to use when the axes, coloring, or <code>extra.vars</code> are based on expression/counts data. See gene for additional information.
<code>swap.rownames</code>	String. For <code>SummarizedExperiment</code> or <code>SingleCellExperiment</code> objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .
<code>show.axes.numbers</code>	Logical which controls whether the axes values should be displayed.
<code>show.grid.lines</code>	Logical which sets whether gridlines of the plot should be shown. They are removed when set to <code>FALSE</code> . Default = <code>FALSE</code> for <code>umap</code> and <code>tsne</code> reduction, <code>TRUE</code> otherwise.
<code>main</code>	String, sets the plot title. The default title is either "Density", <code>color.var</code> , or <code>NULL</code> , depending on the identity of <code>color.var</code> . To remove, set to <code>NULL</code> .
<code>sub</code>	String, sets the plot subtitle.
<code>xlab, ylab</code>	Strings which set the labels for the axes. To remove, set to <code>NULL</code> .
<code>theme</code>	A <code>ggplot</code> theme which will be applied before dittoSeq adjustments. Default = <code>theme_bw()</code> . See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.

<code>do.contour</code>	Logical. Whether density-based contours should be displayed.
<code>contour.color</code>	String that sets the color(s) of the <code>do.contour</code> contours.
<code>contour.linetype</code>	String or numeric which sets the type of line used for <code>do.contour</code> contours. Defaults to "solid", but see linetype for other options.
<code>min.density, max.density</code>	Number which sets the min/max values used for the density scale. Used no matter whether density is represented through opacity or color.
<code>min.color, max.color</code>	color for the min/max values of the color scale.
<code>min.opacity, max.opacity</code>	Scalar between [0,1] which sets the minimum or maximum opacity used for the density legend (when color is used for <code>color.var</code> data and density is shown via opacity).
<code>min, max</code>	Number which sets the values associated with the minimum or maximum color for <code>color.var</code> data.
<code>rename.color.groups</code>	String vector containing new names for the identities of discrete color groups.
<code>do.ellipse</code>	Logical. Whether the groups should be surrounded by median-centered ellipses.
<code>do.label</code>	Logical. Whether to add text labels near the center (median) of clusters for grouping vars.
<code>labels.size</code>	Size of the the labels text
<code>labels.highlight</code>	Logical. Whether the labels should have a box behind them
<code>labels.repel</code>	Logical, that sets whether the labels' placements will be adjusted with ggrepel to avoid intersections between labels and plot bounds. TRUE by default.
<code>labels.split.by</code>	String of one or two metadata names which controls the facet-split calculations for label placements. Defaults to <code>split.by</code> , so generally there is no need to adjust this except when you are utilizing the <code>extra.vars</code> input to achieve manual faceting control.
<code>add.trajectory.lineages</code>	List of vectors representing trajectory paths, each from start-cluster to end-cluster, where vector contents are the names of clusters provided in the <code>trajectory.cluster.meta</code> input. If the slingshot package was used for trajectory analysis, you can provide <code>add.trajectory.lineages = slingLineages('object')</code> .
<code>add.trajectory.curves</code>	List of matrices, each representing coordinates for a trajectory path, from start to end, where matrix columns represent x (<code>dim.1</code>) and y (<code>dim.2</code>) coordinates of the paths. Alternatively, (for <code>dittoDimHex</code> only, but not <code>dittoScatterHex</code>) a list of lists(/ <code>princurve</code> objects) can be provided. Thus, if the slingshot package was used for trajectory analysis, you can provide <code>add.trajectory.curves = slingCurves('object')</code>

<code>trajectory.cluster.meta</code>	String name of metadata containing the clusters that were used for generating trajectories. Required when plotting trajectories using the <code>add.trajectory.lineages</code> method. Names of clusters inside the metadata should be the same as the contents of <code>add.trajectory.lineages</code> vectors.
<code>trajectory.arrow.size</code>	Number representing the size of trajectory arrows, in inches. Default = 0.15.
<code>data.out</code>	Logical. When set to TRUE, changes the output from the plot alone to a list containing the plot ("plot"), and data.frame of the underlying data for target cells ("data").
<code>legend.show</code>	Logical. Whether any legend should be displayed. Default = TRUE.
<code>legend.density.title</code> , <code>legend.color.title</code>	Strings which set the title for the legends.
<code>legend.density.breaks</code> , <code>legend.color.breaks</code>	Numeric vector which sets the discrete values to label in the density and color.var legends.
<code>legend.density.breaks.labels</code> , <code>legend.color.breaks.labels</code>	String vector, with same length as <code>legend.*.breaks</code> , which sets the labels for the tick marks or hex icons of the associated legend.
<code>x.var</code> , <code>y.var</code>	Single string giving a gene or metadata that will be used for the x- and y-axis of the scatterplot. Note: must be continuous. Alternatively, can be a directly supplied numeric vector of length equal to the total number of cells/samples in object.

Details

The functions create a dataframe with x and y coordinates for each cell/sample, determined by either `x.var` and `y.var` for `dittoScatterHex`, or `reduction.use`, `dim.1` (x), and `dim.2` (y) for `dittoDimHex`. Extra data requested by `color.var` for coloring, `split.by` for faceting, or `extra.var` for manual external manipulations, are added to the dataframe as well. For expression/counts data, `assay`, `slot`, and `adjustment` inputs can be used to select which values to use, and if they should be adjusted in some way.

The dataframe is then subset to only target cells/samples based on the `cells.use` input.

Finally, a hex plot is created using this dataframe:

If `color.var` is not provided, coloring is based on the density of cells/samples within each hex bin. When `color.var` is provided, density is represented through opacity while coloring is based on a summarization, chosen with the `color.method` input, of the target `color.var` data.

If `split.by` was used, the plot will be split into a matrix of panels based on the associated groupings.

Value

A ggplot object where colored hexagonal bins are used to summarize RNAseq data in a scatterplot or tSNE, PCA, UMAP.

Alternatively, if `data.out=TRUE`, a list containing two slots is output: the plot (named 'plot'), and a data.table containing the underlying data for target cells (named 'data').

Functions

- `dittoDimHex`: Show RNAseq data overlaid on a tsne, pca, or similar, grouped into hexagonal bins
- `dittoScatterHex`: Make a scatter plot of RNAseq data, grouped into hexagonal bins

Many characteristics of the plot can be adjusted using discrete inputs

- Colors: `min.color` and `max.color` adjust the colors for continuous data.
- For discrete `color.var` plotting with `color.method = "max"`, colors are instead adjusted with `color.panel` and/or `colors` & the labels of the groupings can be changed using `rename.color.groups`.
- Titles and axes labels can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.color.title` and `legend.density.title` arguments.
- Legends can also be adjusted in other ways, using variables that all start with "legend." for easy tab completion lookup.

Additional Features

Other tweaks and features can be added as well. Each is accessible through 'tab' autocompletion starting with "do.---" or "add.---", and if additional inputs are involved in implementing or tweaking these, the associated inputs will start with the "---.":

- If `do.contour` is provided, density gradient contour lines will be overlaid with color and linetype adjustable via `contour.color` and `contour.linetype`.
- If `add.trajectory.lineages` is provided a list of vectors (each vector being cluster names from start-cluster-name to end-cluster-name), and a metadata name pointing to the relevant clustering information is provided to `trajectory.cluster.meta`, then median centers of the clusters will be calculated and arrows will be overlaid to show trajectory inference paths in the current dimensionality reduction space.
- If `add.trajectory.curves` is provided a list of matrices (each matrix containing x, y coordinates from start to end), paths and arrows will be overlaid to show trajectory inference curves in the current dimensionality reduction space. Arrow size is controlled with the `trajectory.arrow.size` input.

Author(s)

Daniel Bunis with some code adapted from Giuseppe D'Agostino

See Also

[dittoDimPlot](#) and [dittoScatterPlot](#) for making very similar data representations, but where each cell is represented individually. It is often best to investigate your data with both the individual and hex-bin methods, then pick whichever is the best representation for your particular goal.

[getGenes](#) and [getMetas](#) to see what the `var`, `split.by`, etc. options are of an object.

[getReductions](#) to see what the `reduction.use` options are of an object.

Examples

```

example(importDittoBulk, echo = FALSE)
myRNA

# Mock up some nCount_RNA and nFeature_RNA metadata
# == the default way to extract
myRNA$nCount_RNA <- runif(60,200,1000)
myRNA$nFeature_RNA <- myRNA$nCount_RNA*runif(60,0.95,1.05)
# and also percent.mito metadata
myRNA$percent.mito <- sample(c(runif(50,0,0.05),runif(10,0.05,0.2)))

dittoScatterHex(
  myRNA, x.var = "nCount_RNA", y.var = "nFeature_RNA")
dittoDimHex(myRNA)

# We don't have too many samples here, so let's increase the bin size.
dittoDimHex(myRNA, bins = 10)

# x and y bins can be set separately, useful for non-square plots
dittoDimHex(myRNA, bins = c(20, 10))

### Coloring
# Default coloring, as above, is by cell/sample density in the region, but
# 'color.var' can be used to color the data by another metric.
# Density with then be represented via bin opacity.
dittoDimHex(myRNA, color.var = "clustering", bins = 10)
dittoDimHex(myRNA, color.var = "gene1", bins = 10)

# 'color.method' is then used to adjust how the target data is summarized
dittoDimHex(myRNA, color.var = "groups", bins = 10,
  color.method = "max.prop")
dittoDimHex(myRNA, color.var = "gene1", bins = 10,
  color.method = "mean")

### Additional Features:

# Faceting with 'split.by'
dittoDimHex(myRNA, bins = 10, split.by = "groups")
dittoDimHex(myRNA, bins = 10, split.by = c("groups", "clustering"))

# Underlying data output with 'data.out = TRUE'
dittoDimHex(myRNA, data.out = TRUE)

# Contour lines can be added with 'do.contours = TRUE'
dittoDimHex(myRNA, bins = 10,
  do.contour = TRUE,
  contour.color = "lightblue", # Optional, black by default
  contour.linetype = "dashed") # Optional, solid by default

# Trajectories can be added to dittoDimHex plots (see above for details)
dittoDimHex(myRNA, bins = 10,
  add.trajectory.lineages = list(c(1,2,4), c(1,4), c(1,3)),

```

```
trajectory.cluster.meta = "clustering")
```

dittoPlot	<i>Plots continuous data for customizable cells'/samples' groupings on a y- (or x-) axis</i>
-----------	--

Description

Plots continuous data for customizable cells'/samples' groupings on a y- (or x-) axis

Usage

```
dittoPlot(
  object,
  var,
  group.by,
  color.by = group.by,
  shape.by = NULL,
  split.by = NULL,
  extra.vars = NULL,
  cells.use = NULL,
  plots = c("jitter", "vlnplot"),
  assay = .default_assay(object),
  slot = .default_slot(object),
  adjustment = NULL,
  swap.rownames = NULL,
  do.hover = FALSE,
  hover.data = var,
  color.panel = dittoColors(),
  colors = seq_along(color.panel),
  shape.panel = c(16, 15, 17, 23, 25, 8),
  theme = theme_classic(),
  main = "make",
  sub = NULL,
  ylab = "make",
  y.breaks = NULL,
  min = NULL,
  max = NULL,
  xlab = group.by,
  x.labels = NULL,
  x.labels.rotate = NA,
  x.reorder = NULL,
  split.nrow = NULL,
  split.ncol = NULL,
  split.adjust = list(),
  do.raster = FALSE,
  raster.dpi = 300,
```

```

    jitter.size = 1,
    jitter.width = 0.2,
    jitter.color = "black",
    jitter.shape.legend.size = NA,
    jitter.shape.legend.show = TRUE,
    jitter.position.dodge = boxplot.position.dodge,
    boxplot.width = 0.2,
    boxplot.color = "black",
    boxplot.show.outliers = NA,
    boxplot.fill = TRUE,
    boxplot.position.dodge = vlnplot.width,
    boxplot.linewidth = 1,
    vlnplot.linewidth = 1,
    vlnplot.width = 1,
    vlnplot.scaling = "area",
    ridgeplot.linewidth = 1,
    ridgeplot.scale = 1.25,
    ridgeplot.ymax.expansion = NA,
    ridgeplot.shape = c("smooth", "hist"),
    ridgeplot.bins = 30,
    ridgeplot.binwidth = NULL,
    add.line = NULL,
    line.linetype = "dashed",
    line.color = "black",
    legend.show = TRUE,
    legend.title = "make",
    data.out = FALSE
  )

dittoRidgePlot(..., plots = c("ridgeplot"))

dittoRidgeJitter(..., plots = c("ridgeplot", "jitter"))

dittoBoxPlot(..., plots = c("boxplot", "jitter"))

```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
var	Single string representing the name of a metadata or gene, OR a vector with length equal to the total number of cells/samples in the dataset. This is the data that will be displayed.
group.by	String representing the name of a metadata to use for separating the cells/samples into discrete groups.
color.by	String representing the name of a metadata to use for setting fills. Great for highlighting supersets or subgroups when wanted, but it defaults to group.by so this input can be skipped otherwise.
shape.by	Single string representing the name of a metadata to use for setting the shapes of the jitter points. When not provided, all cells/samples will be represented with

	dots.
<code>split.by</code>	<p>1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with <code>ggplot</code> faceting.</p> <p>When 2 metadatas are named, <code>c(row,col)</code>, the first is used as rows and the second is used for columns of the resulting grid.</p> <p>When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code></p>
<code>extra.vars</code>	<p>String vector providing names of any extra metadata to be stashed in the dataframe supplied to <code>ggplot(data)</code>.</p> <p>Useful for making custom splitting/faceting or other additional alterations <i>after</i> dittoSeq plot generation.</p>
<code>cells.use</code>	<p>String vector of cells' (/samples' for bulk data) names OR an integer vector specifying the indices of cells/samples which should be included.</p> <p>Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.</p>
<code>plots</code>	<p>String vector which sets the types of plots to include: possibilities = "jitter", "boxplot", "vlnplot", "ridgeplot".</p> <p>Order matters: <code>c("vlnplot", "boxplot", "jitter")</code> will put a violin plot in the back, boxplot in the middle, and then individual dots in the front.</p> <p>See details section for more info.</p>
<code>assay, slot</code>	single strings or integer that set which data to use when plotting gene expression / feature data. See gene for more information.
<code>adjustment</code>	<p>When plotting gene expression / feature counts, should that data be used directly (default) or should it be adjusted to be</p> <ul style="list-style-type: none"> • "z-score": scaled with the <code>scale()</code> function to produce a relative-to-mean z-score representation • "relative.to.max": divided by the maximum expression value to give percent of max values between [0,1]
<code>swap.rownames</code>	String. For SummarizedExperiment or SingleCellExperiment objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .
<code>do.hover</code>	Logical. Default = FALSE. If set to TRUE: object will be converted to a <code>ggplotly</code> object so that data about individual cells will be displayed when you hover your cursor over the jitter points (assuming that there is a "jitter" in plots),
<code>hover.data</code>	String vector, a list of variable names, <code>c("meta1","gene1","meta2",...)</code> which determines what data to show upon hover when <code>do.hover</code> is set to TRUE.
<code>color.panel</code>	String vector which sets the colors to draw from for plot fills. Default = <code>dittoColors()</code> .
<code>colors</code>	Integer vector, the indexes / order, of colors from <code>color.panel</code> to actually use. (Provides an alternative to directly modifying <code>color.panel</code> .)
<code>shape.panel</code>	Vector of integers corresponding to <code>ggplot</code> shapes which sets what shapes to use. When discrete groupings are supplied by <code>shape.by</code> , this sets the panel of shapes which will be used. When nothing is supplied to <code>shape.by</code> , only the first value is used. Default is a set of 6, <code>c(16, 15, 17, 23, 25, 8)</code> , the first being a simple, solid, circle.

theme	A ggplot theme which will be applied before dittoSeq adjustments. Default = theme_classic(). See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
main	String, sets the plot title. Default = "make" and if left as make, a title will be automatically generated. To remove, set to NULL.
sub	String, sets the plot subtitle
ylab	String, sets the continuous-axis label (=y-axis for box and violin plots, x-axis for ridgeplots). Defaults to "var" or "var expression" if var is a gene.
y.breaks	Numeric vector, a set of breaks that should be used as major gridlines. c(break1,break2,break3,etc.).
min, max	Scalars which control the zoom of the plot. These inputs set the minimum / maximum values of the data to show. Default = set based on the limits of the data in var.
xlab	String which sets the grouping-axis label (=x-axis for box and violin plots, y-axis for ridgeplots). Set to NULL to remove.
x.labels	String vector, c("label1","label2","label3",...) which overrides the names of groupings.
x.labels.rotate	Logical which sets whether the labels should be rotated. Default: TRUE for violin and box plots, but FALSE for ridgeplots.
x.reorder	Integer vector. A sequence of numbers, from 1 to the number of groupings, for rearranging the order of x-axis groupings. Method: Make a first plot without this input. Then, treating the leftmost grouping as index 1, and the rightmost as index n. Values of x.reorder should be these indices, but in the order that you would like them rearranged to be. Recommendation for advanced users: If you find yourself coming back to this input too many times, an alternative solution that can be easier long-term is to make the target data into a factor, and to put its levels in the desired order: factor(data, levels = c("level1", "level2", ...)). metaLevels can be used to quickly get the identities that need to be part of this 'levels' input.
split.nrow, split.ncol	Integers which set the dimensions of faceting/splitting when a single metadata is given to split.by.
split.adjust	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. 'list(scales = "free")'. For options, when giving 1 metadata to split.by, see facet_wrap , OR when giving 2 metadatas to split.by, see facet_grid .
do.raster	Logical. When set to TRUE, rasterizes the jitter plot layer, changing it from individually encoded points to a flattened set of pixels. This can be useful for editing in external programs (e.g. Illustrator) when there are many thousands of data points.
raster.dpi	Number indicating dots/pixels per inch (dpi) to use for rasterization. Default = 300.
jitter.size	Scalar which sets the size of the jitter shapes.

<code>jitter.width</code>	Scalar that sets the width/spread of the jitter in the x direction. Ignored in ridgeplots. Note for when <code>color.by</code> is used to split x-axis groupings into additional bins: <code>ggplot</code> does not shrink jitter widths accordingly, so be sure to do so yourself! Ideally, needs to be $0.5/\text{num_subgroups}$.
<code>jitter.color</code>	String which sets the color of the jitter shapes
<code>jitter.shape.legend.size</code>	Scalar which changes the size of the shape key in the legend. If set to NA, <code>jitter.size</code> is used.
<code>jitter.shape.legend.show</code>	Logical which sets whether the shapes legend will be shown when its shape is determined by <code>shape.by</code> .
<code>jitter.position.dodge</code>	Scalar which adjusts the relative distance between jitter widths when multiple subgroups exist per <code>group.by</code> grouping (a.k.a. when <code>group.by</code> and <code>color.by</code> are not equal). Similar to <code>boxplot.position.dodge</code> input & defaults to the value of that input so that BOTH will actually be adjusted when only, say, <code>boxplot.position.dodge = 0.3</code> is given.
<code>boxplot.width</code>	Scalar which sets the width/spread of the boxplot in the x direction
<code>boxplot.color</code>	String which sets the color of the lines of the boxplot
<code>boxplot.show.outliers</code>	Logical, whether outliers should be including in the boxplot. Default is FALSE when there is a jitter plotted, TRUE if there is no jitter.
<code>boxplot.fill</code>	Logical, whether the boxplot should be filled in or not. Known bug: when boxplot fill is turned off, outliers do not render.
<code>boxplot.position.dodge</code>	Scalar which adjusts the relative distance between boxplots when multiple are drawn per grouping (a.k.a. when <code>group.by</code> and <code>color.by</code> are not equal). By default, this input actually controls the value of <code>jitter.position.dodge</code> unless the jitter version is provided separately.
<code>boxplot.linewidth</code>	Scalar which adjusts the thickness of boxplot lines.
<code>vlplot.linewidth</code>	Scalar which sets the thickness of the line that outlines the violin plots.
<code>vlplot.width</code>	Scalar which sets the width/spread of violin plots in the x direction
<code>vlplot.scaling</code>	String which sets how the widths of the of violin plots are set in relation to each other. Options are "area", "count", and "width". If the default is not right for your data, I recommend trying "width". For an explanation of each, see geom_violin .
<code>ridgeplot.linewidth</code>	Scalar which sets the thickness of the ridgeplot outline.
<code>ridgeplot.scale</code>	Scalar which sets the distance/overlap between ridgeplots. A value of 1 means the tallest density curve just touches the baseline of the next higher one. Higher numbers lead to greater overlap. Default = 1.25

<code>ridgeplot.ymax.expansion</code>	Scalar which adjusts the minimal space between the topmost grouping and the top of the plot in order to ensure the curve is not cut off by the plotting grid. The larger the value, the greater the space requested. When left as NA, dittoSeq will attempt to determine an ideal value itself based on the number of groups & linear interpolation between these goal posts: #groups of 3 or fewer: 0.6; #groups=12: 0.1; #groups or 34 or greater: 0.05.
<code>ridgeplot.shape</code>	Either "smooth" or "hist", sets whether ridges will be smoothed (the typical, and default) versus rectangular like a histogram. (Note: as of the time shape "hist" was added, combination of jittered points is not supported by the stat_binline that dittoSeq relies on.)
<code>ridgeplot.bins</code>	Integer which sets how many chunks to break the x-axis into when <code>ridgeplot.shape = "hist"</code> . Overridden by <code>ridgeplot.binwidth</code> when that input is provided.
<code>ridgeplot.binwidth</code>	Integer which sets the width of chunks to break the x-axis into when <code>ridgeplot.shape = "hist"</code> . Takes precedence over <code>ridgeplot.bins</code> when provided.
<code>add.line</code>	numeric value(s) where one or multiple line(s) should be added
<code>line.linetype</code>	String which sets the type of line for <code>add.line</code> . Defaults to "dashed", but any ggplot linetype will work.
<code>line.color</code>	String that sets the color(s) of the <code>add.line</code> line(s)
<code>legend.show</code>	Logical. Whether the legend should be displayed. Default = TRUE.
<code>legend.title</code>	String or NULL, sets the title for the main legend which includes colors and data representations.
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot (p) and data (data).
<code>...</code>	arguments passed to dittoPlot by dittoRidgePlot, dittoRidgeJitter, and dittoBoxPlot wrappers. Options are all the ones above.

Details

The function creates a dataframe containing the metadata or expression data associated with the given var (or if a vector of data is provided, that data). On the discrete axis, data will be grouped by the metadata given to `group.by` and colored by the metadata given to `color.by`. The `assay` and `slot` inputs can be used to change what expression data is used when displaying gene expression. If a set of cells to use is indicated with the `cells.use` input, the data is subset to include only those cells before plotting.

The `plots` argument determines the types of data representation that will be generated, as well as their order from back to front. Options are "jitter", "boxplot", "vlnplot", and "ridgeplot". Inclusion of "ridgeplot" overrides "boxplot" and "vlnplot" presence and changes the plot to be horizontal.

When `split.by` is provided the name of a metadata containing discrete data, separate plots will be produced representing each of the distinct groupings of the `split.by` data.

`dittoRidgePlot`, `dittoRidgeJitter`, and `dittoBoxPlot` are included as wrappers of the basic `dittoPlot` function that simply change the default for the `plots` input to be "ridgeplot", `c("ridgeplot", "jitter")`, or `c("boxplot", "jitter")`, to make such plots even easier to produce.

Value

a ggplot where continuous data, grouped by sample, age, cluster, etc., shown on either the y-axis by a violin plot, boxplot, and/or jittered points, or on the x-axis by a ridgeplot with or without jittered points.

Alternatively when `data.out=TRUE`, a list containing the plot ("p") and the underlying data as a dataframe ("data").

Alternatively when `do.hover = TRUE`, a plotly converted version of the ggplot where additional data will be displayed when the cursor is hovered over jitter points.

Functions

- `dittoRidgePlot`: Plots continuous data for customizable cells'/samples' groupings horizontally in a density representation
- `dittoRidgeJitter`: `dittoRidgePlot`, but with jitter overlaid
- `dittoBoxPlot`: Plots continuous data for customizable cells'/samples' groupings in boxplot form

Many characteristics of the plot can be adjusted using discrete inputs

The `plots` argument determines the types of **data representation** that will be generated, as well as their order from back to front. Options are "jitter", "boxplot", "vlnplot", and "ridgeplot".

Each plot type has specific associated options which are controlled by variables that start with their associated string. For example, all jitter adjustments start with "jitter.", such as `jitter.size` and `jitter.width`.

Inclusion of "ridgeplot" overrides "boxplot" and "vlnplot" presence and changes the plot to be horizontal.

Additionally:

- **Colors can be adjusted** with `color.panel`.
- **Subgroupings**: `color.by` can be utilized to split major `group.by` groupings into subgroups. When this is done in y-axis plotting, `dittoSeq` automatically ensures the centers of all geoms will align, but users will need to manually adjust `jitter.width` to less than $0.5/\text{num_subgroups}$ to avoid overlaps. There are also three inputs through which one can use to control geom-center placement, but the easiest way to do all at once so is to just adjust `vlnplot.width`! The other two: `boxplot.position.dodge`, and `jitter.position.dodge`.
- **Line(s) can be added** at single or multiple value(s) by providing these values to `add.line`. Linetype and color are set with `line.linetype`, which is "dashed" by default, and `line.color`, which is "black" by default.
- **Titles and axes labels** can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.title` arguments.
- The **legend can be hidden** by setting `legend.show = FALSE`.
- **y-axis zoom and tick marks** can be adjusted using `min`, `max`, and `y.breaks`.
- **x-axis labels and groupings** can be changed / reordered using `x.labels` and `x.reorder`, and rotation of these labels can be turned on/off with `x.labels.rotate = TRUE/FALSE`.

- **Shapes used** in conjunction with `shape.by` can be adjusted with `shape.panel`.
- Single or multiple **additional per-cell features can be retrieved** and stashed within the underlying data using `extra.vars`. This can be very useful for making manual additional alterations *after* dittoSeq plot generation.

Author(s)

Daniel Bunis

See Also

[multi_dittoPlot](#) for easy creation of multiple dittoPlots each focusing on a different var.

[dittoPlotVarsAcrossGroups](#) to create dittoPlots that show summarized expression (or values for metadata), across groups, of multiple vars in a single plot.

[dittoRidgePlot](#), [dittoRidgeJitter](#), and [dittoBoxPlot](#) for shortcuts to a few 'plots' input shortcuts

Examples

```
example(importDittoBulk, echo = FALSE)
myRNA

# Basic dittoPlot, with jitter behind a vlnplot (looks better with more cells)
dittoPlot(object = myRNA, var = "gene1", group.by = "timepoint")

# Color distinctly from the grouping variable using 'color.by'
dittoPlot(object = myRNA, var = "gene1", group.by = "timepoint",
          color.by = "conditions")

# Update the 'plots' input to change / reorder the data representations
dittoPlot(myRNA, "gene1", "timepoint",
          plots = c("vlnplot", "boxplot", "jitter"))
dittoPlot(myRNA, "gene1", "timepoint",
          plots = c("ridgeplot", "jitter"))

# Modify the look with intuitive inputs
dittoPlot(myRNA, "gene1", "timepoint",
          plots = c("vlnplot", "boxplot", "jitter"),
          boxplot.color = "white",
          main = "CD3E",
          legend.show = FALSE)

# Data can also be split in other ways with 'shape.by' or 'split.by'
dittoPlot(object = myRNA, var = "gene1", group.by = "timepoint",
          plots = c("vlnplot", "boxplot", "jitter"),
          shape.by = "clustering",
          split.by = "SNP") # single split.by element
dittoPlot(object = myRNA, var = "gene1", group.by = "timepoint",
          plots = c("vlnplot", "boxplot", "jitter"),
          split.by = c("groups", "SNP")) # row and col split.by elements
```

```

# For faceting, instead of using 'split.by', the target data can alternatively
# be given to 'extra.var' to have it added in the underlying dataframe, then
# faceting can be added manually for extra flexibility
dittoPlot(myRNA, "gene1", "clustering",
  plots = c("vlnplot", "boxplot", "jitter"),
  extra.var = "SNP") + facet_wrap("SNP", ncol = 1, strip.position = "left")

### Provided wrappers enable certain easy adjustments of the 'plots' parameter.
# Quickly make a Boxplot
dittoBoxPlot(myRNA, "gene1", group.by = "timepoint")

# Quickly make a Ridgeplot, with or without jitter
dittoRidgePlot(myRNA, "gene1", group.by = "timepoint")
dittoRidgeJitter(myRNA, "gene1", group.by = "timepoint")

```

dittoPlotVarsAcrossGroups

Generates a dittoPlot where data points are genes/metadata summaries, per groups, instead of individual values per cells/samples.

Description

Generates a dittoPlot where data points are genes/metadata summaries, per groups, instead of individual values per cells/samples.

Usage

```

dittoPlotVarsAcrossGroups(
  object,
  vars,
  group.by,
  color.by = group.by,
  split.by = NULL,
  summary.fxn = mean,
  cells.use = NULL,
  plots = c("vlnplot", "jitter"),
  assay = .default_assay(object),
  slot = .default_slot(object),
  adjustment = "z-score",
  swap.rownames = NULL,
  do.hover = FALSE,
  main = NULL,
  sub = NULL,
  ylab = "make",
  y.breaks = NULL,
  min = NULL,
  max = NULL,

```

```

xlab = group.by,
x.labels = NULL,
x.labels.rotate = NA,
x.reorder = NULL,
color.panel = dittoColors(),
colors = c(seq_along(color.panel)),
theme = theme_classic(),
jitter.size = 1,
jitter.width = 0.2,
jitter.color = "black",
jitter.position.dodge = boxplot.position.dodge,
do.raster = FALSE,
raster.dpi = 300,
boxplot.width = 0.2,
boxplot.color = "black",
boxplot.show.outliers = NA,
boxplot.fill = TRUE,
boxplot.position.dodge = vlnplot.width,
boxplot.linewidth = 1,
vlnplot.linewidth = 1,
vlnplot.width = 1,
vlnplot.scaling = "area",
ridgeplot.linewidth = 1,
ridgeplot.scale = 1.25,
ridgeplot.ymax.expansion = NA,
ridgeplot.shape = c("smooth", "hist"),
ridgeplot.bins = 30,
ridgeplot.binwidth = NULL,
add.line = NULL,
line.linetype = "dashed",
line.color = "black",
split.nrow = NULL,
split.ncol = NULL,
split.adjust = list(),
legend.show = TRUE,
legend.title = NULL,
data.out = FALSE
)

```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
vars	String vector (example: c("gene1", "gene2", "gene3")) which selects which variables, typically genes, to extract from the object, summarize across groups, and add to the plot
group.by	String representing the name of a metadata to use for separating the cells/samples into discrete groups.
color.by	String representing the name of a metadata to use for setting fills. Great for

	highlighting subgroups when wanted, but it defaults to <code>group.by</code> so this input can be skipped otherwise. Affects <code>boxplot</code> , <code>vlnplot</code> , and <code>ridgeplot</code> fills.
<code>split.by</code>	<p>1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with <code>ggplot</code> faceting.</p> <p>When 2 metadatas are named, <code>c(row,col)</code>, the first is used as rows and the second is used for columns of the resulting grid.</p> <p>When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code></p>
<code>summary.fxn</code>	A function which sets how variables' data will be summarized across the groups. Default is <code>mean</code> , which will take the average value, but any function can be used as long as it takes in a numeric vector and returns a single numeric value. Alternative examples: <code>median</code> , <code>max</code> , or <code>function(x) mean(x!=0)</code> .
<code>cells.use</code>	<p>String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included.</p> <p>Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.</p>
<code>plots</code>	String vector which sets the types of plots to include: possibilities = "jitter", "boxplot", "vlnplot", "ridgeplot". Order matters: <code>c("vlnplot", "boxplot", "jitter")</code> will put a violin plot in the back, boxplot in the middle, and then individual dots in the front. See details section for more info.
<code>assay, slot</code>	single strings or integer that set which data to use when plotting expressin data. See <code>gene</code> for more information about how defaults for these are filled in when not provided.
<code>adjustment</code>	<p>When plotting gene expression (or antibody, or other forms of counts data), should that data be used directly or should it be adjusted to be</p> <ul style="list-style-type: none"> • "z-score": DEFAULT, centered and scaled to produce a relative-to-mean z-score representation • NULL: no adjustment, the normal method for all other ditto expression plotting • "relative.to.max": divided by the maximum expression value to give percent of max values between [0,1]
<code>swap.rownames</code>	String. For <code>SummarizedExperiment</code> or <code>SingleCellExperiment</code> objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .
<code>do.hover</code>	Logical. Default = FALSE. If set to TRUE (and if there is a "jitter" in <code>plots</code>): the object will be converted to a <code>plotly</code> object in which underlying data about individual points will be displayed when you hover your cursor over them.
<code>main</code>	String which sets the plot title.
<code>sub</code>	String which sets the plot subtitle.
<code>ylab</code>	String which sets the y axis label. Default = a combination of the name of the summary function + <code>adjustment</code> + "expression". Set to NULL to remove.
<code>y.breaks</code>	Numeric vector, a set of breaks that should be used as major grid lines. <code>c(break1,break2,break3,etc.)</code> .
<code>min, max</code>	Scalars which control the zoom of the plot. These inputs set the minimum / maximum values of the data to show.

<code>xlab</code>	String which sets the grouping-axis label (=x-axis for box and violin plots, y-axis for ridgeplots). Set to NULL to remove.
<code>x.labels</code>	String vector, <code>c("label1","label2","label3",...)</code> which overrides the names of groupings.
<code>x.labels.rotate</code>	Logical which sets whether the labels should be rotated. Default: TRUE for violin and box plots, but FALSE for ridgeplots.
<code>x.reorder</code>	Integer vector. A sequence of numbers, from 1 to the number of groupings, for rearranging the order of x-axis groupings. Method: Make a first plot without this input. Then, treating the leftmost grouping as index 1, and the rightmost as index n. Values of <code>x.reorder</code> should be these indices, but in the order that you would like them rearranged to be. Recommendation for advanced users: If you find yourself coming back to this input too many times, an alternative solution that can be easier long-term is to make the target data into a factor, and to put its levels in the desired order: <code>factor(data, levels = c("level1", "level2", ...))</code> . <code>metaLevels</code> can be used to quickly get the identities that need to be part of this 'levels' input.
<code>color.panel</code>	String vector which sets the colors to draw from for plot fills.
<code>colors</code>	Integer vector, the indexes / order, of colors from <code>color.panel</code> to actually use. (Provides an alternative to directly modifying <code>color.panel</code> .)
<code>theme</code>	A ggplot theme which will be applied before dittoSeq adjustments. Default = <code>theme_classic()</code> . See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
<code>jitter.size</code>	Scalar which sets the size of the jitter shapes.
<code>jitter.width</code>	Scalar that sets the width/spread of the jitter in the x direction. Ignored in ridgeplots. Note for when <code>color.by</code> is used to split x-axis groupings into additional bins: ggplot does not shrink jitter widths accordingly, so be sure to do so yourself! Ideally, needs to be <code>0.5/num_subgroups</code> .
<code>jitter.color</code>	String which sets the color of the jitter shapes
<code>jitter.position.dodge</code>	Scalar which adjusts the relative distance between jitter widths when multiple subgroups exist per group.by grouping (a.k.a. when <code>group.by</code> and <code>color.by</code> are not equal). Similar to <code>boxplot.position.dodge</code> input & defaults to the value of that input so that BOTH will actually be adjusted when only, say, <code>boxplot.position.dodge = 0.3</code> is given.
<code>do.raster</code>	Logical. When set to TRUE, rasterizes the jitter plot layer, changing it from individually encoded points to a flattened set of pixels. This can be useful for editing in external programs (e.g. Illustrator) when there are many thousands of data points.
<code>raster.dpi</code>	Number indicating dots/pixels per inch (dpi) to use for rasterization. Default = 300.
<code>boxplot.width</code>	Scalar which sets the width/spread of the boxplot in the x direction
<code>boxplot.color</code>	String which sets the color of the lines of the boxplot

<code>boxplot.show.outliers</code>	Logical, whether outliers should be including in the boxplot. Default is FALSE when there is a jitter plotted, TRUE if there is no jitter.
<code>boxplot.fill</code>	Logical, whether the boxplot should be filled in or not. Known bug: when boxplot fill is turned off, outliers do not render.
<code>boxplot.position.dodge</code>	Scalar which adjusts the relative distance between boxplots when multiple are drawn per grouping (a.k.a. when <code>group.by</code> and <code>color.by</code> are not equal). By default, this input actually controls the value of <code>jitter.position.dodge</code> unless the <code>jitter</code> version is provided separately.
<code>boxplot.linewidth</code>	Scalar which adjusts the thickness of boxplot lines.
<code>vlplot.linewidth</code>	Scalar which sets the thickness of the line that outlines the violin plots.
<code>vlplot.width</code>	Scalar which sets the width/spread of violin plots in the x direction
<code>vlplot.scaling</code>	String which sets how the widths of the of violin plots are set in relation to each other. Options are "area", "count", and "width". If the default is not right for your data, I recommend trying "width". For an explanation of each, see geom_violin .
<code>ridgeplot.linewidth</code>	Scalar which sets the thickness of the ridgeplot outline.
<code>ridgeplot.scale</code>	Scalar which sets the distance/overlap between ridgeplots. A value of 1 means the tallest density curve just touches the baseline of the next higher one. Higher numbers lead to greater overlap. Default = 1.25
<code>ridgeplot.ymax.expansion</code>	Scalar which adjusts the minimal space between the topmost grouping and the top of the plot in order to ensure the curve is not cut off by the plotting grid. The larger the value, the greater the space requested. When left as NA, dittoSeq will attempt to determine an ideal value itself based on the number of groups & linear interpolation between these goal posts: #groups of 3 or fewer: 0.6; #groups=12: 0.1; #groups or 34 or greater: 0.05.
<code>ridgeplot.shape</code>	Either "smooth" or "hist", sets whether ridges will be smoothed (the typical, and default) versus rectangular like a histogram. (Note: as of the time shape "hist" was added, combination of jittered points is not supported by the stat_binline that dittoSeq relies on.)
<code>ridgeplot.bins</code>	Integer which sets how many chunks to break the x-axis into when <code>ridgeplot.shape = "hist"</code> . Overridden by <code>ridgeplot.binwidth</code> when that input is provided.
<code>ridgeplot.binwidth</code>	Integer which sets the width of chunks to break the x-axis into when <code>ridgeplot.shape = "hist"</code> . Takes precedence over <code>ridgeplot.bins</code> when provided.
<code>add.line</code>	numeric value(s) where one or multiple line(s) should be added
<code>line.linetype</code>	String which sets the type of line for <code>add.line</code> . Defaults to "dashed", but any ggplot linetype will work.

<code>line.color</code>	String that sets the color(s) of the add.line line(s)
<code>split.nrow, split.ncol</code>	Integers which set the dimensions of faceting/splitting when a single metadata is given to <code>split.by</code> .
<code>split.adjust</code>	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code> . For options, when giving 1 metadata to <code>split.by</code> , see facet_wrap , OR when giving 2 metadatas to <code>split.by</code> , see facet_grid .
<code>legend.show</code>	Logical. Whether the legend should be displayed. Default = TRUE.
<code>legend.title</code>	String or NULL, sets the title for the main legend which includes colors and data representations.
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot (p) and data (data).

Details

Generally, this function will output a dittoPlot where each data point represents a gene (or metadata) rather than a cell/sample. Values are the summary (mean by default) of the values for each gene or metadata requested with `vars`, within each group set by `group.by`.

To start with, the data for each element of `vars` is obtained. When elements are genes/features, `assay` and `slot` are utilized to determine which expression data to use, and `adjustment` determines if and how the expression data might be adjusted. By default, a z-score adjustment is applied to all gene/feature `vars`. Note that this adjustment is applied *before* cells/samples subsetting.

x-axis groupings are then determined using `group.by`, and data for each variable is summarized using the `summary.fxn`.

Finally, data is plotted with the data representation types in `plots`.

Value

a ggplot object

Alternatively when `data.out = TRUE`, a list containing the plot ("p") and the underlying data as a dataframe ("data").

Alternatively when `do.hover = TRUE`, a plotly converted version of the plot where additional data will be displayed when the cursor is hovered over jitter points.

Plot Customization

The `plots` argument determines the types of **data representation** that will be generated, as well as their order from back to front. Options are "jitter", "boxplot", "vlnplot", and "ridgeplot".

Each plot type has specific associated options which are controlled by variables that start with their associated string. For example, all jitter adjustments start with "jitter.", such as `jitter.size` and `jitter.width`.

Inclusion of "ridgeplot" overrides "boxplot" and "vlnplot" presence and changes the plot to be horizontal.

Additionally:

- **Colors can be adjusted** with `color.panel`.
- **Subgroupings:** `color.by` can be utilized to split major `group.by` groupings into subgroups. When this is done in y-axis plotting, `dittoSeq` automatically ensures the centers of all geoms will align, but users will need to manually adjust `jitter.width` to less than $0.5/\text{num_subgroups}$ to avoid overlaps. There are also three inputs through which one can use to control geom-center placement, but the easiest way to do all at once so is to just adjust `vlnplot.width!` The other two: `boxplot.position.dodge`, and `jitter.position.dodge`.
- **Line(s) can be added** at single or multiple value(s) by providing these values to `add.line`. Linetype and color are set with `line.linetype`, which is "dashed" by default, and `line.color`, which is "black" by default.
- **Titles and axes labels** can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.title` arguments.
- The **legend can be hidden** by setting `legend.show = FALSE`.
- **y-axis zoom and tick marks** can be adjusted using `min`, `max`, and `y.breaks`.
- **x-axis labels and groupings** can be changed / reordered using `x.labels` and `x.reorder`, and rotation of these labels can be turned on/off with `x.labels.rotate = TRUE/FALSE`.
- **Shapes used** in conjunction with `shape.by` can be adjusted with `shape.panel`.

Author(s)

Daniel Bunis

See Also

[dittoPlot](#) and [multi_dittoPlot](#) for plotting of single or multiple expression and metadata vars, each as separate plots, on a per cell/sample basis.

[dittoDotPlot](#) for an alternative representation of per-group summaries of multiple vars where all vars are displayed separately, but still in a single plot.

Examples

```
example(importDittoBulk, echo = FALSE)

# Pick a set of genes
genes <- getGenes(myRNA)[1:30]

dittoPlotVarsAcrossGroups(
  myRNA, genes, group.by = "timepoint")

# Color can be controlled separately from grouping with 'color.by'
# Just note: all groupings must map to a single color.
dittoPlotVarsAcrossGroups(myRNA, genes, "timepoint",
  color.by = "conditions")

# To change it to have the violin plot in the back, a jitter on
# top of that, and a white boxplot with no fill in front:
dittoPlotVarsAcrossGroups(myRNA, genes, "timepoint",
  plots = c("vlnplot", "jitter", "boxplot"),
```

```

    boxplot.color = "white",
    boxplot.fill = FALSE)

## Data can be summarized in other ways by changing the summary.fxn input.
# median
dittoPlotVarsAcrossGroups(myRNA, genes, "timepoint",
    summary.fxn = median,
    adjustment = NULL)
# Percent non-zero expression (= boring for this fake data)
percent <- function(x) {sum(x!=0)/length(x)}
dittoPlotVarsAcrossGroups(myRNA, genes, "timepoint",
    summary.fxn = percent,
    adjustment = NULL)

# To investigate the identities of outlier genes, we can turn on hovering
# (if the plotly package is available)
if (requireNamespace("plotly", quietly = TRUE)) {
    dittoPlotVarsAcrossGroups(
        myRNA, genes, "timepoint",
        do.hover = TRUE)
}

```

dittoScatterPlot *Show RNAseq data overlaid on a scatter plot*

Description

Show RNAseq data overlaid on a scatter plot

Usage

```

dittoScatterPlot(
  object,
  x.var,
  y.var,
  color.var = NULL,
  shape.by = NULL,
  split.by = NULL,
  extra.vars = NULL,
  cells.use = NULL,
  show.others = FALSE,
  split.show.all.others = TRUE,
  size = 1,
  opacity = 1,
  color.panel = dittoColors(),
  colors = seq_along(color.panel),
  split.nrow = NULL,
  split.ncol = NULL,

```

```
split.adjust = list(),
assay.x = .default_assay(object),
slot.x = .default_slot(object),
adjustment.x = NULL,
assay.y = .default_assay(object),
slot.y = .default_slot(object),
adjustment.y = NULL,
assay.color = .default_assay(object),
slot.color = .default_slot(object),
adjustment.color = NULL,
assay.extra = .default_assay(object),
slot.extra = .default_slot(object),
adjustment.extra = NULL,
swap.rownames = NULL,
shape.panel = c(16, 15, 17, 23, 25, 8),
rename.color.groups = NULL,
rename.shape.groups = NULL,
min.color = "#F0E442",
max.color = "#0072B2",
min = NULL,
max = NULL,
order = c("unordered", "increasing", "decreasing", "randomize"),
xlab = x.var,
ylab = y.var,
main = "make",
sub = NULL,
theme = theme_bw(),
do.hover = FALSE,
hover.data = NULL,
hover.assay = .default_assay(object),
hover.slot = .default_slot(object),
hover.adjustment = NULL,
do.contour = FALSE,
contour.color = "black",
contour.linetype = 1,
add.trajectory.lineages = NULL,
add.trajectory.curves = NULL,
trajectory.cluster.meta,
trajectory.arrow.size = 0.15,
do.letter = FALSE,
do.ellipse = FALSE,
do.label = FALSE,
labels.size = 5,
labels.highlight = TRUE,
labels.repel = TRUE,
labels.split.by = split.by,
legend.show = TRUE,
legend.color.title = color.var,
```

```

    legend.color.size = 5,
    legend.color.breaks = waiver(),
    legend.color.breaks.labels = waiver(),
    legend.shape.title = shape.by,
    legend.shape.size = 5,
    do.raster = FALSE,
    raster.dpi = 300,
    data.out = FALSE
  )

```

Arguments

<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>x.var</code> , <code>y.var</code>	Single string giving a gene or metadata that will be used for the x- and y-axis of the scatterplot. Note: must be continuous. Alternatively, can be a directly supplied numeric vector of length equal to the total number of cells/samples in object.
<code>color.var</code>	Single string giving a gene or metadata that will set the color of cells/samples in the plot. Alternatively, can be a directly supplied numeric or string vector or a factor of length equal to the total number of cells/samples in object.
<code>shape.by</code>	Single string giving a metadata (Note: must be discrete.) that will set the shape of cells/samples in the plot. Alternatively, can be a directly supplied string vector or a factor of length equal to the total number of cells/samples in object.
<code>split.by</code>	1 or 2 strings naming discrete metadata to use for splitting the cells/samples into multiple plots with ggplot faceting. When 2 metadatas are named, <code>c(row,col)</code> , the first is used as rows and the second is used for columns of the resulting grid. When 1 metadata is named, shape control can be achieved with <code>split.nrow</code> and <code>split.ncol</code>
<code>extra.vars</code>	String vector providing names of any extra metadata to be stashed in the dataframe supplied to <code>ggplot(data)</code> . Useful for making custom alterations <i>after</i> dittoSeq plot generation.
<code>cells.use</code>	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
<code>show.others</code>	Logical. FALSE by default, whether other cells should be shown in the background in light gray.
<code>split.show.all.others</code>	Logical which sets whether gray "others" cells of facets should include all cells of other facets (TRUE) versus just cells left out by <code>cell.use</code> (FALSE).
<code>size</code>	Number which sets the size of data points. Default = 1.

opacity	Number between 0 and 1. Great for when you have MANY overlapping points, this sets how solid the points should be: 1 = not see-through at all. 0 = invisible. Default = 1. (In terms of typical ggplot variables, = alpha)
color.panel	String vector which sets the colors to draw from. <code>dittoColors()</code> by default, see dittoColors for contents.
colors	Integer vector, the indexes / order, of colors from <code>color.panel</code> to actually use
split.nrow, split.ncol	Integers which set the dimensions of faceting/splitting when a single metadata is given to <code>split.by</code> .
split.adjust	A named list which allows extra parameters to be pushed through to the faceting function call. List elements should be valid inputs to the faceting functions, e.g. <code>'list(scales = "free")'</code> . For options, when giving 1 metadata to <code>split.by</code> , see facet_wrap , OR when giving 2 metadatas to <code>split.by</code> , see facet_grid .
assay.x, assay.y, assay.color, assay.extra, slot.x, slot.y, slot.color, slot.extra, adjustment.x, adjustment.y	assay, slot, and adjustment set which data to use when the axes, coloring, or extra.vars are based on expression/counts data. See gene for additional information.
swap.rownames	String. For <code>SummarizedExperiment</code> or <code>SingleCellExperiment</code> objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .
shape.panel	Vector of integers corresponding to ggplot shapes which sets what shapes to use. When discrete groupings are supplied by <code>shape.by</code> , this sets the panel of shapes. When nothing is supplied to <code>shape.by</code> , only the first value is used. Default is a set of 6, <code>c(16, 15, 17, 23, 25, 8)</code> , the first being a simple, solid, circle. Note: Unfortunately, shapes can be hard to see when points are on top of each other & they are more slowly processed by the brain. For these reasons, even as a color blind person myself writing this code, I recommend use of colors for variables with many discrete values.
rename.color.groups, rename.shape.groups	String vector containing new names for the identities of the color or shape overlay groups.
min.color	color for min value of <code>color.var</code> data. Default = yellow
max.color	color for max value of <code>color.var</code> data. Default = blue
min, max	Number which sets the values associated with the minimum or maximum colors.
order	String. If the data should be plotted based on the order of the color data, sets whether to plot (from back to front) in "increasing", "decreasing", "randomize" order. If left as "unordered", plot order is simply based on the order of cells within the object.
xlab, ylab	Strings which set the labels for the axes. To remove, set to NULL.
main	String, sets the plot title. A default title is automatically generated if based on <code>color.var</code> and <code>shape.by</code> when either are provided. To remove, set to NULL.
sub	String, sets the plot subtitle.

theme	A ggplot theme which will be applied before dittoSeq adjustments. Default = <code>theme_bw()</code> . See https://ggplot2.tidyverse.org/reference/ggtheme.html for other options and ideas.
do.hover	Logical which controls whether the object will be converted to a plotly object so that data about individual points will be displayed when you hover your cursor over them. <code>hover.data</code> argument is used to determine what data to use.
hover.data	String vector of gene and metadata names, example: <code>c("meta1", "gene1", "meta2", "gene2")</code> which determines what data to show on hover when <code>do.hover</code> is set to TRUE.
hover.assay, hover.slot, hover.adjustment	Similar to the <code>x</code> , <code>y</code> , <code>color</code> , and <code>extra</code> versions, when showing expression data upon hover, these set what data will be shown.
do.contour	Logical. Whether density-based contours should be displayed.
contour.color	String that sets the color(s) of the <code>do.contour</code> contours.
contour.linetype	String or numeric which sets the type of line used for <code>do.contour</code> contours. Defaults to "solid", but see linetype for other options.
add.trajectory.lineages	List of vectors representing trajectory paths, each from start-cluster to end-cluster, where vector contents are the names of clusters provided in the <code>trajectory.cluster.meta</code> input. If the slingshot package was used for trajectory analysis, you can provide <code>add.trajectory.lineages = slingLineages('object')</code> .
add.trajectory.curves	List of matrices, each representing coordinates for a trajectory path, from start to end, where matrix columns represent <code>x</code> and <code>y</code> coordinates of the paths.
trajectory.cluster.meta	String name of metadata containing the clusters that were used for generating trajectories. Required when plotting trajectories using the <code>add.trajectory.lineages</code> method. Names of clusters inside the metadata should be the same as the contents of <code>add.trajectory.lineages</code> vectors.
trajectory.arrow.size	Number representing the size of trajectory arrows, in inches. Default = 0.15.
do.letter	Logical which sets whether letters should be added on top of the colored dots. For extended colorblindness compatibility. NOTE: <code>do.letter</code> is ignored if <code>do.hover = TRUE</code> or <code>shape.by</code> is provided a metadata because lettering is incompatible with plotly and with changing the dots' to be different shapes.
do.ellipse	Logical. Whether the groups should be surrounded by median-centered ellipses.
do.label	Logical. Whether to add text labels near the center (median) of clusters for grouping vars.
labels.size	Size of the the labels text
labels.highlight	Logical. Whether the labels should have a box behind them
labels.repel	Logical, that sets whether the labels' placements will be adjusted with ggrepel to avoid intersections between labels and plot bounds. TRUE by default.

<code>labels.split.by</code>	String of one or two metadata names which controls the facet-split calculations for label placements. Defaults to <code>split.by</code> , so generally there is no need to adjust this except when you are utilizing the <code>extra.vars</code> input to achieve manual faceting control.
<code>legend.show</code>	Logical. Whether any legend should be displayed. Default = TRUE.
<code>legend.color.title</code> , <code>legend.shape.title</code>	Strings which set the title for the color or shape legends.
<code>legend.color.size</code> , <code>legend.shape.size</code>	Numbers representing the size at which shapes should be plotted in the color and shape legends (for discrete variable plotting). Default = 5. *Enlarging the icons in the colors legend is incredibly helpful for making colors more distinguishable by color blind individuals.
<code>legend.color.breaks</code>	Numeric vector which sets the discrete values to label in the color-scale legend for continuous data.
<code>legend.color.breaks.labels</code>	String vector, with same length as <code>legend.breaks</code> , which sets the labels for the tick marks of the color-scale.
<code>do.raster</code>	Logical. When set to TRUE, rasterizes the internal plot layer, changing it from individually encoded points to a flattened set of pixels. This can be useful for editing in external programs (e.g. Illustrator) when there are many thousands of data points.
<code>raster.dpi</code>	Number indicating dots/pixels per inch (dpi) to use for rasterization. Default = 300.
<code>data.out</code>	Logical. When set to TRUE, changes the output, from the plot alone, to a list containing the plot ("p"), a data.frame containing the underlying data for target cells ("Target_data"), and a data.frame containing the underlying data for non-target cells ("Others_data").

Details

This function creates a dataframe with X, Y, color, shape, and faceting data determined by `x.var`, `y.var`, `color.var`, `shape.var`, and `split.by`. Any extra gene or metadata requested with `extra.var` is added as well. For expression/counts data, `assay`, `slot`, and `adjustment` inputs (`.x`, `.y`, and `.color`) can be used to change which data is used, and if it should be adjusted in some way.

Next, if a set of cells or samples to use is indicated with the `cells.use` input, then the dataframe is split into `Target_data` and `Others_data` based on subsetting by the target cells/samples.

Finally, a scatter plot is created using these dataframes. Non-target cells are colored in gray if `show.others=TRUE`, and target cell data is displayed on top, colored and shaped based on the `color.var`- and `shape.by`-associated data. If `split.by` was used, the plot will be split into a matrix of panels based on the associated groupings.

Value

a ggplot scatterplot where colored dots and/or shapes represent individual cells/samples. X and Y axes can be gene expression, numeric metadata, or manually supplied values.

Alternatively, if `data.out=TRUE`, a list containing three slots is output: the plot (named `'p'`), a `data.table` containing the underlying data for target cells (named `'Target_data'`), and a `data.table` containing the underlying data for non-target cells (named `'Others_data'`).

Alternatively, if `do.hover` is set to `TRUE`, the plot is converted from `ggplot` to `plotly` & cell/sample information, determined by the `hover.data` input, is retrieved, added to the dataframe, and displayed upon hovering the cursor over the plot.

Many characteristics of the plot can be adjusted using discrete inputs

- `size` and `opacity` can be used to adjust the size and transparency of the data points.
- Colors used can be adjusted with `color.panel` and/or `colors` for discrete data, or `min.color`, `max.color`, and `max.color` for continuous data.
- Shapes used can be adjusted with `shape.panel`.
- Color and shape labels can be changed using `rename.color.groups` and `rename.shape.groups`.
- Titles and axes labels can be adjusted with `main`, `sub`, `xlab`, `ylab`, and `legend.title` arguments.
- Legends can also be adjusted in other ways, using variables that all start with "legend." for easy tab completion lookup.

Author(s)

Daniel Bunis and Jared Andrews

See Also

[getGenes](#) and [getMetas](#) to see what the `x.var`, `y.var`, `color.var`, `shape.by`, and `hover.data` options are of an object.

[dittoDimPlot](#) for making very similar data representations, but where dimensionality reduction (PCA, t-SNE, UMAP, etc.) dimensions are the scatterplot axes.

[dittoDimHex](#) and [dittoScatterHex](#) for showing very similar data representations, but where nearby cells are summarized together in hexagonal bins.

Examples

```
example(importDittoBulk, echo = FALSE)
myRNA

# Mock up some nCount_RNA and nFeature_RNA metadata
# == the default way to extract
myRNA$nCount_RNA <- runif(60,200,1000)
myRNA$nFeature_RNA <- myRNA$nCount_RNA*runif(60,0.95,1.05)
# and also percent.mito metadata
myRNA$percent.mito <- sample(c(runif(50,0,0.05),runif(10,0.05,0.2)))

dittoScatterPlot(
  myRNA, x.var = "nCount_RNA", y.var = "nFeature_RNA")

# Shapes or colors can be overlaid representing discrete metadata
```

```

# or (only colors) continuous metadata / expression data by providing
# metadata or gene names to 'color.var' and 'shape.by'
dittoScatterPlot(
  myRNA, x.var = "gene1", y.var = "gene2",
  color.var = "groups",
  shape.by = "SNP",
  size = 3)
dittoScatterPlot(
  myRNA, x.var = "gene1", y.var = "gene2",
  color.var = "gene3")

# Note: scatterplots like this can be very useful for dataset QC, especially
# with percentage of mitochondrial reads as the color overlay.
dittoScatterPlot(myRNA,
  x.var = "nCount_RNA", y.var = "nFeature_RNA",
  color.var = "percent.mito")

# Data can be "split" or faceted by a discrete variable as well.
dittoScatterPlot(myRNA, x.var = "gene1", y.var = "gene2",
  split.by = "timepoint") # single split.by element
dittoScatterPlot(myRNA, x.var = "gene1", y.var = "gene2",
  split.by = c("groups","SNP")) # row and col split.by elements
# OR with 'extra.vars' plus manually faceting for added control
dittoScatterPlot(myRNA, x.var = "gene1", y.var = "gene2",
  extra.vars = c("SNP")) +
  facet_wrap("SNP", ncol = 1, strip.position = "left")

# Countours can also be added to help illuminate overlapping samples
dittoScatterPlot(myRNA, x.var = "gene1", y.var = "gene2",
  do.contour = TRUE)

```

dittoSeq

dittoSeq

Description

This package was built to make the visualization of single-cell and bulk RNA-sequencing data pipeline-agnostic and accessible for both experienced and novice coders, and for color vision impaired individuals.

Details

Includes many plotting functions ([dittoPlot](#), [dittoDimPlot](#), [dittoBarPlot](#), [dittoHeatmap](#), ...), helper functions ([meta](#), [gene](#), [isMeta](#), [getMetas](#), ...), and color adjustment functions ([Simulate](#), [Darken](#), [Lighten](#)), to aid in making sense of RNA sequencing data. All included plotting functions produce a ggplot object (or [pheatmap](#) / [Heatmap](#) for [dittoHeatmap](#)) by default and can spit out a full plot with just a few arguments. Many additional arguments are available for customization to generate complex, publication-ready figures.

Default `dittoColors` are color blindness friendly and adapted from [Wong B, "Points of view: Color blindness." Nature Methods, 2011.](#)

To report bugs, suggest new features, or ask for help, the best method is to create an issue on the [github](#), [here](#), or the bioconductor support site (be sure to tag 'dittoSeq' so that I get a notification!), [here](#)

Author(s)

Daniel Bunis

gene	<i>Returns the expression values of a gene for all cells/samples</i>
------	--

Description

Returns the expression values of a gene for all cells/samples

Usage

```
gene(
  gene,
  object,
  assay = .default_assay(object),
  slot = .default_slot(object),
  adjustment = NULL,
  adj.fxn = NULL,
  swap.rownames = NULL
)
```

Arguments

gene	quoted "gene" name = REQUIRED. the gene whose expression data should be retrieved.
object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
assay, slot	single strings or integer that set which data to use. Seurat and SingleCellExperiments deal with these differently, so be sure to check the documentation for whichever object you are using. When not provided, these typical defaults for the provided object class are used: <ul style="list-style-type: none"> • SingleCellExperiment (single-cell or bulk data): assay = "logcounts", "normcounts", "counts", or the first element of assays(object), slot not used • Seurat-v3: assay = DefaultAssay(object), slot = "data" • Seurat-v2: assay not used, slot = "data"
adjustment	Should expression data be used directly (default) or should it be adjusted to be <ul style="list-style-type: none"> • "z-score": scaled with the scale() function to produce a relative-to-mean z-score representation

- "relative.to.max": divided by the maximum expression value to give percent of max values between [0,1]

adj.fxn	A function which takes a vector (of metadata values) and returns a vector of the same length. For example, <code>function(x) {log2(x)}</code> or <code>as.factor</code>
swap.rownames	String. For <code>SummarizedExperiment</code> or <code>SingleCellExperiment</code> objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .

Value

Returns the expression values of a gene for all cells/samples.

Author(s)

Daniel Bunis

Examples

```
example(importDittoBulk, echo = FALSE)
gene("gene1", object = myRNA, assay = "counts")

# z-scored
gene("gene1", object = myRNA, assay = "counts",
      adjustment = "z-score")

# Log2'd
gene("gene1", object = myRNA, assay = "counts",
      adj.fxn = function(x) {log2(x)})

# To see expression of the gene for the default assay that dittoSeq would use
# leave out the assay input
# (For this object, the default assay is the logcounts assay)
gene("gene1", myRNA)

# Seurat (raw counts)
if (!requireNamespace("Seurat")) {
  gene("CD14", object = Seurat::pbmc, assay = "RNA", slot = "counts")
}
```

getGenes

Returns the names of all genes of a target object.

Description

Returns the names of all genes of a target object.

Usage

```
getGenes(object, assay = .default_assay(object), swap.rownames = NULL)
```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
assay	Single string or integer that sets which set of seq data inside the object to check.
swap.rownames	String. For SummarizedExperiment or SingleCellExperiment objects, the column name of rowData(object) to be used to identify features instead of rownames(object).

Value

A string vector, returns the names of all genes of the object for the requested assay.

Author(s)

Daniel Bunis

See Also

[isGene](#) for returning all genes in an object
[gene](#) for obtaining the expression data of genes

Examples

```
example(importDittoBulk, echo = FALSE)
getGenes(object = myRNA, assay = "counts")

# To see all genes of an object for the default assay that dittoSeq would use
# leave out the assay input
getGenes(myRNA)

# Seurat
# pbmc <- Seurat::pbmc_small
# # To see all genes of an object of a particular assay
# getGenes(pbmc, assay = "RNA")
```

getMetas

Returns the names of all meta.data slots of a target object.

Description

Returns the names of all meta.data slots of a target object.

Usage

```
getMetas(object, names.only = TRUE)
```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
names.only	Logical, TRUE by default, which sets whether just the names should be output versus the entire metadata dataframe.

Value

A string vector of the names of all metadata slots of the object, or alternatively the entire dataframe of metadata if `names.only` is set to `FALSE`

Author(s)

Daniel Bunis

See Also

[isMeta](#) for checking if certain metadata slots exist in an object
[meta](#) for obtaining the contents of metadata slots

Examples

```
example(importDittoBulk, echo = FALSE)

# To see all metadata slots of an object
getMetas(myRNA)

# To retrieve the entire metadata matrix
getMetas(myRNA, names.only = FALSE)
```

getReductions	<i>Returns the names of all dimensionality reduction slots of a target object.</i>
---------------	--

Description

Returns the names of all dimensionality reduction slots of a target object.

Usage

```
getReductions(object)
```

Arguments

object A Seurat, SingleCellExperiment, or SummarizedExperiment object.

Value

A string vector of the names of all dimensionality reduction slots of the object. These represent the options for the reduction.use input of `dittoDimPlot`.

Author(s)

Daniel Bunis

Examples

```
example("addDimReduction", echo = FALSE)

# To see all metadata slots of an object
getReductions(myRNA)
```

importDemux	<i>Extracts Demuxlet information into a pre-made SingleCellExperiment or Seurat object</i>
-------------	--

Description

Extracts Demuxlet information into a pre-made SingleCellExperiment or Seurat object

Usage

```
importDemux(
  object,
  raw.cell.names = NULL,
  lane.meta = NULL,
  lane.names = NA,
  demuxlet.best,
  trim.before_ = TRUE,
  bypass.check = FALSE,
  verbose = TRUE
)
```

Arguments

object A pre-made Seurat(v3+) or SingleCellExperiment object to add demuxlet information to.

<code>raw.cell.names</code>	A string vector consisting of the raw cell barcodes of the object as they would have been output by <code>cellranger aggr</code> . Format per <code>cell.name</code> = <code>NNN...NNN-#</code> where <code>NNN...NNN</code> are the cell barcode nucleotides, and <code>#</code> is the lane number. This input should be used when additional information has been added directly into the cell names outside of Seurat's standard merge prefix: <code>"user-text_"</code> .
<code>lane.meta</code>	A string which names a metadata slot that contains which cells came from which droplet-generation wells.
<code>lane.names</code>	String vector which sets how the lanes should be named (if you want to give them something different from the default = <code>Lane1</code> , <code>Lane2</code> , <code>Lane3...</code>)
<code>demuxlet.best</code>	String or String vector pointing to the location(s) of the <code>.best</code> output file from running of <code>demuxlet</code> . Alternatively, a <code>data.frame</code> representing an already imported <code>.best</code> matrix.
<code>trim.before_</code>	Logical which sets whether any characters in front of an <code>"_"</code> should be deleted from the <code>raw.cell.names</code> before matching with <code>demuxlet</code> barcodes.
<code>bypass.check</code>	Logical which sets whether the function should run even when <code>meta.data</code> slots would be over-written.
<code>verbose</code>	whether to print messages about the stage of this process that is currently being run & also the summary at the end.

Details

The function takes in a previously generated Seurat or `SingleCellExperiment` (SCE) object.

It also takes in `demuxlet` information either in the form of: (1) the location of a single `demuxlet.best` out file, (2) the locations of multiple `demuxlet.best` output files, (3) a user-constructed `data.frame` created by reading in a `demuxlet.best` file.

Then it matches barcodes and adds `demuxlet`-information to the Seurat or SCE as metadata.

For a note on how best to utilize this function with multi-lane droplet-based data, see the devoted section below.

Specifically:

1. If a metadata slot name is provided to `lane.meta`, information in that metadata slot is copied into a metadata slot called "Lane". Alternatively, if `lane.meta` is left as `NULL`, separate lanes are assumed to be marked by distinct values of `"-#"` at the end of cell names, as is the typical output of the 10X `cellranger count` & `aggr` pipeline.

- (1a. If `demuxlet.best` was provided as a set of separate file locations (recommended usage in conjunction with `'cellranger aggr'`), the `"-#"` at the ends of `BARCODES` columns from these files are incremented on read-in so that they can match the incrementation applied by `cellranger aggr`. See the section on multi-lane `scRNAseq` for more.)

2. Barcodes in the `demuxlet .best` data are then matched to barcodes in the object. The cell names, `colnames(object)`, are used by default for this matching, but if these have been modified from what would have been given to `demuxlet` – outside of `-#` at the end or `***_`'s at the beginning, as can be added in common merge functions – `raw.cell.names` can be provided and these cell names used instead.

3. Singlet/doublet/ambiguous calls and sample identities (1st only for doublets) are parsed and carried into metadata.

4. Finally, a summary of the results including mean number of SNPs and percentages of singlets and doublets is output unless verbose is set to FALSE.

Value

The Seurat or SingleCellExperiment object with metadata added for "Sample" calls and other relevant statistics.

Metadata Added

Lane information and demuxlet calls and statistics are imported into the object as these metadata:

- Lane = guided by lane.met a import input or "-#"s in barcodes, represents the separate droplet-generation lanes.
- Sample = The sample call, parsed from the BEST column
- demux.doublet.call = whether the sample was a singlet (SNG), doublet (DBL), or ambiguous (AMB), parsed from the BEST column
- demux.RD.TOTL = RD.TOTL column
- demux.RD.PASS = RD.PASS column
- demux.RD.UNIQ = RD.UNIQ column
- demux.N.SNP = N.SNP column
- demux.PRB.DBL = PRB.DBL column
- demux.barcode.dup = (Only generated when TRUEs will exist) whether a cell's barcode in the demuxlet.best referred to only 1 cell in the object. (When TRUE, indicates that cells from distinct lanes were interpreted together by demuxlet. These will often be mistakenly called as doublets.)

For data from multi-(droplet-gen-)lane scRNAseq

There are many different ways such data might initially be processed which will affect its accessibility to importDemux().

Initial Processing: 10X recommends running cellranger counts individually for each well/lane. Non-10X droplet-based data from separate lanes should also be processed separately, at least for the steps of collecting reads for individual cells. NOT processing such droplet lanes separately will create artificial doublets from cells that ended up with similar barcodes, but in separate droplet-gen lanes. Thus, proper processing initially leads to creation of separate counts matrices for each droplet-generation lane.

Combining data from each lane: These per-lane counts matrices can be combined in various ways. All options will alter the cell barcode names in a way that makes them unique across lanes, but this unification is achieved varies.

Counts table combination methods generally do not adjust adjust BAM files – specifically the cell names embedded within the BAM files which is demuxlet uses for its BARCODEs column. Thus cell names data may needs to be modified in a proper way in order to make the object's cell names and demuxlet.best's BARCODEs match.

Running Demuxlet: Demuxlet should also be run, separately, on the BAM files of each individual lane. Improperly running demuxlet on a combined BAM file can lead to loss of lane information and

then to generation of artificial doublet calls for cells of distinct wells that received similar barcodes. The BAM file associated with each demuxlet run is what is used for generating the BARCODE column of the demuxlet output.

How importDemux() handles barcode matching: importDemux is built to work with the 'cellranger aggr' pipeline by default, but can be used for demuxlet datasets processed differently as well (Option 2).

- Option 1: When you merge matrices of all lanes with **cellranger aggr before R import**, aggr's barcode unification method is to increment a "-1", "-2", "-3", ... "-#" that is appended to the end of all barcode names. The number is incremented for each successive lane. Note that lane-numbers depend on the order in which they were supplied to cellranger aggr.
 - **to use:** Simply supply a demuxlet.best a vector containing the locations of the separate '.best' outputs for each lane, *in the same order that lanes were provided to aggr*. importDemux will adjust the "-#" in the demuxlet.best BARCODEs automatically before performing the matching step.
- Option 2: When you instead **import** your counts data into a Seurat or SingleCellExperiment, and **then merge** the separate objects into one, the unification method is dependent on your particular method.
 - **to use:** For these methods, it is easiest to 1) *import* your counts data, 2) transfer in your demuxlet info with *importDemux()* to each lane's object individually (You can supply unique lane identifiers to the lane.names input.), and then 3) *merge* the separate objects.
- Extra notes for any alternative cases:
 - For Seurat's merge(), user-defined strings can be appended to the start of the barcodes, followed by an "_". By default, importDemux() will ignore these, but such ignorance can be controlled with the trim.before_ input.
 - Alternatively, cell names that are consistent with the demuxlet.best BARCODEs can be supplied to the raw.cell.names input.

Author(s)

Daniel Bunis

See Also

Included QC visualizations:

[demux.calls.summary](#) for plotting the number of sample annotations assigned within each lane.

[demux.SNP.summary](#) for plotting the number of SNPs measured per cell.

Or, see Kang et al. Nature Biotechnology, 2018 <https://www.nature.com/articles/nbt.4042> for more information about the demuxlet cell-sample deconvolution method.

Examples

```
#Prep: loading in an example dataset and sample demuxlet data
example("importDittoBulk", echo = FALSE)
demux <- demuxlet.example
colnames(myRNA) <- demux$BARCODE[seq_len(ncol(myRNA))]
```

```

###
### Method 1: Lanes info stored in a metadata
###

# Notice there is a groups metadata in this Seurat object.
getMetas(myRNA)
# We will treat these as if that holds Lane information

# Now, running importDemux:
myRNA <- importDemux(
  myRNA,
  lane.meta = "groups",
  demuxlet.best = demux)

# Note, importDemux can also take in the location of the .best file.
# myRNA <- importDemux(
#   object = myRNA,
#   lane.meta = "groups",
#   demuxlet.best = "Location/filename.best")

# demux.SNP.summary() and demux.calls.summary() can now be used.
demux.SNP.summary(myRNA)
demux.calls.summary(myRNA)

###
### Method 2: cellranger aggr combined data (denoted with "-#" in barcodes)
###

# If cellranger aggr was used, lanes will be denoted by "-1", "-2", ... "-#"
# at the ends of Seurat cellnames.
# Demuxlet should be run on each lane individually.
# Provided locations of each demuxlet.best output file, *in the same order
# that lanes were provided to cellranger aggr* this function will then
# adjust the "-#" within the .best BARCODEs automatically before matching
#
# myRNA <- importDemux(
#   object = myRNA,
#   demuxlet.best = c(
#     "Location/filename1.best",
#     "Location/filename2.best"),
#   lane.names = c("g1", "g2"))

```

importDittoBulk

import bulk sequencing data into a SingleCellExperiment format that will work with other dittoSeq functions.

Description

import bulk sequencing data into a SingleCellExperiment format that will work with other dittoSeq functions.

Usage

```
importDittoBulk(x, reductions = NULL, metadata = NULL, combine_metadata = TRUE)
```

Arguments

- x** A `DGEList`, or `SummarizedExperiment` (includes `DESeqDataSet`) class object containing the sequencing data to be imported.
- Alternatively, for import from a raw matrix format, a named list of matrices (or matrix-like objects) where names will become the assay names of the eventual SCE.
- NOTE: As of dittoSeq version 1.1.11, all dittoSeq functions can work directly with `SummarizedExperiment` objects, so this import function is no longer required for such data.
- reductions** A named list of dimensionality reduction embeddings matrices. Names will become the names of the dimensionality reductions and how each will be used with the `reduction.use` input of `dittoDimPlot` and `dittoDimHex`.
- For each matrix, rows of the matrices should represent the different samples of the dataset, and columns the different dimensions.
- metadata** A `data.frame` (or `data.frame`-like object) where rows represent samples and named columns represent the extra information about such samples that should be accessible to visualizations. The names of these columns can then be used to retrieve and plot such data in any dittoSeq visualization.
- combine_metadata** Logical which sets whether original `colData` (`DESeqDataSet/SummarizedExperiment`) or `$samples` (`DGEList`) from `x` should be retained.
- When `x` is a `SummarizedExperiment` or `DGEList`:
- When `FALSE`, sample metadata inside `x` (`colData` or `$samples`) is ignored entirely.
 - When `TRUE` (the default), metadata inside `x` is combined with what is provided to the `metadata` input; but names must be unique, so when there are similarly named slots, the **values provided to the metadata input take priority**.

Value

A `SingleCellExperiment` object...

that contains all assays (`SummarizedExperiment`; includes `DESeqDataSets`), all standard slots (`DGEList`; see below for specifics), or expression matrices of the input `x`, as well as any dimensionality reductions provided to `reductions`, and any provided `metadata` stored in `colData`.

Note about SummarizedExperiments

As of dittoSeq version 1.1.11, all dittoSeq functions can work directly with `SummarizedExperiment` objects, so this import function is no longer required for such data.

Note on assay names

One recommended assay to create if it is not already present in your dataset, is a log-normalized version of the counts data. The `logNormCounts` function of the `scater` package is an easy way to make such a slot.

`dittoSeq` visualizations default to grabbing expression data from an assay named `logcounts > normcounts > counts`

See Also

[SingleCellExperiment](#) for more information about this storage structure.

Examples

```
library(SingleCellExperiment)

# Generate some random data
nsamples <- 60
exp <- matrix(rpois(1000*nsamples, 20), ncol=nsamples)
colnames(exp) <- paste0("sample", seq_len(ncol(exp)))
rownames(exp) <- paste0("gene", seq_len(nrow(exp)))
logexp <- log2(exp + 1)

# Dimensionality Reductions
pca <- matrix(runif(nsamples*5,-2,2), nsamples)
tsne <- matrix(rnorm(nsamples*2), nsamples)

# Some Metadata
conds <- factor(rep(c("condition1", "condition2"), each=nsamples/2))
timept <- rep(c("d0", "d3", "d6", "d9"), each = 15)
genome <- rep(c(rep(TRUE,7),rep(FALSE,8)), 4)
grps <- sample(c("A","B","C","D"), nsamples, TRUE)
cclus <- as.character(1*(tsne[,1]>0&tsne[,2]>0) +
  2*(tsne[,1]<0&tsne[,2]>0) +
  3*(tsne[,1]>0&tsne[,2]<0) +
  4*(tsne[,1]<0&tsne[,2]<0))

score1 <- seq_len(nsamples)/2
score2 <- rnorm(nsamples)

### We can import the counts directly
myRNA <- importDittoBulk(
  x = list(counts = exp,
    logcounts = logexp))

### Adding metadata & PCA or other dimensionality reductions
# We can add these directly during import, or after.
myRNA <- importDittoBulk(
  x = list(counts = exp,
    logcounts = logexp),
  metadata = data.frame(
    conditions = conds,
    timepoint = timept,
```

```

        SNP = genome,
        groups = grps),
    reductions = list(
        pca = pca))

myRNA$clustering <- clusts

myRNA <- addDimReduction(
    myRNA,
    embeddings = tsne,
    name = "tsne")

# (other packages SCE manipulations can also be used)

### When we import from SummarizedExperiment, all metadata is retained.
# The object is just 'upgraded' to hold extra slots.
# The output is the same, aside from a message when metadata are replaced.
se <- SummarizedExperiment(
    list(counts = exp, logcounts = logexp))
myRNA <- importDittoBulk(
    x = se,
    metadata = data.frame(
        conditions = conds,
        timepoint = timept,
        SNP = genome,
        groups = grps,
        clustering = clusts,
        score1 = score1,
        score2 = score2),
    reductions = list(
        pca = pca,
        tsne = tsne))
myRNA

### For DESeq2, how we might have made this:
# DESeqDataSets are SummarizedExperiments, and behave similarly
# library(DESeq2)
# dds <- DESeqDataSetFromMatrix(
#     exp, data.frame(conditions), ~ conditions)
# dds <- DESeq(dds)
# dds_ditto <- importDittoBulk(dds)

### For edgeR, DGELists are a separate beast.
# dittoSeq imports what I know to commonly be inside them, but please submit
# an issue on the github (dtm2451/dittoSeq) if more should be retained.
# library(edgeR)
# dgelist <- DGEList(counts=exp, group=conditions)
# dge_ditto <- importDittoBulk(dgelist)

```

isBulk *Retrieve whether a given object would be treated as bulk versus single-cell by dittoSeq*

Description

Retrieve whether a given object would be treated as bulk versus single-cell by dittoSeq

Usage

```
isBulk(object)
```

Arguments

object A target Seurat, SingleCellExperiment, or SummarizedExperiment object

Value

Logical: whether the provided object would be treated as bulk data by dittoSeq.

- TRUE for SummarizedExperiments that are not SCEs, and for SCEs with \$bulk = TRUE in their internal metadata.
- FALSE for any other object type and for SCEs without such internal metadata

See Also

[setBulk](#) to (add to and) set the internal metadata of an SCE to say whether the object represents bulk data.

Examples

```
example(importDittoBulk, echo = FALSE)
myRNA

isBulk(myRNA)

scRNA <- setBulk(myRNA, FALSE)
isBulk(scRNA)
```

isGene *Tests if input is the name of a gene in a target object.*

Description

Tests if input is the name of a gene in a target object.

Usage

```
isGene(
  test,
  object,
  assay = .default_assay(object),
  return.values = FALSE,
  swap.rownames = NULL
)
```

Arguments

<code>test</code>	String or vector of strings, the "potential.gene.name"(s) to check for.
<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>assay</code>	single string or integer that sets which set of seq data inside the object to check.
<code>return.values</code>	Logical which sets whether the function returns a logical TRUE/FALSE versus the TRUE test values . Default = FALSE REQUIRED, unless 'DEFAULT <- "object"' has been run.
<code>swap.rownames</code>	String. For SummarizedExperiment or SingleCellExperiment objects, the column name of <code>rowData(object)</code> to be used to identify features instead of <code>rownames(object)</code> .

Value

Returns a logical vector indicating whether each instance in `test` is a rowname within the requested assay of the object. Alternatively, returns the values of `test` that were indeed rownames if `return.values = TRUE`.

Author(s)

Daniel Bunis

See Also

[getGenes](#) for returning all genes in an object
[gene](#) for obtaining the expression data of genes

Examples

```
example(importDittoBulk, echo = FALSE)

# To see the first 10 genes of an object of a particular assay
getGenes(myRNA, assay = "counts")[1:10]

# To see all genes of an object for the default assay that dittoSeq would use
# leave out the assay input (again, remove `head()`)
head(getGenes(myRNA))

# To test if something is a gene in an object:
```



```

isGene("gene1", object = myRNA) # TRUE
isGene("CD12345", myRNA) # FALSE

# To test if many things are genes of an object
isGene(c("gene1", "gene2", "not-a-gene", "CD12345"), myRNA)

# 'return.values' input is especially useful in these cases.
isGene(c("gene1", "gene2", "not-a-gene", "CD12345"), myRNA,
       return.values = TRUE)

```

isMeta

Tests if an input is the name of a meta.data slot in a target object.

Description

Tests if an input is the name of a meta.data slot in a target object.

Usage

```
isMeta(test, object, return.values = FALSE)
```

Arguments

test	String or vector of strings, the "potential.metadata.name"(s) to check for.
object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
return.values	Logical which sets whether the function returns a logical TRUE/FALSE versus the TRUE test values . Default = FALSE

Details

For Seurat objects, also returns TRUE for the input "ident" because, for all dittoSeq visualizations, "ident" will retrieve a Seurat objects' clustering slot.

Value

Returns a logical or logical vector indicating whether each instance in test is a meta.data slot within the object. Alternatively, returns the values of test that were indeed metadata slots if return.values = TRUE.

Author(s)

Daniel Bunis

See Also

[getMetas](#) for returning all metadata slots of an object
[meta](#) for obtaining the contents of metadata slots

Examples

```

example(importDittoBulk, echo = FALSE)

# To check if something is a metadata slot
isMeta("timepoint", object = myRNA) # FTRUE
isMeta("nCount_RNA", object = myRNA) # FALSE

# To test if many things are metadata of an object
isMeta(c("age", "groups"), myRNA) # FALSE, TRUE

# 'return.values' input is especially useful in these cases.
isMeta(c("age", "groups"), myRNA,
       return.values = TRUE)

# Alternatively, to see all metadata slots of an object, use getMetas
getMetas(myRNA)

```

Lighten

Lightens input colors by a set amount

Description

A wrapper for the `lighten` function of the `colorspace` package.

Usage

```
Lighten(colors, percent.change = 0.25, relative = TRUE)
```

Arguments

`colors` the color(s) input. Can be a list of colors, for example, `/codedittoColors()`.

`percent.change` # between 0 and 1. the percentage to darken by. Defaults to 0.25 if not given.

`relative` TRUE/FALSE. Whether the percentage should be a relative change versus an absolute one. Default = TRUE.

Value

Return a lighter version of the color in hexadecimal color form (= "#RRGGBB" in base 16)

Author(s)

Daniel Bunis

Examples

```

Lighten("blue") #"blue" = "#0000FF"
#Output: "#4040FF"
Lighten(dittoColors()[1:8]) #Works for multiple color inputs as well.

```

meta	<i>Returns the values of a meta.data for all cells/samples</i>
------	--

Description

Returns the values of a meta.data for all cells/samples

Usage

```
meta(meta, object, adjustment = NULL, adj.fxn = NULL)
```

Arguments

meta	String, the name of the "metadata" slot to grab. OR "ident" to retrieve the clustering of a Seurat object.
object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
adjustment	A recognized string indicating whether numeric metadata should be used directly (default) versus adjusted to be <ul style="list-style-type: none"> • "z-score": scaled with the scale() function to produce a relative-to-mean z-score representation • "relative.to.max": divided by the maximum expression value to give percent of max values between [0,1] <p>Ignored if the target metadata is not numeric.</p>
adj.fxn	A function which takes a vector (of metadata values) and returns a vector of the same length. For example, function(x) {log2(x)} or as.factor

Details

Retrieves the values of a metadata slot from object, or the clustering slot if meta = "ident" and the object is a Seurat.

If adjustment or adj.fxn are provided, then these requested adjustments are applied to these values (adjustment first). Note: Alterations via adjustment are only applied when metadata is numeric, but adj.fxn alterations are applied to metadata of any type.

Lastly, outputs these values are named as the cells'/samples' names.

Value

A named vector.

Author(s)

Daniel Bunis

See Also

[metaLevels](#) for returning just the unique discrete identities that exist within a metadata slot

[getMetas](#) for returning all metadata slots of an object

[isMeta](#) for testing whether something is the name of a metadata slot

Examples

```
example(importDittoBulk, echo = FALSE)
meta("groups", object = myRNA)

myRNA$numbers <- seq_len(ncol(myRNA))
meta("numbers", myRNA, adjustment = "z-score")
meta("numbers", myRNA, adj.fxn = as.factor)
meta("numbers", myRNA, adj.fxn = function(x) {log2(x)})
```

metaLevels

Gives the distinct values of a meta.data slot (or ident)

Description

Gives the distinct values of a meta.data slot (or ident)

Usage

```
metaLevels(meta, object, cells.use = NULL, used.only = TRUE)
```

Arguments

meta	quoted "meta.data.slot" name = REQUIRED. the meta.data slot whose potential values should be retrieved.
object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
cells.use	String vector of cells'/samples' names OR an integer vector specifying the indices of cells/samples which should be included. Alternatively, a Logical vector, the same length as the number of cells in the object, which sets which cells to include.
used.only	TRUE by default, for target metadata that are factors, whether levels nonexistent in the target data should be ignored.

Value

String vector, the distinct values of a metadata slot (factor or not) among all cells/samples, or for a subset of cells/samples. (Alternatively, returns the distinct values of clustering if meta = "ident" and the object is a Seurat object).

Author(s)

Daniel Bunis

See Also

[meta](#) for returning an entire metadata slots of an object, not just the potential levels

[getMetas](#) for returning all metadata slots of an object

[isMeta](#) for testing whether something is the name of a metadata slot

Examples

```
example(importDittoBulk, echo = FALSE)

metaLevels("clustering", object = myRNA)

# Note: Set 'used.only' (default = TRUE) to FALSE to show unused levels
# of metadata that are already factors. By default, only the in use options
# of a metadata are shown.
metaLevels("clustering", myRNA,
  used.only = FALSE)
```

multi_dittoDimPlot *Generates dittoDimPlots for multiple features.*

Description

Generates dittoDimPlots for multiple features.

Usage

```
multi_dittoDimPlot(
  object,
  vars,
  ncol = NULL,
  nrow = NULL,
  axes.labels.show = FALSE,
  list.out = FALSE,
  OUT.List = NULL,
  ...,
  xlab = NA,
  ylab = NA,
  data.out = FALSE,
  do.hover = FALSE,
  legend.show = FALSE
)
```

Arguments

<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>vars</code>	<code>c("var1", "var2", "var3", ...)</code> . A vector of vars ('var' in regular <code>dittoDimPlot</code>) from which to generate the separate plots.
<code>ncol, nrow</code>	Integer or NULL. How many columns or rows the plots should be arranged into.
<code>axes.labels.show</code>	Logical. Whether axis labels should be shown. Subordinate to <code>xlab</code> and <code>ylab</code> .
<code>list.out</code>	Logical. (Default = FALSE) When set to TRUE, a list of the individual plots, named by the vars being shown in each, is output instead of the combined multi-plot.
<code>OUT.List</code>	Deprecated. Use <code>list.out</code>
<code>..., xlab, ylab, data.out, do.hover, legend.show</code>	other parameters passed to <code>dittoDimPlot</code> .

Details

Given multiple 'var' parameters to vars, this function creates a `dittoDimPlot` for each one, with minor defaulting tweaks (see below).

By default, these dittoDimPlots are arranged into a grid. Alternatively, if `list.out` is set to TRUE, they are output as a list with each plot named as the vars being shown.

All parameters that can be adjusted in `dittoDimPlot` can be adjusted here, but the only input that will change between plots is var.

Value

A set of dittoDimPlots either arranged into a grid (default), or output as a list.

Slight tweaks to dittoDimPlot defaults

- axes labels are not shown by default to save space (control with `axes.labels.show` or `xlab` and `ylab`)
- legends are also not shown to save space (control with `legend.show`)

Author(s)

Daniel Bunis

See Also

`multi_dittoDimPlotVaryCells` for an alternate `dittoDimPlot` multi-plotter where the cells/samples are varied between plots.

`dittoDimPlot` for the base dittoDimPlot plotting function and details on all accepted inputs.

Examples

```
example(importDittoBulk, echo = FALSE)

multi_dittoDimPlot(myRNA, c("gene1", "gene2", "clustering"))

# Control grid shape with ncol / nrow
multi_dittoDimPlot(myRNA, c("gene1", "gene2", "clustering"),
  nrow = 1)

# Output as list instead
multi_dittoDimPlot(myRNA, c("gene1", "gene2", "clustering"),
  list.out = TRUE)
```

multi_dittoDimPlotVaryCells

Generates multiple dittoDimPlots, for a single feature, where each showing different cells

Description

Generates multiple dittoDimPlots, for a single feature, where each showing different cells

Usage

```
multi_dittoDimPlotVaryCells(
  object,
  var,
  vary.cells.meta,
  vary.cells.levels = metaLevels(vary.cells.meta, object),
  show.titles = TRUE,
  show.allcells.plot = TRUE,
  allcells.main = "All Cells",
  show.legend.single = TRUE,
  show.legend.plots = FALSE,
  show.legend.allcells.plot = FALSE,
  nrow = NULL,
  ncol = NULL,
  list.out = FALSE,
  OUT.List = NULL,
  ...,
  assay = .default_assay(object),
  slot = .default_slot(object),
  adjustment = NULL,
  min = NULL,
  max = NULL,
  color.panel = dittoColors(),
```

```

    colors = seq_along(color.panel),
    data.out = FALSE,
    do.hover = FALSE,
    swap.rownames = NULL
  )

```

Arguments

<code>object</code>	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
<code>var</code>	String name of a "gene" or "metadata" (or "ident" for a Seurat object) to use for coloring the plots. This is the data that will be displayed, using colors, for each cell/sample. Alternatively, can be a vector of same length as there are cells/samples in the object. Discrete or continuous data both work.
<code>vary.cells.meta</code>	String name of a metadata that should be used for selecting which cells to show in each "VaryCells" <code>dittoDimPlot</code> .
<code>vary.cells.levels</code>	The values/groupings of the <code>vary.cells.meta</code> metadata for which to generate a plot.
<code>show.titles</code>	Logical which sets whether grouping-levels should be used as titles for the individual VaryCell plots. Default = TRUE.
<code>show.allcells.plot</code>	Logical which sets whether an additional plot showing all of the cells should be added.
<code>allcells.main</code>	String which adjusts the title of the allcells plot. Default = "All Cells". Set to NULL to remove.
<code>show.legend.single</code>	Logical which sets whether to add a single legend as an additional plot. Default = TRUE.
<code>show.legend.plots</code>	Logical which sets whether or not legends should be plotted in individual VaryCell plots. Default = FALSE.
<code>show.legend.allcells.plot</code>	Logical which sets whether or a legend should be plotted in the allcells plot. Default = FALSE.
<code>ncol, nrow</code>	Integers which set dimensions of the plot grid when <code>list.out = FALSE</code> .
<code>list.out</code>	Logical which controls whether the list of plots should be returned as a list instead of as a single grid arrangement of the plots.
<code>OUT.List</code>	Deprecated. Use <code>list.out</code>
<code>..., color.panel, colors, min, max, assay, slot, adjustment, data.out, do.hover, swap.rownames</code>	additional parameters passed to <code>dittoDimPlot</code> . All parameters of <code>dittoDimPlot</code> can be utilized and adjusted except for <code>cells.use</code> , <code>main</code> , and <code>legend.show</code> which are handled with alternative methods here. A few suggestions: <code>reduction.use</code> for setting which dimensionality reduction space to use. <code>xlab</code> and <code>ylab</code> can be set to NULL to remove the axes labels and provide extra room for the data. <code>size</code> can be used to adjust the size of the dots.

Details

This function generates separate dittoDimPlots that show the same target data, but each for distinct cells.

How cells are separated into distinct plots is controlled with the vary.cells.meta parameter. Individual dittoDimPlots are created for all levels of var.cells.meta groupings given to the vary.cells.levels input (default = all).

The function then appends a plot containing all cell/samples when show.allcells.plot = TRUE, with title of this plot controlled by allcells.main, as well as as single legend when show.legend.single = TRUE.

By default, these dittoDimPlots are output in a grid (default) with ncol columns and nrow rows. Alternatively, if list.out is set to TRUE, they are returned as a list. In the list, the VaryCell plots will be named by the levels of vary.cells.meta that they contain, and the optional allcells plot and single legend will be named "allcells" and "legend", respectively.

Either continuous or discrete var data can be displayed.

- For continuous data, the range of potential values is calculated at the start, and set, so that colors represent the same value across all plots.
- For discrete data, colors used in each plot are adjusted so that colors represent the same groupings across all plots.

Value

A set of dittoDimPlots either arranged into a grid (default), or output as a list.

Author(s)

Daniel Bunis

See Also

[multi_dittoDimPlot](#) for an alternate dittoDimPlot multi-plotter where vars are varied across plots rather than cells/samples

[dittoDimPlot](#) for the base dittoDimPlot plotting function and details on all accepted inputs.

Examples

```
example(importDittoBulk, echo = FALSE)

# This function can be used to quickly scan for differences in expression
# within or across clusters/cell types.
multi_dittoDimPlotVaryCells(myRNA, "gene1", vary.cells.meta = "clustering")

# Output as list instead
multi_dittoDimPlotVaryCells(myRNA, "gene1", vary.cells.meta = "clustering",
  list.out = TRUE)

# This function is also great for generating separate plots of each individual
# grouping of a tsne/PCA/umap. This can be useful to check for dispersion
```

```

# of groups that might otherwise be hidden behind other cells/samples.
# The effect is similar to faceting, but: all distinct plots are treated
# separately rather than being just a part of the whole, and with portrayal
# of all cells/samples in an additional plot by default.
#
# To do so, set 'var' and 'vary.cells.meta' the same.
multi_dittoDimPlotVaryCells(myRNA, "clustering", vary.cells.meta = "clustering")

# The function can also be used to quickly visualize how separate clustering
# resolutions match up to each other, or perhaps how certain conditions of
# cells disperse across clusters.
# (For an alternative method of viewing, and easily quantifying, how discrete
# conditions of cells disperse across clusters, see '?dittoBarPlot')
multi_dittoDimPlotVaryCells(myRNA, "groups", vary.cells.meta = "clustering")

```

multi_dittoPlot	<i>Generates dittoPlots for multiple features.</i>
-----------------	--

Description

Generates dittoPlots for multiple features.

Usage

```

multi_dittoPlot(
  object,
  vars,
  group.by,
  ncol = 3,
  nrow = NULL,
  main = "var",
  ylab = NULL,
  list.out = FALSE,
  OUT.List = NULL,
  ...,
  xlab = NULL,
  data.out = FALSE,
  do.hover = FALSE,
  legend.show = FALSE
)

```

Arguments

object	A Seurat, SingleCellExperiment, or SummarizedExperiment object.
vars	c("var1", "var2", "var3", ...). A vector of gene or metadata names from which to generate the separate plots

<code>group.by</code>	String representing the name of a metadata to use for separating the cells/samples into discrete groups.
<code>ncol, nrow</code>	Integer or NULL. How many columns or rows the plots should be arranged into.
<code>main, ylab</code>	String which sets whether / how plot titles or y-axis labels should be added to each individual plot <ul style="list-style-type: none"> • When set to "var", the vars names alone will be used. • When set to "make", the default dittoPlot behavior will be observed: For y-axis labels, gene vars will become "'var' expression". Equivalent to "var" for main. • When set as any other string, that string will be used as the title / y-axis label for every plot. • When set to NULL, titles / axes labels will not be added.
<code>list.out</code>	Logical. (Default = FALSE) When set to TRUE, a list of the individual plots, named by the vars being shown in each, is output instead of the combined multi-plot.
<code>OUT.List</code>	Deprecated. Use <code>list.out</code>
<code>..., xlab, data.out, do.hover, legend.show</code>	other paramters passed along to dittoPlot .

Details

Given multiple 'var' parameters to vars, this function creates a [dittoPlot](#) for each one, with minor defaulting tweaks (see below).

By default, these dittoPlots are arranged into a grid. Alternatively, if `list.out` is set to TRUE, they are output as a list with each plot named as the vars being shown.

All parameters that can be adjusted in [dittoPlot](#) can be adjusted here, but the only input that will change between plots is the var.

Value

A set of dittoPlots either arranged into a grid (default), or output as a list.

Slight tweaks to dittoPlot defaults

- axes labels are not shown by default to save space (control with `xlab` and `ylab`)
- legends are also not shown to save space (control with `legend.show`)

Author(s)

Daniel Bunis

See Also

[dittoPlot](#) for the single plot version of this function and details on all accepted inputs.

[dittoDotPlot](#) and [dittoPlotVarsAcrossGroups](#) to show, in a single plot, per-group summaries of the values for multiple vars.

Examples

```

example(importDittoBulk, echo = FALSE)
genes <- getGenes(myRNA)[1:4]

multi_dittoPlot(myRNA,
  vars = c("gene1", "gene2", "gene3", "gene4"),
  group.by = "clustering")

#To make it output a grid that is 2x2, to add y-axis labels
# instead of titles, and to show legends...
multi_dittoPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  nrow = 2, ncol = 2,          #Make grid 2x2 (only one of these needed)
  main = NULL, ylab = "make",  #Add y axis labels instead of titles
  legend.show = TRUE)         #Show legends

# Output as list instead
multi_dittoPlot(myRNA, c("gene1", "gene2", "gene3", "gene4"), "clustering",
  list.out = TRUE)

```

setBulk	<i>Set whether a SingleCellExperiment object should be treated as bulk versus single-cell by dittoSeq</i>
---------	---

Description

Set whether a SingleCellExperiment object should be treated as bulk versus single-cell by dittoSeq

Usage

```

setBulk(object, set = TRUE)

## S4 method for signature 'SingleCellExperiment'
setBulk(object, set = TRUE)

```

Arguments

object	A target SingleCellExperiment object
set	Logical, whether the object should be considered as bulk (TRUE) or not (FALSE)

Value

A [SingleCellExperiment](#) object with "bulk" internal metadata set to set

Examples

```

example(importDittoBulk, echo = FALSE)
myRNA

isBulk(myRNA)

scRNA <- setBulk(myRNA, FALSE)
isBulk(scRNA)

# Now, if we make a heatmap with this data, we will see that single-cell
# defaults (ordering by the first 'annot.by' & cell names not shown) are used.
dittoHeatmap(scRNA, getGenes(scRNA)[1:30],
  annot.by = c("clustering", "groups"),
  main = "isBulk(object) == FALSE")

```

 Simulate

Simulates what a colorblind person would see for any dittoSeq plot!

Description

Essentially a wrapper function for `colorspace`'s `deutan()`, `protan()`, and `tritan()` functions. This function will output any dittoSeq plot as it might look to an individual with one of the common forms of colorblindness: deutanopia/deutanomaly, the most common, is when the cones mainly responsible for red vision are defective. Protanopia/protanomaly is when the cones mainly responsible for green vision are defective. In tritanopia/tritanomaly, the defective cones are responsible for blue vision. Note: there are more severe color deficiencies that are even more rare. Unfortunately, for these types of color vision deficiency, only non-color methods, like lettering or shapes, will do much to help.

Usage

```

Simulate(
  type = c("deutan", "protan", "tritan"),
  plot.function,
  ...,
  color.panel = dittoColors(),
  min.color = "#F0E442",
  max.color = "#0072B2"
)

```

Arguments

<code>type</code>	The type of colorblindness that you want to simulate for. Options: "deutan", "protan", "tritan". Anything else, and you will get an error.
<code>plot.function</code>	The plotting function that you want to use/simulate. not quoted. and make sure to remove the () that R will try to add.

... other paramters that can be given to dittoSeq plotting functions, including color.panel, used in exactly the same way they are used for those functions. (contrary to the look of this documentation, color.panel will still default to dittoColors() when not provided.)

color.panel, min.color, max.color
The set of colors to be used.

Value

Outputs a dittoSeq plot with the color.panel / min.color & max.color updated as it might look to a colorblind individual.

Note: Does not currently adjust dittoHeatmap.

Author(s)

Daniel Bunis

Examples

```
example(importDittoBulk, echo = FALSE)
Simulate("deutan", dittoDimPlot, object=myRNA, var="clustering", size = 2)
Simulate("protan", dittoDimPlot, myRNA, "clustering", size = 2)
Simulate("tritan", dittoDimPlot, myRNA, "clustering", size = 2)
```

Index

- * **datasets**
 - demuxlet.example, 9

- addDimReduction, 3, 5, 23
- addPrcomp, 3, 4

- Darken, 5, 74
- demux.calls.summary, 6, 9, 82
- demux.SNP.summary, 7, 7, 82
- demuxlet.example, 9
- dittoBarPlot, 10, 23, 36, 74
- dittoBoxPlot, 59
- dittoBoxPlot (dittoPlot), 52
- dittoColors, 14, 19, 47, 70, 75
- dittoDimHex, 23, 73
- dittoDimHex (dittoHex), 43
- dittoDimPlot, 3–5, 15, 50, 73, 74, 79, 94, 96, 97
- dittoDotPlot, 24, 66, 99
- dittoFreqPlot, 13, 29
- dittoHeatmap, 37, 74
- dittoHex, 43
- dittoPlot, 8, 9, 23, 28, 35, 52, 66, 74, 99
- dittoPlotVarsAcrossGroups, 28, 59, 60, 99
- dittoRidgeJitter, 59
- dittoRidgeJitter (dittoPlot), 52
- dittoRidgePlot, 59
- dittoRidgePlot (dittoPlot), 52
- dittoScatterHex, 23, 73
- dittoScatterHex (dittoHex), 43
- dittoScatterPlot, 23, 50, 67
- dittoSeq, 74

- facet_grid, 12, 18, 27, 47, 55, 65, 70
- facet_wrap, 12, 18, 27, 32, 47, 55, 65, 70

- gene, 18, 26, 39, 47, 54, 62, 70, 74, 75, 77, 88
- geom_violin, 34, 56, 64
- getGenes, 23, 50, 73, 76, 88
- getMetas, 23, 50, 73, 74, 77, 89, 92, 93

- getReductions, 23, 50, 78
- ggrepel, 20, 48, 71

- Heatmap, 40–42, 74

- importDemux, 7, 9, 79
- importDittoBulk, 3, 5, 23, 83
- isBulk, 86
- isGene, 77, 87
- isMeta, 74, 78, 89, 92, 93

- Lighten, 74, 90
- linetype, 21, 48, 71

- max, 62
- mean, 62
- median, 62
- meta, 74, 78, 89, 91, 93
- metaLevels, 12, 27, 31–33, 42, 55, 63, 92, 92
- multi_dittoDimPlot, 93, 97
- multi_dittoDimPlotVaryCells, 94, 95
- multi_dittoPlot, 28, 59, 66, 98

- pheatmap, 38–42, 74

- setBulk, 87, 100
- setBulk, SingleCellExperiment-method (setBulk), 100
- Simulate, 74, 101
- SingleCellExperiment, 3–5, 23, 84, 85, 100
- slingshot, 20, 48, 71
- stat_binline, 34, 57, 64
- SummarizedExperiment, 84