

# Package ‘iSEEhex’

March 22, 2023

**Title** iSEE extension for summarising data points in hexagonal bins

**Version** 1.0.0

**Date** 2022-06-16

**Description** This package provides panels summarising data points in hexagonal bins for `iSEE`. It is part of `iSEEu`, the iSEE universe of panels that extend the `iSEE` package.

**License** Artistic-2.0

**URL** <https://github.com/iSEE/iSEEhex>

**BugReports** <https://support.bioconductor.org/t/iSEEhex>

**biocViews** Software, Infrastructure

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.0

**Depends** SummarizedExperiment, iSEE

**Imports** ggplot2, hexbin, methods, shiny

**Suggests** BiocStyle, covr, knitr, RefManageR, rmarkdown, sessioninfo, testthat (>= 3.0.0), scRNAseq, scater

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/iSEEhex>

**git\_branch** RELEASE\_3\_16

**git\_last\_commit** 1e2f7ce

**git\_last\_commit\_date** 2022-11-01

**Date/Publication** 2023-03-22

**Author** Kevin Rue-Albrecht [aut, cre] (<<https://orcid.org/0000-0003-3899-3872>>),  
Charlotte Soneson [aut] (<<https://orcid.org/0000-0003-3833-2169>>),  
Federico Marini [aut] (<<https://orcid.org/0000-0003-3252-7758>>),  
Aaron Lun [aut] (<<https://orcid.org/0000-0002-3564-4813>>)

**Maintainer** Kevin Rue-Albrecht <[kevinrue67@gmail.com](mailto:kevinrue67@gmail.com)>

## R topics documented:

ReducedDimensionHexPlot-class . . . . .	2
<b>Index</b>	<b>4</b>

---

ReducedDimensionHexPlot-class

*The ReducedDimensionHexPlot class*

---

### Description

The ReducedDimensionHexPlot is a [ReducedDimensionPlot](#) subclass that is dedicated to creating a reduced dimension plot summarising data points in hexagonal bins.

### Slot overview

The following slots control the parameters used in the visualization:

- `BinResolution`, a numeric positive scalar specifying the number of hexagonal bins in both vertical and horizontal directions. Defaults to 100.

In addition, this class inherits all slots from its parent [ReducedDimensionPlot](#), [ColumnDotPlot](#), [DotPlot](#) and [Panel](#) classes.

### Constructor

`ReducedDimensionHexPlot(...)` creates an instance of a `ReducedDimensionHexPlot` class, where any slot and its value can be passed to `...` as a named argument.

### Supported methods

In the following code snippets, `x` is an instance of a [ReducedDimensionHexPlot](#) class. Refer to the documentation for each method for more details on the remaining arguments.

For defining the interface:

- `.panelColor(x)` will return the specified default color for this panel class.
- `.fullName(x)` will return "Hexagonal reduced dimension plot".
- `.hideInterface(x, field)` will return TRUE for `field="Downsample"` as downsampling is not applicable to this panel that summarizes all data points in each hexagonal bin; otherwise this function will call the [ReducedDimensionPlot](#) method.
- `.defineVisualShapeInterface(x)` will return NULL for this panel, as the shape aesthetic is not applicable to this panel that does not display individual data points.
- `.defineVisualSizeInterface(x)` overrides the equivalent method inherited from all parents classes and will return instead an HTML tag definition that contains a user input controlling the number of hexagonal bins in both vertical and horizontal directions.
- `.defineVisualOtherInterface(x)` will return NULL, as there are no additional visual parameters for this panel.

- `.allowableColorByDataChoices(x, se)` will return a character vector with the names of all continuous fields in `colData(se)`, where `se` is the input `SummarizedExperiment` object.

For monitoring reactive expressions:

- `.createObservers(x, se, input, session, pObjects, rObjects)` sets up observers for all new slots described above, as well as in the parent classes via the `ReducedDimensionPlot` method.

For creating the plot:

- `.generateDotPlot(x, envir)` will return a list with `plot`, a `ggplot2::ggplot()` object; and `commands`, a character vector of commands to produce that object when evaluated inside `envir`.

For documentation:

- `.definePanelTour(x)` returns an `data.frame` containing the steps of a panel-specific tour.
- `.getDotPlotColorHelp(x, color_choices)` returns a function that generates an `rintrojs` tour for the color choice UI.

### Author(s)

Kevin Rue-Albrecht

### See Also

[ReducedDimensionPlot](#), for the base class.

### Examples

```
library(scRNAseq)

# Example data ----
sce <- ReprocessedAllenData(assays="tophat_counts")
class(sce)

library(scater)
sce <- logNormCounts(sce, exprs_values="tophat_counts")

sce <- runPCA(sce, ncomponents=4)
sce <- runTSNE(sce)
rowData(sce)$ave_count <- rowMeans(assay(sce, "tophat_counts"))
rowData(sce)$n_cells <- rowSums(assay(sce, "tophat_counts") > 0)

# launch the app itself ----

if (interactive()) {
  iSEE(sce, initial=list(
    ReducedDimensionHexPlot(BinResolution=50),
    ReducedDimensionPlot()
  ))
}
```

# Index

[.allowableColorByDataChoices](#), [3](#)  
[.allowableColorByDataChoices, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.createObservers](#), [3](#)  
[.createObservers, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.definePanelTour](#), [3](#)  
[.definePanelTour, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.defineVisualOtherInterface](#), [2](#)  
[.defineVisualOtherInterface, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.defineVisualShapeInterface](#), [2](#)  
[.defineVisualShapeInterface, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.defineVisualSizeInterface](#), [2](#)  
[.defineVisualSizeInterface, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.fullName](#), [2](#)  
[.fullName, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.generateDotPlot](#), [3](#)  
[.generateDotPlot, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.getDotPlotColorHelp](#), [3](#)  
[.getDotPlotColorHelp, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)  
[.hideInterface](#), [2](#)  
[.hideInterface, ReducedDimensionHexPlot-method](#)  
 (ReducedDimensionHexPlot-class), [2](#)