

Package ‘trackViewer’

January 24, 2021

Type Package

Title A R/Bioconductor package with web interface for drawing elegant interactive tracks or lollipop plot to facilitate integrated analysis of multi-omics data

Version 1.26.0

Maintainer Jianhong Ou <jianhong.ou@duke.edu>

Description Visualize mapped reads along with annotation as track layers for NGS dataset such as ChIP-seq, RNA-seq, miRNA-seq, DNA-seq, SNPs and methylation data.

License GPL (>= 2)

Depends R (>= 3.5.0), grDevices, methods, GenomicRanges, grid

Imports GenomeInfoDb, GenomicAlignments, GenomicFeatures, Gviz, Rsamtools, S4Vectors, rtracklayer, BiocGenerics, scales, tools, IRanges, AnnotationDbi, grImport, htmlwidgets, plotrix, Rgraphviz, InteractionSet, graph, utils

Suggests biomaRt, TxDb.Hsapiens.UCSC.hg19.knownGene, RUnit, org.Hs.eg.db, BiocStyle, knitr, VariantAnnotation, httr, htmltools

biocViews Visualization

VignetteBuilder knitr

RoxygenNote 7.1.0

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/trackViewer>

git_branch RELEASE_3_12

git_last_commit b897542

git_last_commit_date 2020-10-27

Date/Publication 2021-01-23

Author Jianhong Ou [aut, cre] (<<https://orcid.org/0000-0002-8652-2488>>),
Julie Lihua Zhu [aut]

R topics documented:

| | |
|-------------------------------|---|
| trackViewer-package | 2 |
| addArrowMark | 3 |
| addGuideLine | 4 |

| | |
|------------------------|-----------|
| browseTracks | 5 |
| browseTracks-shiny | 6 |
| coverageGR | 6 |
| dandelion.plot | 7 |
| geneModelFromTxdb | 8 |
| geneTrack | 10 |
| getCurTrackViewport | 10 |
| getGeneIDsFromTxDb | 11 |
| getLocation | 12 |
| gi2track | 12 |
| gieStain | 13 |
| gridPlot | 13 |
| GRoperator | 14 |
| ideogramPlot | 15 |
| importBam | 16 |
| importData | 17 |
| importScore | 18 |
| loadIdeogram | 19 |
| lollipop | 20 |
| optimizeStyle | 21 |
| parse2GRanges | 22 |
| parseWIG | 23 |
| plotGInteractions | 23 |
| plotGRanges | 24 |
| plotIdeo | 25 |
| plotOneIdeo | 26 |
| pos-class | 27 |
| trackList-class | 27 |
| trackStyle-class | 28 |
| trackViewerStyle-class | 30 |
| viewGene | 31 |
| viewTracks | 32 |
| xscale-class | 33 |
| yaxisStyle-class | 33 |
| Index | 34 |

trackViewer-package *Minimal designed plotting tool for genomic data*

Description

A package that plot data and annotation information along genomic coordinates in an elegance style. This tool is based on Gviz but want to draw figures in minimal style for publication.

Author(s)

Maintainer: Jianhong Ou <jianhong.ou@duke.edu> ([ORCID](#))

Authors:

- Julie Lihua Zhu <Julie.Zhu@umassmed.edu>

Examples

```

library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
trs <- geneModelFromTxdb(TxDb.Hsapiens.UCSC.hg19.knownGene,
                        org.Hs.eg.db,
                        chrom="chr11",
                        start=122929275,
                        end=122930122)
extdata <- system.file("extdata", package="trackViewer",
                      mustWork=TRUE)
repA <- importScore(paste(extdata, "cpsf160.repA+.wig", sep="/"),
                  paste(extdata, "cpsf160.repA-.wig", sep="/"),
                  format="WIG")
strand(repA@dat) <- "+"
strand(repA@dat2) <- "-"
fox2 <- importScore(paste(extdata, "fox2.bed", sep="/"), format="BED")
dat <- coverageGR(fox2@dat)
fox2@dat <- dat[strand(dat)=="+"]
fox2@dat2 <- dat[strand(dat)=="-"]
gr <- GRanges("chr11", IRanges(122929275, 122930122), strand="-")
vp <- viewTracks(trackList(repA, fox2, trs), gr=gr, autoOptimizeStyle=TRUE)
addGuideLine(c(122929767, 122929969), vp=vp)
addArrowMark(list(x=unit(.5, "npc"),
                 y=unit(.39, "npc")),
             col="blue")

```

addArrowMark

Add arrow mark to the figure at a given position

Description

A function to add arrow mark for emphasizing peaks

Usage

```

addArrowMark(
  pos = grid.locator(),
  label = NULL,
  angle = 15,
  length = unit(0.25, "inches"),
  col = "red",
  cex = 1,
  quadrant = 4,
  type = "closed",
  vp = NULL
)

```

Arguments

pos A unit object representing the location of arrow mark to be placed at current viewport. Default is the value of `grid.locator`, which will get the location of the mouse click.

| | |
|----------|--|
| label | A character or expression vector. |
| angle | A parameter passed into grid::arrow function. The angle of arrow head in degrees (smaller numbers produce narrower, pointier arrows). Essentially describes the width of the arrow head. |
| length | A parameter passed into grid::arrow function. A unit specifying the length of the arrow head. |
| col | color of the arrow |
| cex | Multiplier applied to fontsize |
| quadrant | the direction of arrow, 1: to bottomleft, 2: to bottomright, 3: to topright, 4: to topleft |
| type | A parameter passed into grid::arrow function. One of "open" or "closed" indicating whether the arrow head should be a closed triangle. |
| vp | A Grid viewport object. It must be output of viewTracks |

Value

invisible x, y position value.

See Also

See Also as [addGuideLine](#), [arrow](#)

Examples

```
grid.newpage()
addArrowMark(list(x=unit(.5, "npc"),
                 y=unit(.5, "npc")),
             label="label1",
             col="blue")
## how to get the position by mouse click
if(interactive()){
  pos <- addArrowMark(label="byClick")
  addArrowMark(pos, label="samePosAsAbove")
}
```

| | |
|--------------|--------------------------------------|
| addGuideLine | <i>Add guide lines to the tracks</i> |
|--------------|--------------------------------------|

Description

A function to add lines for emphasizing the positions

Usage

```
addGuideLine(guideLine, col = "gray", lty = "dashed", lwd = 1, vp = NULL)
```

Arguments

| | |
|-----------|---|
| guideLine | The genomic coordinates to draw the lines |
| col | A vector for the line color |
| lty | A vector for the line type |
| lwd | A vector for the line width |
| vp | A Grid viewport object. It must be output of viewTracks |

See Also

See Also as [getCurTrackViewport](#), [addArrowMark](#), [viewTracks](#)

Examples

```
vp <- getCurTrackViewport(trackViewerStyle(), 10000, 10200)
addGuideLine(c(10010, 10025, 10150), vp=vp)
```

| | |
|--------------|----------------------|
| browseTracks | <i>browse tracks</i> |
|--------------|----------------------|

Description

browse tracks by a web browser.

Usage

```
browseTracks(
  trackList,
  gr = GRanges(),
  ignore.strand = TRUE,
  width = NULL,
  height = NULL,
  ...
)
```

Arguments

| | |
|---------------|---|
| trackList | an object of trackList |
| gr | an object of GRanges |
| ignore.strand | ignore the strand or not when do filter. default TRUE |
| width | width of the figure |
| height | height of the figure |
| ... | parameters not used |

Value

An object of class `htmlwidget` that will intelligently print itself into HTML in a variety of contexts including the R console, within R Markdown documents, and within Shiny output bindings.

Examples

```

extdata <- system.file("extdata", package="trackViewer", mustWork=TRUE)
files <- dir(extdata, "-.wig")
tracks <- lapply(paste(extdata, files, sep="/"),
                importScore, format="WIG")
tracks <- lapply(tracks, function(.ele) {strand(.ele@dat) <- "-"; .ele})
names(tracks) <- c("trackA", "trackB")
fox2 <- importScore(paste(extdata, "fox2.bed", sep="/"), format="BED")
dat <- coverageGR(fox2@dat)
fox2@dat <- dat[strand(dat)=="+"]
fox2@dat2 <- dat[strand(dat)=="-"]
gr <- GRanges("chr11", IRanges(122929275, 122930122))
browseTracks(trackList(tracks, fox2), gr=gr)

```

browseTracks-shiny *Shiny bindings for browseTracks*

Description

Output and render functions for using browseTracks within Shiny applications and interactive Rmd documents.

Usage

```

browseTracksOutput(outputId, width = "100%", height = "600px")

renderbrowseTracks(expr, env = parent.frame(), quoted = FALSE)

```

Arguments

| | |
|---------------|--|
| outputId | output variable to read from |
| width, height | Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended. |
| expr | An expression that generates a browseTracks |
| env | The environment in which to evaluate expr. |
| quoted | Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable. |

coverageGR *calculate coverage*

Description

calculate coverage for [GRanges](#), [GAlignments](#) or [GAlignmentPairs](#)

Usage

```
coverageGR(gr)
```

Arguments

`gr` an object of `GRanges`, `GAlignments` or `GAlignmentPairs`

Value

an object of `GRanges`

See Also

See Also as [coverage](#), [coverage-methods](#)

Examples

```
bed <- system.file("extdata", "fox2.bed", package="trackViewer",
                  mustWork=TRUE)
fox2 <- importScore(bed)
fox2$dat <- coverageGR(fox2$dat)
```

dandelion.plot

dandelion.plots

Description

Plot variants and somatic mutations

Usage

```
dandelion.plot(
  SNP.gr,
  features = NULL,
  ranges = NULL,
  type = c("fan", "circle", "pie", "pin"),
  newpage = TRUE,
  ylab = TRUE,
  ylab.gp = gpar(col = "black"),
  xaxis = TRUE,
  xaxis.gp = gpar(col = "black"),
  yaxis = FALSE,
  yaxis.gp = gpar(col = "black"),
  legend = NULL,
  cex = 1,
  maxgaps = 1/50,
  heightMethod = NULL,
  ...
)
```

Arguments

| | |
|-----------------------------|--|
| SNP.gr | A object of GRanges or GRangesList . All the width of GRanges must be 1. |
| features | A object of GRanges or GRangesList . |
| ranges | A object of GRanges or GRangesList . |
| type | Character. Could be fan, circle, pie or pin. |
| newpage | plot in the new page or not. |
| ylab | plot ylab or not. If it is a character vector, the vector will be used as ylab. |
| ylab.gp, xaxis.gp, yaxis.gp | An object of class gpar for ylab, xaxis or yaxis. |
| xaxis, yaxis | plot xaxis/yaxis or not. If it is a numeric vector with length greater than 1, the vector will be used as the points at which tick-marks are to be drawn. And the names of the vector will be used to as labels to be placed at the tick points if it has names. |
| legend | If it is a list with named color vectors, a legend will be added. |
| cex | cex will control the size of circle. |
| maxgaps | maxgaps between the stem of dandelions. It is calculated by the width of plot region divided by maxgaps. If a GRanges object is set, the dandelions stem will be clustered in each genomic range. |
| heightMethod | A function used to determine the height of stem of dandelion. eg. Mean. Default is length. |
| ... | not used. |

Details

In SNP.gr and features, metadata of the GRanges object will be used to control thecolor, fill, border, height, data source of pie if the type is pie.

Examples

```
SNP <- c(10, 100, 105, 108, 400, 410, 420, 600, 700, 805, 840, 1400, 1402)
SNP.gr <- GRanges("chr1", IRanges(SNP, width=1, names=paste0("snp", SNP)),
  score=sample.int(100, length(SNP))/100)
features <- GRanges("chr1", IRanges(c(1, 501, 1001),
  width=c(120, 500, 405),
  names=paste0("block", 1:3)),
  color="black",
  fill=c("#FF8833", "#51C6E6", "#DFA32D"),
  height=c(0.1, 0.05, 0.08))
dandelion.plot(SNP.gr, features, type="fan")
```

geneModelFromTxdb

Prepare gene model from an object of TxDb

Description

Generate an object of [track](#) for [viewTracks](#) by given parameters.

Usage

```
geneModelFromTxdb(  
  txdb,  
  orgDb,  
  gr,  
  chrom,  
  start,  
  end,  
  strand = c("*", "+", "-"),  
  txdump = NULL  
)
```

Arguments

| | |
|--------|---|
| txdb | An object of TxDb |
| orgDb | An object of "OrgDb" |
| gr | An object of GRanges. |
| chrom | chromosome name, must be a seqname of txdb |
| start | start position |
| end | end position |
| strand | strand |
| txdump | output of <code>as.list(txdb)</code> , a list of data frames that can be used to make the db again with no loss of information. |

Value

An object of [track](#)

See Also

See Also as [importScore](#), [importBam](#), [viewTracks](#)

Examples

```
library(TxDb.Hsapiens.UCSC.hg19.knownGene)  
library(org.Hs.eg.db)  
trs <- geneModelFromTxdb(TxDb.Hsapiens.UCSC.hg19.knownGene,  
  org.Hs.eg.db,  
  chrom="chr20",  
  start=22560000,  
  end=22565000,  
  strand="-")
```

geneTrack *track from TxDb*

Description

Generate a track object from TxDb by given gene ids

Usage

```
geneTrack(ids, txdb, symbols, type = c("gene", "transcript"), asList = TRUE)
```

Arguments

| | |
|---------|---|
| ids | Gene IDs. A vector of character. It should be keys in txdb. |
| txdb | An object of TxDb . |
| symbols | symbol of genes. |
| type | Output type of track, "gene" or "transcript". |
| asList | Output a list of tracks or not. Default TRUE. |

Value

An object of [track](#)

Examples

```
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
ids <- c("3312", "390259", "341056", "79827")
symbols <- mget(ids, org.Hs.egSYMBOL)
geneTrack(ids, TxDb.Hsapiens.UCSC.hg19.knownGene, symbols)
```

getCurTrackViewport *Get current track viewport*

Description

Get current track viewport for addGuideLine

Usage

```
getCurTrackViewport(curViewerStyle, start, end)
```

Arguments

| | |
|----------------|---|
| curViewerStyle | an object of trackViewerStyle |
| start | start position of current track |
| end | end position of current track |

Value

an object of [viewport](#)

See Also

See Also as [addGuideline](#)

Examples

```
vp <- getCurTrackViewport(trackViewerStyle(), 10000, 10200)
addGuideline(c(10010, 10025, 10150), vp=vp)
```

| | |
|---------------------------------|---|
| <code>getGeneIDsFromTxDb</code> | <i>get gene ids by genomic location</i> |
|---------------------------------|---|

Description

retrieve gene ids from txdb object by genomic location.

Usage

```
getGeneIDsFromTxDb(gr, txdb)
```

Arguments

- `gr` GRanges object.
- `txdb` An object of [TxDb](#).

Value

A character vector of gene ids

Examples

```
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
gr <- parse2GRanges("chr11:122,830,799-123,116,707")
ids <- getGeneIDsFromTxDb(gr, TxDb.Hsapiens.UCSC.hg19.knownGene)
```

getLocation *get genomic location by gene symbol*

Description

given a gene name, get the genomic coordinates.

Usage

```
getLocation(symbol, txdb, org)
```

Arguments

| | |
|--------|--|
| symbol | Gene symbol |
| txdb | txdb will be used to extract the genes |
| org | org package name |

Examples

```
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
getLocation("HSPA8", TxDb.Hsapiens.UCSC.hg19.knownGene, "org.Hs.eg.db")
```

gi2track *convert GInteractions to track object*

Description

Convert GInteractions object to track object

Usage

```
gi2track(gi)
```

Arguments

| | |
|----|----------------------------|
| gi | an object of GInteractions |
|----|----------------------------|

Value

an track object

Examples

```
gi <- readRDS(system.file("extdata", "nij.chr6.51120000.53200000.gi.rds", package="trackViewer"))
gi2track(gi)
```

| | |
|----------|---|
| gieStain | <i>color scheme for the schema for Chromosome Band (Ideogram)</i> |
|----------|---|

Description

Describe the colors of giemsa stain results

Usage

```
gieStain()
```

Value

A character vector of colors

Examples

```
gieStain()
```

| | |
|----------|------------------------------|
| gridPlot | <i>plot GRanges metadata</i> |
|----------|------------------------------|

Description

plot GRanges metadata for different types

Usage

```
gridPlot(gr, gp, type, xscale)
```

Arguments

| | |
|--------|---|
| gr | an object of GRanges with metadata. All metadata must be numeric. |
| gp | an object of gpar |
| type | type of the figure, could be barplot, line, point and heatmap |
| xscale | x scale of the viewport |

GRoperator

GRanges operator

Description

GRanges operations (add, subtract, multiply, divide)

Usage

```
GRoperator(
  A,
  B,
  col = "score",
  operator = c("+", "-", "*", "/", "^", "%%"),
  ignore.strand = TRUE
)
```

Arguments

A an object of GRanges

B an object of GRanges

col colname of A and B to be calculated

operator operator, "+" means A + B, and so on. User-defined function also could be used.

ignore.strand When set to TRUE, the strand information is ignored in the overlap calculations.

Value

an object of GRanges

Examples

```
gr2 <- GRanges(seqnames=c("chr1", "chr1"),
  ranges=IRanges(c(7,13), width=3),
  strand=c("-", "-"), score=3:4)
gr3 <- GRanges(seqnames=c("chr1", "chr1"),
  ranges=IRanges(c(1, 4), c(3, 9)),
  strand=c("-", "-"), score=c(6L, 2L))
GRoperator(gr2, gr3, col="score", operator="+")
GRoperator(gr2, gr3, col="score", operator="-")
GRoperator(gr2, gr3, col="score", operator="*")
GRoperator(gr2, gr3, col="score", operator="/")
GRoperator(gr2, gr3, col="score", operator=mean)
```

| | |
|--------------|--------------------------------|
| ideogramPlot | <i>plot ideogram with data</i> |
|--------------|--------------------------------|

Description

plot ideogram with data for multiple chromosomes

Usage

```
ideogramPlot(
  ideo,
  dataList,
  layout = NULL,
  horiz = TRUE,
  parameterList = list(vp = plotViewport(margins = c(0.1, 4.1, 0.3, 0.1)), ideoHeight =
    unit(1/(1 + length(dataList)), "npc"), vgap = unit(0.3, "lines"), ylabs = "auto",
    ylabsRot = ifelse(horiz, 0, 90), ylabsPos = unit(2.5, "lines"), xaxis = FALSE, yaxis
    = FALSE, xlab = "", types = "barplot", heights = NULL, dataColumn = "score", gps =
    gpar(col = "black", fill = "gray")),
  colorScheme = gieStain(),
  gp = gpar(fill = NA, lwd = 2),
  ...
)
```

Arguments

| | |
|---------------|--|
| ideo | output of loadIdeogram . |
| dataList | a GRangesList of data to plot. |
| layout | The layout of chromosomes. Could be a list with chromosome names as its elements. |
| horiz | a logical value. If FALSE, the ideograms are drawn vertically to the left. If TRUE, the ideograms are drawn horizontally at the bottom. |
| parameterList | a list of parameters for each dataset in the dataList. The elements of the parameters could be xlabs, ylabs, etc. type could be barplot, line, point, heatmap. |
| colorScheme | A character vector of giemsa stain colors. |
| gp | parameters used for grid.roundrect . |
| ... | parameters not used. |

Examples

```
## Not run:
ideo <- loadIdeogram("hg38")
library(rtracklayer)
library(grid)
dataList <- ideo
dataList$score <- as.numeric(dataList$gieStain)
dataList <- dataList[dataList$gieStain!="gneg"]
dataList <- GRangesList(dataList)
grid.newpage()
ideogramPlot(ideo, dataList,
```

```

layout=list("chr1", "chr2", c("chr3", "chr22"),
            c("chr4", "chr21"), c("chr5", "chr20"),
            c("chr6", "chr19"), c("chr7", "chr18"),
            c("chr8", "chr17"), c("chr9", "chr16"),
            c("chr10", "chr15"), c("chr11", "chr14"),
            c("chr12", "chr13"), c("chrX", "chrY")),
parameterList = list(types="heatmap", colorKeyTitle="sample1"))

## End(Not run)

```

importBam

Reading data from a BAM file

Description

Read a [track](#) object from a BAM file

Usage

```
importBam(file, file2, ranges = GRanges(), pairs = FALSE)
```

Arguments

| | |
|--------|--|
| file | The path to the BAM file to read. |
| file2 | The path to the second BAM file to read. |
| ranges | An object of GRanges to indicate the range to be imported |
| pairs | logical object to indicate the BAM is paired or not. See readGAlignments |

Value

a [track](#) object

See Also

See Also as [importScore](#), [track](#), [viewTracks](#)

Examples

```

bamfile <- system.file("extdata", "ex1.bam", package="Rsamtools",
mustWork=TRUE)
dat <- importBam(file=bamfile, ranges=GRanges("seq1", IRanges(1, 50), strand="+"))

```

| | |
|------------|---|
| importData | <i>Reading data from a BED or WIG file to RleList</i> |
|------------|---|

Description

Read a [track](#) object from a BED, bedGraph, WIG or BigWig file to RleList

Usage

```
importData(files, format = NA, ranges = GRanges())
```

Arguments

| | |
|--------|---|
| files | The path to the files to read. |
| format | The format of import file. Could be BAM, BED, bedGraph, WIG or BigWig |
| ranges | An object of GRanges to indicate the range to be imported |

Value

a list of [RleList](#).

Examples

```
#import a BED file
bedfile <- system.file("tests", "test.bed", package="rtracklayer",
  mustWork=TRUE)
dat <- importData(files=bedfile, format="BED",
  ranges=GRanges("chr7", IRanges(127471197, 127474697)))

##import a WIG file
wigfile <- system.file("tests", "step.wig", package = "rtracklayer",
  mustWork=TRUE)
dat <- importData(files=wigfile, format="WIG",
  ranges=GRanges("chr19",
    IRanges(59104701, 59110920)))

##import a BigWig file
if(!.Platform$OS.type!="windows"){
  ##this is because we are using rtracklayer::import
  bwfile <- system.file("tests", "test.bw", package = "rtracklayer",
    mustWork=TRUE)
  dat <- importData(files=bwfile, format="BigWig",
    ranges=GRanges("chr19", IRanges(1500, 2700)))
}
```

importScore

*Reading data from a BED or WIG file***Description**

Read a [track](#) object from a BED, bedGraph, WIG or BigWig file

Usage

```
importScore(
  file,
  file2,
  format = c("BED", "bedGraph", "WIG", "BigWig"),
  ranges = GRanges(),
  ignore.strand = TRUE
)
```

Arguments

| | |
|---------------|---|
| file | The path to the file to read. |
| file2 | The path to the second file to read. |
| format | The format of import file. Could be BED, bedGraph, WIG or BigWig |
| ranges | An object of GRanges to indicate the range to be imported |
| ignore.strand | ignore the strand or not when do filter. default TRUE |

Value

a [track](#) object

See Also

See Also as [importBam](#), [track](#), [viewTracks](#)

Examples

```
#import a BED file
bedfile <- system.file("tests", "test.bed", package="rtracklayer",
  mustWork=TRUE)
dat <- importScore(file=bedfile, format="BED",
  ranges=GRanges("chr7", IRanges(127471197, 127474697)))

##import a WIG file
wigfile <- system.file("tests", "step.wig", package = "rtracklayer",
  mustWork=TRUE)
dat <- importScore(file=wigfile, format="WIG")

##import a BigWig file
if(!.Platform$OS.type!="windows"){##this is because we are using rtracklayer::import
  bwfile <- system.file("tests", "test.bw", package = "rtracklayer",
    mustWork=TRUE)
  dat <- importScore(file=bwfile, format="BigWig")
}
```

```
##import 2 file
wigfile1 <- system.file("extdata", "cpsf160.repA+.wig", package="trackViewer",
                        mustWork=TRUE)
wigfile2 <- system.file("extdata", "cpsf160.repA-.wig", package="trackViewer",
                        mustWork=TRUE)
dat <- importScore(wigfile1, wigfile2, format="WIG",
                  ranges=GRanges("chr11", IRanges(122817703, 122889073)))
```

| | |
|--------------|--------------------------------|
| loadIdeogram | <i>load ideogram from UCSC</i> |
|--------------|--------------------------------|

Description

Download ideogram table from UCSC

Usage

```
loadIdeogram(genome, chrom = NULL, ranges = NULL, ...)
```

Arguments

| | |
|--------|--|
| genome | Assembly name assigned by UCSC, such as hg38, mm10. |
| chrom | A character vector of chromosome names, or NULL. |
| ranges | A Ranges object with the intervals. |
| ... | Additional arguments to pass to the GRanges constructor. |

Value

A [GRanges](#) object.

See Also

See Also as [ideogramPlot](#)

Examples

```
## Not run:
head(loadIdeogram("hg38"))

## End(Not run)
```

lollipoplot

*Lollipoplots***Description**

Plot variants and somatic mutations

Usage

```
lollipoplot(
  SNP.gr,
  features = NULL,
  ranges = NULL,
  type = "circle",
  newpage = TRUE,
  ylab = TRUE,
  ylab.gp = gpar(col = "black"),
  yaxis = TRUE,
  yaxis.gp = gpar(col = "black"),
  xaxis = TRUE,
  xaxis.gp = gpar(col = "black"),
  legend = NULL,
  cex = 1,
  dashline.col = "gray80",
  jitter = c("node", "label"),
  rescale = FALSE,
  ...
)
```

Arguments

| | |
|-----------------------------|--|
| SNP.gr | A object of GRanges , GRangesList or a list of GRanges . All the width of GRanges must be 1. |
| features | A object of GRanges , GRangesList or a list of GRanges . The metadata 'featureLayerID' are used for drawing features in different layers. See details in vignette. |
| ranges | A object of GRanges or GRangesList . |
| type | character. Could be circle, pie, pin, pie.stack or flag. |
| newpage | Plot in the new page or not. |
| ylab | Plot ylab or not. If it is a character vector, the vector will be used as ylab. |
| ylab.gp, xaxis.gp, yaxis.gp | An object of class gpar for ylab, xaxis or yaxis. |
| yaxis | Plot yaxis or not. |
| xaxis | Plot xaxis or not. If it is a numeric vector with length greater than 1, the vector will be used as the points at which tick-marks are to be drawn. And the names of the vector will be used to as labels to be placed at the tick points if it has names. |
| legend | If it is a list with named color vectors, a legend will be added. |
| cex | cex will control the size of circle. |

| | |
|--------------|---|
| dashline.col | color for the dashed line. |
| jitter | jitter the position of nodes or labels. |
| rescale | logical(1) or a dataframe with rescale from and to. Recalse the x-axis or not. if dataframe is used, colnames must be from.start, from.end, to.start, to.end. |
| ... | not used. |

Details

In SNP.gr and features, metadata of the GRanges object will be used to control the color, fill, border, alpha, shape, height, cex, dashline.col, data source of pie if the type is pie. And also the controls for labels by name the metadata start as label.parameter.<properties> such as label.parameter.rot, label.parameter.gp. The parameter is used for [grid.text](#). The metadata 'featureLayerID' for features are used for drawing features in different layers. The metadata 'SNPsideID' for SNP.gr are used for determining the side of lollipops. And the 'SNPsideID' could only be 'top' or 'bottom'.

Examples

```
SNP <- c(10, 100, 105, 108, 400, 410, 420, 600, 700, 805, 840, 1400, 1402)
x <- sample.int(100, length(SNP))
SNP.gr <- GRanges("chr1", IRanges(SNP, width=1, names=paste0("snp", SNP)),
                  value1=x, value2=100-x)
SNP.gr$color <- rep(list(c("red", 'blue')), length(SNP))
SNP.gr$border <- sample.int(7, length(SNP), replace=TRUE)
features <- GRanges("chr1", IRanges(c(1, 501, 1001),
                                   width=c(120, 500, 405),
                                   names=paste0("block", 1:3)),
                  color="black",
                  fill=c("#FF8833", "#51C6E6", "#DFA32D"),
                  height=c(0.1, 0.05, 0.08),
                  label.parameter.rot=45)
lollipop(SNP.gr, features, type="pie")
```

optimizeStyle

Optimize the style of plot

Description

Automatic optimize the stlye of trackViewer

Usage

```
optimizeStyle(trackList, viewerStyle = trackViewerStyle(), theme = NULL)
```

Arguments

| | |
|-------------|---|
| trackList | An object of trackList |
| viewerStyle | An object of trackViewerStyle |
| theme | A character string. Could be "bw", "col" or "safe". |

Value

a list of a [trackList](#) and a [trackViewerStyle](#)

See Also

See Also as [viewTracks](#)

Examples

```
extdata <- system.file("extdata", package="trackViewer",
                      mustWork=TRUE)
files <- dir(extdata, ".wig")
tracks <- lapply(paste(extdata, files, sep="/"),
               importScore, format="WIG")
re <- optimizeStyle(trackList(tracks))
trackList <- re$tracks
viewerStyle <- re$style
```

parse2GRanges

parse text into GRanges

Description

parse text like "chr13:99,443,451-99,848,821:-" into GRanges

Usage

```
parse2GRanges(text)
```

Arguments

text character vector like "chr13:99,443,451-99,848,821:-" or "chr13:99,443,451-99,848,821"

Value

an object of [GRanges](#)

Examples

```
parse2GRanges("chr13:99,443,451-99,848,821:-")
```

| | |
|----------|---|
| parseWIG | <i>convert WIG format track to BED format track</i> |
|----------|---|

Description

convert WIG format track to BED format track for a given range

Usage

```
parseWIG(trackScore, chrom, from, to)
```

Arguments

| | |
|------------|------------------------------------|
| trackScore | an object of track with WIG format |
| chrom | sequence name of the chromosome |
| from | start coordinate |
| to | end coordinate |

Value

an object of [track](#)

Examples

```
extdata <- system.file("extdata", package="trackViewer", mustWork=TRUE)
repA <- importScore(file.path(extdata, "cpsf160.repA_-.wig"),
                   file.path(extdata, "cpsf160.repA_+.wig"),
                   format="WIG")
strand(repA$dat) <- "-"
strand(repA$dat2) <- "+"
parseWIG(repA, chrom="chr11", from=122929275, to=122930122)
```

| | |
|-------------------|---------------------------|
| plotGInteractions | <i>plot GInteractions</i> |
|-------------------|---------------------------|

Description

plot graph for GInteractions

Usage

```
plotGInteractions(gi, range, feature.gr, ...)
```

Arguments

| | |
|------------|--|
| gi | an object of GInteractions |
| range | the region to plot. an object of GRanges |
| feature.gr | the feature.gr to be added. an object of GRanges |
| ... | Not used. |

Examples

```

library(InteractionSet)
gi <- readRDS(system.file("extdata", "gi.rds", package="trackViewer"))
range <- GRanges("chr2", IRanges(234500000, 235000000))
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
feature.gr <- genes(TxDb.Hsapiens.UCSC.hg19.knownGene)
feature.gr <- subsetByOverlaps(feature.gr, regions(gi))
feature.gr$col <- sample(1:7, length(feature.gr), replace=TRUE)
feature.gr$type <- sample(c("promoter", "enhancer", "gene"),
                        length(feature.gr), replace=TRUE,
                        prob=c(0.1, 0.2, 0.7))
plotGInteractions(gi, range, feature.gr)

```

plotGRanges

plot GRanges data

Description

A function to plot GRanges data for given range

Usage

```

plotGRanges(
  ...,
  range = GRanges(),
  viewerStyle = trackViewerStyle(),
  autoOptimizeStyle = FALSE,
  newpage = TRUE
)

```

Arguments

| | |
|-------------------|--|
| ... | one or more objects of GRanges |
| range | an object of GRanges |
| viewerStyle | an object of trackViewerStyle |
| autoOptimizeStyle | should use optimizeStyle to optimize style |
| newpage | should be draw on a new page? |

Value

An object of [viewport](#) for [addGuideLine](#)

See Also

See Also as [addGuideLine](#), [addArrowMark](#)

Examples

```

gr1 <- GRanges("chr1", IRanges(1:50, 51:100))
gr2 <- GRanges("chr1", IRanges(seq(from=10, to=80, by=5),
                               seq(from=20, to=90, by=5)))
vp <- plotGRanges(gr1, gr2, range=GRanges("chr1", IRanges(1, 100)))
addGuideLine(guideLine=c(5, 10, 50, 90), col=2:5, vp=vp)

gr <- GRanges("chr1", IRanges(c(1, 11, 21, 31), width=9),
              score=c(5, 10, 5, 1))
plotGRanges(gr, range=GRanges("chr1", IRanges(1, 50)))

```

plotIdeo

*plot ideogram***Description**

plot ideogram for one chromosome

Usage

```

plotIdeo(
  ideo,
  chrom = seqlevels(ideo)[1],
  colorSheme = gieStain(),
  gp = gpar(fill = NA),
  ...
)

```

Arguments

| | |
|------------|--|
| ideo | output of loadIdeogram . |
| chrom | A length 1 character vector of chromosome name. |
| colorSheme | A character vector of giemsa stain colors. |
| gp | parameters used for grid.roundrect . |
| ... | parameters not used. |

Examples

```

## Not run:
ideo <- loadIdeogram("hg38")
library(grid)
grid.newpage()
plotIdeo(ideo)

## End(Not run)

```

plotOneIdea *plot ideogram with data for one chromosome*

Description

plot ideogram with data for one chromosome

Usage

```
plotOneIdea(
  ideo,
  dataList,
  parameterList = list(vp = plotViewport(margins = c(0.1, 4.1, 1.1, 0.1)), ideoHeight =
    unit(1/(1 + length(dataList)), "npc"), vgap = unit(1, "lines"), ylabs =
    seqlevels(ideo)[1], ylabsRot = 90, ylabsPos = unit(2.5, "lines"), xaxis = FALSE,
    yaxis = FALSE, xlab = "", types = "barplot", heights = NULL, dataColumn = "score",
    gps = gpar(col = "black", fill = "gray")),
  chrom = seqlevels(ideo)[1],
  colorScheme = gieStain(),
  gp = gpar(fill = NA, lwd = 2),
  ...
)
```

Arguments

| | |
|---------------|--|
| ideo | output of loadIdeogram . |
| dataList | a GRangesList of data to plot. |
| parameterList | a list of parameters for each dataset in the dataList. The elements of the parameters could be xlabs, ylabs, etc. type could be barplot, line, point, heatmap. |
| chrom | A length 1 character vector of chromosome name. |
| colorScheme | A character vector of giemsa stain colors. |
| gp | parameters used for grid.roundrect . |
| ... | parameters not used. |

Examples

```
## Not run:
ideo <- loadIdeogram("hg38")
library(rtracklayer)
library(grid)
dataList <- ideo[seqnames(ideo) %in% "chr1"]
dataList$score <- as.numeric(dataList$gieStain)
dataList <- dataList[dataList$gieStain!="gneg"]
dataList <- GRangesList(dataList, dataList)
grid.newpage()
plotOneIdea(ideo, dataList, chrom="chr1")

## End(Not run)
```

| | |
|-----------|--------------------|
| pos-class | <i>Class "pos"</i> |
|-----------|--------------------|

Description

An object of class "pos" represents a point location

Slots

x A [numeric](#) value, indicates the x position

y A [numeric](#) value, indicates the y position

unit "character" apesifying the units for the corresponding numeric values. See [unit](#)

| | |
|-----------------|-----------------------|
| trackList-class | <i>List of tracks</i> |
|-----------------|-----------------------|

Description

An extension of List that holds only [track](#) objects.

Usage

```
trackList(..., heightDist = NA)
```

Arguments

... Each tracks in ... becomes an element in the new trackList, in the same order. This is analogous to the list constructor, except every argument in ... must be derived from [track](#).

heightDist A vector or NA to define the height of each track.

See Also

[track](#).

```
trackStyle-class      Class "trackStyle"
```

Description

An object of class "trackStyle" represents track style.

An object of class "track" represents scores of a given track.

Usage

```
## S4 method for signature 'track'
show(object)

## S4 method for signature 'track'
x$name

## S4 replacement method for signature 'track'
x$name <- value

setTrackStyleParam(ts, attr, value)

## S4 method for signature 'track,character'
setTrackStyleParam(ts, attr, value)

setTrackXscaleParam(ts, attr, value)

## S4 method for signature 'track,character'
setTrackXscaleParam(ts, attr, value)

setTrackYaxisParam(ts, attr, value)

## S4 method for signature 'track,character'
setTrackYaxisParam(ts, attr, value)
```

Arguments

| | |
|--------|--|
| object | an object of trackStyle. |
| x | an object of trackStyle |
| name | slot name of trackStyle |
| value | values to be assigned. |
| ts | An object of track. |
| attr | the name of slot of trackStyle object to be changed. |

Details

The attr of setTrackXscaleParam could not only be a slot of xscale, but also be position. If the attr is set to position, value must be a list of x, y and label. For example setTrackXscaleParam(track, attr="position", value=list(x=122929675, y=4, label=500))

Slots

`tracktype` "character" track type, could be peak or cluster. Default is "peak". "cluster" is not supported yet.

`color` "character" track color. If the track has `dat` and `dat2` slot, it should have two values.

`NAcolor` "character" NA color for `interactionData`.

`breaks` "numeric" breaks for color keys of `interactionData`.

`height` "numeric" track height. It should be a value between 0 and 1

`marginTop` "numeric" track top margin

`marginBottom` "numeric" track bottom margin

`xscale` object of `xscale`, describe the details of x-scale

`yaxis` object of `yaxisStyle`, describe the details of y-axis

`ylim` "numeric" y-axis range

`ylabpos` "character", ylable position, `ylabpos` should be 'left', 'right', 'topleft', 'bottomleft', 'topright', 'bottomright', 'abovebaseline' or 'underbaseline'. For gene type track, it also could be 'upstream' or 'downstream'

`ylablas` "numeric" y lable direction. It should be a integer 0-3. See `par:las`

`ylabgp` A "list" object, It will convert to an object of class `gpar`. This is basically a list of graphical parameter settings of y-label.

`dat` Object of class `GRanges` the scores of a given track. It should contain score metadata.

`dat2` Object of class `GRanges` the scores of a given track. It should contain score metadata. When `dat2` and `dat` is paired, `dat` will be drawn as positive value where `dat2` will be drawn as negative value ($-1 * \text{score}$)

`type` The type of track. It could be 'data', 'gene', 'transcript', 'lollipopData' or 'interactionData'.

`format` The format of the input. It could be "BED", "bedGraph", "WIG", "BigWig" or "BAM"

`style` Object of class `trackStyle`

`name` unused yet

See Also

Please try to use `importScore` and `importBam` to generate the object.

Examples

```
extdata <- system.file("extdata", package="trackViewer",
mustWork=TRUE)
fox2 <- importScore(file.path(extdata, "fox2.bed"), format="BED")
setTrackStyleParam(fox2, "color", c("red","green"))
setTrackXscaleParam(fox2, "gp", list(cex=.5))
setTrackYaxisParam(fox2, "gp", list(col="blue"))
fox2$dat <- GRanges(score=numeric(0))
```

```
trackViewerStyle-class
      Class "trackViewerStyle"
```

Description

An object of class "trackViewerStyle" represents track viewer style.

Usage

```
trackViewerStyle(...)

setTrackViewerStyleParam(tvs, attr, value)

## S4 method for signature 'trackViewerStyle,character'
setTrackViewerStyleParam(tvs, attr, value)
```

Arguments

| | |
|-------|---|
| ... | Each argument in ... becomes an slot in the new trackViewerStyle. |
| tvs | An object of trackViewerStyle. |
| attr | the name of slot to be changed. |
| value | values to be assigned. |

Slots

margin "numeric", specify the bottom, left, top and right margin.

xlas "numeric", label direction of x-axis mark. It should be a integer 0-3. See [par:las](#)

xgp A "list", object, It will convert to an object of class [gpar](#). This is basically a list of graphical parameter settings of x-axis. For y-axis, see [yaxisStyle](#)

xaxis "logical", draw x-axis or not

autolas "logical" automatic determine y label direction

flip "logical" flip the x-axis or not, default FALSE

Examples

```
tvs <- trackViewerStyle()
setTrackViewerStyleParam(tvs, "xaxis", TRUE)
```

| | |
|----------|---------------------------------------|
| viewGene | <i>plot tracks based on gene name</i> |
|----------|---------------------------------------|

Description

given a gene name, plot the tracks.

Usage

```
viewGene(  
  symbol,  
  filenames,  
  format,  
  txdb,  
  org,  
  upstream = 1000,  
  downstream = 1000,  
  anchor = c("gene", "TSS"),  
  plot = FALSE  
)
```

Arguments

| | |
|------------|--|
| symbol | Gene symbol |
| filenames | files used to generate tracks |
| format | file format used to generate tracks |
| txdb | txdb will be used to extract the genes |
| org | org package name |
| upstream | upstream from anchor |
| downstream | downstream from anchor |
| anchor | TSS, or gene |
| plot | plot the tracks or not. |

Value

an invisible list of a [trackList](#), a [trackViewerStyle](#) and a [GRanges](#)

Examples

```
library(TxDb.Hsapiens.UCSC.hg19.knownGene)  
library(org.Hs.eg.db)  
extdata <- system.file("extdata", package="trackViewer", mustWork=TRUE)  
filename = file.path(extdata, "fox2.bed")  
optSty <- viewGene("HSPA8", filenames=filename, format="BED",  
                  txdb=TxDb.Hsapiens.UCSC.hg19.knownGene,  
                  org="org.Hs.eg.db")
```

viewTracks

*plot the tracks***Description**

A function to plot the data for given range

Usage

```
viewTracks(
  trackList,
  chromosome,
  start,
  end,
  strand,
  gr = GRanges(),
  ignore.strand = TRUE,
  viewerStyle = trackViewerStyle(),
  autoOptimizeStyle = FALSE,
  newpage = TRUE,
  operator = NULL,
  smooth = FALSE
)
```

Arguments

| | |
|-------------------|---|
| trackList | an object of trackList |
| chromosome | chromosome |
| start | start position |
| end | end position |
| strand | strand |
| gr | an object of GRanges |
| ignore.strand | ignore the strand or not when do filter. default TRUE |
| viewerStyle | an object of trackViewerStyle |
| autoOptimizeStyle | should use optimizeStyle to optimize style |
| newpage | should be draw on a new page? |
| operator | operator, could be +, -, *, /, ^, %%. "-" means dat - dat2, and so on. |
| smooth | logical(1) or numeric(1). Smooth the curve or not. If it is numeric, eg n, mean of nearby n points will be used for plot. |

Value

An object of [viewport](#) for [addGuideLine](#)

See Also

See Also as [addGuideLine](#), [addArrowMark](#)

Examples

```

extdata <- system.file("extdata", package="trackViewer",
                      mustWork=TRUE)
files <- dir(extdata, "-.wig")
tracks <- lapply(paste(extdata, files, sep="/"),
                importScore, format="WIG")
tracks <- lapply(tracks, function(.ele) {strand(.ele@dat) <- "-"; .ele})
fox2 <- importScore(paste(extdata, "fox2.bed", sep="/"), format="BED")
dat <- coverageGR(fox2@dat)
fox2@dat <- dat[strand(dat)=="+"]
fox2@dat2 <- dat[strand(dat)=="-"]
gr <- GRanges("chr11", IRanges(122929275, 122930122), strand="-")
viewTracks(trackList(track=tracks, fox2=fox2), gr=gr, autoOptimizeStyle=TRUE)

```

| | |
|--------------|-----------------------|
| xscale-class | <i>Class "xscale"</i> |
|--------------|-----------------------|

Description

An object of class "xscale" represents x-scale style.

Slots

from A [pos](#) class, indicates the start point position of x-scale.

to A [pos](#) class, indicates the end point position of x-scale.

label "character" the label of x-scale

gp A "list" object, It will convert to an object of class [gpar](#). This is basically a list of graphical parameter settings of x-scale.

draw A "logical" value indicating whether the x-scale should be draw.

| | |
|------------------|---------------------------|
| yaxisStyle-class | <i>Class "yaxisStyle"</i> |
|------------------|---------------------------|

Description

An object of class "yaxisStyle" represents y-axis style.

Slots

at "numeric" vector of y-value locations for the tick marks

label "logical" value indicating whether to draw the labels on the tick marks.

gp A "list" object, It will convert to an object of class [gpar](#). This is basically a list of graphical parameter settings of y-axis.

draw A "logical" value indicating whether the y-axis should be draw.

main A "logical" value indicating whether the y-axis should be draw in left (TRUE) or right (FALSE).

Index

\$, track-method (trackStyle-class), 28
\$<-, track-method (trackStyle-class), 28

addArrowMark, 3, 5, 24, 32
addGuideLine, 4, 4, 11, 24, 32
arrow, 4

browseTracks, 5
browseTracks-shiny, 6
browseTracksOutput
 (browseTracks-shiny), 6

coverage, 7
coverageGR, 6

dandelion.plot, 7

GAlignmentPairs, 6
GAlignments, 6
geneModelFromTxdb, 8
geneTrack, 10
getCurTrackViewport, 5, 10
getGeneIDsFromTxDb, 11
getLocation, 12
gi2track, 12
gieStain, 13
GInteractions, 23
gpar, 13, 29, 30, 33
GRanges, 5, 6, 8, 13, 16–20, 22–24, 29, 31, 32
GRangesList, 8, 15, 20, 26
grid.roundrect, 15, 25, 26
grid.text, 21
gridPlot, 13
GROperator, 14

ideogramPlot, 15, 19
importBam, 9, 16, 18, 29
importData, 17
importScore, 9, 16, 18, 29

loadIdeogram, 15, 19, 25, 26
lollipop, 20

numeric, 27

optimizeStyle, 21, 24, 32

par, 29, 30
parse2GRanges, 22
parseWIG, 23
plotGInteractions, 23
plotGRanges, 24
plotIdeo, 25
plotOneIdeo, 26
pos, 33
pos (pos-class), 27
pos-class, 27

Ranges, 19
readGAlignments, 16
renderbrowseTracks
 (browseTracks-shiny), 6
RleList, 17

setTrackStyleParam (trackStyle-class),
 28
setTrackStyleParam, track, character, ANY-method
 (trackStyle-class), 28
setTrackStyleParam, track, character-method
 (trackStyle-class), 28
setTrackViewerStyleParam
 (trackViewerStyle-class), 30
setTrackViewerStyleParam, trackViewerStyle, character, ANY-
 (trackViewerStyle-class), 30
setTrackViewerStyleParam, trackViewerStyle, character-method
 (trackViewerStyle-class), 30
setTrackXscaleParam (trackStyle-class),
 28
setTrackXscaleParam, track, character, ANY-method
 (trackStyle-class), 28
setTrackXscaleParam, track, character-method
 (trackStyle-class), 28
setTrackYaxisParam (trackStyle-class),
 28
setTrackYaxisParam, track, character, ANY-method
 (trackStyle-class), 28
setTrackYaxisParam, track, character-method
 (trackStyle-class), 28
show, track-method (trackStyle-class), 28
track, 8–10, 16–18, 23, 27

track (trackStyle-class), 28
track-class (trackStyle-class), 28
trackList, 5, 21, 22, 31, 32
trackList (trackList-class), 27
trackList-class, 27
trackStyle, 28, 29
trackStyle (trackStyle-class), 28
trackStyle-class, 28
trackViewer (trackViewer-package), 2
trackViewer-package, 2
trackViewerStyle, 10, 21, 22, 24, 31, 32
trackViewerStyle
 (trackViewerStyle-class), 30
trackViewerStyle-class, 30
TxDb, 9–11

unit, 27

viewGene, 31
viewport, 11, 24, 32
viewTracks, 4, 5, 8, 9, 16, 18, 22, 32

xscale, 29
xscale (xscale-class), 33
xscale-class, 33

yaxisStyle, 29, 30
yaxisStyle (yaxisStyle-class), 33
yaxisStyle-class, 33