

Cardinal design and development

Kylie A. Bemis

January 4, 2019

Contents

1	Introduction	2
2	Design overview	2
3	iSet: high-throughput imaging experiments	3
3.1	SImageSet: pixel-sparse imaging experiments	4
3.2	MSImageSet: mass spectrometry-based imaging experiments	4
4	ImageData: high-throughput image data	5
4.1	SImageData: pixel-sparse imaging experiments	6
4.2	MSImageData: mass spectrometry imaging data.	7
4.2.1	Hashmat: compressed-sparse column matrices	7
5	IAnnotatedDataFrame: pixel metadata for imaging experiments	8
6	MIAPE-Imaging: Minimum Information About a Proteomics Experiment for MS imaging.	9
7	MSImageProcess: mass spectral pre-processing information	10
8	ResultSet: analysis results for imaging experiments	10
9	Visualization for high-throughput imaging experiments	11
9.1	SImageData and MSImageData.	11
9.2	ResultSet	11
10	Testing during development	12
10.1	Simulating mass spectra	13
10.2	Timing and diagnostics	13
11	Session info	13

1 Introduction

Cardinal is designed with two primary purposes in mind: (1) to provide an environment for experimentalists for the handling, pre-processing, analysis, and visualization of mass spectrometry-based imaging experiments, and (2) to provide an infrastructure for computationalists for the development of new computational methods for mass spectrometry-based imaging experiments.

Although MS imaging has attracted the interest of many statisticians and computer scientists, and a number of algorithms have been designed specifically for such experiments, most of these methods remain unavailable to experimentalists, because they are often either proprietary, or difficult for non-experts use. Additionally, the complexity of MS imaging creates a significant barrier to entry for developers. *Cardinal* aims to remove this hurdle, by providing *R* developers with an accessible way to handle MS imaging data.

As an *R* package, *Cardinal* allows for the rapid prototyping of new analysis methods. This vignette describes the design of *Cardinal* data structures for developers interested in writing new *R* packages using or extending them.

2 Design overview

The `iSet` object is the foundational data structure of *Cardinal*. What is an *iSet*?

- Similar to `eSet` in *Biobase* and `pSet` in *MSnbase*.
- Coordinates high-throughput imaging data, feature data, pixel data, and metadata.
- Provides an interface for manipulating data from imaging experiments.

Just as `eSet` from *Biobase* coordinates gene expression data and `pSet` from *MSnbase* coordinates proteomics data, `iSet` coordinates imaging data. It is a virtual class, so it is used only through its subclasses.

`MSImageSet` is a subclass of `iSet`, and is the primary data structure used in *Cardinal*. It is designed to coordinate data from mass spectrometry-based imaging experiments. It contains mass spectra (or mass spectral peaks), feature data (including m/z values), pixel data (including pixel coordinates and phenotype data), and other metadata. When a raw MS image data file is read into *Cardinal*, it is turned into an `MSImageSet`, which can then be used with *Cardinal*'s methods for pre-processing, analysis, and visualization.

`MSImageData` is the class responsible for coordinating the mass spectra themselves, and reconstructing them into images when necessary. Every `MSImageSet` has an `imageData` slot containing an `MSImageData` object. It is similar to the `assayData` slot in *Biobase*, in that it uses an `environment` to store large high-throughput data more efficiently in memory, without *R*'s usual copy-on-edit behavior.

`IAnnotatedDataFrame` extends the *Biobase* `AnnotatedDataFrame` class by making a distinction between *pixels* and *samples*. An `IAnnotatedDataFrame` tracks pixel data, where each row corresponds to a single pixel, and each column corresponds to some measured variable (such as phenotype). An `MSImageSet` may contain multiple samples, where each sample is a single image, and possibly thousands of pixels corresponding to each sample.

Cardinal design and development

`ResultSet` is a class for containing results of analyses performed on `iSet` objects. A single `ResultSet` object may contain results for multiple parameter sets. Using a `ResultSet` provides users and developers with a standard way of viewing and plotting the results of analyses.

Together, these classes (along with a few others) provide a useful way of accessing and manipulating MS imaging data while keeping track of important experimental metadata.

3 `iSet`: high-throughput imaging experiments

Inspired by `eSet` in *Biobase* and `pSet` in *MSnbase*, the virtual class `iSet` provides the foundation for other classes in *Cardinal*. It is a generic class for the storage of imaging data and experimental metadata.

```
> getClass("iSet")
Virtual Class "iSet" [package "Cardinal"]

Slots:

Name:          imageData          pixelData          featureData          experimentData
Class:         ImageData IAnnotatedDataFrame AnnotatedDataFrame MIAxE

Name:          protocolData      .__classVersion__
Class:         AnnotatedDataFrame Versions

Extends:
Class "VersionedBiobase", directly
Class "Versioned", by class "VersionedBiobase", distance 2

Known Subclasses:
Class "SImageSet", directly
Class "ResultSet", directly
Class "MSImageSet", by class "SImageSet", distance 2
Class "CrossValidated", by class "ResultSet", distance 2
Class "PCA", by class "ResultSet", distance 2
Class "PLS", by class "ResultSet", distance 2
Class "OPLS", by class "ResultSet", distance 2
Class "SpatialKMeans", by class "ResultSet", distance 2
Class "SpatialShrunkenCentroids", by class "ResultSet", distance 2
```

Structure:

- `imageData`: high-throughput image data
- `pixelData`: pixel covariates (coordinates, sample, phenotype, etc.)
- `featureData`: feature covariates (m/z , protein annotation, etc.)
- `experimentData`: experiment description
- `protocolData`: sample protocol

Cardinal design and development

Of particular note is the `imageData` slot for the storing of high-throughput image data, which will be discussed further in Section 4, and the `pixelData` slot, which will be discussed further in Section 5.

3.1 SImageSet: pixel-sparse imaging experiments

`SImageSet` extends `iSet` without extending its internal structure. `SImageSet` implements methods assuming that the structure of `imageData` is a (# of features) × (# of pixels) matrix, where each column corresponds to a pixel's feature vector (e.g., a single mass spectrum), and each row corresponds to a vector of flattened image intensities.

`SImageSet` further assumes that there may be a number of missing pixels in the experiment. This is useful for non-rectangular images, and experiments with multiple images of different dimensions.

```
> getClass("SImageSet")
Class "SImageSet" [package "Cardinal"]

Slots:

Name:          imageData          pixelData          featureData          experimentData
Class:         SImageData IAnnotatedDataFrame AnnotatedDataFrame MIAxE

Name:          protocolData      .__classVersion__
Class: AnnotatedDataFrame          Versions

Extends:
Class "iSet", directly
Class "VersionedBiobase", by class "iSet", distance 2
Class "Versioned", by class "iSet", distance 3

Known Subclasses: "MSImageSet"
```

3.2 MSImageSet: mass spectrometry-based imaging experiments

`MSImageSet` extends `SImageSet` with mass spectrometry-specific features, including expecting m/z values to be stored in the `featureData` slot. This is the primary class in *Cardinal* for handling MS imaging experiments. It also adds a slot `processingData` for tracking the what pre-processing has been applied to the dataset.

```
> getClass("MSImageSet")
Class "MSImageSet" [package "Cardinal"]

Slots:

Name:          processingData      experimentData          imageData          pixelData
Class:         MSImageProcess      MIAPE-Imaging          SImageData IAnnotatedDataFrame
```

Cardinal design and development

```
Name:          featureData      protocolData      .__classVersion__
Class: AnnotatedDataFrame AnnotatedDataFrame      Versions

Extends:
Class "SImageSet", directly
Class "iSet", by class "SImageSet", distance 2
Class "VersionedBiobase", by class "SImageSet", distance 3
Class "Versioned", by class "SImageSet", distance 4
```

4 ImageData: high-throughput image data

`iSet` and all of its subclasses have an `imageData` slot for storing the high-throughput image data. This must be an object of class `ImageData` or one of its subclasses.

Similar to the `assayData` slot in `eSet` from *Biobase* and `pSet` from *MSnbase*, `ImageData` uses an `environment` as its data slot to store data objects in memory more efficiently, and bypass *R*'s usual copy-on-edit behavior. Because these data elements of `ImageData` may be very large, editing any metadata in an `iSet` object would trigger expensive copying of these large data elements if a usual *R* `list` were used. Using an `environment` avoids this behavior.

`ImageData` makes no assumptions about the class of objects that make up the elements of its data slot, but they must be array-like objects that return a positive-length vector to a call to `dim`. These data elements must also have the same number of dimensions, but they may have different extents.

```
> getClass("ImageData")
Class "ImageData" [package "Cardinal"]

Slots:

Name:          data      storageMode .__classVersion__
Class:         environment  character      Versions

Extends: "Versioned"

Known Subclasses:
Class "SImageData", directly
Class "MSImageData", by class "SImageData", distance 2
```

Structure:

- `data`: high-throughput image data
- `storageMode`: mode of the data environment

Similar to `assayData`, the elements of `ImageData` can be stored in three different ways. These are as a `immutableEnvironment`, `lockedEnvironment`, or `environment`.

Cardinal design and development

The modes *lockedEnvironment* and *environment* behave the same as for *assayData* in *Biobase* and *MSnbase*. *Cardinal* introduces *immutableEnvironment*, which is a compromise between the two. When the storage mode is *immutableEnvironment*, only changing the values of the elements of *ImageData* directly will trigger copying, while changing object metadata will not trigger copying.

4.1 SImageData: pixel-sparse imaging experiments

While *ImageData* makes very few assumptions about the objects that are the elements of its data slot, its subclass *SImageData* expects a very specific structure to its data elements.

SImageData expects at least one element named "iData" (accessed by *iData*) which is a (# of features) × (# of pixels) matrix, where each column is a feature vector (i.e., a single mass spectrum) associated with a single pixel, and each row is a vector of flattened image intensities. Additional elements should follow the same structure, with the same dimensions.

```
> getClass("SImageData")
Class "SImageData" [package "Cardinal"]

Slots:

Name:          coord      positionArray      dim      dimnames      data
Class:         data.frame  array              numeric  list           environment

Name:          storageMode  ___classVersion__
Class:         character    Versions

Extends:
Class "ImageData", directly
Class "Versioned", by class "ImageData", distance 2

Known Subclasses: "MSImageData"
```

Structure:

- *data*: high-throughput image data
- *storageMode*: mode of the data environment
- *coord*: *data.frame* of pixel coordinates.
- *positionArray*: *array* mapping coordinates to pixel column indices
- *dim*: dimensions of array elements in *data*
- *dimnames*: dimension names

SImageData implements methods for re-constructing images from the rows of flattened image intensities on-the-fly. In addition, it assumes the images may be pixel-sparse. This means data for missing pixels does not need to be stored. Instead, the *positionArray* slot holds an *array* of the same dimension as the *true dimensions* of the imaging dataset, i.e., the maximum of each column of *coord*. For each pixel coordinate from the *true image*, the *positionArray* stores the index of the column for which the associated feature vector is stored in the matrix elements of *data*.

Cardinal design and development

This allows transforming the image (e.g., changing the pixel coordinates such as transposing the image, rotating it, etc.) without editing (and thereby triggering R to make a copy of) the (possibly very large) data matrix elements in data. This also means that it doesn't matter what order the pixels' feature vectors (e.g., mass spectra) are stored.

4.2 MSImageData: mass spectrometry imaging data

MSImageData is a small extension of SImageData, which adds methods for accessing additional elements of data specific to mass spectrometry. There are an element named "peakData" (accessed by peakData) for storing the intensities of peaks, and "mzData" (accessed by mzData) for storing the m/z values of peaks. Generally, these elements will only exist after peak-picking has been performed. (They may not exist if the data has been reduced to contain *only* peaks, i.e., if the "iData" element consists of peaks rather than full mass spectra.)

```
> getClass("MSImageData")
Class "MSImageData" [package "Cardinal"]

Slots:

Name:      coord      positionArray      dim      dimnames      data
Class:     data.frame      array      numeric      list      environment

Name:      storageMode  .__classVersion__
Class:     character      Versions

Extends:
Class "SImageData", directly
Class "ImageData", by class "SImageData", distance 2
Class "Versioned", by class "SImageData", distance 3
```

The "peakData" and "mzData" elements (when they exist) are usually objects of class Hashmat.

4.2.1 Hashmat: compressed-sparse column matrices

The Hashmat class is a compressed-sparse column matrix implementation designed to store mass spectral peaks efficiently alongside full spectra, and allow dynamic filtering and re-alignment of peaks without losing data.

```
> getClass("Hashmat")
Class "Hashmat" [package "Cardinal"]

Slots:

Name:      data      keys      dim      dimnames  .__classVersion__
Class:     list      character      numeric      list      Versions

Extends: "Versioned"
```

Cardinal design and development

Structure:

- `data`: sparse data matrix elements
- `keys`: identifiers of non-zero elements
- `dim`: dimensions of (full) matrix
- `dimnames`: dimension names

In a `Hashmat` object, the `data` slot is a `list` where each element is a column of the sparse matrix, represented by a named `numeric` vector. The `keys` slot is a `character` vector. The columns of the dense matrix are reconstructing by indexing each of the named vectors in `data` by the `keys`. This means that a `Hashmat` can store matrix elements that are selectively zero or non-zero depending on the keys.

In the context of mass spectral peak-picking, this means that each sparse column is a vector of mass spectral peaks. Peaks can be filtered (e.g., removing low-intensity peaks) or aligned (e.g., to the mean spectrum) loss-lessly, by changing the keys. Filtering peaks simply means deleting a key, while peak alignment simply means re-arranging the keys. Additionally, the dimension of the dense matrix will be the same as the full mass spectra, while requiring very little additional storage.

5 `IAnnotatedDataFrame`: pixel metadata for imaging experiments

`IAnnotatedDataFrame` is extension of `AnnotatedDataFrame` from *Biobase*. It serves as the `pixelData` slot for `iSet` and its subclasses. In an `AnnotatedDataFrame`, each row corresponds to a sample. However, in an `IAnnotatedDataFrame`, each row instead corresponds to a pixel.

In an imaging experiment, each image is a sample, and a single image is composed of many pixels. Therefore, `IAnnotatedDataFrame` may have very many pixels, but have very few (or even just a single) sample.

An `IAnnotatedDataFrame` must have a column named "sample", which is a `factor`, and gives the sample to which each pixel belongs.

For an `IAnnotatedDataFrame`, `pixelNames` retrieves the row names, while `sampleNames` retrieves the levels of the "sample" column.

```
> getClass("IAnnotatedDataFrame")
Class "IAnnotatedDataFrame" [package "Cardinal"]

Slots:

Name:          varMetadata          data          dimLabels  .__classVersion__
Class:         data.frame           data.frame    character  Versions

Extends:
Class "AnnotatedDataFrame", directly
Class "Versioned", by class "AnnotatedDataFrame", distance 2
```


Cardinal design and development

In addition, varMetadata must have a column named "labelType", which is a `factor`, and takes on the values "pheno", "sample", or "dim". If a variable is "dim", then it describes pixel coordinates; if a variable is "sample", then the variable is the "sample" column *and it is not currently acting as a pixel coordinate*; if a variable is "pheno", then it is describing phenotype.

Note that the "sample" column may sometimes act as a pixel coordinate, in which case its "labelType" will be "dim", while all other times its "labelType" will be "sample".

6 MIAPE-Imaging: Minimum Information About a Proteomics Experiment for MS imaging

For `MSImageSet` objects, the `experimentData` slot must be an object of class `MIAPE-Imaging`. That is the Minimum Information About a Proteomics Experiment for Imaging. Most of its unique slots are based on the imzML specification.

```
> getClass("MIAPE-Imaging")
Class "MIAPE-Imaging" [package "Cardinal"]

Slots:

Name:          title          abstract          url          pubMedIds          preprocessing
Class:         character      character        character    character          list

Name:          other          name             lab           contact            samples
Class:         list           character        character    character          list

Name:          specimenOrigin specimenType      stainingMethod tissueThickness    tissueWash
Class:         character      character        character    numeric            character

Name:          embeddingMethod inSituChemistry matrixApplication pixelSize          instrumentModel
Class:         character      character        character    numeric            character

Name:          instrumentVendor massAnalyzerType ionizationType    scanPolarity       softwareName
Class:         character      character        character        character           character

Name:          softwareVersion scanType          scanPattern      scanDirection      lineScanDirection
Class:         character      character        character        character           character

Name:          imageShape  .__classVersion__
Class:         character    Versions

Extends:
Class "MIAxE", directly
Class "Versioned", by class "MIAxE", distance 2
```

7 MSImageProcess: mass spectral pre-processing information

MSImageSet objects also have a processingData slot, which must be an object of class MSImageProcess. This gives information about the pre-processing steps that have been applied to the dataset. All of the standard pre-processing methods in Cardinal will fill in processingData with the appropriate processing type automatically.

```
> getClass("MSImageProcess")
Class "MSImageProcess" [package "Cardinal"]

Slots:

Name:          files          normalization          smoothing          baselineReduction
Class:         character      character            character          character

Name: spectrumRepresentation          peakPicking          centroided          history
Class:         character              character            logical            list

Name:          CardinalVersion          .__classVersion__
Class:         character                Versions

Extends: "Versioned"
```

8 ResultSet: analysis results for imaging experiments

ResultSet is a subclass of iSet, and is used to storing the results of analyses applied to iSet and iSet-derived objects.

```
> getClass("ResultSet")
Virtual Class "ResultSet" [package "Cardinal"]

Slots:

Name:          resultData          modelData          imageData          pixelData
Class:         list AnnotatedDataFrame          ImageData IAnnotatedDataFrame

Name:          featureData          experimentData          protocolData          .__classVersion__
Class:         AnnotatedDataFrame          MIAxE AnnotatedDataFrame          Versions

Extends:
Class "iSet", directly
Class "VersionedBiobase", by class "iSet", distance 2
Class "Versioned", by class "iSet", distance 3

Known Subclasses: "CrossValidated", "PCA", "PLS", "OPLS", "SpatialKMeans", "SpatialShrunkenCentroids"
```

Cardinal design and development

In addition to the usual `iSet` slots, a `ResultSet` also has a `resultData` slot, which is a `list` used to store results, and a `modelData` slot, which describes the parameters of the fitted model. The `ResultSet` class assumes that multiple models may be fit (i.e., multiple parameter sets over a grid search). Therefore, each element of the `resultData list` should be another `list` containing the results for a single model, and each row of `modelData` should describe the parameters for that one model.

9 Visualization for high-throughput imaging experiments

Cardinal provides a thorough methods for data visualization inspired by the *lattice* graphics system. *Cardinal* can display multiple images or plots in a grid of panels based on conditions.

For example, for mass spectrometry imaging, multiple ion images or mass spectra can be plotted together on the same intensity scale. They can be plotted according to different conditions, such as the mean spectra for different phenotypes, etc.

9.1 `SImageData` and `MSImageData`

The main *Cardinal* walkthrough vignette describes in detail the `plot` and `image` methods for `SImageData` and `MSImageData` objects, which use *lattice*-style formulae and arguments.

9.2 `ResultSet`

Of interest to developers is writing simple methods for the plotting of `ResultSet` objects. The `plot` and `image` methods for `ResultSet` make it straightforward to write visualization methods for any kind of analysis results.

The `plot` method can create plots of results against features (such as model coefficients), while `image` creates images of results (such as predicted values).

For example, consider the `plot` and `image` methods for the `PCA` class, which is a subclass of `ResultSet` for principal components analysis.

```
> selectMethod("plot", c("PCA", "missing"))  
Method Definition:  
  
function (x, y, ...)  
{  
  .local <- function (x, formula = substitute(mode ~ mz), mode = "loadings",  
    type = "h", ...)  
  {  
    mode <- match.arg(mode)  
    callNextMethod(x, formula = formula, type = type, ...)  
  }  
  .local(x, ...)  
}
```

Cardinal design and development

```
<bytecode: 0xabc3e08>
<environment: namespace:Cardinal>

Signatures:
      x      y
target  "PCA" "missing"
defined "PCA" "missing"
> selectMethod("image", "PCA")

Method Definition:

function (x, ...)
{
  .local <- function (x, formula = substitute(mode ~ x * y),
    mode = "scores", ...)
  {
    mode <- match.arg(mode)
    callNextMethod(x, formula = formula, ...)
  }
  .local(x, ...)
}
<bytecode: 0xd73a0a0>
<environment: namespace:Cardinal>

Signatures:
      x
target  "PCA"
defined "PCA"
```

The left-hand side of the formula (which can be changed by the “mode” argument in the above example) should be an element in the `resultData` of the `ResultSet` class. So `plot` will plot the PC loadings, while `image` will plot an image of the PC scores.

Such a method will work for two types of results: matrices with the same number of rows as the number of features (for `plot`), and matrices with the same number of rows as the number of pixels (for `image`).

Usual *lattice*-style arguments will work for `ResultSet` as they would for `SImageData` and `MSImageData`, such as “superpose” for plotting results from different models on the same panel or separate panels.

10 Testing during development

Cardinal provides some simple tools to aid in the development of new analysis methods, such as for testing simulated data and timing analyses.

Cardinal design and development

10.1 Simulating mass spectra

The main *Cardinal* walkthrough vignette describes in detail the `generateSpectrum` and `generateImage` methods for generating mass spectra and images.

10.2 Timing and diagnostics

Cardinal provides an option for automatically timing all of its own pre-processing and analysis routines.

```
> options(Cardinal.timing=TRUE)
```

Some of its analysis methods such as `spatialkMeans` and `spatialShrunkenCentroids` also report timings as part of their standard results.

11 Session info

- R version 3.5.2 (2018-12-20), x86_64-pc-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_US.UTF-8, LC_COLLATE=C, LC_MONETARY=en_US.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_US.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_US.UTF-8, LC_IDENTIFICATION=C
- Running under: Ubuntu 16.04.5 LTS
- Matrix products: default
- BLAS: /home/biocbuild/bbs-3.8-bioc/R/lib/libRblas.so
- LAPACK: /home/biocbuild/bbs-3.8-bioc/R/lib/libRlapack.so
- Base packages: base, datasets, grDevices, graphics, methods, parallel, stats, stats4, utils
- Other packages: BiocGenerics 0.28.0, BiocParallel 1.16.5, Cardinal 2.0.3, EBImage 4.24.0, ProtGenerics 1.14.0, S4Vectors 0.20.1
- Loaded via a namespace (and not attached): Biobase 2.42.0, BiocManager 1.30.4, BiocStyle 2.10.0, DBI 1.0.0, MASS 7.3-51.1, Matrix 1.2-15, R6 2.3.0, RCurl 1.95-4.11, Rcpp 1.0.0, abind 1.4-5, assertthat 0.2.0, biglm 0.9-1, bindr 0.1.1, bindrcpp 0.2.2, bitops 1.0-6, compiler 3.5.2, crayon 1.3.4, digest 0.6.18, dplyr 0.7.8, evaluate 0.12, fftwtools 0.9-8, glue 1.3.0, grid 3.5.2, htmltools 0.3.6, htmlwidgets 1.3, irlba 2.3.2, jpeg 0.1-8, knitr 1.21, lattice 0.20-38, locfit 1.5-9.1, magrittr 1.5, matter 1.8.3, pillar 1.3.1, pkgconfig 2.0.2, png 0.1-7, purrr 0.2.5, rlang 0.3.0.1, rmarkdown 1.11, signal 0.7-6, sp 1.3-1, tibble 2.0.0, tidyselect 0.2.5, tiff 0.1-5, tools 3.5.2, xfun 0.4, yaml 2.2.0