

# Package ‘EWCE’

May 16, 2024

**Type** Package

**Title** Expression Weighted Celltype Enrichment

**Version** 1.12.0

**Description** Used to determine which cell types are enriched within gene lists. The package provides tools for testing enrichments within simple gene lists (such as human disease associated genes) and those resulting from differential expression studies. The package does not depend upon any particular Single Cell Transcriptome dataset and user defined datasets can be loaded in and used in the analyses.

**URL** <https://github.com/NathanSkene/EWCE>

**BugReports** <https://github.com/NathanSkene/EWCE/issues>

**License** GPL-3

**Depends** R (>= 4.2), RNOmni (>= 1.0)

**VignetteBuilder** knitr

**Imports** stats, utils, methods, ewceData (>= 1.7.1), dplyr, ggplot2, reshape2, limma, stringr, HGNCHELPER, Matrix, parallel, SingleCellExperiment, SummarizedExperiment, DelayedArray, BiocParallel, orthogene (>= 0.99.8), data.table

**Suggests** rworkflows, remotes, knitr, BiocStyle, rmarkdown, testthat (>= 3.0.0), readxl, memoise, markdown, sctransform, DESeq2, MAST, DelayedMatrixStats, ggdendro, scales, patchwork

**biocViews** GeneExpression, Transcription, DifferentialExpression, GeneSetEnrichment, Genetics, Microarray, mRNA Microarray, OneChannel, RNASeq, BiomedicalInformatics, Proteomics, Visualization, FunctionalGenomics, SingleCell

**RoxygenNote** 7.2.3

**Encoding** UTF-8

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/EWCE>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** d697d5e

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-05-16

**Author** Alan Murphy [cre] (<<https://orcid.org/0000-0002-2487-8753>>),  
 Brian Schilder [aut] (<<https://orcid.org/0000-0001-5949-2191>>),  
 Nathan Skene [aut] (<<https://orcid.org/0000-0002-6807-3180>>)

**Maintainer** Alan Murphy <alanmurph94@hotmail.com>

## Contents

EWCE-package . . . . .	4
add_res_to_merging_list . . . . .	5
assign_cores . . . . .	6
bin_columns_into_quantiles . . . . .	6
bin_specificity_into_quantiles . . . . .	7
bootstrap_enrichment_test . . . . .	8
bootstrap_plot . . . . .	11
bootstrap_plots_for_transcriptome . . . . .	12
calculate_meanexp_for_level . . . . .	12
calculate_specificity_for_level . . . . .	13
cell_list_dist . . . . .	13
check_annotLevels . . . . .	14
check_args_for_bootstrap_plot_generation . . . . .	14
check_bootstrap_args . . . . .	15
check_controlled_args . . . . .	16
check_ewce_expression_data_args . . . . .	17
check_ewce_genelist_inputs . . . . .	18
check_full_results . . . . .	20
check_generate_controlled_bootstrap_geneset . . . . .	20
check_group_name . . . . .	21
check_nas . . . . .	21
check_numeric . . . . .	22
check_percent_hits . . . . .	22
check_sce . . . . .	23
check_species . . . . .	23
compute_gene_counts . . . . .	24
compute_gene_scores . . . . .	25
controlled_geneset_enrichment . . . . .	26
convert_new_ewce_to_old . . . . .	28
convert_old_ewce_to_new . . . . .	28
create_background_multilist . . . . .	29
create_list_network . . . . .	30
ctd_to_sce . . . . .	30
delayedarray_normalize . . . . .	31
drop_nonexpressed_cells . . . . .	32
drop_nonexpressed_genes . . . . .	32

drop_uninformative_genes . . . . .	33
dt_to_df . . . . .	36
ewce_expression_data . . . . .	37
ewce_plot . . . . .	39
example_bootstrap_results . . . . .	40
example_transcriptome_results . . . . .	41
extract_matrix . . . . .	42
filter_ctd_genes . . . . .	45
filter_genes_without_1to1_homolog . . . . .	46
filter_nonorthologs . . . . .	47
filter_variance_quantiles . . . . .	50
fix_bad_hgnc_symbols . . . . .	51
fix_bad_mgi_symbols . . . . .	52
fix_celltype_names . . . . .	53
fix_celltype_names_full_results . . . . .	54
generate_bootstrap_plots . . . . .	54
generate_bootstrap_plots_for_transcriptome . . . . .	57
generate_celltype_data . . . . .	60
generate_controlled_bootstrap_geneset . . . . .	64
get_celltype_table . . . . .	65
get_ctd_levels . . . . .	65
get_ctd_matrix_names . . . . .	66
get_exp_data_for_bootstrapped_genes . . . . .	66
get_sig_results . . . . .	67
get_summed_proportions . . . . .	68
is_32bit . . . . .	69
is_celltypedataset . . . . .	70
is_ctd_standardised . . . . .	70
is_delayed_array . . . . .	71
is_matrix . . . . .	71
is_sparse_matrix . . . . .	72
list_species . . . . .	72
load_rdata . . . . .	73
max_ctd_depth . . . . .	73
merged_ewce . . . . .	74
merge_ctd . . . . .	75
merge_sce . . . . .	77
merge_sce_list . . . . .	78
merge_two_expfiles . . . . .	79
messenger . . . . .	80
message_parallel . . . . .	80
myScalesComma . . . . .	81
plot_ctd . . . . .	81
plot_log_bootstrap_distributions . . . . .	82
plot_with_bootstrap_distributions . . . . .	82
prep.dendro . . . . .	83
prepare_genesize_control_network . . . . .	84
prepare_tt . . . . .	85

prep_dendro . . . . .	86
report_dge . . . . .	86
report_results . . . . .	87
run_deseq2 . . . . .	87
run_limma . . . . .	88
run_mast . . . . .	89
sce_lists_apply . . . . .	90
sce_merged_apply . . . . .	90
sct_normalize . . . . .	91
standardise_ctd . . . . .	91
theme_graph . . . . .	95
to_dataframe . . . . .	95
to_delayed_array . . . . .	96
to_sparse_matrix . . . . .	96
<b>Index</b>	<b>97</b>

---

EWCE-package

*EWCE: Expression Weighted Celltype Enrichment*


---

## Description

Used to determine which cell types are enriched within gene lists. The package provides tools for testing enrichments within simple gene lists (such as human disease associated genes) and those resulting from differential expression studies. The package does not depend upon any particular Single Cell Transcriptome dataset and user defined datasets can be loaded in and used in the analyses.

## Details

EWCE: Expression Weighted Celltype Enrichment

Used to determine which cell types are enriched within gene lists. The package provides tools for testing enrichments within simple gene lists (such as human disease associated genes) and those resulting from differential expression studies.

The package does not depend upon any particular Single Cell Transcriptome dataset and user defined datasets can be loaded in and used in the analyses.

## Author(s)

**Maintainer:** Alan Murphy <alanmurph94@hotmail.com> ([ORCID](#))

Authors:

- Brian Schilder <brian\_schilder@alumni.brown.edu> ([ORCID](#))
- Nathan Skene <nathan.skene@gmail.com> ([ORCID](#))

## See Also

Useful links:

- <https://github.com/NathanSkene/EWCE>
- Report bugs at <https://github.com/NathanSkene/EWCE/issues>

---

add\_res\_to\_merging\_list

*Add to results to merging list*

---

## Description

add\_res\_to\_merging\_list adds EWCE results to a list for merging analysis.

## Usage

```
add_res_to_merging_list(full_res, existing_results = NULL)
```

## Arguments

**full\_res** Results list generated using [bootstrap\\_enrichment\\_test](#) or [ewce\\_expression\\_data](#) functions. Multiple results tables can be merged into one results table, as long as the 'list' column is set to distinguish them.

**existing\_results** Output of previous rounds from adding results to list. Leave empty if this is the first item in the list.

## Value

Merged results list.

## Examples

```
# Load the single cell data
ctd <- ewceData::ctd()

# Load the data
tt_alzh <- ewceData::tt_alzh()
# tt_alzh_BA36 <- ewceData::tt_alzh_BA36()
# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
# Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5
# Run EWCE analysis
# tt_results <- ewce_expression_data(
#   sct_data = ctd, tt = tt_alzh, annotLevel = 1, thresh = thresh,
#   reps = reps, ttSpecies = "human", sctSpecies = "mouse"
# )
```

```
# tt_results_36 <- ewce_expression_data(
#   sct_data = ctd, tt = tt_alzh_BA36, annotLevel = 1, thresh = thresh,
#   reps = reps, ttSpecies = "human", sctSpecies = "mouse"
# )

# Fill a list with the results
results <- add_res_to_merging_list(tt_alzh)
# results <- add_res_to_merging_list(tt_alzh_BA36, results)
```

---

assign\_cores

*Assign cores*

---

### Description

Assign cores automatically for parallel processing, while reserving some.

### Usage

```
assign_cores(worker_cores = 0.9, verbose = TRUE)
```

### Arguments

worker\_cores    Number (>1) or proportion (<1) of worker cores to use.  
 verbose        Print messages.

### Value

List of core allocations.

---

bin\_columns\_into\_quantiles

*bin\_columns\_into\_quantiles*

---

### Description

`bin_columns_into_quantiles` is an internal function used to convert a vector of specificity into a vector of specificity quantiles. This function can be iterated across a matrix using [apply](#) to create a matrix of specificity quantiles.

### Usage

```
bin_columns_into_quantiles(
  vec,
  numberOfBins = 40,
  defaultBin = as.integer(numberOfBins/2)
)
```

**Arguments**

vec	The vector of gene of specificity values.
numberOfBins	Number of quantile bins to use (40 is recommended).
defaultBin	Which bin to assign when there's only one non-zero quantile. In situations where there's only one non-zero quantile, <code>cut</code> throws an error. Avoid these situations by using a default quantile.

**Value**

A vector with same length as `vec` but with columns storing quantiles instead of specificity.

**Examples**

```
ctd <- ewceData::ctd()
ctd[[1]]$specificity_quantiles <- apply(ctd[[1]]$specificity, 2,
  FUN = bin_columns_into_quantiles)
```

---

```
bin_specificity_into_quantiles
      bin_specificity_into_quantiles
```

---

**Description**

`bin_specificity_into_quantiles` is an internal function used to convert add '`$specificity_quantiles`' to a `ctd`

**Usage**

```
bin_specificity_into_quantiles(
  ctdIN,
  numberOfBins,
  matrix_name = "specificity_quantiles",
  as_sparse = TRUE,
  verbose = TRUE
)
```

**Arguments**

ctdIN	A single <code>annotLevel</code> of a <code>ctd</code> , i.e. <code>ctd[[1]]</code> (the function is intended to be used via <code>apply</code> ).
numberOfBins	Number of quantile 'bins' to use (40 is recommended).
matrix_name	Name of the specificity matrix to create (default: "specificity_quantiles").
as_sparse	Convert to <code>sparseMatrix</code> .
verbose	Print messages.

**Value**

A ctd with "specificity\_quantiles" matrix in each level (or whatever matrix\_name was set to.).

**Examples**

```
ctd <- ewceData::ctd()
ctd <- lapply(ctd, EWCE::bin_specificity_into_quantiles, numberOfBins = 40)
print(ctd[[1]]$specificity_quantiles[1:3, ])
```

---

bootstrap\_enrichment\_test

*Bootstrap cell type enrichment test*

---

**Description**

bootstrap\_enrichment\_test takes a genelist and a single cell type transcriptome dataset and determines the probability of enrichment and fold changes for each cell type.

**Usage**

```
bootstrap_enrichment_test(
  sct_data = NULL,
  hits = NULL,
  bg = NULL,
  genelistSpecies = NULL,
  sctSpecies = NULL,
  sctSpecies_origin = sctSpecies,
  output_species = "human",
  method = "homologene",
  reps = 100,
  no_cores = 1,
  annotLevel = 1,
  geneSizeControl = FALSE,
  controlledCT = NULL,
  mtc_method = "BH",
  sort_results = TRUE,
  standardise_sct_data = TRUE,
  standardise_hits = FALSE,
  verbose = TRUE,
  localHub = FALSE,
  store_gene_data = TRUE
)
```



**Arguments**

sct_data	List generated using <a href="#">generate_celltype_data</a> .
hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if <code>geneSizeControl=TRUE</code> .
bg	List of gene symbols containing the background gene list (including hit genes). If <code>bg=NULL</code> , an appropriate gene background will be created automatically.
genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies	Species that sct_data is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies_origin	Species that the sct_data originally came from, regardless of its current gene format (e.g. it was previously converted from mouse to human gene orthologs). This is used for computing an appropriate background.
output_species	Species to convert sct_data and hits to (Default: "human"). See <a href="#">list_species</a> for all available species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
no_cores	Number of cores to parallelise bootstrapping reps over.
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
geneSizeControl	Whether you want to control for GC content and transcript length. Recommended if the gene list originates from genetic studies ( <i>Default: FALSE</i> ). If set to TRUE, then hits must be from humans.
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.
mtc_method	Multiple-testing correction method (passed to <a href="#">p.adjust</a> ).
sort_results	Sort enrichment results from smallest to largest p-values.
standardise_sct_data	Should sct_data be standardised? if TRUE: <ul style="list-style-type: none"> <li>• When <code>sctSpecies!=output_species</code> the sct_data will be checked for object formatting and the genes will be converted to the orthologs of the output_species with <a href="#">standardise_ctd</a> (which calls <a href="#">map_genes</a> internally).</li> <li>• When <code>sctSpecies==output_species</code>, the sct_data will be checked for object formatting with <a href="#">standardise_ctd</a>, but the gene names will remain untouched.</li> </ul>

standardise_hits	Should hits be standardised? If TRUE: <ul style="list-style-type: none"> <li>• When <code>genelistSpecies!=output_species</code>, the genes will be converted to the orthologs of the <code>output_species</code> with <a href="#">convert_orthologs</a>.</li> <li>• When <code>genelistSpecies==output_species</code>, the genes will be standardised with <a href="#">map_genes</a>.</li> </ul> If FALSE, hits will be passed on to subsequent steps as-is.
verbose	Print messages.
localHub	If working offline, add argument <code>localHub=TRUE</code> to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see <a href="#">BiocManager vignette</a> section on offline use to ensure proper functionality.
store_gene_data	Store sampled gene data for every bootstrap iteration. When the number of bootstrap reps is very high ( $\geq 100k$ ) and/or the number of genes in hits is very high, you may want to set <code>store_gene_data=FALSE</code> to avoid using excessive amounts of CPU memory.

## Value

A list containing three elements:

- `hit.cells`: vector containing the summed proportion of expression in each cell type for the target list.
- `gene_data`: `data.table` showing the number of time each gene appeared in the bootstrap sample.
- `bootstrap_data`: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists
- `controlledCT`: the controlled cell type (if applicable)

## Examples

```
# Load the single cell data
sct_data <- ewceData::ctd()
# Set the parameters for the analysis
# Use 3 bootstrap lists for speed, for publishable analysis use  $\geq 10,000$ 
reps <- 3
# Load gene list from Alzheimer's disease GWAS
hits <- ewceData::example_genelist()

# Bootstrap significance test, no control for transcript length or GC content
full_results <- EWCE::bootstrap_enrichment_test(
  sct_data = sct_data,
  hits = hits,
  reps = reps,
  annotLevel = 1,
  sctSpecies = "mouse",
  genelistSpecies = "human")
```

---

bootstrap_plot	<i>Bootstrap plot</i>
----------------	-----------------------

---

## Description

Plot bootstrap enrichment results. Support function for [generate\\_bootstrap\\_plots](#).

## Usage

```
bootstrap_plot(  
  gene_data,  
  exp_mats = NULL,  
  save_dir = file.path(tempdir(), "BootstrapPlots"),  
  listFileName,  
  signif_ct = NULL,  
  hit_thresh = 25,  
  facets = "CellType",  
  scales = "free_x",  
  show_plot = TRUE,  
  verbose = TRUE  
)
```

## Arguments

gene_data	Output from <a href="#">compute_gene_scores</a> .
exp_mats	Output of <a href="#">generate_bootstrap_plots_exp_mats</a> .
save_dir	Directory to save plots to.
listFileName	listFileName
signif_ct	Significant celltypes to include the plots.
facets	<b>[Deprecated]</b> Please use rows and cols instead.
scales	Are scales shared across all facets (the default, "fixed"), or do they vary across rows ("free_x"), columns ("free_y"), or both rows and columns ("free")?
show_plot	Print the plot.

## Value

Null output.

---

bootstrap\_plots\_for\_transcriptome  
*Bootstrap plot*

---

**Description**

Plot results of [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#).

**Usage**

```
bootstrap_plots_for_transcriptome(  
  dat,  
  tag,  
  listFileName,  
  cc,  
  showGNameThresh,  
  graph_theme,  
  maxX,  
  save_dir = file.path(tempdir(), paste0("BootstrapPlots", "_for_transcriptome")),  
  height = 3.5,  
  width = 3.5,  
  show_plot = TRUE  
)
```

**Value**

Null result.

---

calculate\_meanexp\_for\_level  
*calculate\_meanexp\_for\_level*

---

**Description**

calculate\_meanexp\_for\_level

**Usage**

```
calculate_meanexp_for_level(  
  ctd_oneLevel,  
  expMatrix,  
  as_sparse = TRUE,  
  verbose = TRUE  
)
```

**Value**

One level of a CellTypeDataset.

---

```
calculate_specificity_for_level
      Calculate specificity for one CTD level
```

---

**Description**

Calculate specificity for one CellTypeDataset (CTD) level.

**Usage**

```
calculate_specificity_for_level(
  ctd_oneLevel,
  matrix_name = "mean_exp",
  as_sparse = TRUE,
  verbose = TRUE
)
```

**Arguments**

ctd_oneLevel	One level from a CTD.
matrix_name	Name of the matrix to extract.
as_sparse	Whether to convert exp to sparse matrix
verbose	Print messages.

**Value**

One CTD level.

---

```
cell_list_dist      cell_list_dist
```

---

**Description**

specificity is generated in the main\_CellTypeAnalysis\_Preperation.r file

**Usage**

```
cell_list_dist(hits, sct_data, annotLevel)
```

**Arguments**

hits	List of gene symbols containing the target gene list.
sct_data	List generated using <a href="#">generate_celltype_data</a> .
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).

**Value**

The summed specificity of each celltype across a set of hits.

---

check_annotLevels	<i>check_annotLevels First, check the number of annotations equals the number of columns in the expression data.</i>
-------------------	--

---

**Description**

check\_annotLevels

First, check the number of annotations equals the number of columns in the expression data.

**Usage**

```
check_annotLevels(annotLevels, exp)
```

**Arguments**

exp            exp (#fix).

**Value**

Null output.

---

check_args_for_bootstrap_plot_generation	<i>check_args_for_bootstrap_plot_generation</i>
--	---

---

**Description**

Check the input arguments of the [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#).

**Usage**

```

check_args_for_bootstrap_plot_generation(
  sct_data,
  tt,
  thresh,
  annotLevel,
  reps,
  full_results,
  listFileName,
  showGNameThresh,
  sortBy
)

```

**Arguments**

sct_data	List generated using <a href="#">generate_celltype_data</a> .
tt	Differential expression table. Can be output of <a href="#">topTable</a> function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
thresh	The number of up- and down- regulated genes to be included in each analysis (Default: 250).
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
full_results	The full output of <a href="#">ewce_expression_data</a> for the same gene list.
listFileName	String used as the root for files saved using this function.
showGNameThresh	Integer. If a gene has over X percent of it's expression proportion in a cell type, then list the gene name.
sortBy	Column name of metric in tt which should be used to sort up- from down-regulated genes (Default: "t").

**Value**

Null output.

---

check\_bootstrap\_args    *check\_bootstrap\_args*

---

**Description**

Check the input arguments of the [bootstrap\\_enrichment\\_test](#).

**Usage**

```

check_bootstrap_args(
  sct_data,
  hits,
  annotLevel,
  reps,
  controlledCT = NULL,
  fix_celltypes = TRUE
)

```

**Arguments**

sct_data	List generated using <a href="#">generate_celltype_data</a> .
hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if geneSizeControl=TRUE.
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.

**Value**

Null output.

---

check\_controlled\_args *check\_controlled\_args*

---

**Description**

Check the input arguments of the [controlled\\_geneset\\_enrichment](#).

**Usage**

```

check_controlled_args(
  bg,
  sct_data,
  annotLevel,
  disease_genes,
  hits,
  functional_genes,
  funcGenes,
  combinedGenes
)

```



**Arguments**

bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
sct_data	List generated using <a href="#">generate_celltype_data</a> .
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
disease_genes	Array of gene symbols containing the disease gene list. Does not have to be disease genes. Must be from same species as the single cell transcriptome dataset.
hits	Hit genes.
functional_genes	Array of gene symbols containing the functional gene list. The enrichment of this gene set within the disease_genes is tested. Must be from same species as the single cell transcriptome dataset.
funcGenes	functional_genes that are within combinedGenes.
combinedGenes	sct_data genes that are in the background bg.

**Value**

Null output.

---

check\_ewce\_expression\_data\_args

*check\_ewce\_expression\_data\_args*

---

**Description**

Check the input arguments of the [ewce\\_expression\\_data](#).

**Usage**

```
check_ewce_expression_data_args(sortBy, tt, thresh)
```

**Arguments**

sortBy	Column name of metric in tt which should be used to sort up- from down-regulated genes (Default: "t").
tt	Differential expression table. Can be output of <a href="#">topTable</a> function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
thresh	The number of up- and down- regulated genes to be included in each analysis (Default: 250).

**Value**

Null output.

---

```
check_ewce_genelist_inputs
    check_ewce_genelist_inputs
```

---

### Description

check\_ewce\_genelist\_inputs Is used to check that hits and bg gene lists passed to EWCE are setup correctly. Checks they are the appropriate length. Checks all hits are in bg. Checks the species match and if not reduces to 1:1 orthologs.

### Usage

```
check_ewce_genelist_inputs(
  sct_data,
  hits,
  bg = NULL,
  genelistSpecies = NULL,
  sctSpecies = NULL,
  sctSpecies_origin = sctSpecies,
  output_species = "human",
  method = "homologene",
  geneSizeControl = FALSE,
  standardise_sct_data = TRUE,
  standardise_hits = FALSE,
  min_genes = 4,
  verbose = TRUE
)
```

### Arguments

sct_data	List generated using <a href="#">generate_celltype_data</a> .
hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if geneSizeControl=TRUE.
bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies	Species that sct_data is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies_origin	Species that the sct_data originally came from, regardless of its current gene format (e.g. it was previously converted from mouse to human gene orthologs). This is used for computing an appropriate background.
output_species	Species to convert sct_data and hits to (Default: "human"). See <a href="#">list_species</a> for all available species.

method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
geneSizeControl	Whether you want to control for GC content and transcript length. Recommended if the gene list originates from genetic studies ( <i>Default: FALSE</i> ). If set to TRUE, then hits must be from humans.
standardise_sct_data	Should sct_data be standardised? if TRUE: <ul style="list-style-type: none"> <li>• When sctSpecies!=output_species the sct_data will be checked for object formatting and the genes will be converted to the orthologs of the output_species with <a href="#">standardise_ctd</a> (which calls <a href="#">map_genes</a> internally).</li> <li>• When sctSpecies==output_species, the sct_data will be checked for object formatting with <a href="#">standardise_ctd</a>, but the gene names will remain untouched.</li> </ul>
standardise_hits	Should hits be standardised? If TRUE: <ul style="list-style-type: none"> <li>• When genelistSpecies!=output_species, the genes will be converted to the orthologs of the output_species with <a href="#">convert_orthologs</a>.</li> <li>• When genelistSpecies==output_species, the genes will be standardised with <a href="#">map_genes</a>.</li> </ul> If FALSE, hits will be passed on to subsequent steps as-is.
min_genes	Minimum number of genes in a gene list to test.
verbose	Print messages.

**Value**

A list containing

- hits: Array of MGI/HGNC gene symbols containing the target gene list.
- bg: Array of MGI/HGNC gene symbols containing the background gene list.

**Examples**

```
ctd <- ewceData::ctd()
example_genelist <- ewceData::example_genelist()

# Called from "bootstrap_enrichment_test()" and "generate_bootstrap_plots()"
checkedLists <- EWCE::check_ewce_genelist_inputs(
  sct_data = ctd,
  hits = example_genelist,
  sctSpecies = "mouse",
  genelistSpecies = "human"
)
```

---

check\_full\_results     *check\_full\_results*

---

**Description**

Check full results generated by [bootstrap\\_enrichment\\_test](#).

**Usage**

```
check_full_results(full_results, sct_data)
```

**Arguments**

full\_results     The full output of [bootstrap\\_enrichment\\_test](#) for the same gene list.  
sct\_data         List generated using [generate\\_celltype\\_data](#).

**Value**

Null output.

---

check\_generate\_controlled\_bootstrap\_geneset  
                                  *generate\_controlled\_bootstrap\_geneset*

---

**Description**

Check input arguments to [generate\\_controlled\\_bootstrap\\_geneset](#).

**Usage**

```
check_generate_controlled_bootstrap_geneset(  

  controlledCT,  

  annotLevel,  

  sct_data,  

  hits  

)
```

**Arguments**

controlledCT    [Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.  
annotLevel      An integer indicating which level of sct\_data to analyse (*Default: 1*).  
sct\_data        List generated using [generate\\_celltype\\_data](#).  
hits            List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if geneSizeControl=TRUE.

**Value**

Null output.

---

check_group_name	<i>Check group name</i>
------------------	-------------------------

---

**Description**

Ensure groupName argument is provided to [generate\\_celltype\\_data](#).

**Usage**

```
check_group_name(groupName)
```

**Arguments**

groupName      A human readable name for referring to the dataset being used.

**Value**

Null output.

---

check_nas	<i>Check NAs</i>
-----------	------------------

---

**Description**

Check for any NAs in an expression matrix.

**Usage**

```
check_nas(exp)
```

**Arguments**

exp      Expression matrix.

**Value**

Null output.

---

check_numeric	<i>Check numeric</i>
---------------	----------------------

---

**Description**

Ensure that a matrix is numeric. If not, it will be converted to numeric.

**Usage**

```
check_numeric(exp)
```

**Arguments**

exp	Input matrix.
-----	---------------

**Value**

Numeric expression matrix.

---

check_percent_hits	<i>Get percentage of target cell type hits</i>
--------------------	--

---

**Description**

After you run [bootstrap\\_enrichment\\_test](#), check what percentage of significantly enriched cell types match an expected cell type.

**Usage**

```
check_percent_hits(
  full_results,
  target_celltype,
  mtc_method = "bonferroni",
  q_threshold = 0.05,
  verbose = TRUE
)
```

**Arguments**

full_results	bootstrap_enrichment_test results.
target_celltype	Substring to search to matching cell types (case-insensitive).
mtc_method	Multiple-testing correction method.
q_threshold	Corrected significance threshold.
verbose	Print messages.

**Value**

Report list.

**Examples**

```
## Bootstrap significance test,
## no control for transcript length or GC content
## Use pre-computed results to speed up example
full_results <- EWCE::example_bootstrap_results()

report <- EWCE::check_percent_hits(
  full_results = full_results,
  target_celltype = "microglia"
)
```

---

check\_sce

*Check SingleCellExperiment*

---

**Description**

Check whether exp is a SingleCellExperiment (SCE) object and extract the relevant components.

**Usage**

```
check_sce(exp, verbose = TRUE)
```

**Value**

List of extracted SCE components.

---

check\_species

*Check species*

---

**Description**

If species arguments are NULL, set default species.

**Usage**

```
check_species(
  genelistSpecies = NULL,
  sctSpecies = NULL,
  sctSpecies_origin = NULL,
  sctSpecies_origin_default = "mouse",
  verbose = TRUE
)
```

**Arguments**

genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies	Species that sct_data is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies_origin	Species that the sct_data originally came from, regardless of its current gene format (e.g. it was previously converted from mouse to human gene orthologs). This is used for computing an appropriate background.
sctSpecies_origin_default	Default value for sctSpecies_origin.
verbose	Print messages.

**Value**

List of corrected species names.

---

compute\_gene\_counts    *Compute gene counts*

---

**Description**

Counts the number of times each gene appeared in the randomly sampled gene lists.

**Usage**

```
compute_gene_counts(bootstrap_list, verbose = TRUE)
```

**Arguments**

bootstrap_list	The output of <code>get_summed_proportions_iterate</code> .
verbose	Print messages.

**Value**

[data.table](#)



---

compute\_gene\_scores    *Compute gene counts*

---

## Description

Aggregate gene-level scores across all bootstrap iterations.

- boot: Mean specificity of all genes within a given cell type.
- hit: Mean specificity of a hit gene within a given cell type.

## Usage

```
compute_gene_scores(  
  sct_data,  
  annotLevel,  
  bootstrap_list = NULL,  
  hits,  
  combinedGenes,  
  reps = NULL,  
  exp_mats = NULL,  
  return_hit_exp = FALSE,  
  verbose = TRUE  
)
```

## Arguments

sct_data	List generated using <a href="#">generate_celltype_data</a> .
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
bootstrap_list	The output of <code>get_summed_proportions_iterate</code> .
hits	list of gene names. The target gene set.
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
return_hit_exp	Return the expression of each hit gene.
verbose	Print messages.

## Value

[data.table](#)

---

 controlled\_geneset\_enrichment

*Celltype controlled geneset enrichment*


---

## Description

controlled\_geneset\_enrichment tests whether a functional gene set is still enriched in a disease gene set after controlling for the disease gene set's enrichment in a particular cell type (the 'controlledCT')

## Usage

```
controlled_geneset_enrichment(
  disease_genes,
  functional_genes,
  bg = NULL,
  sct_data,
  sctSpecies = NULL,
  output_species = "human",
  disease_genes_species = NULL,
  functional_genes_species = NULL,
  method = "homologene",
  annotLevel,
  reps = 100,
  controlledCT,
  use_intersect = FALSE,
  verbose = TRUE
)
```

## Arguments

**disease\_genes** Array of gene symbols containing the disease gene list. Does not have to be disease genes. Must be from same species as the single cell transcriptome dataset.

**functional\_genes** Array of gene symbols containing the functional gene list. The enrichment of this gene set within the disease\_genes is tested. Must be from same species as the single cell transcriptome dataset.

**bg** List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.

**sct\_data** List generated using [generate\\_celltype\\_data](#).

**sctSpecies** Species that sct\_data is currently formatted as (no longer limited to just "mouse" and "human"). See [list\\_species](#) for all available species.

**output\_species** Species to convert sct\_data and hits to (Default: "human"). See [list\\_species](#) for all available species.

**disease\_genes\_species** Species of the disease\_genes gene set.

functional_genes_species	Species of the functional_genes gene set.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.
use_intersect	When species1 and species2 are both different from output_species, this argument will determine whether to use the intersect (TRUE) or union (FALSE) of all genes from species1 and species2.
verbose	Print messages.

### Value

A list containing three data frames:

- p\_controlled The probability that functional\_genes are enriched in disease\_genes while controlling for the level of specificity in controlledCT
- z\_controlled The z-score that functional\_genes are enriched in disease\_genes while controlling for the level of specificity in controlledCT
- p\_uncontrolled The probability that functional\_genes are enriched in disease\_genes WITHOUT controlling for the level of specificity in controlledCT
- z\_uncontrolled The z-score that functional\_genes are enriched in disease\_genes WITHOUT controlling for the level of specificity in controlledCT
- reps=reps
- controlledCT
- actualOverlap=actual The number of genes that overlap between functional and disease gene sets

### Examples

```
# See the vignette for more detailed explanations
# Gene set enrichment analysis controlling for cell type expression
# set seed for bootstrap reproducibility
set.seed(12345678)
## load merged dataset from vignette
ctd <- ewceData::ctd()
schiz_genes <- ewceData::schiz_genes()
hpsd_genes <- ewceData::hpsd_genes()
# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
```

```
res_hpsd_schiz <- EWCE::controlled_geneset_enrichment(  
  disease_genes = schiz_genes,  
  functional_genes = hpsd_genes,  
  sct_data = ctd,  
  annotLevel = 1,  
  reps = reps,  
  controlledCT = "pyramidal CA1"  
)
```

---

```
convert_new_ewce_to_old  
  convert_new_ewce_to_old
```

---

### Description

convert\_new\_ewce\_to\_old Used to get an old style EWCE ctd file from a new one

### Usage

```
convert_new_ewce_to_old(ctd, lvl)
```

### Arguments

ctd	A cell type data structure containing "mean_exp" and "specificity".
lvl	The annotation level to extract.

### Value

CellTypeData in the old data structure style.

---

```
convert_old_ewce_to_new  
  convert_old_ewce_to_new
```

---

### Description

convert\_old\_ewce\_to\_new Used to get a new style EWCE ctd file (mean\_exp/specificity) from old ones (all\_scts).

### Usage

```
convert_old_ewce_to_new(level1 = NA, level2 = NA, celltype_data = NA)
```

**Arguments**

level1            File path to old level1 of EWCE ctd.  
 level2            File path to old level2 of EWCE ctd.  
 celltype\_data    The ctd to be converted.

**Details**

If you've already loaded it and want to pass it as a celltype\_data structure, then don't set level1 or level2.

**Value**

CellTypeData in the new data structure style.

---

create\_background\_multilist

*Create background gene list for multiple species*

---

**Description**

Create background gene list for the intersection/union between multiple species (gene\_list1\_species, gene\_list2\_species, and sctSpecies), and then filter the gene lists to only include genes within the background.

**Usage**

```
create_background_multilist(
  gene_list1,
  gene_list2,
  gene_list1_species,
  gene_list2_species,
  output_species = "human",
  bg = NULL,
  use_intersect = FALSE,
  method = "homologene",
  verbose = TRUE
)
```

**Arguments**

output\_species    Species to convert all genes from species1 and species2 to first. Default="human", but can be to either any species supported by **orthogene**, including species1 or species2.  
 bg                User supplied background list that will be returned to the user after removing duplicate genes.

use_intersect	When species1 and species2 are both different from output_species, this argument will determine whether to use the intersect (TRUE) or union (FALSE) of all genes from species1 and species2.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
verbose	Print messages.

**Value**

Background and gene list.

---

create\_list\_network    create\_list\_network

---

**Description**

Support function for prepare\_genesize\_control\_network.

**Usage**

```
create_list_network(data_byGene2, hits_NEW, reps = 10000, no_cores = 1)
```

**Value**

List network

---

ctd\_to\_sce                      *CellTypeDataset to SingleCellExperiment*

---

**Description**

Copied from [scKirby](#), which is not yet on CRAN or Bioconductor.

**Usage**

```
ctd_to_sce(object, as_sparse = TRUE, as_DelayedArray = FALSE, verbose = TRUE)
```

**Arguments**

object	CellTypeDataset object.
as_sparse	Store SingleCellExperiment matrices as sparse.
as_DelayedArray	Store SingleCellExperiment matrices as DelayedArray.
verbose	Print messages.

**Value**

SingleCellExperiment

**Examples**

```
ctd <- ewceData::ctd()
sce <- EWCE::ctd_to_sce(ctd)
```

---

delayedarray\_normalize

*Efficiently normalize a DelayedArray*

---

**Description**

The following is a matrix normalization procedure that takes advantage of functions designed to be more efficient for DelayedArray objects.

**Usage**

```
delayedarray_normalize(  
  exp,  
  log_norm = TRUE,  
  min_max = TRUE,  
  plot_hists = FALSE,  
  no_cores = 1  
)
```

**Arguments**

exp	Input matrix (e.g. gene expression).
log_norm	Whether to first log-normalise exp with <a href="#">log1p</a> .
min_max	Whether to min/max-normalise exp.
no_cores	Number of cores to parallelise across.

**Value**

Normalised matrix.

drop\_nonexpressed\_cells

*Drop cells with zero gene counts*

---

**Description**

Remove columns (cells) in which (gene) counts sum to zero.

**Usage**

```
drop_nonexpressed_cells(exp, annotLevels, verbose = TRUE)
```

**Arguments**

exp	Gene expression matrix.
annotLevels	Cell-wise annotations to be subset if some cells are dropped.
verbose	Print messages.

**Value**

List of filtered exp and annotLevels.

---

drop\_nonexpressed\_genes

*Drop genes with zero counts*

---

**Description**

Remove rows (genes) in which counts sum to zero.

**Usage**

```
drop_nonexpressed_genes(exp, verbose = TRUE)
```

**Arguments**

exp	Gene expression matrix.
verbose	Print messages.

**Value**

List of filtered exp.



---

 drop\_uninformative\_genes

*Drop uninformative genes*


---

## Description

drop\_uninformative\_genes drops uninformative genes in order to reduce compute time and noise in subsequent steps. It achieves this through several steps, each of which are optional:

- Drop non-1:1 orthologs:  
Removes genes that don't have 1:1 orthologs with the output\_species ("human" by default).
- Drop non-varying genes:  
Removes genes that don't vary across cells based on variance deciles.
- Drop non-differentially expressed genes (DEGs):  
Removes genes that are not significantly differentially expressed across cell-types (multiple DEG methods available).

## Usage

```
drop_uninformative_genes(
  exp,
  level2annot,
  mtc_method = "BH",
  adj_pval_thresh = 1e-05,
  convert_orths = FALSE,
  input_species = NULL,
  output_species = "human",
  non121_strategy = "drop_both_species",
  method = "homologene",
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  return_sce = FALSE,
  no_cores = 1,
  verbose = TRUE,
  ...
)
```

## Arguments

exp	Expression matrix with gene names as rownames.
level2annot	Array of cell types, with each sequentially corresponding a column in the expression matrix.
mtc_method	Multiple-testing correction method used by DGE step. See <a href="#">p.adjust</a> for more details.
adj_pval_thresh	Minimum differential expression significance that a gene must demonstrate across level2annot (i.e. cell types).

convert_orths	If <code>input_species!=output_species</code> and <code>convert_orths=TRUE</code> , will drop genes without 1:1 <code>output_species</code> orthologs and then convert exp gene names to those of <code>output_species</code> .
input_species	Which species the gene names in exp come from. See <a href="#">list_species</a> for all available species.
output_species	Which species' genes names to convert exp to. See <a href="#">list_species</a> for all available species.
non121_strategy	How to handle genes that don't have 1:1 mappings between <code>input_species:output_species</code> . Options include: <ul style="list-style-type: none"> <li>• "drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the <code>input_species</code> or <code>output_species</code> (<i>DEFAULT</i>).</li> <li>• "drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the <code>input_species</code>.</li> <li>• "drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the <code>output_species</code>.</li> <li>• "keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species.</li> <li>• "keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.</li> <li>• "sum", "mean", "median", "min" or "max" : When <code>gene_df</code> is a matrix and <code>gene_output="rownames"</code>, these options will aggregate many-to-one gene mappings (<code>input_species-to-output_species</code>) after dropping any duplicate genes in the <code>output_species</code>.</li> </ul>
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
as_sparse	Convert exp to sparse matrix.
as_DelayedArray	Convert exp to DelayedArray for scalable processing.
return_sce	Whether to return the filtered results as an expression matrix or a <b>SingleCellExperiment</b> .
no_cores	Number of cores to parallelise across. Set to NULL to automatically optimise.
verbose	Print messages. #' @inheritParams orthogene::convert_orthologs
...	Arguments passed on to <a href="#">orthogene::convert_orthologs</a>

`gene_df` Data object containing the genes (see `gene_input` for options on how the genes can be stored within the object).

Can be one of the following formats:

- `matrix` :  
A sparse or dense matrix.
- `data.frame` :  
A `data.frame`, `data.table`, or `tibble`.
- `codelist` :  
A list or character vector.

Genes, transcripts, proteins, SNPs, or genomic ranges can be provided in any format (HGNC, Ensembl, RefSeq, UniProt, etc.) and will be automatically converted to gene symbols unless specified otherwise with the ... arguments.

*Note:* If you set `method="homologene"`, you must either supply genes in gene symbol format (e.g. "Sox2") OR set `standardise_genes=TRUE`.

`gene_input` Which aspect of `gene_df` to get gene names from:

- `"rownames"` :  
From row names of `data.frame/matrix`.
- `"colnames"` :  
From column names of `data.frame/matrix`.
- `<column name>` :  
From a column in `gene_df`, e.g. `"gene_names"`.

`gene_output` How to return genes. Options include:

- `"rownames"` :  
As row names of `gene_df`.
- `"colnames"` :  
As column names of `gene_df`.
- `"columns"` :  
As new columns `"input_gene"`, `"ortholog_gene"` (and `"input_gene_standard"` if `standardise_genes=TRUE`) in `gene_df`.
- `"dict"` :  
As a dictionary (named list) where the names are `input_gene` and the values are `ortholog_gene`.
- `"dict_rev"` :  
As a reversed dictionary (named list) where the names are `ortholog_gene` and the values are `input_gene`.

`standardise_genes` If `TRUE` AND `gene_output="columns"`, a new column `"input_gene_standard"` will be added to `gene_df` containing standardised HGNC symbols identified by [gorth](#).

`drop_nonorths` Drop genes that don't have an ortholog in the `output_species`.

`agg_fun` Aggregation function passed to [aggregate\\_mapped\\_genes](#). Set to `NULL` to skip aggregation step (default).

`mthreshold` Maximum number of ortholog names per gene to show. Passed to `gorth`. Only used when `method="gprofiler"` (*DEFAULT* : Inf).

`sort_rows` Sort `gene_df` rows alphanumerically.

`gene_map` A [data.frame](#) that maps the current gene names to new gene names.

This function's behaviour will adapt to different situations as follows:

- `gene_map=<data.frame>` :  
When a `data.frame` containing the gene key:value columns (specified by `input_col` and `output_col`, respectively) is provided, this will be used to perform aggregation/expansion.
- `gene_map=NULL` and `input_species!=output_species` :  
A `gene_map` is automatically generated by `map_orthologs` to perform inter-species gene aggregation/expansion.
- `gene_map=NULL` and `input_species==output_species` :  
A `gene_map` is automatically generated by `map_genes` to perform within-species gene symbol standardization and aggregation/expansion.

`input_col` Column name within `gene_map` with gene names matching the row names of `X`.

`output_col` Column name within `gene_map` with gene names that you wish you map the row names of `X` onto.

## Value

`exp` Expression matrix with gene names as row names.

## Examples

```
cortex_mrna <- ewceData::cortex_mrna()
# Use only a subset of genes to keep the example quick
cortex_mrna$exp <- cortex_mrna$exp[1:300, ]

## Convert orthologs at the same time
exp2_orth <- drop_uninformative_genes(
  exp = cortex_mrna$exp,
  level2annot = cortex_mrna$annot$level2class,
  input_species = "mouse"
)
```

---

dt\_to\_df

*Convert a data.table to a data.frame.*

---

## Description

Converts a `data.table` to a `data.frame` by setting the first column as the rownames.

## Usage

```
dt_to_df(exp)
```

**Value**[data.frame](#)


---

ewce\_expression\_data *Bootstrap cell type enrichment test for transcriptome data*


---

**Description**

ewce\_expression\_data takes a differential gene expression (DGE) results table and determines the probability of cell type enrichment in the up- and down- regulated genes.

**Usage**

```
ewce_expression_data(
  sct_data,
  annotLevel = 1,
  tt,
  sortBy = "t",
  thresh = 250,
  reps = 100,
  ttSpecies = NULL,
  sctSpecies = NULL,
  output_species = NULL,
  bg = NULL,
  method = "homologene",
  verbose = TRUE,
  localHub = FALSE
)
```

**Arguments**

sct_data	List generated using <a href="#">generate_celltype_data</a> .
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
tt	Differential expression table. Can be output of <a href="#">topTable</a> function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
sortBy	Column name of metric in tt which should be used to sort up- from down-regulated genes ( <i>Default: "t"</i> ).
thresh	The number of up- and down- regulated genes to be included in each analysis ( <i>Default: 250</i> ).
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
ttSpecies	The species the differential expression table was generated from.

sctSpecies	Species that sct_data is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See <a href="#">list_species</a> for all available species.
bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
verbose	Print messages.
localHub	If working offline, add argument localHub=TRUE to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see BiocManager vignette section on offline use to ensure proper functionality.

## Value

A list containing five data frames:

- results: dataframe in which each row gives the statistics (p-value, fold change and number of standard deviations from the mean) associated with the enrichment of the stated cell type in the gene list. An additional column \*Direction\* stores whether it the result is from the up or downregulated set.
- hit.cells.up: vector containing the summed proportion of expression in each cell type for the target list.
- hit.cells.down: vector containing the summed proportion of expression in each cell type for the target list.
- bootstrap\_data.up: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists.
- bootstrap\_data.down: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists.

## Examples

```
# Load the single cell data
ctd <- ewceData::ctd()

# Set the parameters for the analysis
# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
# Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5
annotLevel <- 1 # Use cell level annotations (i.e. Interneurons)

# Load the top table
```

```

tt_alzh <- ewceData::tt_alzh()

tt_results <- EWCE::ewce_expression_data(
  sct_data = ctd,
  tt = tt_alzh,
  annotLevel = 1,
  thresh = thresh,
  reps = reps,
  ttSpecies = "human",
  sctSpecies = "mouse"
)

```

---

ewce\_plot

*Plot EWCE results*


---

### Description

ewce\_plot generates plots of EWCE enrichment results

### Usage

```

ewce_plot(
  total_res,
  mtc_method = "bonferroni",
  q_threshold = 0.05,
  ctd = NULL,
  annotLevel = 1,
  heights = c(0.3, 1),
  make_dendro = FALSE,
  verbose = TRUE
)

```

### Arguments

total_res	Results data.frame generated using <a href="#">bootstrap_enrichment_test</a> or <a href="#">ewce_expression_data</a> functions. Multiple results tables can be merged into one results table, as long as the 'list' column is set to distinguish them. Multiple testing correction is then applied across all merged results.
mtc_method	Method to be used for multiple testing correction. Argument is passed to <a href="#">p.adjust</a> (DEFAULT: "bonferroni").
q_threshold	Corrected significance threshold.
ctd	CellTypeDataset object. Should be provided so that the dendrogram can be taken from it and added to plots.
annotLevel	An integer indicating which level of ctd to analyse ( <i>Default: 1</i> ).
heights	The relative heights row in the grid. Will get repeated to match the dimensions of the grid. Passed to <a href="#">wrap_plots</a> .
make_dendro	Add a dendrogram (requires ctd).
verbose	Print messages.

**Value**

A named list containing versions of the [ggplot](#) with and without the dendrogram. Note that cell type order on the x-axis is based on hierarchical clustering for both plots if `make_dendro = TRUE`.

**Examples**

```
## Bootstrap significance test,  
## no control for transcript length or GC content  
## Use pre-computed results to speed up example  
total_res <- EWCE::example_bootstrap_results()$results  
plt <- ewce_plot(total_res = total_res)
```

---

example\_bootstrap\_results

*Example bootstrap enrichment results*

---

**Description**

Example cell type enrichment results produced by [bootstrap\\_enrichment\\_test](#).

**Usage**

```
example_bootstrap_results(verbose = TRUE, localHub = FALSE)
```

**Arguments**

<code>verbose</code>	Print messages.
<code>localHub</code>	If working offline, add argument <code>localHub=TRUE</code> to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see <a href="#">BiocManager vignette</a> section on offline use to ensure proper functionality.

**Value**

List with 3 items.

**Source**

```
# Load the single cell data  
ctd <- ewceData::ctd()  
# Set the parameters for the analysis  
# Use 3 bootstrap lists for speed, for publishable analysis use >=10,000  
reps <- 3  
# Load gene list from Alzheimer's disease GWAS  
example_genelist <- ewceData::example_genelist()
```



```
# Bootstrap significance test, no control for transcript length or GC content
full_results <- EWCE::bootstrap_enrichment_test( sct_data = ctd, hits = example_genelist, reps =
reps, annotLevel = 1, sctSpecies = "mouse", genelistSpecies = "human" )
bootstrap_results <- full_results
save(bootstrap_results,file = "inst/extdata/bootstrap_results.rda")
```

### Examples

```
full_results <- example_bootstrap_results()
```

---

```
example_transcriptome_results
```

*Example bootstrap celltype enrichment test for transcriptome data*

---

### Description

Example celltype enrichment results produced by [ewce\\_expression\\_data](#).

### Usage

```
example_transcriptome_results(verbose = TRUE, localHub = FALSE)
```

### Arguments

verbose	Print messages.
localHub	If working offline, add argument localHub=TRUE to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see BiocManager vignette section on offline use to ensure proper functionality.

### Value

List with 5 items.

### Source

```
## Load the single cell data
ctd <- ewceData::ctd()
## Set the parameters for the analysis
## Use 3 bootstrap lists for speed, for publishable analysis use >10,000
reps <- 3
annotLevel <- 1 # <- Use cell level annotations (i.e. Interneurons)
## Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5
```

```
## Load the top table
tt_alzh <- ewceData::tt_alzh()
tt_results <- EWCE::ewce_expression_data( sct_data = ctd, tt = tt_alzh, annotLevel = 1, thresh =
thresh, reps = reps, ttSpecies = "human", sctSpecies = "mouse" )
save(tt_results, file = "inst/extdata/tt_results.rda")
```

## Examples

```
tt_results <- EWCE::example_transcriptome_results()
```

---

extract_matrix	<i>Extract a matrix from a CellTypeDataset</i>
----------------	--

---

## Description

Extracts a particular matrix (e.g., mean\_exp, specificity) from a CellTypeDataset object.

## Usage

```
extract_matrix(
  ctd,
  dataset,
  level = 1,
  input_species = NULL,
  output_species = "human",
  metric = "specificity",
  non121_strategy = "drop_both_species",
  method = "homologene",
  numberOfBins = 40,
  remove_unlabeled_clusters = FALSE,
  force_new_quantiles = FALSE,
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  rename_columns = TRUE,
  make_columns_unique = FALSE,
  verbose = TRUE,
  ...
)
```

## Arguments

ctd	Input CellTypeData.
dataset	CellTypeData. name.
level	CTD level to extract from.
input_species	Which species the gene names in exp come from. See <a href="#">list_species</a> for all available species.

output_species	Which species' genes names to convert exp to. See <a href="#">list_species</a> for all available species.
metric	Name of the matrix to extract.
non121_strategy	How to handle genes that don't have 1:1 mappings between input_species:output_species. Options include: <ul style="list-style-type: none"> <li>• "drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the input_species or output_species (<i>DEFAULT</i>).</li> <li>• "drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the input_species.</li> <li>• "drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the output_species.</li> <li>• "keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species.</li> <li>• "keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.</li> <li>• "sum", "mean", "median", "min" or "max" : When gene_df is a matrix and gene_output="rownames", these options will aggregate many-to-one gene mappings (input_species-to-output_species) after dropping any duplicate genes in the output_species.</li> </ul>
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
numberOfBins	Number of non-zero quantile bins.
remove_unlabeled_clusters	Remove any samples that have numeric column names.
force_new_quantiles	By default, quantile computation is skipped if they have already been computed. Set =TRUE to override this and generate new quantiles.
as_sparse	Convert to sparse matrix.
as_DelayedArray	Convert to DelayedArray.
rename_columns	Remove replace_chars from column names.
make_columns_unique	Rename each columns with the prefix dataset.species.celltype.
verbose	Print messages. Set verbose=2 if you want to print all messages from internal functions as well.

...

Arguments passed on to `orthogene::convert_orthologs`

`gene_df` Data object containing the genes (see `gene_input` for options on how the genes can be stored within the object).

Can be one of the following formats:

- `matrix` :  
A sparse or dense matrix.
- `data.frame` :  
A `data.frame`, `data.table`. or `tibble`.
- `codelist` :  
A list or character vector.

Genes, transcripts, proteins, SNPs, or genomic ranges can be provided in any format (HGNC, Ensembl, RefSeq, UniProt, etc.) and will be automatically converted to gene symbols unless specified otherwise with the ... arguments.

*Note:* If you set `method="homologene"`, you must either supply genes in gene symbol format (e.g. "Sox2") OR set `standardise_genes=TRUE`.

`gene_input` Which aspect of `gene_df` to get gene names from:

- `"rownames"` :  
From row names of `data.frame/matrix`.
- `"colnames"` :  
From column names of `data.frame/matrix`.
- `<column name>` :  
From a column in `gene_df`, e.g. `"gene_names"`.

`gene_output` How to return genes. Options include:

- `"rownames"` :  
As row names of `gene_df`.
- `"colnames"` :  
As column names of `gene_df`.
- `"columns"` :  
As new columns `"input_gene"`, `"ortholog_gene"` (and `"input_gene_standard"` if `standardise_genes=TRUE`) in `gene_df`.
- `"dict"` :  
As a dictionary (named list) where the names are `input_gene` and the values are `ortholog_gene`.
- `"dict_rev"` :  
As a reversed dictionary (named list) where the names are `ortholog_gene` and the values are `input_gene`.

`standardise_genes` If TRUE AND `gene_output="columns"`, a new column `"input_gene_standard"` will be added to `gene_df` containing standardised HGNC symbols identified by `gorth`.

`drop_nonorths` Drop genes that don't have an ortholog in the `output_species`.

`agg_fun` Aggregation function passed to `aggregate_mapped_genes`. Set to NULL to skip aggregation step (default).

`mthreshold` Maximum number of ortholog names per gene to show. Passed to `gorth`. Only used when `method="gprofiler"` (*DEFAULT* : Inf).

`sort_rows` Sort `gene_df` rows alphanumerically.

`gene_map` A `data.frame` that maps the current gene names to new gene names.

This function's behaviour will adapt to different situations as follows:

- `gene_map=<data.frame>` :  
When a `data.frame` containing the gene key:value columns (specified by `input_col` and `output_col`, respectively) is provided, this will be used to perform aggregation/expansion.
- `gene_map=NULL` and `input_species!=output_species` :  
A `gene_map` is automatically generated by `map_orthologs` to perform inter-species gene aggregation/expansion.
- `gene_map=NULL` and `input_species==output_species` :  
A `gene_map` is automatically generated by `map_genes` to perform within-species gene gene symbol standardization and aggregation/expansion.

`input_col` Column name within `gene_map` with gene names matching the row names of `X`.

`output_col` Column name within `gene_map` with gene names that you wish you map the row names of `X` onto.

## Value

(specificity) matrix.

---

<code>filter_ctd_genes</code>	<i>Filter genes in a CellTypeDataset</i>
-------------------------------	--

---

## Description

Removes rows from each matrix within a `CellTypeDataset` (CTD) that are not within `gene_subset`.

## Usage

```
filter_ctd_genes(ctd, gene_subset)
```

## Arguments

<code>ctd</code>	<code>CellTypeDataset</code> .
<code>gene_subset</code>	Genes to subset to.

## Value

Filtered `CellTypeDataset`.

**Examples**

```
ctd <- ewceData::ctd()
ctd <- standardise_ctd(ctd, input_species="mouse")
gene_subset <- rownames(ctd[[1]]$mean_exp)[1:100]
ctd_subset <- EWCE::filter_ctd_genes(ctd = ctd, gene_subset = gene_subset)
```

---

```
filter_genes_without_1to1_homolog
      filter_genes_without_1to1_homolog
```

---

**Description**

Deprecated function. Please use [filter\\_nonorthologs](#) instead.

**Usage**

```
filter_genes_without_1to1_homolog(
  filenames,
  input_species = "mouse",
  convert_nonhuman_genes = TRUE,
  annot_levels = NULL,
  suffix = "_orthologs",
  verbose = TRUE
)
```

**Arguments**

filenames	List of file names for sct_data saved as <i>.rda</i> files.
input_species	Which species the gene names in exp come from.
convert_nonhuman_genes	Whether to convert the exp row names to human gene names.
annot_levels	[Optional] Names of each annotation level.
suffix	Suffix to add to the file name (right before <i>.rda</i> ).
verbose	Print messages.

**Details**

**Note:** This function replaces the original `filter_genes_without_1to1_homolog` function. `filter_genes_without_1to1_homolog` is now a wrapper for `filter_nonorthologs`.

**Value**

List of the filtered CellTypeData file names.

**Examples**

```
# Load the single cell data
ctd <- ewceData::ctd()
tmp <- tempfile()
save(ctd, file = tmp)
fNames_ALLCELLS_orths <- EWCE::filter_nonorthologs(filenamees = tmp)
```

---

filter\_nonorthologs     *Filter non-orthologs*

---

**Description**

filter\_nonorthologs Takes the filenames of CellTypeData files, loads them, drops any genes which don't have a 1:1 orthologs with humans, and then convert the gene to human orthologs. The new files are then saved to disk, appending '\_orthologs' to the file name.

**Usage**

```
filter_nonorthologs(
  filenames,
  input_species = NULL,
  convert_nonhuman_genes = TRUE,
  annot_levels = NULL,
  suffix = "_orthologs",
  method = "homologene",
  non121_strategy = "drop_both_species",
  verbose = TRUE,
  ...
)
```

**Arguments**

filenames	List of file names for sct_data saved as <i>.rda</i> files.
input_species	Which species the gene names in exp come from.
convert_nonhuman_genes	Whether to convert the exp row names to human gene names.
annot_levels	[Optional] Names of each annotation level.
suffix	Suffix to add to the file name (right before <i>.rda</i> ).
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>

## non121\_strategy

How to handle genes that don't have 1:1 mappings between input\_species:output\_species. Options include:

- "drop\_both\_species" or "dbs" or 1 :  
Drop genes that have duplicate mappings in either the input\_species or output\_species (DEFAULT).
- "drop\_input\_species" or "dis" or 2 :  
Only drop genes that have duplicate mappings in the input\_species.
- "drop\_output\_species" or "dos" or 3 :  
Only drop genes that have duplicate mappings in the output\_species.
- "keep\_both\_species" or "kbs" or 4 :  
Keep all genes regardless of whether they have duplicate mappings in either species.
- "keep\_popular" or "kp" or 5 :  
Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.
- "sum", "mean", "median", "min" or "max" :  
When gene\_df is a matrix and gene\_output="rownames", these options will aggregate many-to-one gene mappings (input\_species-to-output\_species) after dropping any duplicate genes in the output\_species.

## verbose

Print messages.

## ...

Arguments passed on to `orthogene::convert_orthologs`

gene\_df Data object containing the genes (see gene\_input for options on how the genes can be stored within the object).

Can be one of the following formats:

- matrix :  
A sparse or dense matrix.
- data.frame :  
A data.frame, data.table. or tibble.
- codelist :  
A list or character vector.

Genes, transcripts, proteins, SNPs, or genomic ranges can be provided in any format (HGNC, Ensembl, RefSeq, UniProt, etc.) and will be automatically converted to gene symbols unless specified otherwise with the ... arguments.

*Note:* If you set method="homologene", you must either supply genes in gene symbol format (e.g. "Sox2") OR set standardise\_genes=TRUE.

gene\_input Which aspect of gene\_df to get gene names from:

- "rownames" :  
From row names of data.frame/matrix.



- "colnames" :  
From column names of data.frame/matrix.
- <column name> :  
From a column in gene\_df, e.g. "gene\_names".

gene\_output How to return genes. Options include:

- "rownames" :  
As row names of gene\_df.
- "colnames" :  
As column names of gene\_df.
- "columns" :  
As new columns "input\_gene", "ortholog\_gene" (and "input\_gene\_standard" if standardise\_genes=TRUE) in gene\_df.
- "dict" :  
As a dictionary (named list) where the names are input\_gene and the values are ortholog\_gene.
- "dict\_rev" :  
As a reversed dictionary (named list) where the names are ortholog\_gene and the values are input\_gene.

standardise\_genes If TRUE AND gene\_output="columns", a new column "input\_gene\_standard" will be added to gene\_df containing standardised HGNC symbols identified by [gorth](#).

output\_species Name of the output species (e.g. "human","chicken"). Use [map\\_species](#) to return a full list of available species.

drop\_nonorths Drop genes that don't have an ortholog in the output\_species.

agg\_fun Aggregation function passed to [aggregate\\_mapped\\_genes](#). Set to NULL to skip aggregation step (default).

mthreshold Maximum number of ortholog names per gene to show. Passed to [gorth](#). Only used when method="gprofiler" (DEFAULT : Inf).

as\_sparse Convert gene\_df to a sparse matrix. Only works if gene\_df is one of the following classes:

- matrix
- Matrix
- data.frame
- data.table
- tibble

If gene\_df is a sparse matrix to begin with, it will be returned as a sparse matrix (so long as gene\_output= "rownames" or "colnames").

as\_DelayedArray Convert aggregated matrix to [DelayedArray](#).

sort\_rows Sort gene\_df rows alphanumerically.

gene\_map A [data.frame](#) that maps the current gene names to new gene names. This function's behaviour will adapt to different situations as follows:

- gene\_map=<data.frame> :  
When a data.frame containing the gene key:value columns (specified

by `input_col` and `output_col`, respectively) is provided, this will be used to perform aggregation/expansion.

- `gene_map=NULL` and `input_species!=output_species` :  
A `gene_map` is automatically generated by [map\\_orthologs](#) to perform inter-species gene aggregation/expansion.
- `gene_map=NULL` and `input_species==output_species` :  
A `gene_map` is automatically generated by [map\\_genes](#) to perform within-species gene symbol standardization and aggregation/expansion.

`input_col` Column name within `gene_map` with gene names matching the row names of `X`.

`output_col` Column name within `gene_map` with gene names that you wish you map the row names of `X` onto.

### Details

**Note:** This function replaces the original `filter_genes_without_1to1_homolog` function. `filter_genes_without_1to1` is now a wrapper for `filter_nonorthologs`.

### Value

List of the filtered `CellTypeData` file names.

### Examples

```
# Load the single cell data
ctd <- ewceData::ctd()
tmp <- tempfile()
save(ctd, file = tmp)
fNames_ALLCELLS_orths <- EWCE::filter_nonorthologs(filenamees = tmp)
```

---

filter\_variance\_quantiles

*Filter variance quantiles*

---

### Description

Remove rows in `exp` that do not vary substantially across rows.

### Usage

```
filter_variance_quantiles(
  exp,
  log10_norm = TRUE,
  n_quantiles = 10,
  min_variance_quantile = as.integer(n_quantiles/2),
  verbose = TRUE
)
```

**Arguments**

exp	Gene expression matrix.
log10_norm	Log10-normalise exp before computing variance.
n_quantiles	Number of quantile bins to use. Defaults to deciles (n_quantiles=10).
min_variance_quantile	The minimum variance quantile to keep values from.
verbose	Print messages.

**Value**

Filtered exp.

---

fix\_bad\_hgnc\_symbols *fix\_bad\_hgnc\_symbols*

---

**Description**

Given an expression matrix, wherein the rows are supposed to be HGNC symbols, find those symbols which are not official HGNC symbols, then correct them if possible. Return the expression matrix with corrected symbols.

**Usage**

```
fix_bad_hgnc_symbols(
  exp,
  dropNonHGNC = FALSE,
  as_sparse = TRUE,
  verbose = TRUE,
  localHub = FALSE
)
```

**Arguments**

exp	An expression matrix where the rows are HGNC symbols or a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object.
dropNonHGNC	Boolean. Should symbols not recognised as HGNC symbols be dropped?
as_sparse	Convert exp to sparse matrix.
verbose	Print messages.
localHub	If working offline, add argument localHub=TRUE to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see BiocManager vignette section on offline use to ensure proper functionality.

**Value**

Returns the expression matrix with the rownames corrected and rows representing the same gene merged. If a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object was inputted this will be returned with the corrected expression matrix under counts.

**Examples**

```
# create example expression matrix, could be part of a exp, annot list obj
exp <- matrix(data = runif(70), ncol = 10)
# Add HGNC gene names but add with an error:
# MARCH8 is a HGNC symbol which if opened in excel will convert to Mar-08
rownames(exp) <-
  c("MT-TF", "MT-RNR1", "MT-TV", "MT-RNR2", "MT-TL1", "MT-ND1", "Mar-08")
exp <- fix_bad_hgnc_symbols(exp)
# fix_bad_hgnc_symbols warns the user of this possible issue
```

---

`fix_bad_mgi_symbols`     *fix\_bad\_mgi\_symbols - Given an expression matrix, wherein the rows are supposed to be MGI symbols, find those symbols which are not official MGI symbols, then check in the MGI synonym database for whether they match to a proper MGI symbol. Where a symbol is found to be an aliases for a gene that is already in the dataset, the combined reads are summed together.*

---

**Description**

Also checks whether any gene names contain "Sep", "Mar" or "Feb". These should be checked for any suggestion that excel has corrupted the gene names.

**Usage**

```
fix_bad_mgi_symbols(
  exp,
  mrk_file_path = NULL,
  printAllBadSymbols = FALSE,
  as_sparse = TRUE,
  verbose = TRUE,
  localHub = FALSE
)
```

**Arguments**

`exp`                    An expression matrix where the rows are MGI symbols, or a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object.

`mrk_file_path`        Path to the MRK\_List2 file which can be downloaded from [www.informatics.jax.org/downloads/reports/in](http://www.informatics.jax.org/downloads/reports/in)

`printAllBadSymbols`    Output to console all the bad gene symbols

as_sparse	Convert exp to sparse matrix.
verbose	Print messages.
localHub	If working offline, add argument localHub=TRUE to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see BiocManager vignette section on offline use to ensure proper functionality.

**Value**

Returns the expression matrix with the rownames corrected and rows representing the same gene merged. If no corrections are necessary, input expression matrix is returned. If a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object was inputted this will be returned with the corrected expression matrix under counts.

**Examples**

```
# Load the single cell data
cortex_mrna <- ewceData::cortex_mrna()
# take a subset for speed
cortex_mrna$exp <- cortex_mrna$exp[1:50, 1:5]
cortex_mrna$exp <- fix_bad_mgi_symbols(cortex_mrna$exp)
```

---

fix_celltype_names	<i>Fix celltype names</i>
--------------------	---------------------------

---

**Description**

Make sure celltypes don't contain characters that could interfere with downstream analyses. For example, the R package [MAGMA.Celltyping](#) cannot have spaces in celltype names because spaces are used as a delimiter in later steps.

**Usage**

```
fix_celltype_names(
  celltypes,
  replace_chars = "[ - ] | [ . ] | [ ] | [ / ] | [ \\ ]",
  make_unique = TRUE
)
```

**Arguments**

celltypes	Character vector of celltype names.
replace_chars	Regex string of characters to replace with "_" when renaming columns.
make_unique	Make all entries unique.

**Value**

Fixed celltype names.

### Examples

```
ct <- c("microglia", "astrocytes", "Pyramidal SS")
ct_fixed <- fix_celltype_names(celltypes = ct)
```

---

```
fix_celltype_names_full_results
```

*Fix celltype name in full results*

---

### Description

Aligns celltype names in full results generated by [bootstrap\\_enrichment\\_test](#) with the standardised CellTypeDataset (CTD) produced by [standardise\\_ctd](#).

### Usage

```
fix_celltype_names_full_results(full_results, verbose = TRUE)
```

### Arguments

`full_results` Cell-type enrichment results generated by [bootstrap\\_enrichment\\_test](#).  
`verbose` Print messages.

### Value

Fixed full results.

---

```
generate_bootstrap_plots
```

*Generate bootstrap plots*

---

### Description

`generate_bootstrap_plots` takes a gene list and a single cell type transcriptome dataset and generates plots which show how the expression of the genes in the list compares to those in randomly generated gene lists.

**Usage**

```

generate_bootstrap_plots(
  sct_data = NULL,
  hits = NULL,
  bg = NULL,
  genelistSpecies = NULL,
  sctSpecies = NULL,
  output_species = "human",
  method = "homologene",
  reps = 100,
  annotLevel = 1,
  geneSizeControl = FALSE,
  full_results = NULL,
  listFileName = paste0("_level", annotLevel),
  adj_pval_thresh = 0.05,
  facets = "CellType",
  scales = "free_x",
  save_dir = file.path(tempdir(), "BootstrapPlots"),
  show_plot = TRUE,
  verbose = TRUE
)

```

**Arguments**

sct_data	List generated using <a href="#">generate_celltype_data</a> .
hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if geneSizeControl=TRUE.
bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
sctSpecies	Species that sct_data is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See <a href="#">list_species</a> for all available species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).

geneSizeControl	Whether you want to control for GC content and transcript length. Recommended if the gene list originates from genetic studies ( <i>Default: FALSE</i> ). If set to TRUE, then hits must be from humans.
full_results	The full output of <code>bootstrap_enrichment_test</code> for the same gene list.
listFileName	String used as the root for files saved using this function.
adj_pval_thresh	Adjusted p-value threshold of celltypes to include in plots.
facets	<b>[Deprecated]</b> Please use rows and cols instead.
scales	Are scales shared across all facets (the default, "fixed"), or do they vary across rows ("free_x"), columns ("free_y"), or both rows and columns ("free")?
save_dir	Directory where the BootstrapPlots folder should be saved, default is a temp directory.
show_plot	Print the plot.
verbose	Print messages.

### Value

Saves a set of pdf files containing graphs and returns the file where they are saved. These will be saved with the file name adjusted using the value of `listFileName`. The files are saved into the 'BootstrapPlot' folder. Files start with one of the following:

- `qqplot_noText`: sorts the gene list according to how enriched it is in the relevant cell type. Plots the value in the target list against the mean value in the bootstrapped lists.
- `qqplot_wtGSym`: as above but labels the gene symbols for the highest expressed genes.
- `bootDists`: rather than just showing the mean of the bootstrapped lists, a boxplot shows the distribution of values
- `bootDists_LOG`: shows the bootstrapped distributions with the y-axis shown on a log scale

### Examples

```
## Load the single cell data
sct_data <- ewceData::ctd()

## Set the parameters for the analysis
## Use 5 bootstrap lists for speed, for publishable analysis use >10000
reps <- 5

## Load the gene list and get human orthologs
hits <- ewceData::example_genelist()

## Bootstrap significance test,
## no control for transcript length or GC content
## Use pre-computed results to speed up example
full_results <- EWCE::example_bootstrap_results()

### Skip this for example purposes
# full_results <- EWCE::bootstrap_enrichment_test(
```



```

#   sct_data = sct_data,
#   hits = hits,
#   reps = reps,
#   annotLevel = 1,
#   sctSpecies = "mouse",
#   genelistSpecies = "human"
# )

output <- EWCE::generate_bootstrap_plots(
  sct_data = sct_data,
  hits = hits,
  reps = reps,
  full_results = full_results,
  sctSpecies = "mouse",
  genelistSpecies = "human",
  annotLevel = 1
)

```

---

```

generate_bootstrap_plots_for_transcriptome
  Generate bootstrap plots

```

---

## Description

Takes a gene list and a single cell type transcriptome dataset and generates plots which show how the expression of the genes in the list compares to those in randomly generated gene lists.

## Usage

```

generate_bootstrap_plots_for_transcriptome(
  sct_data,
  tt,
  bg = NULL,
  thresh = 250,
  annotLevel = 1,
  reps = 100,
  full_results = NA,
  listFileName = "",
  showGNameThresh = 25,
  ttSpecies = NULL,
  sctSpecies = NULL,
  output_species = NULL,
  sortBy = "t",
  sig_only = TRUE,
  sig_col = "q",
  sig_thresh = 0.05,
  celltype_col = "CellType",
  plot_types = c("bootstrap", "bootstrap_distributions", "log_bootstrap_distributions"),

```

```

save_dir = file.path(tempdir(), "BootstrapPlots"),
method = "homologene",
verbose = TRUE
)

```

### Arguments

sct_data	List generated using <a href="#">generate_celltype_data</a> .
tt	Differential expression table. Can be output of <a href="#">topTable</a> function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
thresh	The number of up- and down- regulated genes to be included in each analysis (Default: 250).
annotLevel	An integer indicating which level of sct_data to analyse (Default: 1).
reps	Number of random gene lists to generate (Default: 100, but should be >=10,000 for publication-quality results).
full_results	The full output of <a href="#">ewce_expression_data</a> for the same gene list.
listFileName	String used as the root for files saved using this function.
showGNameThresh	Integer. If a gene has over X percent of it's expression proportion in a cell type, then list the gene name.
ttSpecies	The species the differential expression table was generated from.
sctSpecies	Species that sct_data is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See <a href="#">list_species</a> for all available species.
sortBy	Column name of metric in tt which should be used to sort up- from down-regulated genes (Default: "t").
sig_only	Should plots only be generated for cells which have significant changes?
sig_col	Column name in tt that contains the significance values.
sig_thresh	Threshold by which to filter tt by sig_col.
celltype_col	Column within tt that contains celltype names.
plot_types	Plot types to generate.
save_dir	Directory where the BootstrapPlots folder should be saved, default is a temp directory.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
verbose	Print messages.

**Value**

Saves a set of PDF files containing graphs. Then returns a nested list with each plot and the path where it was saved to. Files start with one of the following:

- qqplot\_noText: sorts the gene list according to how enriched it is in the relevant cell type. Plots the value in the target list against the mean value in the bootstrapped lists.
- qqplot\_wtGSym: as above but labels the gene symbols for the highest expressed genes.
- bootDists: rather than just showing the mean of the bootstrapped lists, a boxplot shows the distribution of values
- bootDists\_LOG: shows the bootstrapped distributions with the y-axis shown on a log scale

**Examples**

```
## Load the single cell data
ctd <- ewceData::ctd()

## Set the parameters for the analysis
## Use 3 bootstrap lists for speed, for publishable analysis use >10,000
reps <- 3
annotLevel <- 1 # <- Use cell level annotations (i.e. Interneurons)
## Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5

## Load the top table
tt_alzh <- ewceData::tt_alzh()

## See ?example_transcriptome_results for full code to produce tt_results
tt_results <- EWCE::example_transcriptome_results()

## Bootstrap significance test,
## no control for transcript length or GC content
savePath <- EWCE::generate_bootstrap_plots_for_transcriptome(
  sct_data = ctd,
  tt = tt_alzh,
  thresh = thresh,
  annotLevel = 1,
  full_results = tt_results,
  listFileName = "examples",
  reps = reps,
  ttSpecies = "human",
  sctSpecies = "mouse",
  # Only do one plot type for demo purposes
  plot_types = "bootstrap"
)
```

---

 generate\_celltype\_data

*Generate CellTypeData (CTD) file*


---

### Description

generate\_celltype\_data takes gene expression data and cell type annotations and creates Cell-TypeData (CTD) files which contain matrices of mean expression and specificity per cell type.

### Usage

```
generate_celltype_data(
  exp,
  annotLevels,
  groupName,
  no_cores = 1,
  savePath = tempdir(),
  file_prefix = "ctd",
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  normSpec = FALSE,
  convert_orths = FALSE,
  input_species = "mouse",
  output_species = "human",
  non121_strategy = "drop_both_species",
  method = "homologene",
  force_new_file = TRUE,
  specificity_quantiles = TRUE,
  numberOfBins = 40,
  dendrograms = TRUE,
  return_ctd = FALSE,
  verbose = TRUE,
  ...
)
```

### Arguments

exp	Numerical matrix with row for each gene and column for each cell. Row names are gene symbols. Column names are cell IDs which can be cross referenced against the annot data frame.
annotLevels	List with arrays of strings containing the cell type names associated with each column in exp.
groupName	A human readable name for referring to the dataset being used.
no_cores	Number of cores that should be used to speedup the computation. <i>NOTE:</i> Use no_cores=1 when using this package in windows system.
savePath	Directory where the CTD file should be saved.

file_prefix	Prefix to add to saved CTD file name.
as_sparse	Convert exp to a sparse Matrix.
as_DelayedArray	Convert exp to DelayedArray.
normSpec	Boolean indicating whether specificity data should be transformed to a normal distribution by cell type, giving equivalent scores across all cell types.
convert_orths	If input_species!=output_species and convert_orths=TRUE, will drop genes without 1:1 output_species orthologs and then convert exp gene names to those of output_species.
input_species	The species that the exp dataset comes from. See <a href="#">list_species</a> for all available species.
output_species	Species to convert exp to (Default: "human"). See <a href="#">list_species</a> for all available species.
non121_strategy	How to handle genes that don't have 1:1 mappings between input_species:output_species. Options include: <ul style="list-style-type: none"> <li>• "drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the input_species or output_species (DEFAULT).</li> <li>• "drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the input_species.</li> <li>• "drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the output_species.</li> <li>• "keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species.</li> <li>• "keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.</li> <li>• "sum", "mean", "median", "min" or "max" : When gene_df is a matrix and gene_output="rownames", these options will aggregate many-to-one gene mappings (input_species-to-output_species) after dropping any duplicate genes in the output_species.</li> </ul>
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
force_new_file	If a file of the same name as the one being created already exists, overwrite it.
specificity_quantiles	Compute specificity quantiles. Recommended to set to TRUE.

numberOfBins Number of quantile 'bins' to use (40 is recommended).  
 dendrograms Add dendrogram plots  
 return\_ctd Return the CTD object in a list along with the file name, instead of just the file name.  
 verbose Print messages.  
 ... Arguments passed on to `orthogene::convert_orthologs`

**gene\_df** Data object containing the genes (see `gene_input` for options on how the genes can be stored within the object).

Can be one of the following formats:

- `matrix` :  
A sparse or dense matrix.
- `data.frame` :  
A `data.frame`, `data.table`, or `tibble`.
- `codelist` :  
A list or character vector.

Genes, transcripts, proteins, SNPs, or genomic ranges can be provided in any format (HGNC, Ensembl, RefSeq, UniProt, etc.) and will be automatically converted to gene symbols unless specified otherwise with the ... arguments.

*Note:* If you set `method="homologene"`, you must either supply genes in gene symbol format (e.g. "Sox2") OR set `standardise_genes=TRUE`.

**gene\_input** Which aspect of `gene_df` to get gene names from:

- `"rownames"` :  
From row names of `data.frame/matrix`.
- `"colnames"` :  
From column names of `data.frame/matrix`.
- `<column name>` :  
From a column in `gene_df`, e.g. `"gene_names"`.

**gene\_output** How to return genes. Options include:

- `"rownames"` :  
As row names of `gene_df`.
- `"colnames"` :  
As column names of `gene_df`.
- `"columns"` :  
As new columns `"input_gene"`, `"ortholog_gene"` (and `"input_gene_standard"` if `standardise_genes=TRUE`) in `gene_df`.
- `"dict"` :  
As a dictionary (named list) where the names are `input_gene` and the values are `ortholog_gene`.
- `"dict_rev"` :  
As a reversed dictionary (named list) where the names are `ortholog_gene` and the values are `input_gene`.

**standardise\_genes** If TRUE AND `gene_output="columns"`, a new column "input\_gene\_standard" will be added to `gene_df` containing standardised HGNC symbols identified by `gorth`.

**drop\_nonorths** Drop genes that don't have an ortholog in the `output_species`.

**agg\_fun** Aggregation function passed to `aggregate_mapped_genes`. Set to NULL to skip aggregation step (default).

**mthreshold** Maximum number of ortholog names per gene to show. Passed to `gorth`. Only used when `method="gprofiler"` (*DEFAULT* : Inf).

**sort\_rows** Sort `gene_df` rows alphanumerically.

**gene\_map** A `data.frame` that maps the current gene names to new gene names. This function's behaviour will adapt to different situations as follows:

- `gene_map=<data.frame>` :  
When a `data.frame` containing the gene key:value columns (specified by `input_col` and `output_col`, respectively) is provided, this will be used to perform aggregation/expansion.
- `gene_map=NULL` and `input_species!=output_species` :  
A `gene_map` is automatically generated by `map_orthologs` to perform inter-species gene aggregation/expansion.
- `gene_map=NULL` and `input_species==output_species` :  
A `gene_map` is automatically generated by `map_genes` to perform within-species gene gene symbol standardization and aggregation/expansion.

**input\_col** Column name within `gene_map` with gene names matching the row names of X.

**output\_col** Column name within `gene_map` with gene names that you wish you map the row names of X onto.

## Value

File names for the saved CellTypeData (CTD) files.

## Examples

```
# Load the single cell data
cortex_mrna <- ewceData::cortex_mrna()
# Use only a subset to keep the example quick
expData <- cortex_mrna$exp[1:100, ]
l1 <- cortex_mrna$annot$level1class
l2 <- cortex_mrna$annot$level2class
annotLevels <- list(l1 = l1, l2 = l2)
fNames_ALLCELLS <- EWCE::generate_celltype_data(
  exp = expData,
  annotLevels = annotLevels,
  groupName = "allKlmouse"
)
```

---

```
generate_controlled_bootstrap_geneset
      generate_controlled_bootstrap_geneset
```

---

### Description

Used to generate cell type-controlled bootstrapped gene sets.

### Usage

```
generate_controlled_bootstrap_geneset(
  hits,
  sct_data,
  annotLevel,
  reps,
  controlledCT = FALSE,
  verbose = TRUE
)
```

### Arguments

hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if <code>geneSizeControl=TRUE</code> .
sct_data	List generated using <a href="#">generate_celltype_data</a> .
annotLevel	An integer indicating which level of <code>sct_data</code> to analyse ( <i>Default: 1</i> ).
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.
verbose	Print messages.

### Details

See [controlled\\_geneset\\_enrichment](#) for examples.

### Value

Matrix of genes (such that `nrows=length(hits)` and `ncols=reps`), where each column is a gene list.



---

```
get_celltype_table    get_celltype_table
```

---

**Description**

`get_celltype_table` Generates a table that can be used for supplementary tables of publications. The table lists how many cells are associated with each cell type, the level of annotation, and the dataset from which it was generated.

**Usage**

```
get_celltype_table(annot)
```

**Arguments**

`annot` An annotation dataframe, which columns named 'level1class', 'level2class' and 'dataset\_name'

**Value**

A dataframe with columns 'name', 'level', 'freq' and 'dataset\_name'

**Examples**

```
# See PrepLDSC.Rmd for origin of merged_ALLCELLS$annot
cortex_mrna <- ewceData::cortex_mrna()
cortex_mrna$annot$dataset_name <- "cortex_mrna"
celltype_table <- EWCE::get_celltype_table(cortex_mrna$annot)
```

---

```
get_ctd_levels    Get the names of CellTypeDataset levels
```

---

**Description**

Returns the level names of a CellTypeDataset. If none are available, will instead return a vector of numbers (one number per level).

**Usage**

```
get_ctd_levels(ctd, max_only = FALSE)
```

**Arguments**

`ctd` CellTypeDataset.  
`max_only` Only return the level with the greatest depth (e.g. "level3" in c("level1", "level2", "level3")).

**Value**

List of levels in ctd.

---

get\_ctd\_matrix\_names    *Get CTD matrix names*

---

**Description**

Find the names of all data matrices in a CellTypeDataset.

**Usage**

```
get_ctd_matrix_names(  
  ctd = NULL,  
  matrices = c("mean_exp", "median_exp", "specificity", "median_specificity",  
    "specificity_quantiles"),  
  verbose = TRUE  
)
```

**Arguments**

ctd	CellTypeDataset. If set to NULL (default), will simply return all possible matrix names.
matrices	Matrix names to search for.
verbose	Print messages.

**Value**

List of matrix names.

---

get\_exp\_data\_for\_bootstrapped\_genes  
*get\_exp\_data\_for\_bootstrapped\_genes*

---

**Description**

Support function for [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#).

**Usage**

```

get_exp_data_for_bootstrapped_genes(
  results,
  signif_res,
  sct_data,
  hits,
  combinedGenes,
  annotLevel,
  nReps = 100,
  as_sparse = TRUE,
  verbose = TRUE
)

```

**Arguments**

signif_res	signif_res (#fix).
sct_data	List generated using <a href="#">generate_celltype_data</a> .
hits	Gene hits.
combinedGenes	Combined list of genes from sct_data, hits, and background bg.
annotLevel	An integer indicating which level of sct_data to analyse ( <i>Default: 1</i> ).
verbose	Print messages.
full_results	full_results (#fix).

**Value**

exp\_mats

---

get_sig_results	<i>Extract significant results</i>
-----------------	------------------------------------

---

**Description**

Extract significant results from output of [bootstrap\\_enrichment\\_test](#).

**Usage**

```

get_sig_results(
  full_results,
  mtc_method = "BH",
  q_threshold = 0.05,
  verbose = TRUE
)

```

**Arguments**

full_results	Output of <a href="#">bootstrap_enrichment_test</a> .
mtc_method	Multiple-testing correction method (passed to <a href="#">p.adjust</a> ).
q_threshold	Maximum multiple-testing-corrected p-value to include.
verbose	Print messages.

**Value**

Filtered enrichment results table.

---

```
get_summed_proportions
      Get summed proportions
```

---

**Description**

`get_summed_proportions` Given the target gene set, randomly sample gene lists of equal length, obtain the specificity of these and then obtain the mean specificity in each sampled list (and the target list).

**Usage**

```
get_summed_proportions(
  hits,
  sct_data,
  annotLevel,
  reps,
  no_cores = 1,
  geneSizeControl,
  controlledCT = NULL,
  control_network = NULL,
  store_gene_data = TRUE,
  verbose = TRUE
)
```

**Arguments**

hits	list of gene names. The target gene set.
sct_data	List generated using <a href="#">generate_celltype_data</a> .
annotLevel	An integer indicating which level of <code>sct_data</code> to analyse ( <i>Default: 1</i> ).
reps	Number of random gene lists to generate ( <i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
no_cores	Number of cores to parallelise bootstrapping reps over.

geneSizeControl	Whether you want to control for GC content and transcript length. Recommended if the gene list originates from genetic studies ( <i>Default: FALSE</i> ). If set to TRUE, then hits must be from humans.
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.
control_network	If geneSizeControl=TRUE, then must provide the control network.
store_gene_data	Store sampled gene data for every bootstrap iteration. When the number of bootstrap reps is very high ( $\geq 100k$ ) and/or the number of genes in hits is very high, you may want to set store_gene_data=FALSE to avoid using excessive amounts of CPU memory.
verbose	Print messages.

### Details

See [bootstrap\\_enrichment\\_test](#) for examples.

### Value

A list containing three elements:

- hit.cells: vector containing the summed proportion of expression in each cell type for the target list.
- gene\_data: data.table showing the number of time each gene appeared in the bootstrap sample.
- bootstrap\_data: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists
- controlledCT: the controlled cell type (if applicable)

---

is\_32bit

*Checks whether OS is a 32-bit Windows*

---

### Description

Helper function to avoid duplicate test runs on Windows OS.

### Usage

```
is_32bit()
```

### Value

Null

---

is\_celltypedataset      *Check whether object is a CellTypeDataset*

---

**Description**

Check whether an object is a CellTypeDataset.

**Usage**

```
is_celltypedataset(ctd)
```

**Arguments**

ctd                      Object.

**Value**

boolean

---

is\_ctd\_standardised      *Check whether a CellTypeDataset is standardised*

---

**Description**

Check whether a CellTypeDataset was previously standardised using [standardise\\_ctd](#).

**Usage**

```
is_ctd_standardised(ctd)
```

**Arguments**

ctd                      CellTypeDataset.

**Value**

Whether the ctd is standardised.

---

*is\_delayed\_array*      *Assess whether an object is a DelayedArray.*

---

**Description**

Assess whether an object is a DelayedArray or one of its derived object types.

**Usage**

`is_delayed_array(X)`

**Arguments**

X                      Object.

**Value**

boolean

---

*is\_matrix*                      *Assess whether an object is a Matrix*

---

**Description**

Assess whether an object is a Matrix or one of its derived object types.

**Usage**

`is_matrix(X)`

**Arguments**

X                      Object.

**Value**

boolean

---

is_sparse_matrix	<i>Assess whether an object is a sparse matrix</i>
------------------	--

---

**Description**

Assess whether an object is a sparse matrix or one of its derived object types.

**Usage**

```
is_sparse_matrix(X)
```

**Arguments**

X                    Object.

**Value**

boolean

---

list_species	<i>List all species</i>
--------------	-------------------------

---

**Description**

List all species that EWCE can convert genes from/to. Wrapper function for [map\\_species](#).

**Usage**

```
list_species(verbose = TRUE)
```

**Arguments**

verbose            Print messages.

**Value**

List of species EWCE can input/output genes as.

**Examples**

```
list_species()
```



---

load_rdata	load_rdata
------------	------------

---

**Description**

Load processed data (*.rda* format) using a function that assigns it to a specific variable (so you don't have to guess what the loaded variable name is).

**Usage**

```
load_rdata(fileName)
```

**Arguments**

fileName      Name of the file to load.

**Value**

Data object.

**Examples**

```
tmp <- tempfile()
save(mtcars, file = tmp)
mtcars2 <- load_rdata(tmp)
```

---

max_ctd_depth	<i>Get max CTD depth</i>
---------------	--------------------------

---

**Description**

Get the maximum level depth from a list of CellTypeDataset objects.

**Usage**

```
max_ctd_depth(CTD_list)
```

**Arguments**

CTD\_list      A list of CellTypeDataset objects.

**Value**

integer

---

`merged_ewce`*Multiple EWCE results from multiple studies*

---

### Description

`merged_ewce` combines enrichment results from multiple studies targetting the same scientific problem

### Usage

```
merged_ewce(results, reps = 100)
```

### Arguments

`results` a list of EWCE results generated using [add\\_res\\_to\\_merging\\_list](#).  
`reps` Number of random gene lists to generate (Default=100 but should be  $\geq 10,000$  for publication-quality results).

### Value

dataframe in which each row gives the statistics (p-value, fold change and number of standard deviations from the mean) associated with the enrichment of the stated cell type in the gene list.

### Examples

```
# Load the single cell data
ctd <- ewceData::ctd()

# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
# Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5

# Load the data
tt_alzh_BA36 <- ewceData::tt_alzh_BA36()
tt_alzh_BA44 <- ewceData::tt_alzh_BA44()

# Run EWCE analysis
tt_results_36 <- EWCE::ewce_expression_data(
  sct_data = ctd,
  tt = tt_alzh_BA36,
  thresh = thresh,
  annotLevel = 1,
  reps = reps,
  ttSpecies = "human",
  sctSpecies = "mouse"
)
tt_results_44 <- EWCE::ewce_expression_data(
  sct_data = ctd,
```

```

    tt = tt_alzh_BA44,
    thresh = thresh,
    annotLevel = 1,
    reps = reps,
    ttSpecies = "human",
    sctSpecies = "mouse"
  )

# Fill a list with the results
results <- EWCE::add_res_to_merging_list(tt_results_36)
results <- EWCE::add_res_to_merging_list(tt_results_44, results)

# Perform the merged analysis
# For publication reps should be higher
merged_res <- EWCE::merged_ewce(
  results = results,
  reps = 2
)
print(merged_res)

```

---

merge\_ctd

---

*Merge multiple CellTypeDataset references*


---

## Description

Import CellTypeDataset (CTD) references from a remote repository, standardize each, and then merge into one CTD. Optionally, can return these as a merged [SingleCellExperiment](#).

## Usage

```

merge_ctd(
  CTD_list,
  save_dir = tempdir(),
  standardise_CTD = FALSE,
  as_SCE = FALSE,
  gene_union = TRUE,
  merge_levels = seq(1, 5),
  save_split_SCE = FALSE,
  save_split_CTD = FALSE,
  save_merged_SCE = TRUE,
  force_new_quantiles = FALSE,
  numberOfBins = 40,
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  verbose = TRUE,
  ...
)

```

**Arguments**

CTD_list	(Named) list of CellTypeDatasets.
save_dir	The directory to save merged files in.
standardise_CTD	Whether to run standardise_ctd.
as_SCE	If TRUE (default), returns the merged results as a named list of <a href="#">SingleCellExperiments</a> . If FALSE, returns as a CTD object.
gene_union	Whether to take the gene union or intersection when merging matrices (mean_exp,specificity, etc.).
merge_levels	Which CTD levels you want to merge. Can be a single value (e.g. merge_levels=5) or a list c(e.g. merge_levels=c(1:5)). If some CTD don't have the same number of levels, the maximum level depth available in that CTD will be used instead.
save_split_SCE	Whether to save individual SCE files in the subdirectory <i>standardized_CTD_SCE</i> .
save_split_CTD	Whether to save individual CTD files in the subdirectory <i>standardized_CTD</i> .
save_merged_SCE	Save the final merged SCE object, or simply to return it.
force_new_quantiles	If specificity quantiles matrix already exists, create a new one.
numberOfBins	Number of bins to compute specificity quantiles with.
as_sparse	Convert matrices to sparse matrix.
as_DelayedArray	Convert matrices to DelayedArray.
verbose	Print messages.
...	Additional arguments to be passed to standardise_ctd.

**Value**

List of CellTypeDatasets or SingleCellExperiments.

**Examples**

```
## Let's pretend these are different CTD datasets
ctd1 <- ewceData::ctd()
ctd2 <- ctd1
CTD_list <- list(ctd1, ctd2)
CTD_merged <- EWCE::merge_ctd(CTD_list = CTD_list)
```

---

merge_sce	<i>Merge multiple SingleCellExperiment objects</i>
-----------	--

---

### Description

Merge several SingleCellExperiment (SCE) objects from different batches/experiments. Extracted from the `scMerge` package.

### Usage

```
merge_sce(
  sce_list,
  method = "intersect",
  cut_off_batch = 0.01,
  cut_off_overall = 0.01,
  use_assays = NULL,
  colData_names = NULL,
  batch_names = NULL,
  verbose = TRUE
)
```

### Arguments

sce_list	A list contains the SingleCellExperiment Object from each batch.
method	A string indicates the method of combining the gene expression matrix, either union or intersect. Default to intersect. union only supports matrix class.
cut_off_batch	A numeric vector indicating the cut-off for the proportion of a gene is expressed within each batch.
cut_off_overall	A numeric vector indicating the cut-off for the proportion of a gene is expressed overall data.
use_assays	A string vector indicating the expression matrices to be combined. The first assay named will be used to determine the proportion of zeros.
colData_names	A string vector indicating the colData that are combined.
batch_names	A string vector indicating the batch names for the output SCE object.
verbose	Print messages.

### Value

A SingleCellExperiment object with the list of SCE objects combined.

### Author(s)

Yingxin Lin (modified by Brian Schilder)

**Source**

[scMerge](#).

**Examples**

```
ctd <- ewceData::ctd()
sce_list <- EWCE::ctd_to_sce(object = ctd)
sce_combine <- merge_sce(sce_list = sce_list)
```

---

merge_sce_list	<i>Merge of list of SingleCellExperiment objects</i>
----------------	--

---

**Description**

Merge of list of CellTypeDatasets stored as [SingleCellExperiment](#) objects into one [SingleCellExperiment](#) object.

**Usage**

```
merge_sce_list(
  SCE_lists = NULL,
  parent_folder = NULL,
  pattern = ".rds$",
  merge_levels = seq(1, 5),
  gene_union = TRUE,
  as_sparse = TRUE,
  as_DelayedArray = TRUE,
  verbose = TRUE
)
```

**Arguments**

SCE_lists	A list of <a href="#">SingleCellExperiment</a> objects.
parent_folder	Can supply the path to a folder instead of SCE_lists. Any <a href="#">SingleCellExperiment</a> objects matching pattern will be imported.
merge_levels	CellTypeDataset levels to merge.

**Value**

SingleCellExperiment

---

merge\_two\_expfiles      *Merge two exp files*

---

### Description

merge\_two\_expfiles Used to combine two single cell type datasets.

### Usage

```
merge_two_expfiles(  
  exp1,  
  exp2,  
  annot1,  
  annot2,  
  name1 = "",  
  name2 = "",  
  as_sparse = TRUE,  
  as_DelayedArray = FALSE,  
  verbose = TRUE  
)
```

### Arguments

exp1	Numerical expression matrix for dataset1 with row for each gene and column for each cell. Row names are gene symbols. Column names are cell IDs which can be cross referenced against the annot data frame.
exp2	Numerical expression matrix for dataset2 with row for each gene and column for each cell. Row names are gene symbols. Column names are cell IDs which can be cross referenced against the annot data frame.
annot1	Annotation data frame for dataset1 which contains three columns at least: cell_id, level1class and level2class
annot2	Annotation data frame for dataset2 which contains three columns at least: cell_id, level1class and level2class
name1	Name used to refer to dataset 1. Leave blank if it's already a merged dataset.
name2	Name used to refer to dataset 2. Leave blank if it's already a merged dataset.
as_sparse	Convert the merged exp to a sparse matrix.
as_DelayedArray	Convert the merged exp to a DelayedArray.
verbose	Print messages.

### Value

List containing merged exp and annot.

**Examples**

```

cortex_mrna <- ewceData::cortex_mrna()
exp1 <- cortex_mrna$exp[, 1:50]
exp2 <- cortex_mrna$exp[, 51:100]
annot1 <- cortex_mrna$annot[1:50, ]
annot2 <- cortex_mrna$annot[51:100, ]
merged_res <- EWCE::merge_two_expfiles(
  exp1 = exp1,
  exp2 = exp2,
  annot1 = annot1,
  annot2 = annot2,
  name1 = "dataset1",
  name2 = "dataset2"
)

```

---

messenger	<i>Print messages</i>
-----------	-----------------------

---

**Description**

Print messages with option to silence.

**Usage**

```
messenger(..., v = TRUE)
```

**Arguments**

...	Message input.
v	Whether to print messages.

**Value**

Null output.

---

message_parallel	<i>Print messages</i>
------------------	-----------------------

---

**Description**

Print messages even from within parallelised functions.

**Usage**

```
message_parallel(...)
```



**Arguments**

... Message input.

**Value**

Null output.

---

myScalesComma	myScalesComma
---------------	---------------

---

**Description**

Adjusts **ggplot2** label display. See [comma](#) for details. Support function for [plot\\_log\\_bootstrap\\_distributions](#).

**Usage**

```
myScalesComma(x)
```

**Value**

Numeric vector

---

plot_ctd	<i>Plot CellTypeData metrics</i>
----------	----------------------------------

---

**Description**

Plot *CellTypeData* metrics such as mean\_exp, specificity and/or specificity\_quantiles.

**Usage**

```
plot_ctd(ctd, genes, level = 1, metric = "specificity", show_plot = TRUE)
```

**Arguments**

ctd	CellTypeDataset.
genes	Which genes in ctd to plot.
level	Annotation level in ctd to plot.
metric	Which metric in the ctd to plot: <ul style="list-style-type: none"> <li>• "mean_exp"</li> <li>• "specificity"</li> <li>• "specificity_quantiles"</li> </ul>
show_plot	Whether to print the plot or simply return it.

**Value**

ggplot object.

**Examples**

```
ctd <- ewceData::ctd()
plt <- EWCE::plot_ctd(ctd, genes = c("ApoE", "Gfap", "Gapdh"))
```

---

plot\_log\_bootstrap\_distributions  
*Plot log bootstrap distributions*

---

**Description**

Plot results of [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#).

**Usage**

```
plot_log_bootstrap_distributions(  
  dat,  
  exp_mats,  
  cc,  
  hit_exp,  
  tag,  
  listFileName,  
  graph_theme,  
  save_dir = file.path(tempdir(), paste0("BootstrapPlots", "_for_transcriptome")),  
  height = 3.5,  
  width = 3.5  
)
```

**Value**

Null result.

---

plot\_with\_bootstrap\_distributions  
*Plot with bootstrap distributions*

---

**Description**

Plot results of [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#).

**Usage**

```
plot_with_bootstrap_distributions(  
  exp_mats,  
  cc,  
  hit_exp,  
  tag,  
  listFileName,  
  graph_theme,  
  save_dir = file.path(tempdir(), paste0("BootstrapPlots", "_for_transcriptome")),  
  height = 3.5,  
  width = 3.5  
)
```

**Value**

Null result.

---

prep.dendro

*prep.dendro*

---

**Description**

prep\_dendro adds a dendrogram to a CellTypeDataset (CTD).

**Usage**

```
prep.dendro(ctdIN)
```

**Arguments**

ctdIN            A single annotLevel of a ctd, i.e. ctd[[1]] (the function is intended to be used via apply).

**Value**

A CellTypeDataset with dendrogram plotting info added.

---

```
prepare_genesize_control_network
      Prepare genesize control network
```

---

### Description

prepare\_genesize\_control\_network takes a gene list and finds semi-randomly selected gene lists which are matched for gene length and GC content.

### Usage

```
prepare_genesize_control_network(
  hits,
  bg = NULL,
  reps = 10000,
  no_cores = 1,
  sctSpecies = NULL,
  genelistSpecies = NULL,
  verbose = TRUE,
  localHub = FALSE
)
```

### Arguments

hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if <code>geneSizeControl=TRUE</code> .
bg	List of gene symbols containing the background gene list (including hit genes). If <code>bg=NULL</code> , an appropriate gene background will be created automatically.
reps	Number of gene lists to sample.
no_cores	Number of cores to parallelise bootstrapping reps over.
sctSpecies	Species that <code>sct_data</code> is currently formatted as (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
genelistSpecies	Species that <code>hits</code> genes came from (no longer limited to just "mouse" and "human"). See <a href="#">list_species</a> for all available species.
verbose	Print messages.
localHub	If working offline, add argument <code>localHub=TRUE</code> to work with a local, non-updated hub; It will only have resources available that have previously been downloaded. If offline, Please also see <code>BiocManager</code> vignette section on offline use to ensure proper functionality.

### Value

A list containing three data frames:

- hits: Array of HGNC symbols containing the hit genes. May be slightly reduced if gene length / GC content could not be found for all genes.
- list\_network: The control gene lists as a data frame of HGNC symbols

---

```
prepare_tt
```

---

*Prepare differential gene expression table*

---

## Description

Prepare differential gene expression table for [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#) or [ewce\\_expression\\_data](#).

## Usage

```
prepare_tt(
  tt,
  tt_genecol = NULL,
  ttSpecies,
  output_species,
  method = "homologene",
  verbose = TRUE
)
```

## Arguments

tt	Differential expression table. Can be output of <a href="#">topTable</a> function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
ttSpecies	The species the differential expression table was generated from.
output_species	Species to convert sct_data and hits to (Default: "human"). See <a href="#">list_species</a> for all available species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> <li>• "gprofiler" : Slower but more species and genes.</li> <li>• "homologene" : Faster but fewer species and genes.</li> <li>• "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.</li> </ul>
verbose	Print messages.

## Value

List of 3 items

---

prep_dendro	<i>Prepare dendrogram</i>
-------------	---------------------------

---

**Description**

prep\_dendro adds a dendrogram to a CellTypeDataset (CTD).

**Usage**

```
prep_dendro(ctdIN, expand = c(0, 0.66))
```

**Arguments**

ctdIN	A single annotLevel of a ctd, i.e. ctd[[1]] (the function is intended to be used via apply).
-------	--

**Value**

A CellTypeDataset with dendrogram plotting info added.

---

report_dge	<i>Report DGE</i>
------------	-------------------

---

**Description**

Report differential gene expression (DGE) results

**Usage**

```
report_dge(exp, keep_genes, adj_pval_thresh = 0.05, verbose = TRUE)
```

**Arguments**

exp	Gene expression matrix.
keep_genes	Genes kept after DGE.
adj_pval_thresh	Minimum differential expression significance that a gene must demonstrate across level2annot (i.e. cell types).
verbose	Print messages. #' @inheritParams orthogene::convert_orthologs

**Value**

Null output.

---

report_results	<i>Report cell type enrichment results</i>
----------------	--

---

**Description**

Report cell type enrichment results generated by [bootstrap\\_enrichment\\_test](#).

**Usage**

```
report_results(results, sig_thresh = 0.05, verbose = TRUE)
```

**Value**

NULL output.

---

run_deseq2	<i>Run DGE: DESeq2</i>
------------	------------------------

---

**Description**

Run Differential Gene Expression with **DESeq2**.

**Usage**

```
run_deseq2(exp, level2annot, test = "LRT", no_cores = 1, verbose = TRUE, ...)
```

**Arguments**

exp	Expression matrix with gene names as rownames.
level2annot	Array of cell types, with each sequentially corresponding a column in the expression matrix.
test	either "Wald" or "LRT", which will then use either Wald significance tests (defined by <a href="#">nbinomWaldTest</a> ), or the likelihood ratio test on the difference in deviance between a full and reduced model formula (defined by <a href="#">nbinomLRT</a> )
no_cores	Number of cores to parallelise across. Set to NULL to automatically optimise.
verbose	Print messages. #' @inheritParams orthogene::convert_orthologs
...	Additional arguments to be passed to <a href="#">gorth</a> or <a href="#">homologene</a> .

*NOTE:* To return only the most "popular" interspecies ortholog mappings, supply `mthreshold=1` here AND set `method="gprofiler"` above. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.

For more details, please see [here](#).

**Value**

DESeq results

---

run\_limma

*Run DGE: limma*

---

**Description**

Run Differential Gene Expression with **limma**.

**Usage**

```
run_limma(exp, level2annot, mtc_method = "BH", verbose = TRUE, ...)
```

**Arguments**

exp	Expression matrix with gene names as rownames.
level2annot	Array of cell types, with each sequentially corresponding a column in the expression matrix.
mtc_method	Multiple-testing correction method used by DGE step. See <a href="#">p.adjust</a> for more details.
verbose	Print messages. #' @inheritParams orthogene::convert_orthologs
...	Additional arguments to be passed to <a href="#">gorth</a> or <a href="#">homologene</a> .

*NOTE:* To return only the most "popular" interspecies ortholog mappings, supply `mthreshold=1` here AND set `method="gprofiler"` above. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.

For more details, please see [here](#).

**Value**

limma results.



---

run_mast	<i>Run DGE: MAST</i>
----------	----------------------

---

## Description

Run Differential Gene Expression with **MAST**.

## Usage

```
run_mast(exp, level2annot, test = "LRT", mtc_method = "BH", no_cores = 1, ...)
```

## Arguments

exp	Expression matrix with gene names as rownames.
level2annot	Array of cell types, with each sequentially corresponding a column in the expression matrix.
mtc_method	Multiple-testing correction method used by DGE step. See <a href="#">p.adjust</a> for more details.
no_cores	Number of cores to parallelise DGE across.
...	Additional arguments to be passed to <a href="#">gorth</a> or <a href="#">homologene</a> .

*NOTE:* To return only the most "popular" interspecies ortholog mappings, supply `mtthreshold=1` here AND set `method="gprofiler"` above. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.

For more details, please see [here](#).

## Value

MAST results

## Source

[MAST tutorial](#)

sce\_lists\_apply      *sce\_lists\_apply*

---

**Description**

Support function for EWCE::merge\_sce\_list.

**Usage**

```
sce_lists_apply(  
  SCE_lists,  
  return_genes = FALSE,  
  level = 2,  
  as_matrix = FALSE,  
  as_DelayedArray = FALSE  
)
```

**Value**

List of SingleCellExperiments.

---

sce\_merged\_apply      *sce\_merged\_apply*

---

**Description**

Merge a list of SingleCellExperiments.

**Usage**

```
sce_merged_apply(SCE_merged, as_sparse = TRUE, as_DelayedArray = FALSE)
```

**Value**

Merged SingleCellExperiment.

---

sct_normalize	<i>Normalize expression matrix</i>
---------------	------------------------------------

---

**Description**

Normalize expression matrix by accounting for library size. Uses **sctransform**.

**Usage**

```
sct_normalize(exp, as_sparse = TRUE, verbose = TRUE)
```

**Arguments**

exp	Gene x cell expression matrix.
as_sparse	Convert exp to sparse matrix.
verbose	Print messages.

**Value**

Normalised expression matrix.

**Examples**

```
cortex_mrna <- ewceData::cortex_mrna()
exp_sct_normed <- EWCE::sct_normalize(exp = cortex_mrna$exp[1:300, ])
```

---

standardise_ctd	<i>Convert a CellTypeDataset into standardized format</i>
-----------------	---

---

**Description**

This function will take a CTD, drop all genes without 1:1 orthologs with the output\_species ("human" by default), convert the remaining genes to gene symbols, assign names to each level, and convert all matrices to sparse matrices and/or DelayedArray.

**Usage**

```
standardise_ctd(
  ctd,
  dataset,
  input_species = NULL,
  output_species = "human",
  sctSpecies_origin = input_species,
  non121_strategy = "drop_both_species",
  method = "homologene",
```

```

force_new_quantiles = TRUE,
force_standardise = FALSE,
remove_unlabeled_clusters = FALSE,
numberOfBins = 40,
keep_annot = TRUE,
keep_plots = TRUE,
as_sparse = TRUE,
as_DelayedArray = FALSE,
rename_columns = TRUE,
make_columns_unique = FALSE,
verbose = TRUE,
...
)

```

### Arguments

ctd	Input CellTypeData.
dataset	CellTypeData. name.
input_species	Which species the gene names in exp come from. See <a href="#">list_species</a> for all available species.
output_species	Which species' genes names to convert exp to. See <a href="#">list_species</a> for all available species.
sctSpecies_origin	Species that the sct_data originally came from, regardless of its current gene format (e.g. it was previously converted from mouse to human gene orthologs). This is used for computing an appropriate background.
non121_strategy	How to handle genes that don't have 1:1 mappings between input_species:output_species. Options include: <ul style="list-style-type: none"> <li>"drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the input_species or output_species (DEFAULT).</li> <li>"drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the input_species.</li> <li>"drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the output_species.</li> <li>"keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species.</li> <li>"keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.</li> <li>"sum", "mean", "median", "min" or "max" : When gene_df is a matrix and gene_output="rownames", these options</li> </ul>

will aggregate many-to-one gene mappings (input\_species-to-output\_species) after dropping any duplicate genes in the output\_species.

method R package to use for gene mapping:

- "gprofiler" : Slower but more species and genes.
- "homologene" : Faster but fewer species and genes.
- "babelgene" : Faster but fewer species and genes. Also gives consensus scores for each gene mapping based on a several different data sources.

force\_new\_quantiles By default, quantile computation is skipped if they have already been computed. Set =TRUE to override this and generate new quantiles.

force\_standardise If ctd has already been standardised, whether to rerun standardisation anyway (Default: FALSE).

remove\_unlabeled\_clusters Remove any samples that have numeric column names.

numberOfBins Number of non-zero quantile bins.

keep\_annot Keep the column annotation data if provided.

keep\_plots Keep the dendrograms if provided.

as\_sparse Convert to sparse matrix.

as\_DelayedArray Convert to DelayedArray.

rename\_columns Remove replace\_chars from column names.

make\_columns\_unique Rename each columns with the prefix dataset.species.celltype.

verbose Print messages. Set verbose=2 if you want to print all messages from internal functions as well.

... Arguments passed on to [orthogene::convert\\_orthologs](#)

gene\_df Data object containing the genes (see gene\_input for options on how the genes can be stored within the object).  
Can be one of the following formats:

- matrix :  
A sparse or dense matrix.
- data.frame :  
A data.frame, data.table. or tibble.
- codelist :  
A list or character vector.

Genes, transcripts, proteins, SNPs, or genomic ranges can be provided in any format (HGNC, Ensembl, RefSeq, UniProt, etc.) and will be automatically converted to gene symbols unless specified otherwise with the ... arguments.

*Note:* If you set method="homologene", you must either supply genes in gene symbol format (e.g. "Sox2") OR set standardise\_genes=TRUE.

gene\_input Which aspect of gene\_df to get gene names from:

- "rownames" :  
From row names of data.frame/matrix.
- "colnames" :  
From column names of data.frame/matrix.
- <column name> :  
From a column in gene\_df, e.g. "gene\_names".

gene\_output How to return genes. Options include:

- "rownames" :  
As row names of gene\_df.
- "colnames" :  
As column names of gene\_df.
- "columns" :  
As new columns "input\_gene", "ortholog\_gene" (and "input\_gene\_standard" if standardise\_genes=TRUE) in gene\_df.
- "dict" :  
As a dictionary (named list) where the names are input\_gene and the values are ortholog\_gene.
- "dict\_rev" :  
As a reversed dictionary (named list) where the names are ortholog\_gene and the values are input\_gene.

standardise\_genes If TRUE AND gene\_output="columns", a new column "input\_gene\_standard" will be added to gene\_df containing standardised HGNC symbols identified by [gorth](#).

drop\_nonorths Drop genes that don't have an ortholog in the output\_species.

agg\_fun Aggregation function passed to [aggregate\\_mapped\\_genes](#). Set to NULL to skip aggregation step (default).

mthreshold Maximum number of ortholog names per gene to show. Passed to [gorth](#). Only used when method="gprofiler" (DEFAULT : Inf).

sort\_rows Sort gene\_df rows alphanumerically.

gene\_map A [data.frame](#) that maps the current gene names to new gene names. This function's behaviour will adapt to different situations as follows:

- gene\_map=<data.frame> :  
When a data.frame containing the gene key:value columns (specified by input\_col and output\_col, respectively) is provided, this will be used to perform aggregation/expansion.
- gene\_map=NULL and input\_species!=output\_species :  
A gene\_map is automatically generated by [map\\_orthologs](#) to perform inter-species gene aggregation/expansion.
- gene\_map=NULL and input\_species==output\_species :  
A gene\_map is automatically generated by [map\\_genes](#) to perform within-species gene symbol standardization and aggregation/expansion.

input\_col Column name within gene\_map with gene names matching the row names of X.

output\_col Column name within gene\_map with gene names that you wish you map the row names of X onto.

### Value

Standardised CellTypeDataset.

### Examples

```
ctd <- ewceData::ctd()
ctd_std <- EWCE::standardise_ctd(
  ctd = ctd,
  input_species = "mouse",
  dataset = "Zeisel2016"
)
```

---

theme_graph	<i>Get graph theme</i>
-------------	------------------------

---

### Description

Get graph theme for plots created by [generate\\_bootstrap\\_plots\\_for\\_transcriptome](#).

### Usage

```
theme_graph()
```

### Value

ggplot2 graph theme.

---

to_dataframe	<i>Convert object to data.frame</i>
--------------	-------------------------------------

---

### Description

Convert a variety of object types to data.frame format.

### Usage

```
to_dataframe(X, verbose = TRUE)
```

### Arguments

X	Object.
verbose	Print messages.

**Value**

[data.frame](#).

---

to_delayed_array	<i>Convert object to DelayedArray</i>
------------------	---------------------------------------

---

**Description**

Convert a variety of object types to [DelayedArray](#) format.

**Usage**

```
to_delayed_array(exp, as_DelayedArray = TRUE, verbose = TRUE)
```

**Arguments**

exp	Object.
as_DelayedArray	Whether to convert exp to <a href="#">DelayedArray</a> .
verbose	Print messages.

**Value**

[DelayedArray](#).

---

to_sparse_matrix	<i>Convert object to sparse matrix</i>
------------------	--

---

**Description**

Convert a variety of object types to sparse matrix format.

**Usage**

```
to_sparse_matrix(exp, as_sparse = TRUE, verbose = TRUE)
```

**Arguments**

exp	Object.
as_sparse	Whether to convert exp to sparse matrix
verbose	Print messages.

**Value**

Sparse matrix.



# Index

## \* internal

assign\_cores, 6  
bootstrap\_plot, 11  
bootstrap\_plots\_for\_transcriptome, 12  
calculate\_meanexp\_for\_level, 12  
calculate\_specificity\_for\_level, 13  
cell\_list\_dist, 13  
check\_annotLevels, 14  
check\_args\_for\_bootstrap\_plot\_generation, 14  
check\_bootstrap\_args, 15  
check\_controlled\_args, 16  
check\_ewce\_expression\_data\_args, 17  
check\_full\_results, 20  
check\_generate\_controlled\_bootstrap\_geneset, 20  
check\_group\_name, 21  
check\_nas, 21  
check\_numeric, 22  
check\_sce, 23  
check\_species, 23  
compute\_gene\_counts, 24  
compute\_gene\_scores, 25  
convert\_new\_ewce\_to\_old, 28  
convert\_old\_ewce\_to\_new, 28  
create\_background\_multilist, 29  
create\_list\_network, 30  
delayedarray\_normalize, 31  
drop\_nonexpressed\_cells, 32  
drop\_nonexpressed\_genes, 32  
dt\_to\_df, 36  
extract\_matrix, 42  
filter\_variance\_quantiles, 50  
fix\_celltype\_names\_full\_results, 54  
generate\_controlled\_bootstrap\_geneset, 64  
get\_ctd\_levels, 65  
get\_ctd\_matrix\_names, 66  
get\_exp\_data\_for\_bootstrapped\_genes, 66  
get\_sig\_results, 67  
get\_summed\_proportions, 68  
is\_32bit, 69  
is\_celltypedataset, 70  
is\_ctd\_standardised, 70  
max\_ctd\_depth, 73  
merge\_sce\_list, 78  
message\_parallel, 80  
messenger, 80  
myScalesComma, 81  
plot\_log\_bootstrap\_distributions, 82  
plot\_with\_bootstrap\_distributions, 82  
prep\_dendro, 86  
prepare\_genesize\_control\_network, 84  
prepare\_tt, 85  
report\_dge, 86  
report\_results, 87  
run\_deseq2, 87  
run\_limma, 88  
run\_mast, 89  
sce\_lists\_apply, 90  
sce\_merged\_apply, 90  
theme\_graph, 95  
to\_dataframe, 95  
to\_delayed\_array, 96  
to\_sparse\_matrix, 96  
add\_res\_to\_merging\_list, 5, 74  
aggregate\_mapped\_genes, 35, 44, 49, 63, 94  
apply, 6  
assign\_cores, 6

- bin\_columns\_into\_quantiles, 6
- bin\_specificity\_into\_quantiles, 7
- bootstrap\_enrichment\_test, 5, 8, 15, 20, 22, 39, 40, 54, 56, 67–69, 87
- bootstrap\_plot, 11
- bootstrap\_plots\_for\_transcriptome, 12
- calculate\_meanexp\_for\_level, 12
- calculate\_specificity\_for\_level, 13
- cell\_list\_dist, 13
- check\_annotLevels, 14
- check\_args\_for\_bootstrap\_plot\_generation, 14
- check\_bootstrap\_args, 15
- check\_controlled\_args, 16
- check\_ewce\_expression\_data\_args, 17
- check\_ewce\_genelist\_inputs, 18
- check\_full\_results, 20
- check\_generate\_controlled\_bootstrap\_geneset, 20
- check\_group\_name, 21
- check\_nas, 21
- check\_numeric, 22
- check\_percent\_hits, 22
- check\_sce, 23
- check\_species, 23
- comma, 81
- compute\_gene\_counts, 24
- compute\_gene\_scores, 11, 25
- controlled\_geneset\_enrichment, 16, 26, 64
- convert\_new\_ewce\_to\_old, 28
- convert\_old\_ewce\_to\_new, 28
- convert\_orthologs, 10, 19
- create\_background\_multilist, 29
- create\_list\_network, 30
- ctd\_to\_sce, 30
- cut, 7
- data.frame, 36, 37, 45, 49, 63, 94, 96
- data.table, 24, 25
- DelayedArray, 49, 96
- delayedarray\_normalize, 31
- drop\_nonexpressed\_cells, 32
- drop\_nonexpressed\_genes, 32
- drop\_uninformative\_genes, 33
- dt\_to\_df, 36
- EWCE (EWCE-package), 4
- EWCE-package, 4
- ewce\_expression\_data, 5, 15, 17, 37, 39, 41, 58, 85
- ewce\_plot, 39
- example\_bootstrap\_results, 40
- example\_transcriptome\_results, 41
- extract\_matrix, 42
- filter\_ctd\_genes, 45
- filter\_genes\_without\_1to1\_homolog, 46
- filter\_nonorthologs, 46, 47
- filter\_variance\_quantiles, 50
- fix\_bad\_hgnc\_symbols, 51
- fix\_bad\_mgi\_symbols, 52
- fix\_celltype\_names, 53
- fix\_celltype\_names\_full\_results, 54
- generate\_bootstrap\_plots, 11, 54
- generate\_bootstrap\_plots\_for\_transcriptome, 12, 14, 57, 66, 82, 85, 95
- generate\_celltype\_data, 9, 14–18, 20, 21, 25, 26, 37, 55, 58, 60, 64, 67, 68
- generate\_controlled\_bootstrap\_geneset, 20, 64
- get\_celltype\_table, 65
- get\_ctd\_levels, 65
- get\_ctd\_matrix\_names, 66
- get\_exp\_data\_for\_bootstrapped\_genes, 66
- get\_sig\_results, 67
- get\_summed\_proportions, 68
- ggplot, 40
- gorth, 35, 36, 44, 45, 49, 63, 87–89, 94
- homologene, 87–89
- is\_32bit, 69
- is\_celltypedataset, 70
- is\_ctd\_standardised, 70
- is\_delayed\_array, 71
- is\_matrix, 71
- is\_sparse\_matrix, 72
- list\_species, 9, 18, 24, 26, 34, 38, 42, 43, 55, 58, 61, 72, 84, 85, 92
- load\_rdata, 73
- log1p, 31
- map\_genes, 9, 10, 19, 36, 45, 50, 63, 94
- map\_orthologs, 36, 45, 50, 63, 94

map\_species, [49](#), [72](#)  
max\_ctd\_depth, [73](#)  
merge\_ctd, [75](#)  
merge\_sce, [77](#)  
merge\_sce\_list, [78](#)  
merge\_two\_expfiles, [79](#)  
merged\_ewce, [74](#)  
message\_parallel, [80](#)  
messenger, [80](#)  
myScalesComma, [81](#)

nbinomLRT, [87](#)  
nbinomWaldTest, [87](#)

orthogene::convert\_orthologs, [34](#), [44](#), [48](#),  
[62](#), [93](#)

p.adjust, [9](#), [33](#), [39](#), [68](#), [88](#), [89](#)  
plot\_ctd, [81](#)  
plot\_log\_bootstrap\_distributions, [81](#),  
[82](#)  
plot\_with\_bootstrap\_distributions, [82](#)  
prep.dendro, [83](#)  
prep\_dendro, [86](#)  
prepare\_genesize\_control\_network, [84](#)  
prepare\_tt, [85](#)

report\_dge, [86](#)  
report\_results, [87](#)  
run\_deseq2, [87](#)  
run\_limma, [88](#)  
run\_mast, [89](#)

sce\_lists\_apply, [90](#)  
sce\_merged\_apply, [90](#)  
sct\_normalize, [91](#)  
SingleCellExperiment, [75](#), [76](#), [78](#)  
standardise\_ctd, [9](#), [19](#), [54](#), [70](#), [91](#)

theme\_graph, [95](#)  
to\_dataframe, [95](#)  
to\_delayed\_array, [96](#)  
to\_sparse\_matrix, [96](#)  
topTable, [15](#), [17](#), [37](#), [58](#), [85](#)

wrap\_plots, [39](#)