

Package ‘zFPKM’

February 21, 2026

Title A suite of functions to facilitate zFPKM transformations

Version 1.32.0

Description Perform the zFPKM transform on RNA-seq FPKM data. This algorithm is based on the publication by Hart et al., 2013 (Pubmed ID 24215113). Reference recommends using `zFPKM > -3` to select expressed genes. Validated with encode open/closed chromosome data. Works well for gene level data using FPKM or TPM. Does not appear to calibrate well for transcript level data.

License GPL-3 | file LICENSE

URL <https://github.com/ronammar/zFPKM/>

BugReports <https://github.com/ronammar/zFPKM/issues>

Imports checkmate, dplyr, ggplot2, tidyr, SummarizedExperiment

Suggests knitr, limma, edgeR, GEOquery, stringr, printr, rmarkdown

VignetteBuilder knitr

biocViews ImmunoOncology, RNASeq, FeatureExtraction, Software, GeneExpression

Depends R (>= 3.4.0)

LazyData true

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/zFPKM>

git_branch RELEASE_3_22

git_last_commit 1b16803

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2026-02-20

Author Ron Ammar [aut, cre],
John Thompson [aut]

Maintainer Ron Ammar <ron.ammar@bms.com>

Contents

zFPKM	2
zFPKMPlot	3

Index**4**

zFPKM	<i>zFPKM Transformation</i>
-------	-----------------------------

Description

Perform the zFPKM transform on RNA-seq FPKM data. This algorithm is based on the publication by Hart et al., 2013 (Pubmed ID 24215113). Reference recommends using zFPKM > -3 to select expressed genes. Validated with encode open/closed promoter chromatin structure epigenetic data on six of the ENCODE cell lines. Works well for gene level data using FPKM or TPM. Does not appear to calibrate well for transcript level data.

Usage

```
zFPKM(fpkmDF, assayName = "fpkm")
```

Arguments

fpkmDF	A SummarizedExperiment or data frame containing raw FPKM (or TPM) values. Each row corresponds to a gene/transcript and each column corresponds to a sample. NOTE: these are NOT log ₂ transformed. Also, the rownames are gene/transcript names and NOT included as a separate column
assayName	When input is a SummarizedExperiment, names the specific assay. Typically one of "fpkm" or "tpm" [default = "fpkm"]

Value

zFPKM data frame

Author(s)

Ron Ammar, <ron.ammar@bms.com>

References

<http://www.ncbi.nlm.nih.gov/pubmed/24215113>

Examples

```
library(dplyr)
gse94802 <- "ftp://ftp.ncbi.nlm.nih.gov/geo/series/GSE94nnn/GSE94802/suppl/GSE94802_Minkina_etal_normalized"
temp <- tempfile()
download.file(gse94802, temp)
fpkm <- read.csv(gzfile(temp), row.names=1)
MyFPKMdf <- select(fpkm, -MGI_Symbol)

zfpm <- zFPKM(MyFPKMdf)
```

`zFPKMPlot`*zFPKM Transformation*

Description

Perform the zFPKM transform on RNA-seq FPKM data. This algorithm is based on the publication by Hart et al., 2013 (Pubmed ID 24215113). Reference recommends using zFPKM > -3 to select expressed genes. Validated with encode open/closed promoter chromatin structure epigenetic data on six of the ENCODE cell lines. Works well for gene level data using FPKM or TPM. Does not appear to calibrate well for transcript level data.

Usage

```
zFPKMPlot(fpkmDF, assayName = "fpkm", FacetTitles = FALSE,  
          PlotXfloor = -20)
```

Arguments

<code>fpkmDF</code>	A SummarizedExperiment or data frame containing raw FPKM (or TPM) values. Each row corresponds to a gene/transcript and each column corresponds to a sample. NOTE: these are NOT log ₂ transformed. Also, the rownames are gene/transcript names and NOT included as a separate column
<code>assayName</code>	When input is a SummarizedExperiment, names the specific assay. Typically one of "fpkm" or "tpm" [default = "fpkm"]
<code>FacetTitles</code>	use to label each facet with the sample name [default = FALSE]
<code>PlotXfloor</code>	Lower limit for X axis (log ₂ FPKM units) [default = -20] set to NULL to disable

Value

Displays plots of zFPKM distributions

Author(s)

Ron Ammar, <ron.ammar@bms.com>

References

<http://www.ncbi.nlm.nih.gov/pubmed/24215113>

Examples

```
library(dplyr)  
gse94802 <- "ftp://ftp.ncbi.nlm.nih.gov/geo/series/GSE94nnn/GSE94802/suppl/GSE94802_Minkina_et_al_normalized  
temp <- tempfile()  
download.file(gse94802, temp)  
fpkm <- read.csv(gzfile(temp), row.names=1)  
MyFPKMdf <- select(fpkm, -MGI_Symbol)  
  
zFPKMPlot(MyFPKMdf)
```

Index

* **zFPKM**

zFPKM, 2

zFPKMPlot, 3

zFPKM, 2

zFPKMPlot, 3