

# Package ‘gctest’

June 30, 2022

**Title** Genotype Conditional Association TEST

**Version** 1.27.0

**Date** 2015-10-09

**Author** Wei Hao, Minsun Song, John D. Storey

**Maintainer** Wei Hao <whao@princeton.edu>, John D. Storey <jstorey@princeton.edu>

**LazyData** true

**Description** GCAT is an association test for genome wide association studies that controls for population structure under a general class of trait models.

**Imports** lfa

**Depends** R (>= 3.2)

**Suggests** knitr, ggplot2

**VignetteBuilder** knitr

**License** GPL-3

**biocViews** SNP, DimensionReduction, PrincipalComponent, GenomeWideAssociation

**BugReports** <https://github.com/StoreyLab/gctest/issues>

**URL** <https://github.com/StoreyLab/gctest>

**git\_url** <https://git.bioconductor.org/packages/gctest>

**git\_branch** master

**git\_last\_commit** 7a4b9d6

**git\_last\_commit\_date** 2022-04-26

**Date/Publication** 2022-06-30

## R topics documented:

gcat . . . . .	2
sim_genotype . . . . .	3
sim_trait . . . . .	3

<b>Index</b>	<b>4</b>
--------------	----------

---

`gcat`*Genotype Conditional Association TEST*

---

**Description**

Performs the GCAT test for association between SNPs and trait, and returns the p-values.

**Usage**

```
gcat(X, LF, trait, adjustment = NULL)
gcatest(X, LF, trait, adjustment = NULL)
gcat.stat(X, LF, trait, adjustment = NULL)
```

**Arguments**

<code>X</code>	a matrix of SNP genotypes, i.e. an integer matrix of 0's, 1's, and 2's. Sparse matrices of class <code>Matrix</code> are not supported (yet).
<code>LF</code>	matrix of logistic factors outputted from function <code>lfa</code>
<code>trait</code>	vector
<code>adjustment</code>	matrix of adjustment variables

**Value**

vector of p-values

**Functions**

- `gcatest`:
- `gcat.stat`: returns the association statistics instead of the p-value.

**References**

Song, M, Hao, W, Storey, JD (2015). Testing for genetic associations in arbitrarily structured populations. *Nat. Genet.*, 47, 5:550-4.

**Examples**

```
library(lfa)
LF = lfa(sim_geno, 3)
gcat_p = gcat(sim_geno, LF, sim_trait)
gcat_stat = gcat.stat(sim_geno, LF, sim_trait)
```

---

sim_geno	<i>Simulated data from PSD model</i>
----------	--------------------------------------

---

**Description**

10,000 SNPs, 1,000 individuals, first five SNPs are associated.

**Usage**

sim\_geno

**Format**

a matrix of 0's, 1's and 2's for the genotypes

**Value**

simulated genotype matrix

---

sim_trait	<i>Simulated data from PSD model</i>
-----------	--------------------------------------

---

**Description**

10,000 SNPs, 1,000 individuals, first five SNPs are associated.

**Usage**

sim\_trait

**Format**

a vector of traits

**Value**

simulated traits

# Index

`gcat`, [2](#)  
`gcat``test` (`gcat`), [2](#)

`sim_geno`, [3](#)  
`sim_trait`, [3](#)