# **CENTRE**annotation

August 6, 2025

CENTREannotDb

Class object for the CENTRE annotation data

# **Description**

The CENTRE annotation data is accessed through objects of CENTREannotDb class. That either provides access to the ENCODE screen V3 annotation for Human https://screen.encodeproject.org or gives access to GENCODE basic gene annotation version 40.

### Usage

```
CENTREannotDb(x)
tables(x)
```

# **Arguments**

Х

sqlite file path

# **Details**

Using tables(x) on a CENTREannotDb object returns the tables and columns for each table in the database.

#### Value

class CENTREannotDb

### References

Based on CompoundDb::CompDb.

# Examples

```
##load the screen V3 annotation
ah <- AnnotationHub::AnnotationHub()
screen <- ah[["AH116731"]]
tables(screen) #get all tables and columns in the data base</pre>
```

2 fetch\_data

| fetch_data Fetch data from the CENTREannotDb databases | fetch_data | Fetch data from the CENTREannotDb databases |  |
|--|------------|---|--|
|--|------------|---|--|

# Description

Main interface to fetch data from the CENTREannotation package databases through the CENTREannotDb objects.

# Usage

```
fetch_data(x, columns, entries, column_filter)
```

# Arguments

| X             | A CENTREannotDb object.   |
|---------------|---|
| columns       | Columns to select (vector or string). Equivalent to X in SELECT X.  |
| entries       | Element ID to select (vector or sting). Equivalent to ID in SELECT X FROM TABLE WHERE ID in Z. If entries or column_filter is missing the program assumes the query is SELECT X FROM TABLE. |
| column_filter | Column on which to apply filter. Equivalent to Z in SELECT X FROM TABLE WHERE ID in Z. If entries or column_filter is missing the program assumes the query is SELECT X FROM TABLE.         |

# Value

data.frame with the queried data.

# References

Based on the internal query engine of CompoundDb

# **Examples**

```
ah <- AnnotationHub::AnnotationHub()
CENTREannotenhDb <- ah[["AH116731"]]
res <- fetch_data(CENTREannotenhDb,
    columns = c("enhancer_id", "start"),
    entries = c("EH38E1519134", "EH38E1519132"),
    column_filter = "enhancer_id"
)</pre>
```

# Index

```
CENTREannotDb, 1
CENTREannotDb-class (CENTREannotDb), 1
fetch_data, 2
tables (CENTREannotDb), 1
```