

Package ‘FCBF’

June 15, 2019

Type Package

Title Fast Correlation Based Filter for Feature Selection

Version 1.2.2

Maintainer Tiago Lubiana <tiago.lubiana.alves@usp.br>

Description This package provides a simple R implementation for the Fast Correlation Based Filter described in Yu, L. and Liu, H.; Feature Selection for High-Dimensional Data: A Fast Correlation Based Filter Solution, Proc. 20th Intl. Conf. Mach. Learn. (ICML-2003), Washington DC, 2003

The current package is an intent to make easier for bioinformaticians to use FCBF for feature selection, especially regarding transcriptomic data. This implies discretizing expression (function `discretize_exprs`) before calculating the features that explain the class, but are not predictable by other features.

The functions are implemented based on the algorithm of Yu and Liu, 2003 and Rajarshi Guha's implementation from 13/05/2005 available (as of 26/08/2018) at <http://www.rguha.net/code/R/fcbf.R>.

License MIT + file LICENSE

Encoding UTF-8

LazyData False

RoxygenNote 6.1.0.9000

Imports ggplot2, gridExtra, pbapply, parallel, SummarizedExperiment, stats

Suggests caret, mlbench, SingleCellExperiment, knitr, rmarkdown, testthat, BiocManager

biocViews GeneTarget, FeatureExtraction, Classification, GeneExpression, SingleCell, ImmunoOncology

VignetteBuilder knitr

Depends R (>= 3.5.0)

git_url <https://git.bioconductor.org/packages/FCBF>

git_branch RELEASE_3_9

git_last_commit 06fc22f

git_last_commit_date 2019-05-28

Date/Publication 2019-06-14

Author Tiago Lubiana [aut, cre],
Helder Nakaya [aut, ths]

R topics documented:

discretize_exprs	2
discretize_exprs_supervised	3
discretize_gene_supervised	3
fcfb	4
get_ig	5
get_su	6
IG	7
scDengue	7
SU	8
su_plot	9
Index	10

discretize_exprs	<i>discretize_exprs Simple discretizing of gene expression</i>
------------------	--

Description

This function takes the range of values for each gene in a previously normalized expression table (genes/variables in rows, samples/ observations in columns) and uses it for a width-based discretization. Each feature is divide into "n" bins of equal width. The first bin is attributed the class 'low' and the next bins are assigned to "high". It transposes the original expression table.

Usage

```
discretize_exprs(expression_table, number_of_bins = 3)
```

Arguments

`expression_table` A previously normalized expression table Note: this might drastically change the number of selected features.

`number_of_bins` Number of equal-width bins for discretization. Note: it is a binary discretization, with the first bin becoming one class ('low') and the other bins, another class ('high'). Defaults to 3.

Value

A data frame with the discretized features in the same order as previously

Examples

```
data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
head(discrete_expression[,1:4])
```

```
discretize_exprs_supervised
      supervised_disc_df
```

Description

Uses several discretizations and selects the one that is best for a given variable (gene) in comparison to a target class by equivocation

Usage

```
discretize_exprs_supervised(expression_table, target, parallel = FALSE)
```

Arguments

expression_table	A previously normalized expression table
target	A series of labels matching each of the values in the gene vector (genes in rows, cells/samples in columns)
parallel	Set calculations in parallel. May be worth it if the number of rows and columns is really large. Do watchout for memory overload.

Value

A data frame with the discretized features in the same order as previously

Examples

```
data(scDengue)
exprs <- as.data.frame(SummarizedExperiment::assay(scDengue, 'logcounts'))
exprs <- exprs [1:200, 1:120]
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
discrete_expression <- as.data.frame(discretize_exprs_supervised(exprs,target))
fcfb(discrete_expression,target, thresh = 0.05, verbose = TRUE)
```

```
discretize_gene_supervised
      discretize_gene_supervised
```

Description

Uses several discretizations and selects the one that is best for a given variable (gene) in comparison to a target class by equivocation Note that set.seed() should be used for reproducing the results. The inner kmeans #' function would, otherwise, provide different results each time.

Usage

```
discretize_gene_supervised(gene, target, output = "discretized_vector",
  discs = c(".split_vector_in_two_by_median",
    ".split_vector_in_two_by_mean", ".split_vector_by_kmeans",
    ".split_vector_in_three_by_mean_sd", ".split_vector_in_two_by_vw"),
  vw_params = c(0.25, 0.5, 0.75), kmeans_centers = c(2, 3, 4),
  sd_alpha = c(0.75, 1, 1.25))
```

Arguments

gene	A previously normalized gene expression vector
target	A series of labels matching each of the values in the gene vector
output	If it is equal to 'discretized_vector', the output is the vector. If it is 'su', returns a dataframe. Defaults to 'discretized_vector'
discs	Defaults to c(".split_vector_in_two_by_median", "split_vector_in_two_by_mean", ".split_vector_by_kmeans", ".split_vector_in_three_by_mean_sd", ".split_vector_in_two_by_vw")
vw_params	cutoff parameters for the varying width function. Defaults to 0.25, 0.5 and 0.75
kmeans_centers	Numeric vector with the number of centers to use for kmeans. Defaults to 2, 3 and 4
sd_alpha	Parameter for adjusting the 'medium' level of the mean +- sd discretization. Defaults to sd_alpha = c(0.75, 1, 1.25))

Details

Note that a seed for random values has to be set for reproducibility. Otherwise, the "kmeans" value might vary from iteration to iteration.

Value

A data frame with the discretized features in the same order as previously

Examples

```
data(scDengue)
exprs <- as.data.frame(SummarizedExperiment::assay(scDengue, 'logcounts'))
gene <- exprs['ENSG00000166825',]
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
set.seed(3)
discrete_expression <- as.data.frame(discretize_gene_supervised(gene, target))
table(discrete_expression)
```

fcbf

Fast Correlation Based Filter function.

Description

This function allows selection of variables from a feature table of discrete/categorical variables and a target class. The function is based on the algorithm described in Yu, L. and Liu, H.; Feature Selection for High-Dimensional Data A Fast Correlation Based Filter Solution, Proc. 20th Intl. Conf. Mach. Learn. (ICML-2003), Washington DC, 2003

Usage

```
fcbf(x, y, thresh = 0.25, verbose = FALSE, samples_in_rows = FALSE,
     balance_classes = FALSE)
```

Arguments

x	A table of features (samples in rows, variables in columns, and each observation in each cell)
y	A target vector, factor containing classes of the observations. Note: the observations must be in the same order as the parameter x
thresh	A threshold for the minimum correlation (as determined by symmetrical uncertainty) between each variable and the class. Defaults to 0.25.
verbose	Adds verbosity. Defaults to FALSE.
samples_in_rows	A flag for the case in which samples are in rows and variables/genes in columns. Defaults to FALSE. Note: this might drastically change the number of selected features.
balance_classes	Balances number of instances in the target vector y by sampling the number of instances in the minor class from all others. The number of samplings is controlled by resampling_number. Defaults to FALSE.

Details

Obs: For gene expression, you will need to run `discretize_exprs` first

Value

Returns a data frame with the selected features index (first row) and their symmetrical uncertainty values regarding the class (second row). Variable names are present in rownames

Examples

```
data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
head(discrete_expression[,1:4])
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
fcbf(discrete_expression,target, thresh = 0.05, verbose = TRUE)
fcbf(discrete_expression,target, thresh = 0.05, verbose = TRUE, balance_classes = TRUE)
```

get_ig

Get information gain

Description

This functions runs information gain for a feature table and a class, returning the scores of information gain for all features

Usage

```
get_ig(x, y)
```

Arguments

x A table of features (observations in rows, variables in columns)

y A target vector, factor containing classes of the observations. Note: the observations must be in the same order as the parameter x.

Value

A dataframe containing the SU values for each feature

Examples

```
data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
ig_values <- get_ig(discrete_expression[,], target[])
ig_values[1:10,]
```

get_su

Symmetrical Uncertainty diagnostic

Description

This functions runs symmetrical uncertainty for a feature table and a class, returning the scores of symmetrical uncertainty for all features

Usage

```
get_su(x, y)
```

Arguments

x A table of features (observations in rows, variables in columns)

y A target vector, factor containing classes of the observations. Note: the observations must be in the same order as the parameter x.

Value

A dataframe containing the SU values for each feature

Examples

```

data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
su_values <- get_su(discrete_expression[,],target[])
su_values[1:10,]

```

IG

Information Gain This functions runs Information Gain for two features, returning the score

Description

Information Gain This functions runs Information Gain for two features, returning the score

Usage

```
IG(x, y, base = exp(1))
```

Arguments

x A vector containing a categorical feature
y A vector containing other categorical feature

Value

A numerical value for the Information Gain score

Examples

```

data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
discrete_expression_gene_1 <- discrete_expression$V1
discrete_expression_gene_2 <- discrete_expression$V2
IG(discrete_expression_gene_1,discrete_expression_gene_2)

```

scDengue

Dengue infected macrophages; gene expression data from GEO study GSE110496

Description

Expression data from single cells, from adengue virus infection study by Zanini et al, #' 2018. The expression was filtered to get cells 12 hours after infection with #' a multiplicity of infection (moi) of 1 (dengue) or uninfected(ctrl). Gene counts were normalized via Bioconductor package "SCNorm".

Usage

```
data(scDengue)
```

Format

An object of class SingleCellExperiment

Details

Gene expression has to be discretized for use in FCBF.

Source

[GEO](#)

References

Zanini, F., Pu, S. Y., Bekerman, E., Einav, S., & Quake, S. R. (2018). Single-cell transcriptional dynamics of flavivirus infection. *Elife*, 7, e32942. [PubMed](#)

Examples

```
data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
# Discretize gene expression
discrete_expression <- as.data.frame(discretize_exprs(exprs))
fcbf_features <- fcbf(discrete_expression,
                     target,
                     thresh = 0.05,
                     verbose = TRUE)
```

SU

Symmetrical Uncertainty diagnostic This functions runs symmetrical uncertainty for two features, returning the score

Description

Symmetrical Uncertainty diagnostic This functions runs symmetrical uncertainty for two features, returning the score

Usage

```
SU(x, y, base = exp(1))
```

Arguments

x A vector containing a categorical feature
y A vector containing other categorical feature

Value

A numerical value for the Symetrical Uncertainty score

Examples

```
data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
discrete_expression_gene_1 <- discrete_expression$V1
discrete_expression_gene_2 <- discrete_expression$V2
SU(discrete_expression_gene_1,discrete_expression_gene_2)
```

su_plot

Symmetrical Uncertainty diagnostic

Description

This functions runs symmetrical uncertainty for a feature table and a class, returning an histogram of the scores

Usage

```
su_plot(x, y)
```

Arguments

x A table of features (observations in rows, variables in columns)
y A target vector, factor containing classes of the observations. Note: the observations must be in the same order as the parameter x.

Value

Plots an histogram of symmetrical uncertainty values regarding the class.

Examples

```
data(scDengue)
exprs <- SummarizedExperiment::assay(scDengue, 'logcounts')
discrete_expression <- as.data.frame(discretize_exprs(exprs))
infection <- SummarizedExperiment::colData(scDengue)
target <- infection$infection
su_plot(discrete_expression,target)
```

Index

- *Topic **datasets**,
 - scDengue, [7](#)
- *Topic **dengue**,
 - scDengue, [7](#)
- *Topic **single-cell**
 - scDengue, [7](#)

- discretize_exprs, [2](#)
- discretize_exprs_supervised, [3](#)
- discretize_gene_supervised, [3](#)

- fcbf, [4](#)

- get_ig, [5](#)
- get_su, [6](#)

- IG, [7](#)

- scDengue, [7](#)
- SU, [8](#)
- su_plot, [9](#)