

Package ‘fcoex’

February 6, 2023

Title FCBF-based Co-Expression Networks for Single Cells

Version 1.12.0

Description The fcoex package implements an easy-to use interface to co-expression analysis based on the FCBF (Fast Correlation-Based Filter) algorithm. It was implemented specifically to deal with single-cell data. The modules found can be used to redefine cell populations, unveil novel gene associations and predict gene function by guilt-by-association. The package structure is adapted from the CEMiTool package, relying on visualizations and code designed and written by CEMiTool's authors.

Depends R (>= 4.1)

Imports FCBF, parallel, progress, dplyr, ggplot2, ggrepel, igraph, grid, intergraph, stringr, clusterProfiler, data.table, grDevices, methods, network, scales, sna, utils, stats, SingleCellExperiment, pathwayPCA, Matrix

Suggests testthat (>= 2.1.0), devtools, BiocManager, TENxPBMCDData, scater, schex, gridExtra, scran, Seurat, knitr, rmarkdown

License GPL-3

Encoding UTF-8

biocViews GeneExpression, Transcriptomics, GraphAndNetwork, mRNAArray, RNASeq, Network, NetworkEnrichment, Pathways, ImmunoOncology, SingleCell

LazyData true

RoxygenNote 7.1.2

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/fcoex>

git_branch RELEASE_3_16

git_last_commit 4de9d61

git_last_commit_date 2022-11-01

Date/Publication 2023-02-06

Author Tiago Lubiana [aut, cre],
Helder Nakaya [aut, ths]

Maintainer Tiago Lubiana <tiago.lubiana.alves@usp.br>

R topics documented:

<code>.get_correlates</code>	2
<code>.plot_one_interaction</code>	3
<code>discretize</code>	4
<code>fc</code>	5
<code>fcoex-class</code>	5
<code>find_cbf_modules</code>	6
<code>get_nets</code>	7
<code>idents</code>	8
<code>mini_pbmc3k</code>	9
<code>module_genes</code>	9
<code>mod_colors</code>	10
<code>mod_gene_num</code>	11
<code>mod_names</code>	11
<code>mod_ora</code>	12
<code>new_fcoex</code>	13
<code>nmodules</code>	13
<code>ora_data</code>	14
<code>plot_ora</code>	15
<code>recluster</code>	16
<code>save_plots</code>	17
<code>show,fcoex-method</code>	17
<code>show_net</code>	18
<code>show_ora</code>	19
Index	20

<code>.get_correlates</code>	<i>.get_correlates</i>
------------------------------	------------------------

Description

auxiliary function for `find_cbf_modules`

Usage

```
.get_correlates(
  i,
  gene_by_gene_su_correlation,
  discretized_exprs,
  expression_table_only_with_genes_with_high_su
)
```

Arguments

`i` A gene to be correlated
`gene_by_gene_su_correlation` the dataframe with the correlations to be updated
`discretized_exprs` the dataframe with discretized expression to extract a gene
`expression_table_only_with_genes_with_high_su` the dataframe to after the filtering step

Value

the updated column of the `gene_by_gene_su_correlation`

`.plot_one_interaction` *Network visualization*

Description

Creates a graph based on interactions provided This function was copied and adapted from the CEMiTool package. The visualization of networks in this function is derivative of the intellectual work of CEMiTool's authors.

Usage

```
.plot_one_interaction(adjacency_matrix, n, color, name)
```

Arguments

`adjacency_matrix` An adjacency matrix from the `fcoex` object.
`n` Number of genes to be shown
`color` Color of the module to be plotted
`name` Name of the module to be plotted
`...` Optional parameters.

Value

A `ggplot2` ('gg') object

discretize	<i>Set the discretized expression attribute Uses the discretize_exprs function of the FCBF package</i>
------------	--

Description

Set the discretized expression attribute Uses the discretize_exprs function of the FCBF package

Usage

```
discretize(
  fc,
  number_of_bins = 4,
  method = "varying_width",
  min_max_cutoff = 0.25
)

## S4 method for signature 'fcoex'
discretize(
  fc,
  number_of_bins = 4,
  method = "varying_width",
  min_max_cutoff = 0.25
)
```

Arguments

fc	Object of class fcoex
number_of_bins	Number of equal-width bins for discretization. Note: it is a binary discretization, with the first bin becoming one class ('low') and the other bins, another class ('high'). Defaults to 4.
method	Method applied to all genes for discretization. Methods available: "varying_width" (Binarization modulated by the number_of_bins param), "mean" (Split in ON/OFF by each gene mean expression), "median" (Split in ON/OFF by each gene median expression), "min_max_%" (Similat to the "varying width", a binarization threshold in a % of the min-max range is set. (minmax% param)),
min_max_cutoff	<- Modulator for the "min_max_%" method. Defaults to 0.25.

Value

A data frame with the discretized features in the same order as previously

Examples

```
library(SingleCellExperiment)
data("mini_pbmc3k")
targets <- colData(mini_pbmc3k)$clusters
```

```

exprs <- as.data.frame(assay(mini_pbmc3k, "logcounts"))
fc <- new_fcoex(exprs, targets)
fc <- discretize(fc)

```

fc *Example fcoex object*

Description

Example fcoex object processed from the mini_pbmc3k dataset.

Usage

```
fc
```

Format

An object of class fcoex

Examples

```

data(fc)
fc

```

fcoex-class *An S4 class to represent the fcoex analysis.*

Description

An S4 class to represent the fcoex analysis.

Slots

expression Normalized gene expression table from single-cells data . frame.

discretized_expression Discretized gene expression table from single-cells data . frame.

target Original target classes for the cells (factor).

selected_genes Character vector containing the names of genes selected for analysis

module_list list containing genes in each module.

adjacency data.frame containing the adjacency table for the selected genes before trimming.

adjacency_trimmed data.frame containing the adjacency table for the selected genes after trimming.

coex_network_plot list of ggplot graphs with module gene interactions.

new_clusters list containing gene interactions present in modules.

mod_colors character vector containing colors associated with each network module.
 ora Over-representation analysis results data.frame.
 barplot_ora list of ggplot graphs with over-representation analysis results per module.
 mod_idents Identities of cells based on each co-expression module. Determined by the "recluster" method
 parameters list containing analysis parameters.

find_cbf_modules *find_cbf_modules*

Description

find_cbf_modules uses Symmetrical Uncertainty as a correlation measure and the FCBF algorithm to 1 - Filter the gene list by correlations to a class (Step 1) and 2 - Determine soft thresholds for coexpression to genes predominantly correlated to a class.

Usage

```

find_cbf_modules(
  fc,
  n_genes_selected_in_first_step = NULL,
  FCBF_threshold = 0.1,
  verbose = TRUE,
  is_parallel = FALSE
)

## S4 method for signature 'fcoex'
find_cbf_modules(
  fc,
  n_genes_selected_in_first_step = NULL,
  FCBF_threshold = 0.1,
  verbose = TRUE,
  is_parallel = FALSE
)

```

Arguments

fc	A fcoex object containing a discretized expression table
n_genes_selected_in_first_step	Sets the number of genes to be selected in the first part of the algorithm. If left unchanged, it defaults to NULL and the minimum_su parameter is used. Caution: it overrides the minimum_su parameter altogether.
FCBF_threshold	A threshold for the minimum correlation (as determined by symmetrical uncertainty) between each variable and the class used for wrapped FCBF function. Defaults to 0.1.
verbose	Adds verbosity. Defaults to TRUE
is_parallel	Uses package parallel to parallelize calculations. Defaults to FALSE.

Value

Returns a list with the CBF modules found or a adjacency matrix of the graph

Examples

```
library(SingleCellExperiment)
data("mini_pbmc3k")
targets <- colData(mini_pbmc3k)$clusters
exprs <- as.data.frame(assay(mini_pbmc3k, "logcounts"))
fc <- new_fcoex(exprs, targets)
fc <- discretize(fc)
fc <- find_cbf_modules(fc)
```

get_nets

Network visualization

Description

Creates network visualizations based on the adjacency matrix obtained with the `find_cbf_modules` method

Usage

```
get_nets(fc, n = 10, min_elements = 5, ...)

## S4 method for signature 'fcoex'
get_nets(fc, n = 10, min_elements = 5, ...)
```

Arguments

fc	Object of class <code>fcoex</code> .
n	number of nodes to label
min_elements	Minimum number of elements in a module for it to be plotted. Defaults to 5.
...	Optional parameters.

Details

This function was copied and adapted from the `CEMiTool` package. The visualization of networks in this function is derivative of the intellectual work of `CEMiTool`'s authors.

Value

Object of class `fcoex` with profile plots

Examples

```
library(SingleCellExperiment)
data("mini_pbmc3k")
targets <- colData(mini_pbmc3k)$clusters
exprs <- as.data.frame(assay(mini_pbmc3k, "logcounts"))
fc <- new_fcoex(exprs, targets)
fc <- discretize(fc)
fc <- find_cbf_modules(fc)
fc <- get_nets(fc)
```

idents	<i>Retrieves module identities from the recluster function</i>
--------	--

Description

Retrieves module identities from the recluster function

Usage

```
idents(fc)

## S4 method for signature 'fcoex'
idents(fc)
```

Arguments

fc Object of class fcoex

Value

Named object of class `list` with clusterings derived from the recluster function.

References

Guangchuang Yu, Li-Gen Wang, Yanyan Han, Qing-Yu He. clusterProfiler: an R package for comparing biological themes among gene clusters. *OMICS: A Journal of Integrative Biology*. 2012, 16(5):284-287.

Examples

```
data("fc")
idents(fc)
```

mini_pbmc3k	<i>Processed subset of the pbmc3k dataset from PBMC genomics</i>
-------------	--

Description

A subset with 600 sampled cells and the top 1700 variable genes from the TENxPBMCData package pbmc3k dataset.

Usage

```
data(mini_pbmc3k)
```

Format

An object of class SingleCellExperiment

Details

Preprocessed in accordance to OSCA (August 2019, <https://osca.bioconductor.org/>)

scater::normalized . PCA with 50 components. snn graph on the PCA space + louvain clustering to yield 8 clusters . UMAP already ran

Examples

```
data(mini_pbmc3k)
mini_pbmc3k
```

module_genes	<i>Get the module genes in a fcoex object</i>
--------------	---

Description

This function was copied and adapted from the CEMiTool package.

Usage

```
module_genes(fc, module = NULL)

## S4 method for signature 'fcoex'
module_genes(fc, module = NULL)
```

Arguments

fc	Object of class fcoex
module	A character string with the name of the module of which genes are to be returned. Defaults to NULL, which returns the full list of genes and modules.

Value

Object of class `data.frame` containing genes and their respective module

Examples

```
data("fc")
module_genes(fc)
```

mod_colors

Set module colors mod_colors attribute

Description

Set module colors mod_colors attribute

Usage

```
mod_colors(fc)

## S4 method for signature 'fcoex'
mod_colors(fc)
```

Arguments

fc Object of class `fcoex`

Value

A vector with color names.

Examples

```
data("fc")
mod_colors(fc)
```

mod_gene_num	<i>Get the number of genes in modules in a fcoex object This function was copied and adapted from the CEMiTool package.</i>
--------------	---

Description

Get the number of genes in modules in a fcoex object This function was copied and adapted from the CEMiTool package.

Usage

```
mod_gene_num(fc, module = NULL)

## S4 method for signature 'fcoex'
mod_gene_num(fc, module = NULL)
```

Arguments

fc	Object of class fcoex
module	Default is NULL. If a character string designating a module is#’ given, the number of genes in that module is returned instead.

Value

The number of genes in module(s)

Examples

```
data("fc")
mod_gene_num(fc, module = "TYROBP")
```

mod_names	<i>Get module names in a fcoex object</i>
-----------	---

Description

This function was copied and adapted from the CEMiTool package.

Usage

```
mod_names(fc, include_NC = TRUE)

## S4 method for signature 'fcoex'
mod_names(fc, include_NC = TRUE)
```

Arguments

fc Object of class fcoex
include_NC Logical. Whether or not to include "Not.Correlated" module. Defaults to TRUE.

Value

Module names

Examples

```
data("fc")  
mod_names(fc)
```

mod_ora

Over Representation Analysis (ORA)

Description

This function was modified from the CEMiTool package. Chunks of code were retained "as is"

Usage

```
mod_ora(fc, gmt, verbose = FALSE)  
  
## S4 method for signature 'fcoex'  
mod_ora(fc, gmt, verbose = FALSE)
```

Arguments

fc A fcoex object.
gmt A gmt file with gene sets for ora analysis
verbose Controls verbosity. Defaults to FALSE.

Value

A fcoex object containing over-representation analysis data

Examples

```
data("fc")  
gmt_fname <- system.file("extdata", "pathways.gmt", package = "CEMiTool")  
gmt_in <- pathwayPCA::read_gmt(gmt_fname)  
fc <- mod_ora(fc, gmt_in)
```

new_fcoex	<i>Create a fcoex object</i>
-----------	------------------------------

Description

Create a fcoex object

Usage

```
new_fcoex(expression = data.frame(), target = vector())
```

Arguments

expression	Normalized gene expression table from single-cells data. frame.
target	Original target classes for the cells (factor).

Value

Object of class fcoex

Examples

```
# Create new fcoex object
library(SingleCellExperiment)
data("mini_pbmc3k")
targets <- colData(mini_pbmc3k)$clusters
exprs <- as.data.frame(assay(mini_pbmc3k, "logcounts"))
fc <- new_fcoex(exprs, targets)
```

nmodules	<i>Get the number of modules in a fcoex object</i>
----------	--

Description

This function was copied and adapted from the CEMiTool package.

Usage

```
nmodules(fc)

## S4 method for signature 'fcoex'
nmodules(fc)
```

Arguments

fc	Object of class fcoex
----	-----------------------

Value

number of modules

Examples

```
data("fc")
nmodules(fc)
```

ora_data

Retrieve over representation analysis (ORA) results

Description

Retrieve over representation analysis (ORA) results

Usage

```
ora_data(fc)

## S4 method for signature 'fcoex'
ora_data(fc)
```

Arguments

fc Object of class fcoex

Details

This function returns the results of the `mod_ora` function on the `fcoex` object. The ID column corresponds to pathways in the `gmt` file for which genes in the modules were enriched. The Count column shows the number of genes in the module that are enriched for each pathway. The GeneRatio column shows the proportion of genes in the module enriched for a given pathway out of all the genes in the module enriched for any given pathway. The BgRatio column shows the proportion of genes in a given pathway out of all the genes in the `gmt` file. For more details, please refer to the `clusterProfiler` package documentation.

This function was *ipsis litteris* adapted from the `CEMiTool` package.

Value

Object of class `data.frame` with ORA data

References

Guangchuang Yu, Li-Gen Wang, Yanyan Han, Qing-Yu He. `clusterProfiler`: an R package for comparing biological themes among gene clusters. *OMICS: A Journal of Integrative Biology*. 2012, 16(5):284-287.

Examples

```
data("fc")
ora_data(fc)
```

plot_ora

ORA visualization

Description

Creates a bar plot with the results of module Over Representation Analysis (ORA)

Usage

```
plot_ora(fc, n = 10, pv_cut = 0.05, ...)

## S4 method for signature 'fcoex'
plot_ora(fc, n = 10, pv_cut = 0.05, ...)
```

Arguments

fc	Object of class fcoex.
n	number of enrichments to show
pv_cut	p-value significance cutoff. Default is 0.05.
...	parameters to plot_ora_single

Details

This function was copied and adapted from the CEMiTool package. The visualization in this function is derivative of the intellectual work of CEMiTool's authors.

Value

Object of class fcoex with ORA plots

Examples

```
data("fc")
gmt_fname <- system.file("extdata", "pathways.gmt", package = "CEMiTool")
gmt_in <- pathwayPCA::read_gmt(gmt_fname)
fc <- mod_ora(fc, gmt_in)
fc <- plot_ora(fc)
```

`recluster`*Recluster cells based on fcoex module composition*

Description

Recluster cells based on fcoex module composition

Usage

```
recluster(  
  fc,  
  hclust_method = "ward.D2",  
  dist_method = "manhattan",  
  k = 2,  
  verbose = TRUE  
)  
  
## S4 method for signature 'fcoex'  
recluster(  
  fc,  
  hclust_method = "ward.D2",  
  dist_method = "manhattan",  
  k = 2,  
  verbose = TRUE  
)
```

Arguments

<code>fc</code>	Object of class <code>fcoex</code>
<code>hclust_method</code>	method for the <code>hclust</code> function. Defaults to "ward.D2".
<code>dist_method</code>	method for the <code>dist</code> function. Defaults to "manhattan".
<code>k</code>	desired number of clusters. Defaults to 2.
<code>verbose</code>	Adds verbosity, defaults to TRUE.

Value

Object of class `data.frame` with new clusters

Examples

```
data("fc")  
fc <- recluster(fc)
```

save_plots	<i>Save fcoex object plots</i>
------------	--------------------------------

Description

Save plots into the directory specified by the directory argument. Note: If no directory is specified, it will save to tempdir(). A possible option is setting directory = "/Plots"

This function was modified from the CEMiTool package. Chunks of code were retained "as is"

Usage

```
save_plots(fc, name, force = FALSE, directory = "tempdir()")

## S4 method for signature 'fcoex'
save_plots(fc, name, force = FALSE, directory = "tempdir()")
```

Arguments

fc	Object of class fcoex.
name	The name of the file to be saved.
force	If the directory exists, execution will not stop.
directory	Directory into which the files will be saved.

Value

A pdf file or files with the desired plot(s)

Examples

```
## Not run:
data(fc)
save_plots(fc, name = "Example")

## End(Not run)
```

show, fcoex-method	<i>Print a fcoex object</i>
--------------------	-----------------------------

Description

Print a fcoex object

Usage

```
## S4 method for signature 'fcoex'
show(object)
```

Arguments

object Object of class fcoex

Value

A fcoex object.

Examples

```
data("fc")
fc
```

show_net	<i>Retrieve fcoex net plots</i>
----------	---------------------------------

Description

Retrieve fcoex net plots

Usage

```
show_net(fc)

## S4 method for signature 'fcoex'
show_net(fc)
```

Arguments

fc Object of class fcoex.

Value

A plot corresponding to a fcoex analysis

Examples

```
## Not run:
data("fc")
show_net(fc)

## End(Not run)
```

show_ora	<i>Retrieve fcoex ora plots</i>
----------	---------------------------------

Description

This function was copied and adapted from the CEMiTool package. The visualization in this function is derivative of the intellectual work of CEMiTool's authors.

Usage

```
show_ora(fc)

## S4 method for signature 'fcoex'
show_ora(fc)
```

Arguments

fc Object of class fcoex.

Value

A plot corresponding to a fcoex analysis

Examples

```
data("fc")
show_ora(fc)
```

Index

* datasets

- fc, [5](#)
- mini_pbmc3k, [9](#)
- .get_correlates, [2](#)
- .plot_one_interaction, [3](#)

- discretize, [4](#)
- discretize, fcoex-method (discretize), [4](#)

- fc, [5](#)
- fcoex-class, [5](#)
- find_cbf_modules, [6](#)
- find_cbf_modules, fcoex-method (find_cbf_modules), [6](#)

- get_nets, [7](#)
- get_nets, fcoex-method (get_nets), [7](#)

- idents, [8](#)
- idents, fcoex-method (idents), [8](#)

- mini_pbmc3k, [9](#)
- mod_colors, [10](#)
- mod_colors, fcoex-method (mod_colors), [10](#)
- mod_gene_num, [11](#)
- mod_gene_num, fcoex-method (mod_gene_num), [11](#)
- mod_names, [11](#)
- mod_names, fcoex-method (mod_names), [11](#)
- mod_ora, [12](#)
- mod_ora, fcoex-method (mod_ora), [12](#)
- module_genes, [9](#)
- module_genes, fcoex-method (module_genes), [9](#)

- new_fcoex, [13](#)
- nmodules, [13](#)
- nmodules, fcoex-method (nmodules), [13](#)

- ora_data, [14](#)
- ora_data, fcoex-method (ora_data), [14](#)

- plot_ora, [15](#)
- plot_ora, fcoex-method (plot_ora), [15](#)

- recluster, [16](#)
- recluster, fcoex-method (recluster), [16](#)

- save_plots, [17](#)
- save_plots, fcoex-method (save_plots), [17](#)
- show, fcoex-method, [17](#)
- show_net, [18](#)
- show_net, fcoex-method (show_net), [18](#)
- show_ora, [19](#)
- show_ora, fcoex-method (show_ora), [19](#)