

# Package ‘wiggplotr’

May 16, 2024

**Title** Make read coverage plots from BigWig files

**Version** 1.28.0

**Author** Kaur Alasoo [aut, cre]

**Maintainer** Kaur Alasoo <kaur.alasoo@gmail.com>

**Description** Tools to visualise read coverage from sequencing experiments together with genomic annotations (genes, transcripts, peaks). Introns of long transcripts can be rescaled to a fixed length for better visualisation of exonic read coverage.

**Depends** R (>= 3.6)

**Imports** dplyr, ggplot2 (>= 2.2.0), GenomicRanges, rtracklayer, cowplot, assertthat, purrr, S4Vectors, IRanges, GenomeInfoDb

**License** Apache License 2.0

**LazyData** true

**RoxygenNote** 6.1.1

**Suggests** knitr, rmarkdown, biomaRt, GenomicFeatures, testthat, ensemblDb, EnsDb.Hsapiens.v86, org.Hs.eg.db, TxDb.Hsapiens.UCSC.hg38.knownGene, AnnotationDbi, AnnotationFilter

**VignetteBuilder** knitr

**biocViews** ImmunoOncology, Coverage, RNASeq, ChIPSeq, Sequencing, Visualization, GeneExpression, Transcription, AlternativeSplicing

**git\_url** <https://git.bioconductor.org/packages/wiggplotr>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 0bcb1de

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-05-15

## Contents

getGenotypePalette . . . . .	2
makeManhattanPlot . . . . .	3
ncoa7_cdss . . . . .	3
ncoa7_exons . . . . .	4
ncoa7_metadata . . . . .	4
pasteFactors . . . . .	5
plotCoverage . . . . .	5
plotCoverageFromEnsemblDb . . . . .	8
plotCoverageFromUCSC . . . . .	9
plotTranscripts . . . . .	10
plotTranscriptsFromEnsemblDb . . . . .	11
plotTranscriptsFromUCSC . . . . .	12
wiggleplotr . . . . .	13
<b>Index</b>	<b>14</b>

---

getGenotypePalette	<i>Returns a three-colour palette suitable for visualising read coverage stratified by genotype</i>
--------------------	---

---

### Description

Returns a three-colour palette suitable for visualising read coverage stratified by genotype

### Usage

```
getGenotypePalette(old = FALSE)
```

### Arguments

old                   Return old colour palette (now deprecated).

### Value

Vector of three colours.

### Examples

```
getGenotypePalette()
```

---

makeManhattanPlot	<i>Make a Manahattan plot of p-values</i>
-------------------	---

---

**Description**

The Manhattan plots is compatible with wiggplelotr read coverage and transcript strucutre plots. Can be appended to those using the cowplot::plot\_grid() function.

**Usage**

```
makeManhattanPlot(pvalues_df, region_coords, color_R2 = FALSE,
  data_track = TRUE)
```

**Arguments**

pvalues_df	Data frame of association p-values (required columns: track_id, p_nominal, pos)
region_coords	Start and end coordinates of the region to plot.
color_R2	Color the points according to R2 from the lead variant. Require R2 column in the pvalues_df data frame.
data_track	If TRUE, then remove all information from x-axis. Makes it easy to append to read coverage or transcript strcuture plots using cowplot::plot_grid().

**Value**

ggplot2 object

**Examples**

```
data = dplyr::data_frame(track_id = "GWAS", pos = sample(c(1:1000), 200), p_nominal = runif(200, min = 0.0000001, 1)
makeManhattanPlot(data, c(1,1000), data_track = FALSE)
```

---

ncoa7_cdss	<i>Coding sequences from 9 protein coding transcripts of NCOA7</i>
------------	--

---

**Description**

A dataset containing start and end coordinates of coding sequences (CDS) from nine protein coding transcripts of NCOA7.

**Usage**

```
ncoa7_cdss
```

**Format**

A GRangesList object with 9 elements:

**element** CDS start and end coordinates for a single transcript (GRanges object) ...

**Source**

<http://www.ensembl.org/>

---

ncoa7_exons	<i>Exons from 9 protein coding transcripts of NCOA7</i>
-------------	---

---

**Description**

A dataset containing start and end coordinates of exons from nine protein coding transcripts of NCOA7.

**Usage**

ncoa7\_exons

**Format**

A GRangesList object with 9 elements:

**element** Exon start and end coordinates for a single transcript (GRanges object) ...

**Source**

<http://www.ensembl.org/>

---

ncoa7_metadata	<i>Gene metadata for NCOA7</i>
----------------	--------------------------------

---

**Description**

A a list of transcripts for NCOA7.

**Usage**

ncoa7\_metadata

**Format**

A data.frame object with 4 columns:

**transcript\_id** Ensembl transcript id.

**gene\_id** Ensembl gene id.

**gene\_name** Human readable gene name.

**strand** Strand of the transcript (either +1 or -1). ...

**Source**

<http://www.ensembl.org/>

---

pasteFactors

*Paste two factors together and preserved their joint order.*

---

**Description**

Paste two factors together and preserved their joint order.

**Usage**

```
pasteFactors(factor1, factor2)
```

**Arguments**

factor1          First factor

factor2          Second factor

**Value**

Factors factor1 and factor2 pasted together.

---

plotCoverage

*Plot read coverage across genomic regions*

---

**Description**

Also supports rescaling introns to constant length. Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

**Usage**

```
plotCoverage(exons, cdss = NULL, transcript_annotatons = NULL,
  track_data, rescale_introns = TRUE, new_intron_length = 50,
  flanking_length = c(50, 50), plot_fraction = 0.1, heights = c(0.75,
  0.25), alpha = 1, fill_palette = c("#a1dab4", "#41b6c4", "#225ea8"),
  mean_only = TRUE, connect_exons = TRUE, transcript_label = TRUE,
  return_subplots_list = FALSE, region_coords = NULL,
  coverage_type = "area")
```

**Arguments**

exons	list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transcript_annotatons data.frame.
cdss	list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transcript_annotatons data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL).
transcript_annotatons	Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)
track_data	data.frame with the metadata for the bigWig read coverage files. Must contain the following columns: <ul style="list-style-type: none"> <li>• sample_id - unique id for each sample.</li> <li>• track_id - if multiple samples (bigWig files) have the same track_id they will be overlayed on the same plot, track_id is also used as the facet label on the right.</li> <li>• bigWig - path to the bigWig file.</li> <li>• scaling_factor - normalisation factor for each sample, useful if different samples sequenced to different depth and bigWig files not normalised for that.</li> <li>• colour_group - additional column to group samples into, is used as the colour of the coverage track.</li> </ul>
rescale_introns	Specifies if the introns should be scaled to fixed length or not. (default: TRUE)
new_intron_length	length (bp) of introns after scaling. (default: 50)
flanking_length	Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))
plot_fraction	Size of the random sub-sample of points used to plot coverage (between 0 and 1). Smaller values make plotting significantly faster. (default: 0.1)
heights	Specifies the proportion of the height that is dedicated to coverage plots (first value) relative to transcript annotations (second value). (default: c(0.75,0.25))

alpha	Transparency (alpha) value for the read coverage tracks. Useful to set to something < 1 when overlaying multiple tracks (see track_id). (default: 1)
fill_palette	Vector of fill colours used for the coverage tracks. Length must be equal to the number of unique values in track_data\$colour_group column.
mean_only	Plot only mean coverage within each combination of track_id and colour_group values. Useful for example for plotting mean coverage stratified by genotype (which is specified in the colour_group column) (default: TRUE).
connect_exons	Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).
transcript_label	If TRUE then transcript labels are printed above each transcript. (default: TRUE).
return_subplots_list	Instead of a joint plot return a list of subplots that can be joined together manually.
region_coords	Start and end coordinates of the region to plot, overrides flanking_length parameter.
coverage_type	Specifies if the read coverage is represented by either 'line', 'area' or 'both'. The 'both' option tends to give better results for wide regions. (default: area).

## Value

Either object from cow\_plot::plot\_grid() function or a list of subplots (if return\_subplots\_list == TRUE)

## Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
plotCoverage(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts],
  ncoa7_metadata, track_data,
  heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotCoverageFromEnsemblDb

*Plot read coverage directly from ensemblDb object.*

---

## Description

A wrapper around the plotCoverage function. See the documentation for ([plotCoverage](#)) for more information.

## Usage

```
plotCoverageFromEnsemblDb(ensemldb, gene_names, transcript_ids = NULL,
  ...)
```

## Arguments

ensemldb	ensemldb object.
gene_names	List of gene names to be plotted.
transcript_ids	Optional list of transcript ids to be plotted.
...	Additional parameters to be passed to plotCoverage.

## Value

ggplot2 object

## Examples

```
require("EnsDb.Hsapiens.v86")
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aigt_A", "aigt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)
## Not run:
plotCoverageFromEnsemblDb(EnsDb.Hsapiens.v86, "NCOA7", transcript_ids = c("ENST00000438495", "ENST00000392477"),
  track_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```



---

plotCoverageFromUCSC *Plot read coverage directly from UCSC OrgDb and TxDb objects.*

---

### Description

A wrapper around the plotCoverage function. See the documentation for ([plotCoverage](#)) for more information.

### Usage

```
plotCoverageFromUCSC(orgdb, txdb, gene_names, transcript_ids = NULL, ...)
```

### Arguments

orgdb	UCSC OrgDb object.
txdb	UCSC TxDb object.
gene_names	List of gene names to be plotted.
transcript_ids	Optional list of transcript ids to be plotted.
...	Additional parameters to be passed to plotCoverage.

### Value

ggplot2 object

### Examples

```
require("dplyr")
require("GenomicRanges")
require("org.Hs.eg.db")
require("TxDb.Hsapiens.UCSC.hg38.knownGene")

orgdb = org.Hs.eg.db
txdb = TxDb.Hsapiens.UCSC.hg38.knownGene

sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)
## Not run:
##Note: This example does not work, because UCSC and Ensembl use different chromosome names
plotCoverageFromUCSC(orgdb, txdb, "NCOA7", transcript_ids = c("ENST00000438495.6", "ENST00000368357.7"),
  track_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotTranscripts      *Quickly plot transcript structure without read coverage tracks*

---

### Description

Quickly plot transcript structure without read coverage tracks

### Usage

```
plotTranscripts(exons, cdss = NULL, transcript_annotatons = NULL,
  rescale_introns = TRUE, new_intron_length = 50,
  flanking_length = c(50, 50), connect_exons = TRUE,
  transcript_label = TRUE, region_coords = NULL)
```

### Arguments

exons	list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transcript_annotatons data.frame.
cdss	list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transcript_annotatons data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL)
transcript_annotatons	Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)
rescale_introns	Specifies if the introns should be scaled to fixed length or not. (default: TRUE)
new_intron_length	length (bp) of introns after scaling. (default: 50)
flanking_length	Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))
connect_exons	Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).
transcript_label	If TRUE then transcript labels are printed above each transcript. (default: TRUE).
region_coords	Start and end coordinates of the region to plot, overrides flanking_length parameter.

### Value

ggplot2 object

**Examples**

```
plotTranscripts(ncoa7_exons, ncoa7_cdss, ncoa7_metadata, rescale_introns = FALSE)
```

---

```
plotTranscriptsFromEnsemblDb
```

*Plot transcripts directly from ensemblDb object.*

---

**Description**

A wrapper around the plotTranscripts function. See the documentation for ([plotTranscripts](#)) for more information.

**Usage**

```
plotTranscriptsFromEnsemblDb(ensemldb, gene_names,  
  transcript_ids = NULL, ...)
```

**Arguments**

ensemldb	ensemldb object.
gene_names	List of gene names to be plotted.
transcript_ids	Optional list of transcript ids to be plotted.
...	Additional parameters to be passed to plotTranscripts

**Value**

ggplot2 object

**Examples**

```
require("EnsDb.Hsapiens.v86")  
plotTranscriptsFromEnsemblDb(EnsDb.Hsapiens.v86, "NCOA7", transcript_ids = c("ENST00000438495", "ENST00000392477"))
```

---

plotTranscriptsFromUCSC

*Plot transcripts directly from UCSC OrgDb and TxDb objects.*

---

### Description

A wrapper around the plotTranscripts function. See the documentation for ([plotTranscripts](#)) for more information. Note that this function is much slower than ([plotTranscripts](#)) or ([plotTranscriptsFromEnsemblDb](#)) functions, because individually extracting exon coordinates from txdb objects is quite inefficient.

### Usage

```
plotTranscriptsFromUCSC(orgdb, txdb, gene_names, transcript_ids = NULL,
  ...)
```

### Arguments

orgdb	UCSC OrgDb object.
txdb	UCSC TxDb object.
gene_names	List of gene names to be plot.
transcript_ids	Optional list of transcript ids to be plot. (default = NULL)
...	Additional parameters to be passed to plotTranscripts

### Value

Transcript plot.

### Examples

```
#Load OrgDb and TxDb objects with UCSC gene annotations
require("org.Hs.eg.db")
require("TxDb.Hsapiens.UCSC.hg38.knownGene")
orgdb = org.Hs.eg.db
txdb = TxDb.Hsapiens.UCSC.hg38.knownGene

plotTranscriptsFromUCSC(orgdb, txdb, "NCOA7", transcript_ids = c("ENST00000438495.6", "ENST00000368357.7"))
```

---

*wiggleplotr**wiggleplotr*

---

**Description**

*wiggleplotr* package provides tools to visualise transcript annotations ([plotTranscripts](#)) and plot sequencing read coverage over annotated transcripts ([plotCoverage](#)).

**Details**

You can also use convenient wrapper functions ([plotTranscriptsFromEnsemblDb](#)), ([plotCoverageFromEnsemblDb](#)), ([plotTranscriptsFromUCSC](#)) and ([plotCoverageFromUCSC](#)).

To learn more about *wiggleplotr*, start with the vignette: `browseVignettes(package = "wiggleplotr")`

# Index

## \* datasets

- ncoa7\_cdss, 3
- ncoa7\_exons, 4
- ncoa7\_metadata, 4

getGenotypePalette, 2

makeManhattanPlot, 3

ncoa7\_cdss, 3

ncoa7\_exons, 4

ncoa7\_metadata, 4

pasteFactors, 5

plotCoverage, 5, 8, 9, 13

plotCoverageFromEnsemblDb, 8, 13

plotCoverageFromUCSC, 9, 13

plotTranscripts, 10, 11–13

plotTranscriptsFromEnsemblDb, 11, 12, 13

plotTranscriptsFromUCSC, 12, 13

wiggleplotr, 13

wiggleplotr-package (wiggleplotr), 13